

Printing Workflow

Order Processing & Epson SureColor S60600L Operation

This document covers the end-to-end printing workflow at Keith Merrick, from order receipt through KMSignalR to final cutting. Follow all steps in sequence for each production run.

- Equipment: Epson SureColor S60600L — 64" roll-to-roll solvent wide-format printer. Uses UltraChrome GS3 CMYK x2 bulk ink. Max resolution 1440 x 1440 dpi. surecolor = right printer | surecolor2 = left printer

1. Order Receipt via KMSignalR

All orders are received and managed through the KMSignalR system. Monitor the laptop for incoming orders and confirm status updates promptly.

- i Orders come through on **KMSignalR** and the order sheet prints automatically.
- ii Check **KMSignalR on the laptop** to confirm and note the order number.
- iii Set the order status to **Printed** in KMSignalR once confirmed.

- **Do not proceed to printing until the order status has been updated to 'Printed' in KMSignalR. Skipping this step may cause duplicate orders.**

2. Sending the File to the Printer

Locate the correct file and route it to the appropriate SureColor printer. Confirm printer selection before sending — the two units are physically distinguished by position.

- i Find the correct **file name** associated with the order.
- ii Send the file to the correct printer:

Name	Position	Model
surecolor	Right	Epson SureColor S60600L
surecolor2	Left	Epson SureColor S60600L

3. Cutting

Once printing is complete, portraits must be cut to the correct dimensions using the electric cutter. Always follow the printed cut guides precisely.

- i Allow print to finish and advance fully out of the printer before handling.
- ii Cut portraits to the correct dimensions using the **electric cutter**.
- iii Follow the **red cut lines** and **black cut lines** printed on the sheet as guides.



Always use the electric cutter for straight, accurate cuts. Keep hands clear of the blade path at all times during operation.

Printer Quick Reference — Epson SureColor S60600L

Specification	Detail
Print Width	64" (63.6" max printable area)
Ink Type	UltraChrome GS3 solvent-based, CMYK x2
Ink System	Bulk ink pack (4-color) — double capacity vs. previous gen
Max Resolution	1440 x 1440 dpi
Print Speed	Up to 310 sqft/hr (vinyl) / 550 sqft/hr (banner)
Droplet Size	4.2 picoliters (variable droplet technology)
PANTONE Coverage	98.2% of PANTONE PLUS FORMULA GUIDE
Lamination	Same-day (minimum 6 hrs after printing)
Ventilation	No special ventilation required
Media Types	Adhesive vinyl, banner, decals, labels, and more

Quick Reference Checklist

1-i	Order received & sheet printed	KMSignalR (auto)
1-ii	Note order number	KMSignalR laptop
1-iii	Set order status to Printed	KMSignalR
2-i	Find correct file name	File system / RIP
2-ii	Send to correct printer (right or left)	surecolor / surecolor2

3-i	Allow print to complete & advance	Epson S60600L
3-ii	Cut to correct dimensions	Electric cutter
3-iii	Follow red & black cut lines	Printed guides

*For questions regarding this workflow or printer issues, contact your floor supervisor or the Keith Merrick maintenance team.
Epson support: epson.com/support*