## C5PBA LANE CERTIFICATION APPLICATION Season: -\_\_\_-Inspection Date: \_\_\_\_\_ Province: Zone Association: Name of Bowling Centre: Postal Code: Address: Telephone:( ) \_\_\_\_ - \_\_\_ City/Town Manager: Proprietor: ☐ Commercial Private Club Type of Centre: ☐ Ground ☐ Second Floor Location: ☐ Basement Other: Number of Lanes in Centre: \_\_\_\_\_ and are numbered from \_\_\_\_ to \_\_\_\_ APPROACHES YES IF NO, WHAT? NO ☐ Synthetic ☐ Wood 1. Approaches are: Are the beginning of the approaches a minimum of 15' (4.57m) in length 2. from the foul line? Are there dowels/markings on the approach: 3. at the foul line? 9' - 10' (2.74m - 3.05m) from the foul line? b) 11' - 12' (3.35m - 3.66m) from the foul line? C) 14' - 15' (4.27m - 4.57m) from the foul line? d) Are the foul lines $\frac{3}{8}$ " - 1" (0.9cm - 2.5cm) in width? 4. Are automatic foul detection devices installed? $\Box$ 5. Manufacturer's Name: \_\_\_\_\_\_ П Are all devices in working order? П 6. If foul detectors are not installed or operating, is there an area to station 7. a Foul Line Judge? EANERROREOTION DEVICES Manufacturer: \_\_\_\_\_\_ Date Installed \_\_\_\_ 1. Is the lane protection device a minimum of 14' (4.27m) beyond the foul 2. line? Is the lane protection device 7 1/2" - 9 1/2" (19.0cm - 24.0cm) above the П П 3. lane surface? LANEBEDS LA ☐ Wood Synthetic Date Installed: 19 1. Lanebeds are: Does the resurfacer's stamp/stencil appear on lane surface? 2. Firm: Date: Recoating: Verify the lanebed length (not less than 59' 11 1/2" (18.30m) and not more 3. than 60' 1/2" (18.43m) from the foul line to the centre of the 5 pin spot). $\Box$ Verify the lanebed width (not less than 41" (1.04m) and not more than $\Box$ 4. 42" (1.07m).

		YES	NO	IF NO, WHAT?
5.	Do dowels/markings appear 6' - 8' (1.83m - 2.44m) beyond the foul line and conform to specifications?	0		
6.	Do range finders (darts) appear 12' - 16' (3.66m - 4.88m) beyond the foul line and conform to standards?		_	
7.	For synthetic (panelized) surfaces, is the maximum drop between panels 0.015" and the maximum separation 0.050"?			
	PINDECKS			
1.	Pindecks are:			
2.	If synthetic or steel, is the maximum drop between lane and pindeck 0.015" and maximum separation 0.050"?			
3.	Are pin spots 2 1/4" (5.7cm) in diameter and clearly marked?			
4.	Are pin spots 18" (45.7cm) apart, centre to centre?			_
<b>5</b> .	Are the 2 pin spots 36" (91.4cm) apart, centre to centre?			
6.	Is the centre of the 2 pin spots 2 ½" - 3" (6.3cm - 7.6cm) from the channel edge of the pindeck?			
7.	Are striker plates flush mounted and do they conform to sizes: a) 4 ½" x 8" (11.4cm x 20.3cm) behind 5 pin spot? b) 3 ½" x 8" (8.2cm x 20.3cm) behind 3 pin spots?	8		
8.	Is the tail plank a maximum of 2" (5.08cm) in thickness?			
9.	Is the channel moulding strip $\frac{7}{8}$ " x $\frac{3}{4}$ " (2.2cm x 1.9cm) at the point opposite the 5 pin spot and 1 $\frac{7}{4}$ " (3.8cm x 1.9cm) at the point opposite the 2 pin spot?	٥		
10.	Is the maximum width of the channels 9" - 9 1/2" (22.8cm - 24.1cm)?			-
11.	Are channels flat bottomed, starting from/or within 15" (38.1cm) in front of the 5 pin spot?			
12.	Are channels 2 ¾" - 3 ½" (6.9cm - 8.8cm) in depth at a point opposite the 2 pin spot?	О		
13.	Is the distance between kickbacks (wood to wood) 60" - 60 1/4" (1.52m - 1.53m)?	0		
14.	Are kickback plates a maximum of $\frac{3}{16}$ " (4.76mm) in thickness?			-
15.	Do kickback boards measure between 17" and 24" (45.7cm - 60.6cm) in height?	0		
16.	Is the pit depth (lane surface to top of pit mat) in accordance with the Pit Depth Chart on page 12 of the C5PBA Specifications Manual?			
17.	Is the length of the pit, from the end of the lanebed (before the tail plank) to the face of the <b>rear cushion</b> a minimum of 25" (63.5cm)?			
18.	Is the end of the lanebed (after the tail plank) and the face of the pit curtain a minimum of 9" (22.8cm)?	О		
19.	Are rear cushions and curtains a dark colour?			

.· .

-

			THE PRINCE	SPECE CATEURS			
221229212			K.S.L. a. H.A. Dartinullullullullullullullullullullullullull	n, 100 m. h. 1400 h. 1466 h. 1466 h. 1400 h. 1	YES	NO	IF NO, WHAT?
۱.	Do lan	es have:	automatic pinsetters	manual pinsetters			
	Manuf	acturer:	<del></del>	Model:	<del></del>		
2.	Are the	<b>ә</b> у	string string	free-fall machines?			
3.	If string machines:  a) are they equipped with shields?  b) measure the time-lapse between when a pin is hit and when the shield begins to descend. TIME:seconds.  c) by random sample, what is the length of string on any two headpins when fully reeled out?			σ	. 🗖		
4.	Do pin	setting machi	nes spot all pins within toler	rances?			
5.	Do ho	Weight: 3lbs	alls meet specifications for: $34$ 4 ozs to 3lbs 10ozs +/- $\frac{1}{2}$ 4 ozs to 5" +/- $\frac{1}{2}$ " (12.1 to 13)	oz (1.474 to 1.644kg)			
		Brand Name	o:				
3.	Are bo	wling pins?	☐ plastic coate ☐ synthetic Brand Name:	ed wood			
7.	Туре	of pin-band be	ing used on pins: Brand N	ame:		_	
nspe	ection Pa	ssed:	☐ Yes ☐ I	No			
Sign	atures:	Inspector:			_	i	
		Proprietor/M	lanager:				
		Date:					