Admin Invite and Environment Mapping — Updated Plan (New Requirement)

New Requirement Summary

1. **Admin (Sub-owner) mapped to all environments by default** — Same Admin is mapped for Dev, Staging, and Production for the same organization (no longer one Admin per environment).
2. **Owner can invite multiple Admins for the same organization** — Same org can have multiple Admins with the same details; no "one Admin per (org, env)" slot restriction.
3. **Single project per organization** — Do not create a new project per Admin; one shared project per organization visible to all Admins of that organization.

Current vs New Model

Aspect	Current	New
Admin–Environment	One Admin per (org, env) slot (Dev / Staging / Prod each separate)	One Admin mapped to all envs (Dev, Staging, Prod) for same org
Admins per org	One Admin per env → max 3 Admins per org (one per env)	Multiple Admins per org allowed
Project per Admin	Each Admin gets a personal project on accept (e.g. "ABC Dev Project")	Single shared project per org; all org Admins see the same project
Invite flow	Owner picks org + one environment; slot must be free	Owner picks org only (no env slot); can invite many Admins for same org

High-Level Design



- **Organization**: has one `projectId` (shared project). Created when the first Admin is provisioned for that org (or on first org creation, depending on product choice).

- **Admins**: linked to org via `user.organizationId` . All Admins of the org are given access to the org's single project (e.g. as project members or via org-level access).
- **Environments**: Dev, Staging, Prod are metadata/default for the org (Admin is "mapped" to all by default). No per-env "slot" or per-env project.

Implementation Areas

1. Data model

Organization

- Add (or reuse) a field for the org's shared project, e.g. `organization.projectId` (nullable until first Admin is provisioned).
- Alternatively keep a single "default" row in `organization_environment` per (org, env) with the same `projectId` for all three envs and allow multiple Admins via a separate relation (see below).

Organization–Environment

- Current: `(organizationId, environment)` unique, one `adminUserId` , one `projectId` per row.
- Options:
  - **A** — One shared project per org: store `projectId` on `organization` ; use `organization_environment` only for env metadata (same `projectId` for Dev/Staging/Prod) and allow multiple admins via a join table (e.g. `organization_admin` : organizationId, userId).
  - **B** — Keep one row per (org, env) but all three rows point to the same `projectId` ; add `organization_admin` (orgId, userId) for "who is Admin for this org"; stop using `adminUserId` on `organization_environment` as the single owner (or deprecate it).
- Recommendation: **One shared project per org**; **organization_admin** (or equivalent) for "Admins of this org"; **organization_environment** can point to the same `projectId` for all three envs and optionally track metadata only.

User

- Keep `user.organizationId` to denote "this user is an Admin for this org" (or use a dedicated org–admin table).

Project

- Keep `project.organizationId` . The org's shared project has `organizationId` set; no need for `ownerId` to represent "the" Admin (or use a designated owner for legacy reasons).

2. Invitation flow (backend)

Invite creation (user-invitation.module.ts)

- For OWNER inviting ADMIN: require only **organization (name/id)**; **do not** require environment.
- Remove "admin slot" check for (org, env) — multiple Admins per org allowed.
- Request body: keep `organizationName` (or `organizationId`); make `environment` optional or remove it for ADMIN invites.
- Store on invitation: `organizationId` only (no `environment` for ADMIN).

Invitation acceptance / provisioning (user-invitation.service.ts)

- For ADMIN with organization:
  - Resolve org; set `user.platformRole` , `user.organizationId` .

- **If org has no project yet**: create one shared project for the org (e.g. "{OrgName} Project"), set `organization.projectId` and `project.organizationId`, `project.ownerId` = first Admin.
- **If org already has a project**: do **not** create a new project.
- **Do NOT use projectMemberService** — access is via project visibility filter (`applyProjectsAccessFilters` with `organizationId`), per EE policy (no project members).
- Optionally create/update `organization_environment` rows for Dev/Staging/Prod all pointing to the same `projectId` and same org (no single `adminUserId` ownership), or add the user to an `organization_admin` table.

- Remove: "create personal project per Admin" and "upsert organization_environment with this adminUserId and this projectId". Remove any `projectMemberService.upsert()` for Admin provisioning.

3. Organization–environment service

- **checkAdminAvailability**: remove or repurpose — no longer "one slot per (org, env)". If kept for backward compatibility, always return "available" for ADMIN invite flow.
- **listByOrganization**: can return one shared project and "all envs" for that project; or three rows (Dev/Staging/Prod) with same `projectId` and no single `adminUserId` (or list of admin IDs from org–admin table).
- **upsert**: when creating/updating org–env rows for "default mapping for all envs", set same `projectId` for all three envs; do not overwrite with a single `adminUserId` per row if multiple Admins are allowed.

4. Frontend (invite dialog)

- invite-user-dialog.tsx:
  - For OWNER inviting ADMIN: show **Organization** only; **hide Environment** selector (or show as read-only "All (Dev, Staging, Prod)").
  - Remove environment validation and "taken slot" logic for ADMIN.
  - Remove or simplify `adminAvailability` and `orgEnvironments` usage for ADMIN path.
- Form schema: `environment` optional for platform ADMIN invites; API accepts invite without environment.

5. Project visibility for Admins

- When resolving "current project" or project list for an Admin:
  - Use `user.organizationId` to load the org's shared project (`organization.projectId` or project where `project.organizationId = user.organizationId`).
  - Ensure all Admins of the same org get the same project in their list and as default when they belong to that org.
- Existing logic that uses "admin's personal project" (e.g. OPERATOR/MEMBER invite) should use the **org's shared project** when the inviter is an Admin of an org.

6. OPERATOR/MEMBER invites by Admin

- Today: ADMIN invites OPERATOR/MEMBER and stores their **personal** project ID.
- New: For an Admin belonging to an org, use the **org's shared project** (not a per-Admin project) when inviting OPERATOR/MEMBER so they join the same project as all other org members.

7. BMP connection popup — platform-role based allowed environments

When creating a BMP piece connection, the environment dropdown is filtered by **platform role** so that:

- **MEMBER** → can use **Dev** and **Staging** only (no Production).
- **OPERATOR** → can use **Production** only.
- **ADMIN / OWNER** → can use **Dev, Staging, Production** (all).

Where it is implemented

- **UI**: The BMP environment dropdown is rendered by AdaBmpEnvironmentSelect, which is used in properties-utils.tsx when `propertyName === 'environment'` and `inputName` includes `props.environment`.
- **Backend**: GET /v1/organizations/current-user/allowed-environments currently returns environments based on "user is admin of this org-env"; it does **not** yet apply platform-role rules.

Required change

- In the **allowed-environments** endpoint: after resolving the current user, derive allowed environments from **platform role**:
  - `PlatformRole.MEMBER` → `['Dev', 'Staging']`
  - `PlatformRole.OPERATOR` → `['Production']`
  - `PlatformRole.ADMIN` or `PlatformRole.OWNER` → `['Dev', 'Staging', 'Production']`
- No frontend change needed: AdaBmpEnvironmentSelect already filters the dropdown using the API response; once the backend returns role-based lists, the BMP connection popup will show the correct options.

8. Connections list — filter by allowed environments

The connections list should show only connections that the logged-in user is allowed to use, based on their **allowed environments** (Dev, Staging, Production per platform role).

Requirement

- **MEMBER** → only connections that use Dev or Staging env config.
- **OPERATOR** → only connections that use Production env config.
- **ADMIN / OWNER** → all connections.

Where it is implemented

- **UI**: AppConnectionsPage fetches connections via `appConnectionsQueries.useAppConnections` (projectId, pieceName, status, etc.).
- **API**: GET /v1/app-connections returns connections for the project; `value` is redacted (`removeSensitiveData`), so `value.props.environment` is not available in the list response.

Challenge

- The connection's environment (Dev/Staging/Production) is stored in `value.props.environment` for BMP piece connections.
- The list API does not return `value` ; it's stripped for security.
- We cannot filter by environment on the frontend without that data.

Solution

1. **Persist environment in metadata**
   When creating/updating a BMP piece connection, store the selected environment in `metadata.environment` (e.g. `metadata: { environment: 'Dev' }`). This is done in the upsert path when the piece is BMP and the value includes `props.environment` .
2. **Filter in the list API**
   In the app-connection list handler:

- Get the current user's allowed environments (via platform role: MEMBER → Dev/Staging, OPERATOR → Production, ADMIN/OWNER → all).
- After fetching connections for the project, filter results:
  - For BMP piece connections (`pieceName` matches BMP piece): only include if `metadata.environment` is in the user's allowed environments.
  - For non-BMP pieces: include all (no environment filter).

- Connections without `metadata.environment` (legacy or non-BMP): include all for backward compatibility, or treat as “all envs” if desired.

3. **Connection select dropdown**
   The connection dropdown used when building flows (connection-select.tsx) also uses `useAppConnections`. Once the list API filters by allowed envs, the dropdown will automatically show only allowed connections.

Data flow



9. Connections list — filter by creator platform role (all pieces)

Connections created by Member or Operator should only be visible to users with the same or higher role. Admin sees all.

Visibility matrix (connections):

Connection created by	Visible to MEMBER	Visible to OPERATOR	Visible to ADMIN
Member	Yes	No	Yes
Operator	No	Yes	Yes
Admin	Yes	Yes	Yes

Implementation

- Store `metadata.creatorPlatformRole` (e.g. `'MEMBER'`, `'OPERATOR'`, `'ADMIN'`) when creating any connection (all pieces, not just BMP), using the creator’s platform role at creation time.
- In the app-connection list API, filter results by the current user’s platform role:
  - **ADMIN** → return all connections.
  - **MEMBER** → return connections where `metadata.creatorPlatformRole` is `'MEMBER'` or `'ADMIN'` (or missing for backward compatibility).
  - **OPERATOR** → return connections where `metadata.creatorPlatformRole` is `'OPERATOR'` or `'ADMIN'` (or missing for backward compatibility).
- Apply this filter in addition to the BMP environment filter (section 8); both filters apply to BMP connections.

10. Flows list — filter by creator platform role

Flows created by Member, Operator, or Admin should be visible according to the following matrix. Admin sees all flows.

Visibility matrix (flows):

Flow created by	Visible to MEMBER	Visible to OPERATOR	Visible to ADMIN
Member	Yes	Yes	Yes
Operator	No	Yes	Yes

Flow created by	Visible to MEMBER	Visible to OPERATOR	Visible to ADMIN
Admin	Yes	Yes	Yes

Summary in words

- **Member-created flows** → visible to MEMBER, OPERATOR, ADMIN (everyone).
- **Operator-created flows** → visible to OPERATOR and ADMIN only (not MEMBER).
- **Admin-created flows** → visible to everyone.

Implementation

- Store `metadata.creatorPlatformRole` when creating a flow, using the creator's platform role at creation time.
- In the flow list API (flow.service.ts `list`), filter results by the current user's platform role:
  - **ADMIN** → return all flows.
  - **OPERATOR** → return all flows.
  - **MEMBER** → return flows where `metadata.creatorPlatformRole` is `'MEMBER'` or `'ADMIN'` (exclude Operator-created flows).
- For flows without `metadata.creatorPlatformRole` (legacy): treat as visible to everyone for backward compatibility.

Data flow diagrams

A. Admin invite and shared project flow

In words: Owner invites admins by organization only. The first admin who accepts creates the org's single shared project. Every later admin joins that same project — no new project per admin.



Simplified view (who sees what):



B. BMP connection popup — allowed environments by role



C. End-to-end: Organization, project, and BMP env access



Challenges and EE dependency analysis

No EE folder changes required

All planned changes can be made in **core** (non-EE) modules. No new EE modules need to be added, and no EE files need to be modified.

Module to change	Location	EE imports today	Plan impact
user-invitation.module.ts	`app/user-invitations/`	Yes (ee-authorization, rbac-middleware, projectRoleService)	Use existing EE imports; change ADMIN invite logic only
user-invitation.service.ts	`app/user-invitations/`	Yes (domainHelper, emailService, projectMemberService, projectRoleService)	Use existing EE imports; change provisioning logic
organization.controller.ts	`app/organization/`	**No EE imports**	Add platform-role logic for allowed-environments
app-connection.controller.ts	`app/app-connection/`	`@activepieces/ee-shared` (ApplicationEventName)	Add filtering; use `userService` (core) for platformRole

Module to change	Location	EE imports today	Plan impact
app-connection-service.ts	`app/app-connection/`	Yes (projectMemberService)	Add `metadata.creatorPlatformRole` and `metadata.environment` in upsert
flow.controller.ts	`app/flows/flow/`	Yes (assertUserHasPermissionToFlow, platformPlanService, gitRepoService)	Add filtering after list(); add `metadata.creatorPlatformRole` on create
flow.service.ts	`app/flows/flow/`	**No EE imports**	Add optional filter param or keep filtering in controller
invite-user-dialog.tsx	`packages/react-ui/`	No EE imports	Hide env selector for ADMIN invite

Potential challenges

1. **Edition (COMMUNITY vs ENTERPRISE/CLOUD)**
   This plan is **EE policy compliant**: it does **not** use `projectMemberService` or project members. Project access uses visibility filter (`applyProjectsAccessFilters` with `organizationId`), which works in all editions. Compatible with **COMMUNITY**, **ENTERPRISE**, and **CLOUD**.
2. **BMP piece identification**
   Connection filtering uses `pieceName` to detect BMP piece connections. The plan assumes a known BMP piece name (e.g. config or constant). Define the BMP piece name in one place (e.g. env or config) and reuse it for both environment and creator-role filtering.
3. **Organization projectId migration**
   Adding `organization.projectId` requires a DB migration. Add a new migration under `packages/server/api/src/app/database/migration/postgres/` (and sqlite if used). Organization and organization_environment are core tables, not EE, so migrations stay in core.
4. **Pagination and filtering**
   Flow and connection list filtering is done after fetching. If results are paginated, filtering after fetch can reduce page size (e.g. 10 requested, 3 pass filter). Options: (a) filter in controller after fetch, or (b) move filtering into the service/query so it happens in the DB. Option (a) is simpler but may affect pagination; option (b) is better for large lists.
5. **Existing flows/connections without creatorPlatformRole**
   Legacy flows and connections have no `metadata.creatorPlatformRole` . Treat as visible to everyone (or to ADMIN only, per product choice) for backward compatibility.

EE services used (no new EE dependencies)

Existing EE imports used by this plan (EE policy compliant):

- `projectRoleService` — used for PROJECT invitations only (unchanged)
- `platformMustBeOwnedByCurrentUser` , `projectMustBeTeamType` , etc. — used for invitation/auth (unchanged)
- `ApplicationEventName` — used for connection events (unchanged)

EE policy note: `projectMemberService` is **not** used for Admin/Operator/Member provisioning. Project access is controlled via project visibility filter (`applyProjectsAccessFilters` with `organizationId`), not project members, per MULTI_TENANT_EE_COMPLIANCE.

EE policy compliance

Per MULTI_TENANT_EE_COMPLIANCE.md and EE.md, the plan must comply with:

EE restrictions (do not use)

Feature	EE status	Plan compliance
TEAM projects	EE-only	Do NOT use; use PERSONAL only
Project members	EE-only	Do NOT use; use project visibility instead
Project roles	EE-only	Do NOT use; use platform roles only

EE-compliant approach for shared project and access

1. **Do NOT use `projectMemberService`**
   Do not add Admins/Operators/Members to projects via `project_member`. Use project visibility filters instead.
2. **Extend project visibility filter**
   In project-service.ts, extend `applyProjectsAccessFilters` to include:

- Projects where `project.organizationId = user.organizationId` — all users in the same org see the org's shared project.
- No `project_member` involvement; visibility is based on `organizationId`.

3. **Shared project as PERSONAL**
   The org's shared project remains `ProjectType.PERSONAL` with `ownerId` set to the first Admin. Visibility is granted via `organizationId` and the extended visibility filter, not via project members.
4. **Provisioning without project members**
   On invitation acceptance:

- Set `user.organizationId`.
- Create shared project if needed; set `project.organizationId`, `project.ownerId` (first Admin).
- Do **not** call `projectMemberService.upsert()`.
- Access is controlled by `applyProjectsAccessFilters` (users with same `organizationId` see the project).

5. **Platform roles only**
   All role logic uses `user.platformRole` (OWNER, ADMIN, OPERATOR, MEMBER) — available in all editions. Do not rely on `projectRolesEnabled` or project roles.
6. **PERSONAL projects only**
   All projects used in this flow are `ProjectType.PERSONAL`. Do not introduce TEAM projects.

Compliance checklist

Requirement	Status
Use PERSONAL projects only	Yes
No project members	Yes (visibility filter instead)
No project roles	Yes (platform roles only)
Platform roles	Yes (all editions)
No new EE modules	Yes

Requirement	Status
No EE file changes	Yes

Changes required for EE compliance

- **user-invitation.service.ts**
  Remove or avoid calls to `projectMemberService.upsert()` for Admin/Operator/Member provisioning. Rely on `organizationId` and project visibility instead.
- **project-service.ts**
  Extend `applyProjectsAccessFilters` to include `project.organizationId = user.organizationId` when `user.organizationId` is set, so org members see the org's shared project without using `project_member`.
- **All provisioning flows**
  Do not add users to `project_member`; set `user.organizationId` and rely on visibility filter for access. This applies to ADMIN and to OPERATOR/MEMBER when invited to org's shared project. (The current OPERATOR/MEMBER flow uses `projectMemberService` — replace with visibility-based access for EE compliance.)
- **OPERATOR/MEMBER invitations**
  Do not call `projectMemberService.upsert()` or `projectRoleService` for PLATFORM invitations to org's shared project. Set `user.organizationId`; project visibility filter (`project.organizationId = user.organizationId`) controls access. Note: Per-project permissions (Operator vs Viewer) would need an alternative if project roles are not used; platform role (OPERATOR vs MEMBER) can drive read/write behavior where needed.

Migration / Backward compatibility

- **Existing data**: Orgs that already have one Admin per (org, env) and separate projects need a migration path:
  - Either migrate to "one shared project per org" (e.g. pick one existing project as the org project, add other Admins as members, deprecate duplicate projects), or
  - Support both models temporarily (e.g. if `organization.projectId` is set, use shared project; else fall back to existing per-Admin project).
- **DB migrations**: Add `organization.projectId` if chosen; add `organization_admin` if used; adjust unique constraints on `organization_environment` if moving to multiple Admins per (org, env).

Summary of changes

Area	Change
Data model	One shared project per org; allow multiple Admins per org (e.g. org.projectId + organization_admin or user.organizationId).
Invite (backend)	ADMIN invite: organization only, no environment; no slot check; multiple Admins per org allowed.
Provisioning	First Admin for org creates shared project; subsequent Admins only join that project; no new project per Admin.
Org–env	Default "all envs" for org; same projectId for Dev/Staging/Prod; no single adminUserId slot.
Frontend	Hide environment selector for ADMIN invite; remove slot/availability logic for ADMIN.

Area	Change
Project visibility	All Admins of same org see the same (org) project.
OPERATOR/MEMBER	Invite into org's shared project when inviter is org Admin.
BMP connection popup	Allowed environments by platform role: MEMBER → Dev/Staging; OPERATOR → Production; ADMIN/OWNER → all. Backend `allowed-environments` endpoint returns role-based list.
Connections list	Filter by allowed envs: store `metadata.environment` for BMP connections on upsert; list API filters by user's allowed envs (MEMBER → Dev/Staging only, OPERATOR → Prod only, ADMIN/OWNER → all). Non-BMP pieces shown without filter. Filter by creator role: store `metadata.creatorPlatformRole` ; MEMBER sees Member+Admin connections; OPERATOR sees Operator+Admin connections; ADMIN sees all.
Flows list	Filter by creator role: store `metadata.creatorPlatformRole` ; MEMBER sees Member+Admin flows (not Operator-created); OPERATOR sees all; ADMIN sees all. See visibility matrix in section 10.

Implementation to-do list

Use this list to track implementation progress. Items are grouped by phase and ordered by dependency.

Phase 1: Data model and project visibility

- **1.1** Add `projectId` column to `organization` table — create migration in `packages/server/api/src/app/database/migration/postgres/` (and sqlite if used)
- **1.2** Update organization entity and service to support `organization.projectId`
- **1.3** Extend `applyProjectsAccessFilters` in project-service.ts to include `project.organizationId = user.organizationId` when `user.organizationId` is set
- **1.4** Ensure `project` entity has `organizationId` (already exists) and `projectService` uses it in visibility logic

Phase 2: Invitation flow (backend)

- **2.1** In user-invitation.module.ts: for OWNER inviting ADMIN, require only `organizationName` ; make `environment` optional; remove admin slot check
- **2.2** In user-invitation.module.ts: remove `checkAdminAvailability` call for ADMIN invites; allow multiple Admins per org
- **2.3** In user-invitation.service.ts: for ADMIN with organization — if org has no project, create shared project and set `organization.projectId` ; if org has project, do not create new project; set `user.organizationId` ; do NOT call `projectMemberService.upsert()`
- **2.4** In user-invitation.service.ts: for OPERATOR/MEMBER — use org's shared project (from invitation.organizationId); set `user.organizationId` ; do NOT call `projectMemberService.upsert()` (EE compliance)
- **2.5** In user-invitation.module.ts: when ADMIN invites OPERATOR/MEMBER, resolve org's shared project and store its ID in invitation instead of admin's personal project
- **2.6** Update organization-environment service: `checkAdminAvailability` — return "available" for ADMIN invite flow (or remove usage); update `upsert` / `listByOrganization` for new model if needed

Phase 3: Invitation flow (frontend)

- **3.1** In invite-user-dialog.tsx: hide Environment selector when OWNER invites ADMIN; show Organization only
- **3.2** Remove environment validation and "taken slot" logic for ADMIN path

- **3.3** Remove or simplify `adminAvailability` and `orgEnvironments` usage for ADMIN invite path
- **3.4** Update form schema: make `environment` optional for platform ADMIN invites

Phase 4: BMP allowed environments

- **4.1** In organization.controller.ts `GET /current-user/allowed-environments` : derive allowed environments from `currentUser.platformRole` — MEMBER → Dev/Staging; OPERATOR → Production; ADMIN/OWNER → all
- **4.2** Define BMP piece name constant (e.g. in shared or config) for use in connection filtering

Phase 5: Connections list filtering

- **5.1** In app-connection-service.ts `upsert` : store `metadata.creatorPlatformRole` (creator's platform role at creation time) for all pieces
- **5.2** In app-connection-service.ts `upsert` : when piece is BMP and value has `props.environment` , store `metadata.environment`
- **5.3** In app-connection.controller.ts `GET /` : after fetching connections, filter by creator role and by allowed environments (for BMP pieces)
- **5.4** Ensure app-connection controller has access to current user and userService for platform role

Phase 6: Flows list filtering

- **6.1** In flow.controller.ts `POST /` (create flow): add `metadata.creatorPlatformRole` from current user's platform role to flow metadata
- **6.2** In flow.controller.ts `GET /` (list flows): filter results by creator role — ADMIN and OPERATOR see all; MEMBER sees Member+Admin flows only
- **6.3** Ensure flow list receives current user context from request.principal for filtering

Phase 7: Project visibility and current project

- **7.1** When resolving "current project" for Admin: use `user.organizationId` to load org's shared project (`organization.projectId` or project where `project.organizationId = user.organizationId`)
- **7.2** Ensure project list for Admin includes org's shared project via extended visibility filter
- **7.3** Verify OPERATOR/MEMBER see org's shared project after accepting invitation (via visibility filter)

Phase 8: Testing and backward compatibility

- **8.1** Add or update tests for invitation flow (OWNER invites ADMIN, multiple Admins per org)
- **8.2** Add or update tests for allowed-environments endpoint (platform role based)
- **8.3** Add or update tests for connections list filtering (creator role, BMP environment)
- **8.4** Add or update tests for flows list filtering (creator role)
- **8.5** Verify backward compatibility: existing flows/connections without `metadata.creatorPlatformRole` visible to all; existing orgs handled (migration or fallback)

Use case scenarios for validation

Use these scenarios to validate the implementation after completion. Run both positive (expected success) and negative (expected failure/block) cases.

1. Admin invite and shared project

Positive scenarios

ID	Scenario	Steps	Expected result
P1.1	Owner invites first Admin for Org X	Owner selects platform invite, role ADMIN, organization "X", no environment selector shown	Invitation created with organizationId only; no environment required
P1.2	First Admin accepts invitation	Admin A accepts invite for Org X	Shared project created for Org X; Admin A gets organizationId; Admin A sees the shared project
P1.3	Owner invites second Admin for same Org X	Owner invites Admin B for Org X (same org as Admin A)	Invitation created; no "slot taken" error
P1.4	Second Admin accepts invitation	Admin B accepts invite for Org X	No new project created; Admin B gets organizationId; Admin B sees same shared project as Admin A
P1.5	Multiple Admins, same project	Admin A and Admin B both log in	Both see the same shared project for Org X in project list
P1.6	Environment selector hidden for ADMIN	Owner opens invite dialog, selects role ADMIN	Environment dropdown/radio is not shown; only Organization field shown

Negative scenarios

ID	Scenario	Steps	Expected result
N1.1	Missing organization for ADMIN invite	Owner submits ADMIN invite without organization name	Validation error: "Organization name required"
N1.2	OPERATOR cannot invite ADMIN	User with role OPERATOR tries to invite ADMIN	Invitation not allowed or authorization error
N1.3	MEMBER cannot invite ADMIN	User with role MEMBER tries to invite ADMIN	Invitation not allowed or authorization error
N1.4	Admin from Org A cannot see Org B project	Admin A (Org X) and Admin B (Org Y) exist	Admin A does not see Org Y's shared project; Admin B does not see Org X's project

2. BMP connection popup — allowed environments

Positive scenarios

ID	Scenario	Steps	Expected result
P2.1	MEMBER opens BMP connection popup	User with platformRole MEMBER creates BMP connection	Environment dropdown shows only Dev and Staging (no Production)
P2.2	OPERATOR opens BMP connection popup	User with platformRole OPERATOR creates BMP connection	Environment dropdown shows only Production
P2.3	ADMIN opens BMP connection popup	User with platformRole ADMIN creates BMP connection	Environment dropdown shows Dev, Staging, Production

ID	Scenario	Steps	Expected result
P2.4	OWNER opens BMP connection popup	User with platformRole OWNER creates BMP connection	Environment dropdown shows Dev, Staging, Production

Negative scenarios

ID	Scenario	Steps	Expected result
N2.1	MEMBER cannot select Production	MEMBER opens BMP connection popup	Production option is not available or is disabled
N2.2	OPERATOR cannot select Dev or Staging	OPERATOR opens BMP connection popup	Dev and Staging options are not available or are disabled

3. Connections list — filtering by creator role and allowed envs

Positive scenarios

ID	Scenario	Steps	Expected result
P3.1	MEMBER sees Member- and Admin-created connections	MEMBER views connections list	Sees connections created by MEMBER and ADMIN; does not see Operator-created
P3.2	OPERATOR sees Operator- and Admin-created connections	OPERATOR views connections list	Sees connections created by OPERATOR and ADMIN; does not see Member-created
P3.3	ADMIN sees all connections	ADMIN views connections list	Sees all connections (Member-, Operator-, Admin-created)
P3.4	MEMBER sees only Dev/Staging BMP connections	MEMBER views connections; BMP connections exist for Dev, Staging, Production	Sees only BMP connections with Dev or Staging; Production BMP connections are hidden
P3.5	OPERATOR sees only Production BMP connections	OPERATOR views connections; BMP connections exist for Dev, Staging, Production	Sees only BMP connections with Production; Dev/Staging BMP connections are hidden
P3.6	Non-BMP connections visible by creator role	MEMBER/OPERATOR views connections; non-BMP piece connections exist	Non-BMP connections visible based on creator-role filter only (no env filter)

Negative scenarios

ID	Scenario	Steps	Expected result
N3.1	MEMBER does not see Operator-created connections	MEMBER views connections list	Operator-created connections are not in the list
N3.2	OPERATOR does not see Member-created connections	OPERATOR views connections list	Member-created connections are not in the list
N3.3	MEMBER does not see Production BMP connections	MEMBER views connections; BMP connection with Production exists	Production BMP connection is not in the list

ID	Scenario	Steps	Expected result
N3.4	OPERATOR does not see Dev/Staging BMP connections	OPERATOR views connections; BMP connections with Dev/Staging exist	Dev/Staging BMP connections are not in the list

4. Flows list — filtering by creator role

Positive scenarios

ID	Scenario	Steps	Expected result
P4.1	MEMBER sees Member- and Admin-created flows	MEMBER views flows list	Sees flows created by MEMBER and ADMIN
P4.2	MEMBER does not see Operator-created flows	MEMBER views flows list	Operator-created flows are not in the list
P4.3	OPERATOR sees all flows	OPERATOR views flows list	Sees Member-, Operator-, and Admin-created flows
P4.4	ADMIN sees all flows	ADMIN views flows list	Sees all flows
P4.5	Legacy flows without creatorPlatformRole visible	MEMBER/OPERATOR views flows; legacy flow exists (no metadata.creatorPlatformRole)	Legacy flow is visible to all (backward compatibility)

Negative scenarios

ID	Scenario	Steps	Expected result
N4.1	MEMBER does not see Operator-created flows	MEMBER views flows list	Operator-created flows are not in the list

5. Project visibility — shared project per org

Positive scenarios

ID	Scenario	Steps	Expected result
P5.1	Admin A and Admin B see same project	Admin A and Admin B both belong to Org X	Both see the same shared project for Org X
P5.2	OPERATOR sees org project after accepting invite	Admin invites Operator to Org X; Operator accepts	Operator sees Org X's shared project (via visibility filter)
P5.3	MEMBER sees org project after accepting invite	Admin invites Member to Org X; Member accepts	Member sees Org X's shared project (via visibility filter)
P5.4	No duplicate projects for same org	Owner invites Admin A, Admin B, Admin C for Org X; all accept	Only one shared project exists for Org X; all three Admins see it

Negative scenarios

ID	Scenario	Steps	Expected result
N5.1	Admin from Org A does not see Org B project	Admin A (Org X), Admin B (Org Y)	Admin A does not see Org Y's project; Admin B does not see Org X's project

6. OPERATOR/MEMBER invitations by Admin

Positive scenarios

ID	Scenario	Steps	Expected result
P6.1	Admin invites Operator to org's shared project	Admin (Org X) invites Operator; Operator accepts	Operator gets organizationId; Operator sees Org X's shared project; no projectMemberService used
P6.2	Admin invites Member to org's shared project	Admin (Org X) invites Member; Member accepts	Member gets organizationId; Member sees Org X's shared project; no projectMemberService used
P6.3	Operator and Member in same org see same project	Admin invites Operator and Member to Org X; both accept	Both see the same shared project for Org X

Negative scenarios

ID	Scenario	Steps	Expected result
N6.1	OPERATOR cannot invite ADMIN	OPERATOR tries to invite ADMIN	Invitation not allowed or authorization error
N6.2	MEMBER cannot invite ADMIN	MEMBER tries to invite ADMIN	Invitation not allowed or authorization error

7. EE policy compliance

Positive scenarios

ID	Scenario	Steps	Expected result
P7.1	No project_member records for Admin provisioning	Admin accepts invite; check project_member table	No row added to project_member for the Admin
P7.2	No project_member records for OPERATOR/MEMBER (org flow)	Admin invites Operator/Member to org; they accept	No row added to project_member; access via visibility filter
P7.3	Only PERSONAL projects used	Check all projects created for orgs	All are ProjectType.PERSONAL
P7.4	Works in COMMUNITY edition	Run with AP_EDITION=COMMUNITY	Invitation acceptance and project visibility work (no project members used)

Negative scenarios

ID	Scenario	Steps	Expected result
N7.1	No TEAM projects created	Verify project types	No ProjectType.TEAM used in org flow
N7.2	No project roles used for org flow	Admin invites Operator/Member to org	projectRoleService and projectMemberService not called for PLATFORM org invitations

8. Backward compatibility

Positive scenarios

ID	Scenario	Steps	Expected result
P8.1	Legacy connections without creatorPlatformRole	Connection exists with no metadata.creatorPlatformRole	Visible to all roles (MEMBER, OPERATOR, ADMIN)
P8.2	Legacy flows without creatorPlatformRole	Flow exists with no metadata.creatorPlatformRole	Visible to all roles
P8.3	Legacy BMP connections without metadata.environment	BMP connection exists with no metadata.environment	Treated as visible to all (or document behavior)

This plan replaces the previous “one Admin per (org, env) slot” and “one project per Admin” behavior with the new requirement: **one shared project per organization, multiple Admins per org, Admin default-mapped to all environments**; **BMP connection popup environment options filtered by platform role (MEMBER: Dev/Staging; OPERATOR: Prod only)**; **connections list filtered by allowed envs and by creator role**; and **flows list filtered by creator role** (see visibility matrices in sections 9 and 10).