

# Customisation

## Documentation

*Duodu Randy*



*Disclaimer: Content can change at anytime and best to refer to website for latest information. |*





# Table of Contents

---

1 Custom cover page	4
1.1 Using custom cover template	4
2 Adjusting the output	6



# 1 Custom cover page

You can create a custom cover page using a [jinja2](#) or html file.

## Note

You should store the custom cover template file in the directory used for the [custom\\_template\\_path](#).

The plugin provides the following variables which you can use in your custom Jinja template:

- `cover_title`
- `cover_subtitle`
- `cover_image`
- `author`
- `author_logo`
- `copyright`
- `disclaimer`
- `site_url`
- `revision`
- custom variables from the [extra:](#) setting in your `mkdocs.yml`
- and all the options you provide under [local pdf metadata](#) of a Markdown file.

Using [jinja2](#) syntax, you can access all the data above. E.g. use `{{ author }}` to get the value for the [author](#) option:

```
plugins:  
  - pdf-generate:  
    author: Duodu Randy
```

## 1.1 Using custom cover template

You can specify the cover page to use for your PDF by following these steps:

### Step 1



Set the `custom_template_path` option for the plugin to the directory you want to store the cover template file.

```
plugins:
  - pdf-generate:
      custom_template_path: TEMPLATES PATH
```

## Step 2

In the directory you set as `custom_template_path`, create a template file which the name `cover`. E.g. `cover.html` or `cover.html.j2`.

In the cover template file, write your preferred template syntax into it.

*Example of a cover template file using Jinja2 syntax:*

```
<article id="doc-cover">
  {% if cover_image is defined %}
    <div class="wrapper upper">
      <div class="logo" style="background-image: url('{{ cover_image |
to_url }}');"></div>
    </div>
  {% else %}
    <div class="wrapper"></div>
  {% endif %}
  <div class="wrapper">
    <h1>{{ cover_title | e }}</h1>
    <h2>{{ cover_subtitle | e }}</h2>
    {% if revision %}
      <h3>Revision {{ revision | e }}</h3>
    {% endif %}
  </div>
  <div class="properties">
    <address>
      {% if author %}
        <p id="author">{{ author | e }}</p>
      {% endif %}
      <a href="{{ site_url }}" id="project_logo" title="Resource
Centre">
        
      </a>
    </address>
  </div>
  <div class="reserved_rights">
    <address>
      {% if copyright %}
        <p id="copyright">{{ copyright | e }}</p>
      {% endif %}
      {% if disclaimer %}
        <p id="disclaimer">{{ disclaimer | e }}</p>
      {% endif %}
    </address>
```



```
</div>  
</article>
```

### Step 3

Save the file changes and rebuild your MkDocs project.

## 2 Adjusting the output

The resulting PDF can be customized easily by adding a custom stylesheet such as the following:

```
@page {  
  size: a4 portrait;  
  margin: 25mm 10mm 25mm 10mm;  
  counter-increment: page;  
  font-family: "Roboto","Helvetica Neue",Helvetica,Arial,sans-serif;  
  white-space: pre;  
  color: grey;  
  @top-left {  
    content: '© 2018 My Company';  
  }  
  @top-center {  
    content: string(chapter);  
  }  
  @top-right {  
    content: 'Page ' counter(page);  
  }  
}
```

For this to take effect, you need to create a `custom.css` file.

#### Note

You should store the `custom.css` file in the directory used for the `custom_template_path`.

The plugin provides the following CSS variables which you can use in your `custom.css` file:

- `--title`
- `--subtitle`
- `--author`
- `--author-logo`
- `--copyright`



- `--type`
- `--site_url`
- `--revision`
- `--filename`
- `--chapter` (i.e. the H1 element in body content)

Using the `var()` CSS function, you can access all the data above. E.g. use `var(--author)` to get the value for the `author` option.

The custom CSS is appended to the MkDocs stylesheets so, you can override rules by using the `!important` CSS keyword but be cautious about it.