Hello Simtex!

iaacornus

August 15, 2552

1 This is a section: Math

This program is planned to support the ~~all of the~~, no only the **most** *basic* LaTeX features, you can use *inline math* with $a + b = c^2$. And this will be the *paragraph math*:

$$\oint \boldsymbol{B} \cdot d\boldsymbol{A} = 0 \tag{1}$$

And this is for *align*:

$$\sum_i \vec{B_i} \cdot \vec{\ell_i} = \mu_0 \left(I + \varepsilon_0 \frac{\Delta E \cdot A}{\Delta t} \right) \tag{2}$$

$$\sum_i \vec{E_i} \cdot \vec{\ell_i} = -\frac{\Delta B \cdot A}{\Delta t} \tag{3}$$

$$\sum_i E_i \cdot A_i = \frac{Q}{\varepsilon_0} \tag{4}$$

$$\sum_i B_i \cdot A_i = 0 \tag{5}$$

1.1 This is subsection: Images

You can also *insert* **images** with:
or by[this is not footnote] [its a superscript], anyway:
¡img src=”./sample_image.jpeg” align=”center”¿

1.1.1 This is subsubsection: Listings

The *code blocks* below presents the source code of the converted markdown file:

```
# This is a section: Math

This program is planned to support the **most** __basic__ LaTeX features, you can use !*inline math!* with $a + b = c^2$. And this will be the !*paragraph math!*:

$$\oint \boldsymbol{B} \cdot d \boldsymbol{A} = 0$$

And this is for !*align!*:

$$
\sum_{i} \vec{B_{i}} \cdot \vec{\ell_{i}} = \mu_{0} \bigg(I + \varepsilon_{0} \frac{\Delta E \cdot A}{\Delta t} \bigg)
\sum_{i} \vec{E_{i}} \cdot \vec{\ell_{i}} = - \frac{\Delta B \cdot A}{\Delta t}
\sum_{i} E_{i} \cdot A_{i} = \frac{Q}{\varepsilon_{0}}
\sum_{i} B_{i} \cdot A_{i} = 0
```

Figure 1: figure

```
$$

## This is subsection: Images

You can also __insert__ **images** with:

![figure](./sample_image.jpeg)

or by^^this is not footnote^^ -^its a superscript-^, ._anyway._:

<img src="./sample_image.jpeg" align="center">

### This is subsubsection: Listings

The !*code blocks!* below presents the source code of the converted markdown file:

\‘\‘\‘
[REDACTED TO AVOID RECURSION]
\‘\‘\‘

#### This is paragraph

Check [example.tex](./example.tex) for the **LaTeX**, rendition of this markdown file. The output of the
      command is always placed in ‘./out/‘ by **default**.
```

This is paragraph Check ./example.tex for the **LaTeX**, rendition of this markdown file. The output of the command is always placed in `./out/` by **default**.