EZ Chill High Velocity Metal Fan Packaging Artwork

Mr Brand - image-free searchable transcription

Pictures and diagrams were intentionally removed to reduce size. Readable labels, captions, specifications, warnings, and instructions were transcribed where recoverable. Keep the original manufacturer document for wiring, assembly geometry, part placement, and other visual-only details.

Product ID(s): 01288

Original source file(s): 01288.Instruction Manual.01.pdf

Source SHA-256: 2f8801e814c9a41a9ff605d4641c8816beb1262b62f9d0945f0c9c90013bc1c1

Original PDF pages: 1 | Recovered reading units: 5

Source page 1 (embedded text)

3 Speed

3 Speed

3 Speed

ULTRA QUIET

OPERATION

ULTRA QUIET

OPERATION

ULTRA QUIET

OPERATION

©2018 Mr. Brands, LLC

www.mrbrands.net

High Velocity

Metal Fan

3

d

High Velocity

Metal Fan

110-120V, 60hz, 145 Watts

6 ft 18 Guage Grounded Power Cord

3 Pin Plug

110-120V, 60hz, 145 Watts

6 ft 18 Guage Grounded Power Cord

3 Pin Plug

360° Adjustable Vertical Tilt

All Metal Construction

All Metal Fan Blade

Carry Handle

Rubber Feet For Stability

Controls On Back Of Unit

For Safe And Ease Of Use

High Velocity

Metal Fan

360° Adjustable Vertical Tilt

All Metal Construction

All Metal Fan Blade

Carry Handle

Rubber Feet For Stability

Controls On Back Of Unit

For Safe And Ease Of Use

3 Speed

ULTRA QUIET

OPERATION

ULTRA QUIET

OPERATION

ULTRA QUIET

OPERATION

High Velocity

Metal Fan

3

d

High Velocity

Metal Fan

110-120V, 60hz, 145 Watts

6 ft 18 Guage Grounded Power Cord

3 Pin Plug

110-120V, 60hz, 145 Watts

6 ft 18 Guage Grounded Power Cord

3 Pin Plug

360° Adjustable Vertical Tilt

All Metal Construction

All Metal Fan Blade

Carry Handle

Rubber Feet For Stability

Controls On Back Of Unit

For Safe And Ease Of Use

High Velocity

Metal Fan

360° Adjustable Vertical Tilt

All Metal Construction

All Metal Fan Blade

Carry Handle

Rubber Feet For Stability

Controls On Back Of Unit

For Safe And Ease Of Use

Distributed by:

Mr. Brands LLC

Bristol, PA 19007

www.mrbrands.net

Made in China

Item # 01288 EZ-CHILL

18" HIGH VELOCITY

METAL FAN

8

1 9 7 7 2

0 1 2 8 8

9

3 Speed

3 Speed

ity

ity

ity

ity

562

30

155 mm

155 mm

155 mm

525 mm

562

30

155 mm

155 mm

155 mm

525 mm

Source page 1 - Panel 1 (top left) (OCR)

Reading orientation normalized by 270 degrees.

PETE ! ---------

ne | Se

1. Ae we

, 7 s = WW <I) WY

J Lo ‘(Ss @N

1 MWS (CS >

“ ~ | Tr

@ -~<€ S\ SN

xo) Oy roy SS 3 <i

o) > A. \N on

ra - TMN WV) O}

CT "Oo =-_ <

| @

<< | "Tl @

| oD TO

SS \ | -

4 k SN >="

or \\\\ CORERI| V Whig NN

sey Uf lo

XA UY Y |

i

ao

DD ‘e ee ee

re ~ |

: sc

zzS sz Ky (Cc

Ss z ov <

\ i IN

yo e =e

I

:

Source page 1 - Panel 2 (top right) (OCR)

Reading orientation normalized by 270 degrees.

mo MM,

) Ae

£5 Ryan

Ow } NED aN (

Pr. oo > WWE WW

v as LY Ss

97 o=- & \

@ - | © S-

o. oa. NN =r

+r SN Ws =

Z ~< | Y) rT

0 Oo”

= S ra) -

\ g 0

S\\ \\ ~ 350

S\ii)\\ i\\\\ Wt

a Lea

OT AHN We ~

SMH) A Secu)

Z ,

oF |

4 ie

= = =. >

398 UJ a w((ive |

i Fi ow as |W

yo 8 fo OS |

fos a “2. TR

CT (. |

< SS

Source page 1 - Panel 3 (bottom left) (OCR)

ee WLLL TR NON VY l(/f Birk

Se in em

a 360° Adjustable Vertical Titt | Nt Rha Na BLY} }) l| I ! Hh! 1 (ills: $0

| All Metal Construction “Fw \ | \\ Ws sZF LU aan Wie hh \ N30)

» © All Metal Fan Blade a \\\ WS 2uy Gy // Hf)/ mh ST

PA SES (Se

| Rubber Fate Stability \ WN == LY] vy) Carry Handle

For Safe And Ease Of Use i NSS ZF, ors on Eck Of

| SS - | = ‘ Ve | For Safe And Ease Of Use

a= -_

| - >= “ew |

-

@ 110-120V, 60hz, 145 Watts

@ 6 ft 18 Guage Grounded Power Cord @ 110-120V, 60hz, 145 Watts

@ 3 Pin Plug @ 6 ft 18 Guage Grounded Power Cord

@ 3 Pin Plug

_

|

‘ >! < ye | _____ >

Source page 1 - Panel 4 (bottom right) (OCR)

TA f Pdf KZ Oe | i VVVVAV WL a YY E- ww

SSS ed fe

= a My - TAY EZCKI TLR In MH lies TEATRO \

a: 360° Adjustable Vertical Tilt \ Nt | AAAs. | Bf) /]} l| | I ! ph i \ Mls)

| All Metal Construction . 4 A \Ws Ws BOL IIIA. | y | WW)

i FRU Uy) NT

Carry Handle YA \ SS --s Yy // yy). / A SF

Rubber Feet For Stability \ = =F, y~ | _

| Controls On Back Of Unit ' -S Spy | ary Han’

Bi © Conte On Bock OF Uni \SS=Xiijf oe

| SX . rs \ 7: | or sare AN ase se

qa: -_-

| == =~

_-_

@ 110-120V, 60hz, 145 Watts

@ 6 ft 18 Guage Grounded Power Cord @ 110-120V, 60hz, 145 Watts

@ 3 Pin Plug @ 6 ft 18 Guage Grounded Power Cord

@ 3 Pin Plug

=

= ee sige

2 = TM

| |

< >! < > | eS