



Shenzhen Golden Security Technology CO.,Ltd

Add: 13 Floor, Building A1, New Era Gongrong Industrial Zone, Shenzhen, Guangdong, China
 Attns: Lilian Huang | T: +86 189 4879 4227 | E: lilian@cameralarms.com | W: <https://alarm-camera.en.alibaba.com>

Tuya Smart Security Alarm System				
Picture	Features	Model	Price	Packages
 WiFi+2G/4G Alarm System	WiFi+2G/4G smart intelligent alarm system 1. Compatible with Tuya/ Smart Life app, user can receive the alerts at anywhere and anytime. 2. Timer function: Support set schedules and receive real-time push notifications 3. Ultra-long battery: Built-in high-capacity battery ensures continuous operation. 4. Automatically triggers an alarm and sends instant phone calls/SMS alerts. 5. support multiple defense mode: defense zone mode, general defense zone mode, doorbell mode mode, door magnetic zone mode, emergency zone mode, disable zone mode, residual defensive zone function, and elderly SOS function.	GS-A01 (WIFI&2G) GS-A01 (WIFI&4G-EU version)	Enter voltage: DC 5 V Working current: < 100 mA Coding format: Receives and supports 1527/2262 GSM standard: 2G/4G Wi-Fi standard: IEEE802.11b/g/n wireless standard Backup battery: 3.7 V / 1000 mAh Working temperature: -10 °C~55°C Relative humidity: < 80% (no condensation) Product size:	1-50set: \$21 51-100set: \$20.5 101-1000set: \$19.8
 Tuya Smart Alarm system	WiFi+2G/4G touch screen smart intelligent alarm system 2.4 inch TFT display screen, concise user interface and menu hint design. Main interface status bar, date/clock indication, fairly obvious alarm host status.Built-in powerful performance CPU master based on 32-bit Cortex-M3 core. Based on ucos-ll operating system with multitasking design, great useroperation experience. WiFi/GSM/3G intranet alarm system, support different alarm channels,like APP push/SMS/voice monitoring/intranet center etc. to ensure the alarmpreformance stable and reliable. * Support SMS arm/disarm and voice arm/disarm * Support up to 100 learning/storage location for remote control,RFID cards andwireless detector. * Support many defense zones, such as gate, sos, bedroom, window, balcony,perimeter, smoke, gas, carbon monoxide, water leaking, etc. * Support the main power malfunction, backup power shortage, tamper alarm andother extended alarm. * Support entryexit zone, indoor zone, perimeter zone, 24-hour zone..etc. * Up to 5 groups preset alarm phone numbers,SMS on/off and dial on/off can be selectively. * Can store and inquire daily operation records and alarm records. * Support multi-language menu display, voice prompts and alarm SMS setting.Can record 20 seconds voice message and alarm voice. * Telephone function, support 5 groups re-dial number.		GS-103 (WIFI&2G) GS-103 (WIFI&4G-EU version) GS-103 (WIFI&4G-US version)	1-5set: \$28.50 6-50set: \$28.00 51-200set: \$27.50
	GS-103-2G-L (WIFI&2G) GS-103-4GEU-L (WIFI&4G-EU version)	Input voltage: DC5V(micro USB jack). Working current: <120mA Standby current: <80uA Siren output: 500mA Wireless frequency: 3.15MHz/433MHz/868MHz Wireless coding: EV 1527 2Gbands: 850/900/1800/1900MHz - WiFi standard: IEEE802.11b/g/n wireless standard. Back up battery: 3.7V/1000mAh lithium battery. Working temperature: -10~55°C Relative humidity: <80%RH(No freezing) - Product dimension:185x125x14.7MM (LxHxT)	1-5set: \$36.00 6-50set: \$35.50 51-200set: \$35.00	
		GS-103-4GUS-L GS-103 (WIFI&4G-US version)	1-5set: \$37.00 6-50set: \$36.50 51-200set: \$36.00	
	GS107-2G (Standard kit) GS107-4G (EU) (Standard kit) GS107-4G (US) (Standard kit)	Power input: DC 5V (micro USB standard interface power supply) Working current: <120mA Standby current: <80uA Alarm current: <500mA Wireless frequency: 433MHZ Wireless coding: EV 1527 2Gbands: 850/900/1800/1900MHz WiFi bands: IEEE802.11b/g/n RF standard Standby battery: 3.7V/500mAh lithium-ion Temperature range: 0°C ~ 55°C Humidity range: < 80%RH (No freezing)	1-5set: \$74.50 6-50set: \$73.50 51-200set: \$72.50	
			1-5set: \$82.00 6-50set: \$81.50 51-200set: \$80.00	
			1-5set: \$83.00 6-50set: \$82.00 51-200set: \$81.00	
 4.3" Touch Screen Smart Alarm System	4.3" Touch Screen Smart Alarm System * Simple and intuitive operation with 4.3" TFT full color touch screen with computer interface showing live status, date and time * 4G(only in 4G version)/ GSM(2G)+WiFi alarm system, supports multiple alarm notification channels, like APP push/SMS/ voice phone call * 90 wireless zones for accessories including sensors, remote controls and 10 zones for RFID tags * Support SMS arm/disarm and parameters setting, support voice arm/disarm. * Zone name editable * Support accessory low battery, AC power failure, hub or accessory battery power shortage, tamper alarm and other extended alarm. * Door/window unclosed notification while armed. * Support in/out zone, indoor zone, outdoor zone, 24 hours zone, doorbell and other zone settings. * Support 5 groups alarm phone number setting * External wired alarm connectors: 1 channel external wireless siren, 1 channel alarm linked wireless remote socket. * APP or hub can control electrical appliances by smart sockets (with same RF frequency). * Timed arm/disarm function. * Support operation logs and alarm events storage and tracing * Time synchronization function through GSM/WIFI network. * Support multi language menu, voice operation notice and SMS alarm settings * Support 20 seconds message and voice alarm. * support Amazon Alexa and google home	GS107-2G (Standard kit) GS107-4G (EU) (Standard kit) GS107-4G (US) (Standard kit)	1-5set: \$37.50 6-50set: \$37.00 51-200set: \$36.50	01.1.014
	1-5set: \$47.00 6-50set: \$46.50 51-200set: \$46.00			
	1-5set: \$48.00 6-50set: \$47.50 51-200set: \$47.00			
 2.4" Touch Screen Alarm system with touch screen & RFID function	2.4" Touch Screen Alarm system with touch screen & RFID function * Simple and intuitive operation with 2.4" TFT color screen showing live status, date and time, touch keypad and SOS button * Built-in powerful CPU based on 32-bit Cortex-M3 core with multi-task operation function * 4G(only in 4G version)/ GSM(2G)+WiFi alarm system, supports multiple alarm notification channels, like APP push/ SMS/ voice phone call... * 90 wireless zones for accessories including sensors, remote controls and 10 zones for RFID tags * With 3 hardened zone (EoLR) * Support SMS arm/disarm and parameters setting, support voice arm/disarm. * Zone name editable * Support accessory low battery, AC power failure, hub or accessory battery power shortage, tamper alarm and other extended alarm. * Door/window unclosed notification while armed. * Support in/out zone, indoor zone, outdoor zone, 24 hours zone, doorbell and other zone settings. * Support 5 groups alarm phone number setting * External wired alarm connectors: 1 channel external wireless siren, 1 channel alarm linked wireless remote socket. * APP or hub can control electrical appliances by smart sockets. * Timed arm/disarm function.	GS105-2G GS105-4G (EU) GS105-4G (US)	1-5set: \$26.70 6-50set: \$26.20 51-200set: \$26.00	01.1.014 01.1.015 01.1.018
	1-5set: \$34.50 6-50set: \$34.00 51-200set: \$33.50			
	1-5set: \$35.50 6-50set: \$35.00 51-200set: \$34.00			
	GS-106-2G * Simple and intuitive operation with 4.3" TFT full color touch screen with computer interface showing live status, date and time * Built-in powerful CPU based on 32-bit Cortex-M3 core with multi-task operation function * 4G(only in 4G version)/ GSM(2G)+WiFi alarm system, supports multiple alarm notification channels, like APP push/ SMS/ voice phone call... * 90 wireless zones for accessories including sensors, remote controls and 10 zones for RFID tags		1-5set: \$35.00 6-50set: \$34.50 51-200set: \$34.00	01.1.020

  <p>WiFi+2G/4G Alarm System</p>	<ul style="list-style-type: none"> • Support SMS arm/disarm and parameters setting, support voice arm/disarm. • Zone name editable • Support accessory low battery, AC power failure, hub or accessory battery power shortage, tamper alarm and other extended alarm. • Door/window unclosed notification while armed. • Support in/out zone, indoor zone, outdoor zone, 24 hours zone, doorbell and other zone settings. • Support 5 groups alarm phone number setting • External wired alarm connectors: 1 channel external wireless siren, 1 channel alarm linked wireless remote socket. • APP or hub can control electrical appliances by smart sockets (with same RF frequency). • Timed arm/disarm function. • Support operation logs and alarm events storage and tracing • Time synchronization function through GSM/WIFI network. • Support multi language menu, voice operation notice and SMS alarm settings • Support 20 seconds message and voice alarm. • support Amazon Alexa and google home 	<p>GS-106-4G (EU)</p> <p>Working current: >120mA Standby current: <80uA Alarm current: <50mA Wireless frequency: 433MHz Wireless coding: EV 1527 2Gbands: 850/900/1800/1900MHz Wi-Fi bands: IEEE802.11b/g/n RF standard Standby battery: 3.7V/500mAh lithium ion Temperature range: 0°C ~ 55°C Humidity range: < 80%RH (No freezing)</p> <p>GS-106-4G (US)</p>	<p>1-5set: \$43.50 6-50set: \$43.50 51-200set: \$43.00</p> <p>01.1.026</p> <p>1-5set: \$44.50 6-50set: \$44.50 51-200set: \$44.00</p>
---	---	--	--