

356		425-3M-TY	Unique Point 1 inch Mini PTZ Camera APP TUYA -IP Grade IP65 outdoor use -IR leds 6pcs IR leds -Lens 3.6mm	1-50pcs: \$26 51-100pcs: \$25 101-500pcs: \$23.5 02.2.59
357		425-5M-TY	Alexa With Alexa google home , more usd 2.5 (Default version without alexa voice control) -PC Support PC computer view -Storage TF Card (MAX 128GB) & Amazon cloud -Plug standard no plug(option ,	1-50pcs: \$36.6 51-100pcs: \$35.5 101-500pcs: \$33.8 02.2.49
358		GS-42L-4MP	Main features: ① 1/3" 4MP CMOS sensor ② Support two-way voice ③ Support infrared night vision mode ④ Support up to 128G SD card ⑤ H.264 encoding ⑥ Support human detection and motion detection ⑦ Support mobile phone alarm notification ⑧ Support 2.4G WiFi ⑨ Support Bluetooth network configuration Effective Pixels:2560(H) x 1440(V) Video pixels:1440p Shutter:1/15~1/10,000s Day/Night:Auto(ICR)/Color/B&W Lens&FOV(H/V/D):4.0mm@F2.0, 87° / 43° / 104°	SoC:Ingenic-T232N Bluetooth Module chip:NB7238 WiFi chip:NB7238 Bit Rate:32Kbps~1Mbps Frame Rate:15fps Dual Stream:Yes Audio:Two way Alarm Trigger:Motion detection, Human detection, Sound detection Mobile Phone OS:iOS 9 or later, Android 5 or later Security: AES128 1-50pcs: \$29.74 51-100pcs: \$28.8 101-500pcs: \$27.8
359		S518M-3MP-TY(APP-WIFI)	Advantage: 1. Combination of garden lighting and solar camera (industry first); 2. Solar support for extended installation (with 5 meters extension cord, the solar panel can be extended to the place with sunshine outside the eaves for installation) 3. The side-ear lamp can follow the rotation of the sphere without manual adjustment of the Angle; 4. Built-in three 21700 batteries (4000mA*3=12000MA); 5. Small volume, save freight; Easy installation Packing info. Carton : 50*40*42cm, Qty: 12pcs , Weight: 20Kg	 1-50pcs: \$51.00 51-499pcs: \$50.50 ≥500pcs: \$49.50 02.2.58
360		GS-SQW-2 (WIFI VERSION)	1. Main control: Ingenic T31ZL Sensor:SC2335 2. Movement detection :PIR detection + humanoid filtering, effective distance of 10 meters 3. Night vision mode :850nm infrared + white light, App selection switching control 4. Night vision distance: effective lighting distance is about 10 meters 5. Lens: HD lens 3.6mm F=2.8 FOV 120 degrees 6. Battery :21700*4 lithium battery, solar rechargeable battery 7. Charging :8W solar continuous charging, support USB interface full charging about 10 hours 8. Flexible monitoring of holder rotation: Holder rotation can be viewed at 320° horizontal and 90° vertical; 9. Memory: support up to 128GB TF card and cloud storage 10. Supports full-duplex intercom 11. Waterproof grade :IP66 12. Support access to Google Assistant and Amazon Alexa	 1-50pcs: \$55.04 51-499pcs: \$53.94 ≥500pcs: \$52.28 02.2.133
362		GS-SDB-1 (WIFI VERSION)	1. Main control: Ingenic T31ZL Sensor:SC233A 2. Mobile detection :PIR detection + humanoid filtering + regional setting, effective distance of 8 meters 3. Night vision mode :850nm infrared 4. Night vision distance: effective lighting distance is about 8 meters 5. Lens: HD lens 3MM F=2.0 FOV 180 degrees 6. Battery :18650*2 lithium battery, solar rechargeable battery 7. Charging: support USB interface full charging about 4 hours 8. Memory: supports up to 128GB TF card and cloud storage 9. Supports full-duplex intercom 10. Waterproof grade :IP66 11. Support access to Google Assistant and Amazon Alexa	 1-50sets: \$32.5 51-100sets: \$31.6 101-500sets: \$30.5 02.2.121



Shenzhen Golden Security Technology CO.,Ltd
 Add: 6th Floor, Unit 1, Building 1, Kailifang Plaza, Lianrun Road, Taoyuan Community, Dalang Street, Longhua District, Shenzhen
 Attns: Lillian Huang | T: +86 189 4879 4227 | E: lillian@cameralarms.com | W: <https://alarm-camera.en.alibaba.com>

No.	Picture	Model	Features	Price (EXW)	Compatible devices												
259		GS-MS102	Smart Garage Controller .This product is suitable for dry contact motor controlled garage doors Input:AC100-240V 50/60HZ Output:NO Power:300W Electricity:16A	Sample: \$12.53 50~100pcs: \$12.15 201~20K pcs: \$11.90	 02.4.0259												
260		WIFI-LZ	1) Valve pressure: 1.6MPA 2) Rated torque: 30-60kg.CM 3) Rated speed:76rpm 4) Scheduled time for start and stop. 5) Low noise. 6) Auto stop when blocked. 7) Support Amazon Echo voice control.	Sample: \$10.72 50~100pcs: \$10.51 101~200 pcs: \$10.30	02.4.0249												
261		ZIG-LZ	1) Valve pressure: 1.6MPA 2) Rated torque: 30-60kg.CM 3) Rated speed:76rpm 4) Scheduled time for start and stop. 5) Low noise. 6) Auto stop when blocked. 7) Support Amazon Echo voice control.	Sample: \$10.72 50~100pcs: \$10.51 101~200 pcs: \$10.30	02.4.0306												
262		WIFI-QY-WH	1) Valve pressure: 1.6MPA 2) Rated torque: 30-60kg.CM 3) Rated speed:76rpm 4) Scheduled time for start and stop. 5) Low noise. 6) Auto stop when blocked. 7) Support Amazon Echo voice control.	Sample: \$19.6 50~100pcs: \$19.6 101~200 pcs: \$19.3	02.4.0295												
263		ZIG-QY-WH	1) Valve pressure: 1.6MPA 2) Rated torque: 30-60kg.CM 3) Rated speed:76rpm 4) Scheduled time for start and stop. 5) Low noise. 6) Auto stop when blocked. 7) Support Amazon Echo voice control.	Sample: \$19.9 50~100pcs: \$19.7 101~200 pcs: \$19.6	02.4.0322												
264		GS-ZTRV-PJ-601	Zigbee Smart Thermostatic Radiator Valve - Accessible via your smartphone app, easy remote control after successful network configuration - Programmable device with customized exclusive temperature plan, up to 6events allowed to set each day - After no operation for more than 5 seconds, the device enters sleep mode, which can save energy and prolong battery life - Long press the Set Button for 3 seconds to switch the screen display direction. Specifications Power supply: 3x1.5V alkaline AA batteries (not included) Protection degree: IP20 Ambient temperature: 0-50 °C	Sample: \$20.82 50~100pcs: \$20.43 101~200 pcs: \$19.78	02.4.0394												
265		GS-ZTRV-PJ-603	Wi-Fi Smart Thermostatic Radiator Valve Automatic debugging function, suitable for all kinds of mainstream valves! The device supports Wi-Fi fast distribution network, no additional gateways required Intelligent PID algorithm, efficient control of valve opening and closing, energy saving and environmental protectionThe motor adopts ultra-quiet technology to minimize noise pollutionThe device has activated the automatic conversion of summer time and wintertime, which can be activated or terminated as needed Specifications Power supply: 3x1.5V alkaline AA batteries (not included) Protection degree: IP20 Ambient Temperature: 0-50 °C Surface temperature: 90°C Max (at the radiator) Connection: M30x1.5mm Linear Travel: 4.3mm Dimensions(WXHXD): 58.40X97mmX58.40mm Weight: 117.70g	Sample: \$24.77 50~100pcs: \$24.30 101~200 pcs: \$23.53	02.4.0383												
		BLE-YC02-EU-G3/4 EU standard	Bluetooth 2-way water valve controller *User can Tuya Smart or Smart life APP remote control the irrigation system *Users can view irrigation information for the past 7 days through the Smart Life mobile app, thus saving water. *If without a Bluetooth gateway, the Smart Life app's control range is limited to 50 feet. For distances exceeding 50 meters, a Bluetooth mesh gateway is required. <table border="1"><tr><td>Bluetooth Range</td><td>49.2ft without interference</td></tr><tr><td>Working Water Pressure</td><td>7.25-116 psi</td></tr><tr><td>Working Temperature</td><td>40.1°F-113°F(4.5°C-45°C)</td></tr><tr><td>Rain Delay Time</td><td>1 day and up to 7 days</td></tr><tr><td>Waterproof</td><td>IPX5</td></tr><tr><td>Battery</td><td>4x AA alkaline batteries</td></tr></table>	Bluetooth Range	49.2ft without interference	Working Water Pressure	7.25-116 psi	Working Temperature	40.1°F-113°F(4.5°C-45°C)	Rain Delay Time	1 day and up to 7 days	Waterproof	IPX5	Battery	4x AA alkaline batteries	Sample: \$24.77 50~100pcs: \$24.30 101~200 pcs: \$23.53	 02.4.0383
Bluetooth Range	49.2ft without interference																
Working Water Pressure	7.25-116 psi																
Working Temperature	40.1°F-113°F(4.5°C-45°C)																
Rain Delay Time	1 day and up to 7 days																
Waterproof	IPX5																
Battery	4x AA alkaline batteries																
		BLE-YC02-EU-NH3/4 US standard	 <table border="1"><tr><td>Bluetooth Range</td><td>49.2ft without interference</td></tr><tr><td>Working Water Pressure</td><td>7.25-116 psi</td></tr><tr><td>Working Temperature</td><td>40.1°F-113°F(4.5°C-45°C)</td></tr><tr><td>Rain Delay Time</td><td>1 day and up to 7 days</td></tr><tr><td>Waterproof</td><td>IPX5</td></tr><tr><td>Battery</td><td>4x AA alkaline batteries</td></tr></table>	Bluetooth Range	49.2ft without interference	Working Water Pressure	7.25-116 psi	Working Temperature	40.1°F-113°F(4.5°C-45°C)	Rain Delay Time	1 day and up to 7 days	Waterproof	IPX5	Battery	4x AA alkaline batteries	Sample: \$25.77 50~100pcs: \$25.30 101~200 pcs: \$24.53	
Bluetooth Range	49.2ft without interference																
Working Water Pressure	7.25-116 psi																
Working Temperature	40.1°F-113°F(4.5°C-45°C)																
Rain Delay Time	1 day and up to 7 days																
Waterproof	IPX5																
Battery	4x AA alkaline batteries																
266			Tuya WiFi Zigbee circuit breaker and WiFi meter														
267		WCB-SC-1P80-WIFI	WiFi circuit breaker 1P 10A-80A support SAAS	Sample: \$29 50~100pcs: \$28	02.4.0325												
268		WCB-SC-1P80-ZIG	Zigbee circuit breaker 1P 10A-80A support SAAS	Sample: \$31 50~100pcs: \$30	02.4.0310												
269		WCB-SC-1P100-WIFI	WiFi circuit breaker 1P 100A support SAAS	Sample: \$31 50~100pcs: \$30	02.4.0326												
270		WCB-SC-1P100-ZIG	Zigbee circuit breaker 1P 10A-80A support SAAS	Sample: \$33 50~100pcs: \$32	02.4.0331												
271		WCB-SC-2P80-WIFI	Wifi breaker 2P 10A-80A support SAAS	Sample: \$33 50~100pcs: \$32	02.4.0362												
272		WCB-SC-2P80-ZIG	Zigbee breaker 2P 10A-80A support SAAS	Sample: \$35 50~100pcs: \$33	02.4.0336												
273		WCB-SC-2P100-WIFI	WiFi circuit breaker 2P 100A support SAAS	Sample: \$35 50~100pcs: \$33	02.4.0363												
274		WCB-SC-2P100-ZIG	Zigbee circuit breaker 2P 100A support SAAS	Sample: \$37 50~100pcs: \$35	02.4.03191												