48		S52G	Impedance: 8Ω Power: 10-40W Appearance diameter: 205mm Installation size: Φ180mm	**Sample: $22.98** **10~50pcs: $22.86** **50-100 pcs: $22.5**	
49		S65T	Impedance: 8Ω Power: 10-60W Appearance diameter: 232mm Installation size: Φ200mm	**Sample: $46.8** **10~50pcs: $46.3** **50-100 pcs: $45.8**	
50	 **Bluetooth Ceiling Speakers**	GS-CH601	**Suitable for: hotels, exhibition halls, home living room, supermarkets, canteens, stores, script killing stores and other multi-scene applications.** **Ceiling speaker for: fixed resistance 8Ω, 30W;** Function support: Bluetooth, U disk, TF card, AUX, TWS interconnection; Bluetooth version: Jerry program, Bluetooth 5.0; Transmission distance: straight line distance without blocking 12 meters; Battery capacity: no battery, can be connected to 12V power supply; Speaker size: 5 inch; Product size: Φ18.6*7cm; Opening size: Φ16-16.5cm; Single with packing weight: 0.8kg;. Single box size: 21*21*9cm; Outer box size: 17*17*21cm; A box of 20 units, gross weight: 16.6kg, net weight: 16.0kg. Ceiling speakers are: full-frequency hi-fi speakers, no need for amplifier, direct Bluetooth connection, 1 host with up to 3 sets of subs, multi-scene application is recommended to shoot more than one set of hosts with the use of subs (TWS interconnect or with amplifier)	①GS-CH601-Z Master speaker:$17.50/pcs ②GS-CH601-F sub-speaker:$12.5/pcs ③GS-YK03 Remote controller:$3.60/pcs ④5M cable:$1.80 ⑤10M cable:$3.60 ⑥Power Adapter:$0.50/pcs	 ①GS-CHS01-Z Master speaker:02.4.0846 ②GS-CH601-F sub-speaker:02.4.0847 ③GS-YK03 Remote controller:02.4.0707 ④5M cable:02.4.0848 10Mcable：02. 4. 0849
51	 **High quality ceiling speaker Bluetooth 5.0**	GS-S530-B (Master speaker)	**Bluetooth Ceiling Speaker -Master speaker** Product dimension: 200mm*85mm Installation dimension: 175mm*100mm FO: 63Hz Frequency response: 55Hz~20KHz Rated power: 20W Sensitivity: 90dB1W/1W Resistant: 5Ω 	**1-50pcs: $34.50** **51-100pcs:$33.50**	S530-B Packing quantity: 12PCS Packing size: 51.5X51.5X32CM Packing weight: 20KG 01.9.136
52	 **High quality ceiling speaker -Secondary speaker**	GS-S530 (Slave speaker)	**Slave speaker** Product dimension: 200mm*85mm Installation dimension: 175mm*100mm FO: 63Hz Frequency response: 55Hz~20KHz Rated power: 20W Sensitivity: 90dB1W/1W Resistant: 5Ω	**1-50pcs: $24.15** **51-100pcs:$23.15**	S530 Packing quantity: 12PCS Packing size: 51.5X51.5X32CM Packing weight: 19KG 01.9.135
53	 **ZIGBEE Gateway（wired RJ45 port)**	ZIG01	**ZIG-01 is a Lan connection Ethernet (wired) smart home gateway. It supports all kinds of tuya smart Zigbee sub-devices, such as Zigbee wall switch,zigbee PIR human movement sensor, Zigbee temperature and humidity sensor,Zigbee curtain motor,etc.** **Parameter:** 1)Standard:IEEE 802.15.4 2)Frequency:2.4~~2.485GHz 3)Transmission rate: 250kbps 4)Receiving sensitivity:-102dBm，PER<10% 5)Open area transmission distance: 100M to 200M - Power supply: 5V1A - Working temperature: -10~45℃ - Wireless communication protocol: Lan connectip + Zigbee - Product dimension: 60*60*15mm	**Sample: $20.90** **50~100pcs:$20.50** **101~200 pcs: $20.30** **200~1K pcs: $20.00**	tuya works with the Google Assistant WORKS WITH amazon alexa 01.7.025
54	 **Mini smart home WIFI+Bluetooth+Zigbee wireless gateway**	GS-GW006	**This is is a Multi-mode WiFi+Zigbee +Bluetooth smart home gateway. It supports all kinds of tuya smart Zigbee sub-devices, such as Zigbee wall switch,zigbee PIR human movement sensor, Zigbee temperature and humidity sensor,Zigbee curtain motor,etc.** **Parameter:** **1)Standard:IEEE 802.15.4** **2)Frequency:2.4~~2.485GHz** **3)Transmission rate: 250kbps** **4)Receiving sensitivity:-102dBm，PER<10%** **5)Open area transmission distance: 100M to 200M 6) Support devices: 99+** - Power supply: Micro-USB - Working temperature: -10~55℃ - Wireless communication protocol: 2.4G wireless & Zigbee & BLE & Mesh - Product dimension: 60*60*15mm - Weight: 33g Communication protocol: WiFi+Zigbee+bluetooth	**Sample: $12.50** **50~100pcs:$12.00** **101~200 pcs: $11.50**	tuya works with the Google Assistant WORKS WITH amazon alexa 02.4.0667
55	 **Tuya Smart gateway** **(Zigbee/Bluetooth/Multi-mode verson for option)**	Gateway LY-122 Bluetooth version	The bluetooth gateway is only used for the bluetooth robot, it is not a necessary part. You can only use it if you connect to a Google/Amazon device. 	**Bluetooth version** **Sample: $8.6** **50~200 pcs: $7.9** **200~1K pcs: $7.6**	tuya works with the Google Assistant WORKS WITH amazon alexa
56		Gateway LY-122 Zigbee version		**Zigbee version** **Sample: $12.8** **50~200 pcs: $12.3** **200~1K pcs: $11.9**	
57		Gateway LY-122 Multimode version		**Multi- mode version** **Sample: $12.50** **50~100pcs:$12.00** **101~200 pcs: $11.50**	
58	 **Zigbee&BLE gateway hub**	**GS-BLE-G01**	**ZigBee+Bluetooth Multimode Gateway** (with USB cable) One-key arm/disarm/sound and light alarm/voice prompt/doorbell/alarm clock/LED indicator adjustment/security SAAS - Support voice control - Support Google Home finger robot - Support Zigbee PIR movement sensor - Support Bluetooth humidity and temperature sensor - Zigbee blind curtain motor Single weight: 179g Product size:9.3*9.3*8.6 FCL weight: 10kg Parameter: - Power supply: 5V 1A - Working temperature: -10~45℃ - Wireless communication protocol: 2.4G wireless & Zigbee & BLE & Mesh - Product dimension: 92*92*40mm	**Sample: $25.50** **50~100pcs: $25.00** **101~200 pcs: $24.50** **200~1K pcs: $24.00**	tuya works with the Google Assistant WORKS WITH amazon alexa 02.4.0269
59	 **Matter Zigbee Wired gateway**	**GS-MZHUB**	**This is is a Multi-functional MATTER Wired Gateway. It supports both Tuya app and Apple Homekit App.** **- Can be acted as a Matter Gateway** **- Can be acted as a ZigBee Gateway** **- Works with Alexa, Google Home Asistant** **- Can support up to 128 smart devices** **- Lan network connection** **Internet of Everything: It can be seamlessly linked with smart home devices on various platforms. Whether it is lamps or sockets, Matter gateway can interconnect with them to provide agreed control and management.** **Specification** **- Power supply: Type C, Power input: 5V1A** **- Working temperature: -10~55℃** **- Wireless communication protocol: 2.4G wireless & Zigbee** **- Product dimension: 60*60*15mm** **- Weight: 33g** **- Communication protocol: Zigbee, Thread**	**Sample: $29.50** **50~100pcs: $28.58** **101~200 pcs: $28.00**	 **02.4.0733**

60	 2.4GHz WIFI 5 GHZ WIFI Zigbee Sigmesh BLE BLE Long Range Dual-Band Wireless Multi-mode gateway	THP01-ZB-V5	**Dual-Band Wireless Multi-mode gateway** **1.**THP01-ZB-V5 gateway enables remote upgrades firmware of Zigbee, BLE, and SigMESH sub-devices. **2.**It supports right-angle WiFi signal strength diagnosis for routers and gateways, including signal strength detection between Zigbee, BLE, and Sigmesh devices and the gateway. 3.Maximum number of localized scenarios and automation supported: 100. 4.Supports remote gateway restart function WIFI : 2.4G/5G Main frequency: 330Mhz Antenna:IPEX antenna Flash:128Mbit Memory:32G Maximum No.of 220V smart devices:128pcs Maximum low-power Zigbee sub-devices:32pcs Maximum Sigmesh sub-devices:128pcs. Maximum BLE Long Range sub devices:4pcs Product Size:66*66(20.4mm Power supply:5V DC,1A	Sample: $15.8 50~100pcs: $14.8 101~200 pcs: $13.96	 最多支持本地化场景和自动化的数量
61	 2.4 GHz Wi-Fi| 5 GHZ Wi-Fi Dua Band Tuya Smart wirelessBluetooth Gateway(BLE / BLELong Range / SigMesh / Beacon)	Without Zigbee Only BLE SigMESH gateway THP01-B-V6	**Dual band wireless bluetooth gateway notonly supports 2.4 GHz Wi-Fi, but also 5 GHZWi-Fi. It supports BLE, BLE Long RangeSigMesh and Beacon Devices.** **- Max Connectivity** 4 BLE/BLE Long Range devices (Phase 2 upgrade tosupport8 BLE devices),or 64 Beacon devices (Phase2),or 128 SigMesh devices. **- BLE Long Range(Phase 2):** Open area with a distance of 300 meters;Operates over 40m through 35cm reinforced concrete **- Sigmesh 2.1(Phase 2):** Low latency, high control success rate, groupOTA **- Local Automation:** -The localautomation responses even when theexternalnetworkis disconnected **- OTA:** Support BLE, BLE Long Range,SigMesh andBeacon devices OTA through gateway remotely. **- Signal Strength Detection:** Support Wi-Fi strength diagnosis between router and gateway, as well as Bluetooth strength between BLE devices and gateway. **- Faulty Replacement:** Seamlessly migrate your original automation tothe new gateway without reconfiguration	≤10pcs:$8.7 ≤50pcs:$7.9 ≤500pcs:$8.5	 Protocol | Radio Frequency 2.4G Wi-Fi | 2400.0-2483.5MHz 5G Wi-Fi | 5150-5875MHz BLE 5.0 | 2402-2480MHz
62	 Tuya 2.4Gi+5G Wi-Fi Zigbee Gateway	THP12-Z-V5	**Smart Home I RTC Local Timing I Project Deployment I Fault Replacement ! High ReliabilityLocalizationIContinuous CapabilityUpgrade** **1)The core hub of the smarthome, controlling and managing smart devices** It is a professional gateway for the whole smart house, supporting Wi-Fior Ethernet access to the network. Through the access and flexiblecombination of diversified devices, it realizes the intelligence of homescenes, such as remote control, device linkage, various scene modes.etc., allowing you to enjoy smart home life as you wish. **2)Highly stable and reliable Zigbee gatewayTransmission** It adopts low-power, stable and reliable Zigbee communication methoddeveloped based on Ziqbee3.0 standard, connects the whole house.supports 200 sub-devices access and fast and stable control. and can easily play with rich scenarios of smart home. **3)The local deployment capabilityof the gateway is efficient and stable** Data is stored in the local gateway, and all working conditions are stable and controlled.Supports local linkage, scenes, and groups.Supports LAN linkage, and the Master level is the highest, providing highly reliable and stable local management. 4)**Can access the entirehouse SaaS and App Provide professional solutions integrating software and hardware** Supports network-free construction deploymentSupports gateway fault replacement, sub-device fault replacement.etc.under abnormal conditions, simplifies the complexity and **Smart M Gateway is a comprehensive Mattergateway**.The uplink supports Wi-Fi andEthernet, and the downlink supports theecological interoperability of Matter, BLE andZigBee devices **- Matter Capabilities** Standard Matter gateway, with bridge, controller,and border router roles.Supports access tostandard thread devices and third-party standard matter over WiFidevices, and also supports subdevice bridges such as zigbee **- Max Connectivity:** 128 Zigbee devices,or 200 Sigmesh devices,or 32 Matter over thread devices. **- Wireless distance:** ZigBee range > 200 meters, Thread range > 140meters, Bluetooth range > 150 meters **- Optional power supply methods:** Supports plugging in 4G assistant to expand 4G networking. **-Faulty Replacement:** Seamlesslymigrate your original automation to thenew gateway without reconfiguration. **- Extended cloud connection method:** Supports plugging in 4G assistant to expand 4Gnetworking.	≤10pcs:$15.5 ≤50pcs:$14.8 ≤500pcs:$14.3	Input :5V-1A Operating Humidity: 10-90% RH(Non-condensing) Wireless Protocols: WIFI, Zigbee Size:86*86*18mm Weight:113g
64	 Ethernet + 2.4 GHz Wi-Fi+ 5 GHZ Wi-Fi Tuya smart ZigBee BLE Bluetooth Mesh and Thread Matter Gateway	THP23-ZB-X (Matter Gateway)		sample:$45.5 ≤50pcs:$44.5 ≤500pcs:$43.5	
65	 Ethernet + 2.4 GHz Wi-Fi+ 5 GHZ Wi-Fi Tuya smart ZigBee BLE Bluetooth Mesh and Thread Matter Gateway	THP23-ZB-X-4G (Matter gateway + 4G communication asistant)	**Smart M Gateway is a comprehensive Mattergateway.The uplink supports Wi-Fi andEthernet, and the downlink supports theecological interoperability of Matter, BLE andZigBee devices** **- Matter Capabilities** Standard Matter gateway, with bridge, controller,and border router roles.Supports access tostandard thread devices and third-party standard matter over WiFidevices, and also supports subdevice bridges such as zigbee **- Max Connectivity:** 128 Zigbee devices,or 200 Sigmesh devices,or 32 Matter over thread devices. **- Wireless distance:** ZigBee range > 200 meters, Thread range > 140meters, Bluetooth range > 150 meters **- Optional power supply methods:** Supports plugging in 4G assistant to expand 4G networking **-Faulty Replacement:** Seamlesslymigrate your original automation to thenew gateway without reconfiguration. **- Extended cloud connection method:** Supports plugging in 4G assistant to expand 4Gnetworking. Operating Temperature :0-40℃ Operating Humidity: 10-90% RH	sample:$63.5 ≤50pcs:$62.5 ≤500pcs:$61.5