



 <p>WiFi alarm system</p>	<ul style="list-style-type: none"> * Wi-Fi alarm system, supports multiple alarm notification channels, like APP push/ voice phone call, etc. * Support APP remote arm/disarm, parameter setting and accessory management. * Based on uCOS - III operation system with multi-task function * WiFi online to obtain equipment latest working status, auto alarm when offline. * Built-in powerful CPU master based on 32-bit Cortex-M3 core. * Support the AC power failure, backup power shortage, tamper alarm and other extended alarm. *Support APP remote arm / disarm/recording/take picture/monitoring. * Support main brands cameras linking alarm, remote recording, monitoring,checking. 	GS150 WiFi alarm system	Power input: DC 5V (micro USB standard interface power supply) Working current: <120mA Wireless frequency: 433MHz Wireless coding: EV 1527 Wi-Fi: IEEE802.11.b/g/n RF standard Standby battery: 3.7V/800mAh lithium-ion Temperature range: 0℃~+55℃ Humidity range: < 80%RH (No freezing)	1-5set: \$22 6-50set: \$21 51-200set: \$19.5	 <p>1 wireless PIR detector, 1 wireless door sensor, 2 remote controls, 1 wireless siren 1 power adapter</p>
 <p>WiFi gas alarm</p>	<ol style="list-style-type: none"> 1.Self test function 2.Motorola IC control, Reliable without false alarming 3.Field audio and visible alarming 4.Simple installation 5.Excellent reliability & high stability 6.Low battery alarm 7.Durable sensor head 8.Less affected by other organic solvent 8. Operating temperature:-0°C ~+50°C 9. Humidity range: < 80%RH (no freezing) 10. Alarm output: Relay output (relay contact load 3A 250V AC / 3A 30V DC) 	GS210W	<ol style="list-style-type: none"> 1. Working voltage: DC 5V (micro USB) 2. Alarm current: <120mA 3.Response time: <30s 4.Sensor lifetime: 3 years 5.Installation method:wall mounting 6.Air pressure:86~106Kpa 7.2Gbands:850/900/1800/1900MHZ 	1-50pcs:\$12 51-100pcs:\$11.5 101-500pcs:\$10.5	with stand and gift box 01.7.012509
 <p>WiFi smoke alarm</p>	<ol style="list-style-type: none"> 1. High sensitivity smoke detection. 2. Built-in thermistor sensor, high temperature alarm function 3. Smart WIFI remotely push alarm information. 4. Smart APP control. 5. With manually test, manually mute. 6. Sound and light alarm. 	GS443W	<ol style="list-style-type: none"> 1. Working voltage: DC 9V alkaline battery 2. Static current: ≤10uA 3. Alarm current: ≤100mA 4. Alarm sound:>80db 5. Operating temperature:-0°C ~+50°C 6. Humidity range: < 95%RH (no freezing) 7. Low voltage alert:3.9V±0.3V 	1-50pcs: \$13.00 51-100pcs: \$12.90 101-500pcs: \$12.50	with stand and gift box 01.1.85
 <p>WiFi Door/Window alarm</p>	<ol style="list-style-type: none"> 1. support tuya smart APP 2. support google home & amazon alexa 3. door open alert, app notification 4. real time monitoring for in & out at the quarantine places. 5. App remote monitoring, multi-level prevention and control 6. 24 hours monitoring, solve the problem for fatigue on duty 6. installation distance: ≤2cm 7. trigger range: 2-3cm 5. Operating temperature:-0°C ~+50°C 	D41	<ol style="list-style-type: none"> 1. Working voltage: 3V (2*AA battery) 2. Working current: ≤19-59mA 3. standby current: ≤35uA 4. connect method: wifi (802.11b/g/n) 5. wifi range: 30m 	1-50pcs:\$5.3 51-100pcs:\$5.2 101-500pcs:\$5.1	with stand and gift box
Accessories that can work with GS105,GS106,GS107,GS150					
 <p>Remote controller</p>	<ol style="list-style-type: none"> 1. High stability: imported SMD components with SMT, surface acoustic resonator stabilization (SAW),6.5G UHF triode 2. Black and white color for choice 3. 4 remote controller buttons 4. 433mHZ,1527 CODE 	GS-RMC09		1-50pcs:\$2.80 51-100pcs:\$2.70 101-500pcs:\$2.30	with stand and gift box 02.2.110
 <p>wireless PIR motion sensor</p>	<ol style="list-style-type: none"> 1. Adopt the latest technology, the latest program algorithm microprocessor 2. Ultra-low power consumption, longer battery life 3. Built-in million code 4. Wireless transmission of data signals 5. Low voltage alarm function 6. All-round automatic temperature compensation 7. Intelligent logic analysis to prevent false positives 8. Anti-white light, anti-strong light, anti-strong wind, high temperature 9. Anti-high frequency interference 	GS-96R	◎ Working voltage: 9V 6F22 battery ◎ Transmission frequency: 433MHz ◎ Coding method: EV1527 ◎ Transmission distance: ≥120M ◎ Detection angle: wide angle 110°/curtain 15° ◎ Detection distance: 12M/8M (wide angle /curtain)	1-50pcs:\$4.30 51-100pcs:\$4.2 101-500pcs:\$4.00	01.1.54
 <p>Curtain/Motion PIR motion sensor</p>	<ol style="list-style-type: none"> 1. Using a low-power microprocessor 2. Ultra-low power consumption, longer battery life 3. Built-in million code 4. Wireless transmission of data signals 5. Low voltage alarm function 6. All-round automatic temperature compensation 7. Intelligent logic analysis to prevent false positives 8. Anti-white light 9. Anti-high frequency interference 	GS-92RM curtain PIR motion sensor	◎ Working voltage: 3V, two large ◎ Capacity alkaline batteries ◎ Transmission frequency: 433MHz ◎ Coding method: EV1527 ◎ Transmission distance: ≥120M ◎ 12M/8M (wide angle/curtain)	1-50pcs:\$4.5 51-100pcs:\$4.3 101-500pcs:\$4.2	01.1.52
		GS-92R Wireless PIR motion sensor		1-50pcs:\$4.0 51-100pcs:\$3.90 101-500pcs:\$3.80	
 <p>Wireless door/window contact</p>	Tiny appearance * Door/window contact sensor * Low power consumption, long battery life * Low battery report * 1527/2262 IC, oscillation resistance optional * Open/close reports * Tamper switch * RF433MHz	GS-D30	Tiny appearance * Door/window contact sensor * Low power consumption, long battery life * Low battery report * 1527/2262 IC, oscillation resistance optional * Open/close reports * Tamper switch	1-50pcs:\$2.0 51-100pcs:\$1.90 101-500pcs:\$1.80	01.5.071
 <p>GS-67-R Wireless door/window sensor</p>	This product is a multi-functional wireless intelligent door magnet. Emergency button and door magnetic dual-function integrated, using ultra-low power consumption chip design, low voltage fault monitoring report, anti-demolition, anti-damage function. * RF433MHz	GS-67-R	◎ Working voltage: 3V button lithium battery ◎ Transmission frequency: 433MHz ◎ Encoding method: EV1527 ◎ Launch distance: ≥120M	1-50pcs:\$2.3 51-100pcs:\$2.2 101-500pcs:\$2.1	
 <p>Wireless smoke detector</p>	When the alarm detects a certain concentration of smoke around, the alarm will send sound and light alarm and wireless transmission to the alarm host; (APP and NB models can also be customized) 3V10-year lithium battery,	GS-441R	Rated power supply: DC9V (9V alkaline battery) Static current: 15uA Monitoring current: 80uA	1-50pcs:\$4.5 51-100pcs:\$4.3 101-500pcs:\$4.2	01.1.58
 <p>Wireless strobe siren</p>	<ol style="list-style-type: none"> 1.Work as a standalone alarm host or wireless siren. 2.20 wireless defense zones. 3.At most 5 wireless remote controllers. 4.Alarm with both voice prompts and quick flash strobe. 5.Wireless learning code: adding new accessories, convenient , safe and efficient 6.One-key-control function: Remote control to Arm/emergency alarm/disarm 7.Built-in rechargeable Lithium battery 8.Smart screw&mount base. 	GS-519R	<ol style="list-style-type: none"> 1.Power output: DC12V 500mA 2.Standby current: ≤13mA 3.Alarm current: ≤230mA 4.Frequency: 433MHz/315MHz 5.Code: SC 2262 IC / 4.7MΩ 6.Temperature: -20℃ ~ +55℃ 7.Humidity: 40% ~ 80%RH 8.Backup Battery: Lithium-ion battery 7.4V/400mA 	1-50pcs:\$7.5 51-100pcs:\$7.3 101-500pcs:\$7.2	

 <p>Wireless gas detector</p>	<ul style="list-style-type: none"> Working voltage range: AC220V Power consumption: static ≤100 mA alarm ≤150 mA Alarm range: natural gas 3%-15% LEL Response time: < 30 seconds Alarm sound: > 75 db (1m away from the front) Gas sensitive element: life of three years 	GS-209-R	<ul style="list-style-type: none"> Alarm sound: > 75 db (1m away from the front) Gas sensitive element: life of three years 	1-50pcs:\$5.20 51-100pcs:\$5.10 101-500pcs:\$4.95	
 <p>wireless outdoor siren</p>	<ul style="list-style-type: none"> 20 wireless defense zones (number of wired non-defense zones) The alarm can be connected to up to 5 remote controls The alarm can be wired sound and light alarm, or wireless sound and light alarm The alarm has a tamper-proof alarm function The alarm has both a sound prompt and a quick flash prompt when it alarms Wireless learning to code: adding new accessories is convenient, fast, safe and efficient Built-in AAA NI-HM rechargeable battery pack, power failure alarm function 	SS02B	<ul style="list-style-type: none"> One-button control: remote control to go out to arm, remote control to arm at home, remote control emergency alarm, remote control to quickly disarm 	1-50pcs:\$15.5 51-100pcs:\$15.2 101-500pcs:\$14.8	01.1.66
 <p>Wireless solar siren outdoor</p>	<ul style="list-style-type: none"> 20 wireless defense zones (number of wired non-defense zones) The alarm can be connected to up to 5 remote controls The alarm can be wired sound and light alarm, or wireless sound and light alarm The alarm has a tamper-proof alarm function The alarm has both a sound prompt and a quick flash prompt when it alarms Wireless learning to code: adding new accessories is convenient, fast, safe and efficient Built-in AAA NI-HM rechargeable battery pack, power failure alarm function 	GS-520	<ul style="list-style-type: none"> One-button control: remote control to go out to arm, remote control to arm at home, remote control emergency alarm, remote control to quickly disarm 	1-50pcs:\$18.6 51-100pcs:\$18.3 101-500pcs:\$17.6	06.1.10
 <p>wireless doorbell</p>	<p>The wireless the doorbell used the advanced wireless access technology, and the bell button can wireless doorbell the master to code, receiving high sensitivity, distance, the wireless signal is stable, the large capacity high quality speech processing technology can accommodate 36 music, beautiful sounds, adjustable volume 8, exquisite appearance design fashion, contracted and compact, easy to install, plug and play.</p>	GS-16		1-50pcs:\$4.8 51-100pcs:\$4.7 101-500pcs:\$4.6	01.1.56
 <p>water leakage sensor</p>	<ul style="list-style-type: none"> Triggered by water from water sensor. with dry battery model:23A. Working frequency: 433.92 MHz±2KHZ or 315 MHz Widely for bathroom and any place where needs to protect water leakage 	LSTC02		\$4.50	with white box 01.1.60
 <p>360° ceiling Ceiling PIR Sensor</p>	<ul style="list-style-type: none"> Power supply: 9V 6F22 (normal dry batter) . Working current: 12 MA Static < 50μA Wireless frequency:433MHz Detection range :360 degrees, Detection distance :5M Sensor spacing :3s-60s 	GS-CWMS01		\$6.70	with gift box 06.3.08
 <p>wireless signal repeater</p>	<ul style="list-style-type: none"> Working Voltage: DC 12V Operating Current: 150mA-180mA Transmitting Frequency: 315MHz or 433.92MHz(Customized is optional) Receiving time: 3-10 s (Not receiving signal when it transmitted) Oscillation resistance: 1.5M-4.7M Transmitting distance: 3000 m Widely used in encode IC: 2262,2264,2260,1527,2240... etc. 	GS-XHZZQ		\$16.00	with AC power adapter and gift box 06.2.12
 <p>RFID keypad</p>	<p>Used to Away arm/Home Arm/Disarm the system,and also with doorbell button.</p> <ul style="list-style-type: none"> Work power: three AAA batteries Standby current:≤30uA Emission current:≤20mA Tag quantity that keypad support: 5pcs Wireless frequency: 433Mhz 	GS-K07		\$16.50	with 2pcs RFID keyfob and gift box 02.2.37
 <p>wireless smoke + heat detector</p>	<ul style="list-style-type: none"> Operating voltage:DC 9V battery (6F22 carbon battery, DC TYPE Static current: ≤20uA Alarm current: ≤40mA Battery life: carbon battery for about 1 year. Alarm indication: LED flashes in Red Alarm sound : ≥ 85d/3M Radio frequency: 315MHz or 433MHz 	GS-WSD02		9.00	with gift box 02.2.35
 <p>SOS button</p>	<ul style="list-style-type: none"> with external antenna Power Requirements : DC12V Current Consumption: 8~12mA communication Transmit Frequency:315±0.2Mhz/433±0.2Mhz Transmit Duration:less than 1s Operating distance from central controller:less than 80m (no obstacle) Dimension(LWH):85X37X16mm 	GS-WEB01		\$2.60	06.3.24
 <p>Wireless solar outdoor motion sensor</p>	<ul style="list-style-type: none"> Power input : 9-15 VDC; Detect distance: 12m×12m; Fully sealed design, two-layer waterproof, macromolecule film plating Remarkable pet-immunity function to prevent pets under 25kg; Special lens anti UV to reduce false alarm at maximum Germany importedoptical filter to block motley light up to 99%. 	GS-ODPIR03		\$35.7	with stand and gift box 06.3.23
 <p>Wired outdoor motion sensor (Wireless for option)</p>	<ul style="list-style-type: none"> Detect distance: 12m×12m; Fully sealed design, two-layer waterproof, macromolecule film plating Remarkable pet-immunity function to prevent pets under 15kg; Special lens anti UV to reduce false alarm at maximum 	GS-ODPIR02		\$25.0	with stand and gift box 02.4.003