




## Shenzhen Golden Security Technology CO.,Ltd

Add: 6th Floor, Unit 1, Building 1, Kailifang Plaza, Lianrun Road, Taoyuan Community, Dalang Street, Longhua District, Shenzhen

Attns: Lilian Huang | T: +86 189 4879 4227 | E: lilian@cameralarms.com | W: https://alarm-camera.en.alibaba.com

### Wi-Fi alarm system W06 and W07 work with Tuya APP

Picture	Features	model	Price	Function picture	
	4.3 inch full touch capacitive screen, flexible operation. 100 wireless defense zones can be learned, and the first 10 wireless defense zones can be self-defined names. You can learn 10 remote controls, and you can customize the name. You can learn 10 RFID cards, and you can customize your name. Wired siren can be connected externally. Work with Tuya APP. Supports intelligent voice control such as Amazon Alexa, Google Assistant, IFTTT, etc. Switch between 11 languages at any time: Chinese, English, German, Russian, Spanish, Polish, Italian, French, Portuguese, Greek, Romanian. Supports 5 groups of alarm call settings, and can individually set the alarm SMS switch and dialing switch. Support 20 seconds alarm recording SMS. Supports low battery warning for wireless sensors. Warning of open doors and windows. Voice operation prompt. Support 5 kinds of defense zone modes, which can be set as doorbell mode. Telephone remote arming, disarming, monitoring, intercom. SMS remote control. User password protection: Enter 5 consecutive incorrect passwords, and the keyboard will refuse to accept the input within 90 seconds.	GS-X800-2G-S (GSM+ WiFi)  GS-X800-4G-S (4G+ WiFi)	Power input: DC 5V (micro USB standard interface power supply) Working current: <120mA Standby current: <80uA Alarm current: <500mA Wireless frequency: 433MHz Wireless coding: EV 1527 GSM bands: 850/900/1800/1900MHz Wi-Fi bands: IEEE802.11b/g/n RF standard Standby battery: 3.7V/500mAh lithium-ion Temperature range: 0℃ ~ 55℃ Humidity range: < 80%RH (No freezing)	1-50set: \$58 51-100set: \$57 101-200set: \$56  1-50set: \$48.86 51-100set: \$48.50 101-200set: \$47.50	1 wireless PIR detector, 1 wireless door sensor, 1 wired siren, 2 remote controls, 2 RFID, 1 power adapter  works with the Google Assistant amazon alexa
4.3" Touch Screen Alarm System (Standard kit)					
	4.3 inch full touch capacitive screen, flexible operation. 100 wireless defense zones can be learned, and the first 10 wireless defense zones can be self-defined names. You can learn 10 remote controls, and you can customize the name. You can learn 10 RFID cards, and you can customize your name. Wired siren can be connected externally. Work with Tuya APP. Supports intelligent voice control such as Amazon Alexa, Google Assistant, IFTTT, etc. Switch between 11 languages at any time: Chinese, English, German, Russian, Spanish, Polish, Italian, French, Portuguese, Greek, Romanian. Supports 5 groups of alarm call settings, and can individually set the alarm SMS switch and dialing switch. Support 20 seconds alarm recording SMS. Supports low battery warning for wireless sensors. Warning of open doors and windows. Voice operation prompt. Support 5 kinds of defense zone modes, which can be set as doorbell mode. Telephone remote arming, disarming, monitoring, intercom. SMS remote control. User password protection: Enter 5 consecutive incorrect passwords, and the keyboard will refuse to accept the input within 90 seconds.	GS-X800-2G-L (GSM+ WiFi)  GS-X800-4G-L (4G+ WiFi)	Power input: DC 5V (micro USB standard interface power supply) Working current: <120mA Standby current: <80uA Alarm current: <500mA Wireless frequency: 433MHz Wireless coding: EV 1527 GSM bands: 850/900/1800/1900MHz Wi-Fi bands: IEEE802.11b/g/n RF standard Standby battery: 3.7V/500mAh lithium-ion Temperature range: 0℃ ~ 55℃ Humidity range: < 80%RH (No freezing)	1-50set: \$103.00 51-100set: \$102.00 101-200set: \$101.00  1-50set: \$125.50 51-100set: \$124.50 101-200set: \$123.50	01.6.010  works with the Google Assistant amazon alexa
4.3" Touch Screen Alarm System (Full kit)					
	<b>W07 work with Tuya APP or life smart APP.</b> 1.Support English/ German/ Russian/Spanish/ Polish /Italian/French/Portuguese/ Greek/Romanian language 2.GSM Wi-Fi based alarm system,if Wi-Fi network was cut off,W07 will use GSM network automatically. 2.The alarm host W07 can set 5 groups Mobile phone No. for phone call and SMS. 3.Support 200pcs wireless alarm accessories like Door/window contact, PIR motion sensor, remote controllers,doorbell,water leakage sensor,gas leakage sensor, wireless keypad etc. 4.Support entry delay, exit delay,auto-arm/disarm function and alarm duration time setting. 5.Support 20 seconds voice record function. 6.Support self-check whether door/window is closed function and door chime function. 6.APP can be freely shared with family members. 7.Support all series of Tuya products like IP camera, WiFi doorbell, wall switch, power strip smart socket, RGB lamp, curtain motor, smart door lock, etc. 8.Support powerful automation function with WiFi devices.	GS-W07 (2G+Wi-Fi)	Power input: DC 5V Working current: <120mA Standby current: <80uA Alarm current: <500mA Wireless frequency: 433MHz Wireless coding: EV 1527 GSM bands: 850/900/1800/1900MHz	Sample:\$33.00 20~50 sets:\$32.00 51~500 sets:\$31.00 1000pcs : \$29.50	Black color for option
2G+WiFi alarm system				01.6.006	
	<b>W08 work with Tuya APP or life smart APP, W08 is with 4G network version.</b> 1.Support English/ German/ Russian/Spanish/ Polish /Italian/French/Portuguese/ Greek/Romanian language 2.GSM Wi-Fi based alarm system,if Wi-Fi network was cut off,W07 will use GSM network automatically. 2.The alarm host W07 can set 5 groups Mobile phone No. for phone call and SMS. 3.Support 200pcs wireless alarm accessories like Door/window contact, PIR motion sensor, remote controllers,doorbell,water leakage sensor,gas leakage sensor, wireless keypad etc. 4.Support entry delay, exit delay,auto-arm/disarm function and alarm duration time setting. 5.Support 20 seconds voice record function. 6.Support self-check whether door/window is closed function and door chime function. 6.APP can be freely shared with family members. 7.Support all series of Tuya products like IP camera, WiFi doorbell, wall switch, power strip smart socket, RGB lamp, curtain motor, smart door lock, etc. 8.Support powerful automation function with WiFi devices.	W08-GSM+WiFi (2G+Wi-Fi)  W08-4G+WiFi (4G+Wi-Fi)	Power input: DC 5V (micro USB standard interface power supply) Working current: <120mA Standby current: <80uA Alarm current: <500mA Wireless frequency: 433MHz Wireless coding: EV 1527 GSM bands: 850/900/1800/1900MHz Wi-Fi bands: IEEE802.11b/g/n RF standard Standby battery: 3.7V/500mAh lithium-ion Temperature range: 0℃ ~ 55℃ Humidity range: < 80%RH (No freezing)	1-50 sets:\$29.50 51~100 sets:\$29.00 101~500 sets:\$28.50  1-50 sets:\$57.00 51~100 sets:\$56.00 101~500 sets:\$55.00	01.1.34  01.1.29
Smart alarm system					
	1.Self test function 2.Motorola IC control, Reliable without false alarming 3.Field audio and visible alarming 4.Simple installation 5.Excellent reliability & high stability 6.Low battery alarm 7.Durable sensor head 8.Less affected by other organic solvent 8. Operating temperature: -0℃ ~+50℃ 9. Humidity range: < 80%RH (no freezing) 10. Alarm output: Relay output (relay contact load 3A 250V AC / 3A 30V DC)	GS210W	1. Working voltage: DC 5V (micro USB) 2. Alarm current: <120mA 3. Response time: <30s 4. Sensor lifetime: 3 years 5. Installation method: wall mounting 6. Air pressure: 86~108Kpa 7. GSM bands: 850/900/1800/1900MHz	1-50pcs:\$12 51-100pcs:\$11.5 101-500pcs:\$10.5	with stand and gift box 01.7.012509
WiFi Gas sensor					
	1. High sensitivity smoke detection. 2. Built-in thermistor sensor, high temperature alarm function 3. Smart WiFi remotely push alarm information. 4. Smart APP control. 5. With manually test, manually mute. 6. Sound and light alarm.	GS443W	1. Working voltage: DC 9V alkaline battery 2. Static current: <10uA 3. Alarm current: <100mA 4. Alarm sound>80db 5. Operating temperature: -0℃ ~+50℃ 6. Humidity range: < 95%RH (no freezing) 7. Low voltage alert:3.9V±0.3V	1-50pcs:\$7.8 51-100pcs:\$7.6 101-500pcs:\$7.5	with stand and gift box 01.1.85
WiFi Smoke Sensor					
	1. support tuya smart APP 2. support google home & amazon alexa 3. door open alert, app notification 4. real time monitoring for in & out at the quarantine places. 5. App remote monitoring, multi-level prevention and control 6. 24 hours monitoring, solve the problem for fatigue on duty 6. installation distance: <2cm 7. trigger range: 2-3cm 5. Operating temperature: -0℃ ~+50℃	D41	1. Working voltage: 3V (2*AA battery) 2. Working current: <150mA 3. standby current: <35uA 4. connect method: wifi (802.11b/g/n) 5. wifi range: 30m	1-50pcs:\$5.3 51-100pcs:\$5.2 101-500pcs:\$5.1	with stand and gift box 02.4.0346
WiFi Door/Window alarm					
Accessories work with W08 and W07					
	Tiny appearance * Door/window contact sensor * Low power consumption, long battery life * Low battery report * 1527/2262 IC,oscillation resistance optional * Open/close reports * Tamper switch * RF433MHz	GS-D30	1. Power Supply: DC 3V (CR2032 Lithium Battery x1) Standby Current: <8uA 2. Transmitting Distance: <80m (Without obstacles and no interference) 3. Radio Frequency: 433MHz 4. Operation Temperature: -10~55℃	1-50pcs:\$2.0 51-100pcs:\$1.90 101-500pcs:\$1.80	01.5.071
Wireless door/window contact					
	* Low voltage alarm function * Dynamic temperature compensation technology * SMT design, anti-RFI, anti-EMI, anti-strong light, anti-heat, anti-wind * Intelligent logic analysis to prevent false alarm * Low power consumption, long battery life (standby 2 years) * Wireless frequency: 315MHz/433MHz/868MHz * Built-in million encoding * Test:Low consumption mode	GS-P20	1. Power Supply: DC 3V (CR2450 Lithium Battery x1) 2. Standby Current: <15uA 3. Alarm Current: <25mA 4. Detection Scope: <12m/110° 5. Transmitting Distance: <100m (Without obstacles and no interference) 6. Radio Frequency: 433MHz	1-50pcs:\$3.8 51-100pcs:\$3.6 101-500pcs:\$3.5	01.7.121
Wireless Mini PIR motion sensor					

 <p>Wireless PIR motion sensor</p>	<ul style="list-style-type: none"> <li>* Microprocessor with lower false alarm rate</li> <li>* Low voltage alarm function</li> <li>* Dynamic temperature compensation technology</li> <li>* SMT design, anti-RFI, anti-EMI, anti-strong light, anti-heat, anti-wind</li> <li>* Intelligent logic analysis to prevent false alarm</li> <li>* Low power consumption, long battery life (standby 2 years)</li> <li>* Wireless frequency: 315MHz/433MHz/868MHz</li> </ul>	GS-P10	1. Power Supply: 1.5V AA Battery x3 2. Transmitting Distance: <80m (Open Area and No Interference) 3. Standby current: <15 $\mu$ A 4. Alarm current: <25mA 5. Wireless transmitter codes: 1527	1-50pcs:\$3.8 51-100pcs:\$3.6 101-500pcs:\$3.5	06.2.49
 <p>Wireless Indoor Siren</p>	<ul style="list-style-type: none"> <li>* Work as a standalone alarm hub or wireless siren</li> <li>* Wireless learning code, 50 remote controllers and detectors can be learned</li> <li>* Alarm with both High decibel sound and quick flash strobe.</li> <li>1527 code (220K-470K)</li> <li>* Built-in backup lithium battery</li> <li>* AC wide voltage design (AC 100-240V)</li> </ul>	GS-V10	1. Power supply: AC 100 ~ 240V 2. Built-in battery: 3.7V/500mAh 3. Standby current: <10mA 4. Alarm current: <200mA 5. Wireless frequency: 433MHz 6. Receiving distance: <120 m (open air)	1-50pcs:\$6.50 51-100pcs:\$6.30 101-500pcs:\$6.20 501-5000pcs:\$6.1	01.1.92
 <p>Wireless outdoor Siren</p>	<ul style="list-style-type: none"> <li>* Work as a standalone alarm hub or wireless siren</li> <li>* Wireless learning code, 50 remote controllers and detectors can be learned</li> <li>* Alarm with both High decibel sound and quick flash strobe.</li> <li>1527 code (220K-470K)</li> <li>* Built-in backup rechargeable Lithium battery.</li> <li>* Adding new wireless accessories, convenient, safe and efficient</li> <li>* Tamper switch</li> <li>* The hub internal siren sounds at 110dB on-site in the case of alarm.</li> </ul>	GS-V30	1. Power Supply: +12VDC, 1000mA 2. Backup Battery: 3.7V, 500mAh Lithium Battery 3. Consumption: <150mA@normal 4. Alarm Volume: 110dB@powered by 12VDC 5. Radio Frequency: 433Mhz	1-50pcs:\$9.5 51-100pcs:\$8.5 101-500pcs:\$8.3 501-5000pcs:\$8.2	06.1.10
 <p>Wireless outdoor solar Siren</p>	<ul style="list-style-type: none"> <li>* Built-in lithium battery powered by solar energy.</li> <li>* Work as a live/standalone alarm hub, wireless siren.</li> <li>* Support 30 wireless defense zones and remote controllers.</li> <li>* 2 wired zones for 2 wired detectors or wired alarm system.</li> <li>* Alarm with both loud sound and quick flash strobe.</li> <li>* Wireless learning code for adding new accessories, convenient, safe and efficient.</li> <li>* One-key-control function: Remote control to Arm/emergency alarm/disarm</li> <li>* Anti-lamper</li> </ul>	GS-V40	1.Power supply: DC 3.7V (3.7V/400mAh rechargeable lithium ion battery) 2.Max output current from solar panel: 5V/150mA 3.Max alarm current: <170mA 4.Wireless receiving distance: >100m 5.Ambient Humidity: <80% (no freezing) 6.Standby current: <1mA 7.Wireless frequency: 433MHz	1-50pcs:\$17.5 51-100pcs:\$16.5 101-500pcs:\$16 501-5000pcs:\$15	06.1.25
 <p>Wireless gas leakage sensor</p>	<ul style="list-style-type: none"> <li>* Alarm with Indicator, sound, voice prompt</li> <li>* Test/Silence button</li> <li>* Warm-up time 180 seconds</li> <li>* Temperature alarm</li> <li>* Sensor life: about 5 years</li> <li>* Tamper alarm</li> <li>1.Power supply: Micro USB+5V/1A</li> <li>2.Consumption &lt;200mA</li> <li>3.Detecting gas Natural gas(CH4), LPG</li> <li>4.Working Environment Temperature: -10~55℃ Humidity: &lt;95%RH ( non-condensing )</li> <li>5.Range: 0~100%LEL</li> <li>6.Alarm setting value: 6%LEL</li> </ul>	GS-RQ20	1.Response time: $\leq$ 30 seconds 2.Heat alarm value: 57℃ 3.Alarm volume: $\geq$ 70dB 4.Valve/manipulator drive output: 12V/300mA output for 15 seconds 5.Dimension: 86x86x24.5mm	1-50pcs:\$7.20 51-100pcs:\$7.00 101-500pcs:\$6.80	01.1.89
 <p>RFID card</p>	1.Frequency: 125KHz 2.No battery needed 3.Panel Bandwidth: 10KHz	GS-R10		1-50pcs:\$0.6 51-100pcs:\$0.55 101-500pcs:\$0.5	02.2.36
 <p>doorbell</p>	Power Supply: DC 3V (CR2032 Lithium Battery x1) Standby Current: <5uA Transmitting Distance: <80m (Without obstacles and no Interference) Radio Frequency: 433Mhz Operation Temperature: -10~55℃	GS-DB		\$4.00	with Double-sided adhesive
 <p>water leakage sensor</p>	<ul style="list-style-type: none"> <li>*Triggered by water from water sensor.</li> <li>*with dry battery model/23A</li> <li>*Working frequency: 433.92 MHz<math>\pm</math>2KHz or 315 MHz</li> <li>*Widely for bathroom and any place where needs to protect water leakage</li> </ul>	LSTC02		\$4.50	with white box 06.3.08
 <p>360° ceiling Ceiling PIR Sensor</p>	<ul style="list-style-type: none"> <li>*Power supply: 9V 6F22 (normal dry battery) .</li> <li>*Working current: 12 MA Static &lt; 50uA</li> <li>*Wireless frequency:433MHz</li> <li>*Detection range :360 degrees, Detection distance :5M</li> <li>*Sensor spacing :3s-60s</li> </ul>	GS-CWMS01		\$6.70	with gift box 06.2.12
 <p>wireless signal repeater</p>	<ul style="list-style-type: none"> <li>*Working Voltage: DC 12V</li> <li>*Operating Current: 150mA-180mA</li> <li>*Transmitting Frequency: 315MHz or 433.92MHz( Customized is optional)</li> <li>*Receiving time: 3-10 s (Not receiving signal when it transmitted) Oscillation resistance: 1.5M-4.7M</li> <li>*Transmitting distance: 3000 m</li> <li>*Reliable work in models IC-2063,2064,2065,4607,2068,.....etc.....</li> <li>Used to Aways arm/home Arm/Disarm the system, and also with doorbell button.</li> <li>*Work power: three AAA batteries</li> <li>*Standby current: &lt;30uA</li> <li>*Emission current: &lt;20mA</li> <li>*Tag quantity that keypad support: 5pcs</li> <li>*Wireless frequency: 433Mhz</li> </ul>	GS-XHZZQ		\$8.58	with AC power adapter and gift box
 <p>Wireless RFID keypad</p>	<ul style="list-style-type: none"> <li>*Operating voltage:DC 9V battery (6F22 carbon battery, DC TYPE</li> <li>*Static current: &lt;20uA</li> <li>*Alarm current: &lt;40mA</li> <li>*Battery life: carbon battery for about 1 year.</li> <li>*Alarm indication: LED flashes in Red</li> <li>*Alarm sound : <math>\geq</math> 85dB/3M</li> <li>*Radio frequency: 315MHz or 433MHz</li> </ul>	GS-K07		\$16.50	with 2pcs RFID keyfob and gift box 02.2.35
 <p>wireless smoke and temperature detector</p>	<ul style="list-style-type: none"> <li>*with external antenna</li> <li>*Power Requirements : DC12V</li> <li>*Current Consumption: 8~12mA communication</li> <li>*Transmit Frequency:315<math>\pm</math>0.2MHz/433<math>\pm</math>0.2MHz</li> <li>*Transmit Duration:less than 1s</li> <li>*Operating distance from central controller:less than 80m (no obstacle)</li> <li>*Dimension(L*W*H):85X37X16mm</li> </ul>	GS-WSD02		\$9.00	with gift box 06.3.24
 <p>SOS button</p>	<ul style="list-style-type: none"> <li>*with external antenna</li> <li>*Power Requirements : DC12V</li> <li>*Current Consumption: 8~12mA communication</li> <li>*Transmit Frequency:315<math>\pm</math>0.2MHz/433<math>\pm</math>0.2MHz</li> <li>*Transmit Duration:less than 1s</li> <li>*Operating distance from central controller:less than 80m (no obstacle)</li> <li>*Dimension(L*W*H):85X37X16mm</li> </ul>	GS-WEB01		\$2.60	02.4.003
 <p>Wireless door/window contact</p>	Working voltage: DC3V Emission frequency: 315MHz/433MHz Coding Method: EV1527 Action distance: 25-39MM Emission distance: $\geq$ 120M ( open space ) Low Pressure Alarm: 2.2-2.4V	GS-WDS08		\$3	06.3.33
 <p>Remote controller</p>	1. High stability: imported SMD components with SMT, surface acoustic resonator stabilization (SAW) 6.5G UHF triode 2. Black and white color for choice 3. 4 remote controller buttons 4. 433MHz, 1527 CODE	GS-RMC09		\$2.8	02.2.110
 <p>wireless solar outdoor motion sensor</p>	<ul style="list-style-type: none"> <li>*Power input : 9-15 VDC;</li> <li>*Detect distance: 12m*12m;</li> <li>*Fully sealed design, two-layer waterproof, macromolecule film plating</li> <li>*Remarkable pet-immunity function to prevent pets under 25kg</li> <li>*Special lens anti UV to reduce false alarm at maximum</li> <li>*Germany importedoptical filter to block motley light up to 99%.</li> </ul>	GS-ODPIR03		\$35.7	06.2.03
 <p>wired outdoor motion sensor</p>	<ul style="list-style-type: none"> <li>*Detect distance: 12m*12m;</li> <li>*Fully sealed design, two-layer waterproof, macromolecule film plating</li> <li>*Remarkable pet-immunity function to prevent pets under 15kg</li> <li>*Special lens anti UV to reduce false alarm at maximum</li> </ul>	GS-ODPIR02		\$25.0	06.2.14