ISSUEWEAVER | COMMAND NOTEBOOK

Run It, Test It, Publish It Privately

A compact copy-and-paste companion to the complete RUN_GUIDE.md.

A. Windows PowerShell - start with the ZIP

Extract IssueWeaver_Lab.zip and open PowerShell in that folder.

```
python --version
python -m venv .venv
.\.venv\Scripts\Activate.ps1
python -m pip install -e ".[dev]"
python -m issueweaver demo
python -m pytest -q --cov=issueweaver
```

Expected terminal trace: Tester FAIL, Repair, Tester PASS, status passed_dry_run.

B. macOS / Linux

```
python3 -m venv .venv
source .venv/bin/activate
python -m pip install -e '.[dev]'
python -m issueweaver demo
python -m pytest -q --cov=issueweaver
```

C. Upload framework to a NEW PRIVATE repository

Install Git and GitHub CLI first; authenticate as iam-Debabrata in your own browser.

```
gh auth login
# Windows: .\scripts\publish_private.ps1
# macOS/Linux: bash scripts/publish_private.sh
```

This specific interaction still requires you to authorize GitHub creation. These scripts refuse to use an already existing remote.

D. Live Docker worker - safe mode first

```
docker version
docker build -t issueweaver-pytest:local sandbox/
```

Recommended: make a separate fresh, disposable private playground repo for agent-generated changes. Do not configure the target as your existing code repo.

E. Set ignored credentials

Copy .env.example to .env, then edit values in a text editor. Never commit .env.

```
GITHUB_REPOSITORY=iam-Debabrata/issueweaver-playground
GITHUB_TOKEN=YOUR_SCOPED_TOKEN
OPENAI_API_KEY=YOUR_OPENAI_API_KEY
GITHUB_ALLOW_PR=false
```

F. Run one real issue without writing to GitHub

```
python -m issueweaver issue --number 1
```

Inspect runs/issue-1.json. Confirm tests succeeded. Update .env to GITHUB_ALLOW_PR=true only after reviewing the destination and code. Then:

```
python -m issueweaver issue --number 1 --publish
```

This may open a new DRAFT PR in the configured target. Nothing merges automatically.

G. Local API and signed webhook

```
python -m uvicorn issueweaver.api:app --reload --port 8000
# local docs: http://127.0.0.1:8000/docs
# health:     http://127.0.0.1:8000/health
```

For GitHub delivery, you must supply a secured public HTTPS endpoint, a matching webhook secret and an Issues event subscription. Tag the target issue with swarm-ready. The built-in background task runner is not crash-resumable.

H. Quick troubleshooting and pre-public checklist

Symptom	Fix
Python not found	Install Python 3.11+; restart shell
Venv cannot activate	Set-ExecutionPolicy -Scope Process Bypass
langgraph missing	pip install -e .[dev] in the venv
Docker image missing	docker build -t issueweaver-pytest:local sandbox/
GitHub 403	Check fine-grained token repo permissions
No draft PR	Check dry-run, test pass, and allow-pr flag
Webhook 403	Check HMAC secret and GitHub headers

Before making the project public

- Read your own README, graph flow, test policies, security limitations and risk model.
- Run all tests locally and on GitHub Actions; document actual live failures.
- Confirm there are no credentials, private data, or dangerous sandbox options in Git history.
- Review the sample draft PR and human-check generated source and tests.
- ONLY THEN: new framework repo Settings -> General -> Danger Zone -> Change visibility.

Full conceptual explanations, diagram and interview practice: IssueWeaver_Learning_Manual.pdf. Full command details: RUN_GUIDE.md.

Status at package creation: 37 passing local tests; 91% measured coverage. Live Docker, actual model and GitHub PR not yet verified.