Rework Plan — Spike Not Feasible — [Project name]

Field	Entry
Project	[Project name]
Document	Rework Plan
Version	[1.0]
Based on	Spike / Feasibility v[x.x]
Date	[YYYY-MM-DD]
Author	[Name]

Workflow loop: 3. Spike → 1. BRD ("Not feasible / rework").

1. When this applies

Rework starts when a spike experiment fails and no fallback covers it.

Failed experiment	Rework?	Why
[X1 end-to-end]	Yes	[Core promise not proven]
[X2]	Yes / No	[ ]
[X3]	No — use fallback	[ ]

2. Rework process

Guidance: one rework loop should take no more than [5] working days before the spike re-runs.

1. **Record the failure** with the rework record below: experiment, result, data, environment.
2. **Find the cause:** a tuning problem (fixable inside the spike) or a real limit of the chosen approach.
3. **Retry once if it is tuning.** If the retry passes, continue to development without rework.
4. **Choose a rework option** with the product owner (playbook below).
5. **Update the BRD (step 1):** change the affected requirement, priority or target; new BRD version.
6. **Update the gap analysis (step 2)** for the changed requirements only.
7. **Re-run the spike (step 3)** for the failed experiments, plus the end-to-end experiment.
8. **Limit loops:** after 2 loops on the same experiment, the product owner decides between further rework and "not feasible".

3. Failure playbook

Failure	Likely cause	Tuning fix (retry once)	Rework option	BRD change
[X1]	[ ]	[ ]	[Replace component]	[ ]
[X2]	[ ]	[ ]	[Alternative approach]	[Lower priority / relax target]
[X3]	[ ]	[ ]	[Reduce scope]	[Move to later version]

4. Not feasible: when to stop

The product owner declares the project not feasible when, after the rework loops:

- [The core experiment still fails]
- [Two key experiments both fail]
- [The only working option breaks a fixed constraint: cost, licence, regulation, hardware]

When stopping, record: final results, the blocking component, what would need to change, a review date, and any reusable parts.

Alternative to stopping: a reduced release — [describe smallest useful scope] — if the product owner accepts it.

5. Rework record (one per loop)

Field	Entry
Rework loop #	
Date	
Failed experiment(s)	
Result vs pass condition	
Data and environment	
Cause (tuning or limit)	
Tuning retry result	
Rework option chosen	
BRD changes (ID, old → new)	
BRD new version	
Approved by	
Re-spike result	
Decision	Go / rework again / not feasible

6. Change log

Version	Date	Change
1.0	[YYYY-MM-DD]	First version