Test Plan (QA) — [Project name]

Field	Entry
Project	[Project name]
Document	Test Plan (QA)
Version	[1.0]
Based on	BRD v[x.x], Development Plan v[x.x]
Build under test	[version / build hash]
Date	[YYYY-MM-DD]
Author	[QA lead]

Workflow step: 5. Testing (QA). **Next step:** 6. UAT.

1. Entry criteria

- ☐ All Must requirements merged to `main`
- ☐ Release-candidate build available for all target platforms
- ☐ Release notes and known issues provided
- ☐ Test data ready
- ☐ Open bugs: none critical, at most [n] major

2. Scope and approach

In scope: [requirement IDs]. **Out of scope:** [items and reason].

Test type	What it checks	How
Functional	Each acceptance condition	Manual / automated test cases
Regression	Nothing broke between builds	Automated suite
Performance	[Speed, load, resource use]	[Tool / timed runs]
Security / privacy	[Data, access, network]	[ ]
Compatibility	[OS, browsers, devices]	Test matrix
Installation / upgrade	[Install, upgrade, uninstall]	Clean environments
Robustness	Error handling and fallbacks	Fault injection

3. Test environments and data

ID	Environment	Purpose
ENV-1	[ ]	[Recommended]
ENV-2	[ ]	[Minimum]

ID	Test data	Used for
DATA-1	[ ]	[ ]

4. Functional test cases

ID	Requirement	Steps	Expected result	Result	Defect
TC-01	BR-01	[ ]	[ ]	Pass / Fail	
TC-02	BR-02	[ ]	[ ]		

5. Non-functional test cases

ID	Requirement	Test	Pass condition	Result
NT-01	NFR-01	[ ]	[ ]	
NT-02	NFR-02	[ ]	[ ]	

6. Quality review (if output quality needs human judgement)

Reviewers: [n] people from [target user group], not on the project team.

Criterion	Question	Pass (average, 1–5)
[ ]	[ ]	[n]

7. Defect management

Severity	Definition	Fix target
Critical	Crash, data loss, security/privacy failure, or a Must requirement fails	Before next build
Major	Should requirement fails, or quality below pass	Within the test cycle
Minor	Works with a workaround; small visual issue	Before release if time allows
Trivial	Cosmetic	Backlog

Each defect records: build, environment, test case, steps, expected vs actual, logs.

Workflow: New → Triaged → Fixed → Closed / Reopened. A defect that needs a requirement or technology change becomes a change request.

8. Testing change requests

CR class	QA tests	Regression
A. Minor	Affected cases	Related UI / unit tests
B. Requirement tweak	Updated cases	Automated suite
C. New technical approach	All cases for the component, plus performance and security	Full regression
D. New feature	New cases	Full regression
E. Fallback	Fallback works; scope matches release notes	Automated suite

CR test cases are named `TC-CRxxx-nn`. QA marks a CR **Verified** only after its cases pass.

9. Schedule and reporting

Week	Activity
1	[Installation, functional tests]
2	[Non-functional, quality review, fixes]
3	[Re-tests, full regression, report]

Reporting: daily status (run, passed, failed, open defects by severity) and a final test report.

10. Exit criteria to UAT

- ☐ 100% of test cases run; [95]%+ pass; all Must-requirement cases pass
- ☐ Zero open critical defects; at most [n] open major defects with workarounds
- ☐ Performance and security tests pass
- ☐ Final test report approved by the product owner

If not met: another fix cycle of up to [1] week; a failure from a real limit becomes a change request.

11. Change log

Version	Date	Change
1.0	[YYYY-MM-DD]	First version