

B.M.S. COLLEGE OF ENGINEERING

(Autonomous College Affiliated to Visvesvaraya Technological University, Belgaum)

Bull Temple Road, Basavanagudi, Bangalore-560019



REPORT ON “APPLICATION OF FILTERS ON A SOUND SAMPLE”

Submitted in partial fulfilment of the requirements for the partial completion of
DIGITAL SIGNAL PROCESSING
(16EC5DCDSP)

AKSHAY S RAO

SUBMITTED BY:

1BM17EC007

Course instructor
Narayan T Deshpande
Associate Professor, Dept. of ECE

Aug-Dec 2019

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

CONTENTS

1. Code to get audio signal.
2. Code to apply butterworth low pass filter.
3. Code to apply butterworth high pass filter.
4. Code to apply butterworth band pass filter.
5. Code to apply butterworth band stop filter.
6. Code to apply Chebyshev low pass filter.
7. Code to apply Chebyshev high pass filter.
8. Code to apply Chebyshev band pass filter.
9. Code to apply Chebyshev band stop filter.

CODE TO RECORD AUDIO.

```
%get voice signal

recObj = audiorecorder;
disp('Start speaking.')
recordblocking(recObj, 5);
disp('End of Recording. ');
play(recObj);

%get noise signal

recObj1 = audiorecorder;
disp('add noise.')
recordblocking(recObj1, 5);
disp('End of Recording. ');
play(recObj1);

% combine both signals

y = getaudiodata(recObj);
filename = 'audiodsp.wav';
audiowrite(filename,y,8300);

[y,Fs] = audioread(filename);
[y1,Fs1] = audioread('noise.wav');

y2 = y + y1;

filename2 = ('voice_with_noice.wav');
audiowrite(filename2,y2,Fs1);
```

BUTTERWORTH LOW PASS FILTER

```

%read noise + voice signal
[noisy,Fs] = audioread('voice_with_noise.wav');
%read voice signal
[voice,Fs1] = audioread('audiodsp.wav');

figure(1)
%plot periodogram of noise + voice signal
subplot(3,1,1)
%plot periodogram of noise + voice signal
plot(psd(spectrum.periodogram,noisy,'Fs',Fs,'NFFT',length(noisy)));
title('noise + voice signal');grid on;



%plot periodogram of noise + voice signal
subplot(3,1,2)
plot(psd(spectrum.periodogram,voice,'Fs',Fs,'NFFT',length(voice)));
title('voice signal');grid on;

%design butterworth lowpass filter
wp=tan((1/Fs)*pi*2);
ws=tan((100/Fs)*pi*2);

subplot(3,1,3)
[N,Wn] = buttord(wp/pi, ws/pi,3,40);
[b,a] = butter(N,Wn);
filtered = filter(b,a,noisy);
plot(psd(spectrum.periodogram,filtered,'Fs',Fs1,'NFFT',length(filtered)));
title('lowpass filtered');grid on;
audiowrite('low_pass_filtered.wav',filtered,Fs);

%time domain respresentation
figure(2)
subplot(3,1,1)
plot(noisy);
title('time domain noisy signal');grid on;
subplot(3,1,2)
plot(voice);
title('time domain voice signal');grid on;
subplot(3,1,3)
plot(filtered);
title('time domain low pass filtered signal');grid on;

```



BUTTERWORTH HIGH PASS FILTER

```
%read noise + voice signal
[noisy,Fs] = audioread('voice_with_noise.wav');
%read voice signal
[voice,Fs1] = audioread('audiodsp.wav');

figure(1)
%plot periodogram of noise + voice signal
subplot(3,1,1)
%plot periodogram of noise + voice signal
plot(psd(spectrum.periodogram,noisy,'Fs',Fs,'NFFT',length(noisy)));
title('noise + voice signal');grid on;

%plot periodogram of noise + voice signal
subplot(3,1,2)
plot(psd(spectrum.periodogram,voice,'Fs',Fs,'NFFT',length(voice)));
title('voice signal');grid on;



%design butterworth highpass filter
wp=tan((800/Fs)*pi*2);
ws=tan((500/Fs)*pi*2);

subplot(3,1,3)
[N,Wn] = buttord(wp/pi, ws/pi,3,40);
[b,a] = butter(N,Wn,'high');
filtered = filter(b,a,noisy);
plot(psd(spectrum.periodogram,filtered,'Fs',Fs1,'NFFT',length(filtered)));
title('lowpass filtered');grid on;
audiowrite('high_pass_filtered.wav',filtered,Fs);
```

```

figure(2)
subplot(3,1,1)
plot(noisy);
title('time domain noisy signal');grid on;
subplot(3,1,2)
plot(voice);
title('time domain voice signal');grid on;
subplot(3,1,3)
plot(filtered);
title('time domain high pass filtered signal');grid on;

```



BUTTERWORTH BAND PASS FILTER

```

%read noise + voice signal
[noisy,Fs] = audioread('voice_with_noise.wav');
%read voice signal
[voice,Fs1] = audioread('audiodsp.wav');

figure(1)
%plot periodogram of noise + voice signal
subplot(3,1,1)
%plot periodogram of noise + voice signal
plot(psd(spectrum.periodogram,noisy,'Fs',Fs,'NFFT',length(noisy)));
title('noise + voice signal');grid on;

%plot periodogram of noise + voice signal
subplot(3,1,2)
plot(psd(spectrum.periodogram,voice,'Fs',Fs,'NFFT',length(voice)));
title('voice signal');grid on;

```

```
%design butterworth bandpass filter
```

```
wp=[tan((800/Fs)*pi*2), tan((1000/Fs)*pi*2)];
```

```
ws=[tan((600/Fs)*pi*2), tan((1200/Fs)*pi*2)];
```

```
subplot(3,1,3)
```

```
[N,Wn] = buttord(wp/pi, ws/pi,3,40);
```

```
[b,a] = butter(N,Wn);
```

```
filtered = filter(b,a,noisy);
```

```
plot(psd(spectrum.periodogram,filtered,'Fs',Fs1,'NFFT',length(filtered  
)));
```

```
title('bandpass filtered');grid on;
```

```
audiowrite('butterband_pass_filtered.wav',filtered,Fs);
```

```
figure(2)
```

```
subplot(3,1,1)
```

```
plot(noisy);
```

```
title('time domain noisy signal');grid on;
```

```
subplot(3,1,2)
```



```
plot(voice);
```

```
title('time domain voice signal');grid on;
```

```
subplot(3,1,3)
```

```
plot(filtered);
```

```
title('time domain band pass filtered signal');grid on;
```



BUTTERWORTH BAND STOP FILTER

```

%read noise + voice signal
[noisy,Fs] = audioread('voice_with_noice.wav');
%read voice signal
[voice,Fs1] = audioread('audiodsp.wav');

figure(1)
%plot periodogram of noise + voice signal
subplot(3,1,1)
%plot periodogram of noise + voice signal
plot(psd(spectrum.periodogram,noisy,'Fs',Fs,'NFFT',length(noisy)));
title('noise + voice signal');grid on;



%plot periodogram of noise + voice signal
subplot(3,1,2)
plot(psd(spectrum.periodogram,voice,'Fs',Fs,'NFFT',length(voice)));
title('voice signal');grid on;

%design butterworth bandstop filter
wp=[tan((600/Fs)*pi*2), tan((1200/Fs)*pi*2)];
ws=[tan((800/Fs)*pi*2), tan((1000/Fs)*pi*2)];

subplot(3,1,3)
[N,Wn] = buttord(wp/pi, ws/pi,3,40);
[b,a] = butter(N,Wn,'stop');
filtered = filter(b,a,noisy);
plot(psd(spectrum.periodogram,filtered,'Fs',Fs1,'NFFT',length(filtered)));
title('bandstop filtered');grid on;
audiowrite('butterband_stop_filtered.wav',filtered,Fs);

figure(2)
subplot(3,1,1)
plot(noisy);
title('time domain noisy signal');grid on;
subplot(3,1,2)
plot(voice);
title('time domain voice signal');grid on;
subplot(3,1,3)
plot(filtered);
title('time domain band stop filtered signal');grid on;

```

Chebyshev Low Pass Filter

```
%read noise + voice signal
[noisy,Fs] = audioread('voice_with_noise.wav');
%read voice signal
[voice,Fs1] = audioread('audiodsp.wav');

figure(1)
%plot periodogram of noise + voice signal
subplot(3,1,1)
%plot periodogram of noise + voice signal
plot(psd(spectrum.periodogram,noisy,'Fs',Fs,'NFFT',length(noisy)));
title('noise + voice signal');grid on;



%plot periodogram of noise + voice signal
subplot(3,1,2)
plot(psd(spectrum.periodogram,voice,'Fs',Fs,'NFFT',length(voice)));
title('voice signal');grid on;

%design chebyshev lowpass filter
wp=tan((1/Fs)*pi*2);
ws=tan((1000/Fs)*pi*2);

subplot(3,1,3)
[N,Wn] = cheb1ord(wp/pi, ws/pi,0.4,20);
[b,a] = cheby1(N, 0.4, Wn);
filtered = filter(b,a,noisy);
plot(psd(spectrum.periodogram,filtered,'Fs',Fs1,'NFFT',length(filtered)));
title('cheby lowpass filtered');grid on;
```

```
audiowrite('cheby_low_pass_filtered.wav',filtered,Fs);
```

```
figure(2)
subplot(3,1,1)
plot(noisy);
title('time domain noisy signal');grid on;
subplot(3,1,2)
plot(voice);
title('time domain voice signal');grid on;
subplot(3,1,3)
plot(filtered);
title('time domain low pass filtered signal');grid on;
```



CHEBYSHEV HIGH PASS FILTER

```
%read noise + voice signal
[noisy,Fs] = audioread('voice_with_noise.wav');
%read voice signal
[voice,Fs1] = audioread('audiodsp.wav');

figure(1)
%plot periodogram of noise + voice signal
subplot(3,1,1)
%plot periodogram of noise + voice signal
plot(psd(spectrum.periodogram,noisy,'Fs',Fs,'NFFT',length(noisy)));
title('noise + voice signal');grid on;

%plot periodogram of noise + voice signal
subplot(3,1,2)
plot(psd(spectrum.periodogram,voice,'Fs',Fs,'NFFT',length(voice)));
title('voice signal');grid on;
```

```
%design chebyshev high pass filter
```

```
wp=tan((1200/Fs)*pi*2);
```

```
ws=tan((500/Fs)*pi*2);
```

```
subplot(3,1,3)
```

```
[N,Wn] = cheb1ord(wp/pi, ws/pi,0.4,40);
```

```
[b,a] = cheby1(N, 0.4, Wn,'high');
```

```
filtered = filter(b,a,noisy);
```

```
plot(psd(spectrum.periodogram,filtered,'Fs',Fs1,'NFFT',length(filtered  
)));
```

```
title('cheby high pass filtered');grid on;
```

```
audiowrite('cheby_high_pass_filtered.wav',filtered,Fs);
```

```
figure(2)
```

```
subplot(3,1,1)
```

```
plot(noisy);
```

```
title('time domain noisy signal');grid on;
```

```
subplot(3,1,2)
```



```
plot(voice);
```

```
title('time domain voice signal');grid on;
```

```
subplot(3,1,3)
```

```
plot(filtered);
```

```
title('time domain high pass filtered signal');grid on;
```



CHEBYSHEV BAND PASS FILTER

```

%read noise + voice signal
[noisy,Fs] = audioread('voice_with_noise.wav');
%read voice signal
[voice,Fs1] = audioread('audiodsp.wav');

figure(1)
%plot periodogram of noise + voice signal
subplot(3,1,1)
%plot periodogram of noise + voice signal
plot(psd(spectrum.periodogram,noisy,'Fs',Fs,'NFFT',length(noisy)));
title('noise + voice signal');grid on;



%plot periodogram of noise + voice signal
subplot(3,1,2)
plot(psd(spectrum.periodogram,voice,'Fs',Fs,'NFFT',length(voice)));
title('voice signal');grid on;

%design chebyshev band pass filter
wp=[tan((1000/Fs)*pi*2),tan((1200/Fs)*pi*2)];
ws=[tan((800/Fs)*pi*2),tan((1500/Fs)*pi*2)];

subplot(3,1,3)
[N,Wn] = cheb1ord(wp/pi, ws/pi,0.4,40);
[b,a] = cheby1(N, 0.4, Wn);
filtered = filter(b,a,noisy);
plot(psd(spectrum.periodogram,filtered,'Fs',Fs1,'NFFT',length(filtered)));
title('cheby band pass filtered');grid on;
audiowrite('cheby_band_pass_filtered.wav',filtered,Fs);

figure(2)
subplot(3,1,1)
plot(noisy);
title('time domain noisy signal');grid on;
subplot(3,1,2)
plot(voice);
title('time domain voice signal');grid on;
subplot(3,1,3)
plot(filtered);
title('time domain band pass filtered signal');grid on;

```



CHEBYSHEV BAND STOP FILTER

```
%read noise + voice signal
[noisy,Fs] = audioread('voice_with_noise.wav');
%read voice signal
[voice,Fs1] = audioread('audiodsp.wav');

figure(1)
%plot periodogram of noise + voice signal
subplot(3,1,1)
%plot periodogram of noise + voice signal
plot(psd(spectrum.periodogram,noisy,'Fs',Fs,'NFFT',length(noisy)));
title('noise + voice signal');grid on;

%plot periodogram of noise + voice signal
subplot(3,1,2)
plot(psd(spectrum.periodogram,voice,'Fs',Fs,'NFFT',length(voice)));
title('voice signal');grid on;

%design chebyshev bandstop filter
wp=[tan((800/Fs)*pi*2),tan((1500/Fs)*pi*2)];
ws=[tan((1000/Fs)*pi*2),tan((1200/Fs)*pi*2)];

subplot(3,1,3)
[N,Wn] = cheb1ord(wp/pi, ws/pi,0.4,40);
[b,a] = cheby1(N, 0.4, Wn,'stop');
filtered = filter(b,a,noisy);
plot(psd(spectrum.periodogram,filtered,'Fs',Fs1,'NFFT',length(filtered)));
title('cheby band stop filtered');grid on;
```

```
audiowrite('cheby_band_stop_filtered.wav',filtered,Fs);
```

```
figure(2)
subplot(3,1,1)
plot(noisy);
title('time domain noisy signal');grid on;
subplot(3,1,2)
plot(voice);
title('time domain voice signal');grid on;
subplot(3,1,3)
plot(filtered);
title('time domain band stop filtered signal');grid on;
```

