

WEEK 2 STATUS REPORT

CCP-CNS2026 — Problem 1: Multi-Site Enterprise Network

Team Members: Rohma, Muqadas, Ahmad.

Instructor: Sir Tahir Mehmood

TASKS COMPLETED THIS WEEK:

1. Built complete network topology in Cisco Packet Tracer

- 1 Router (Cisco 2911)
- 1 Switch (Cisco 2960)
- 3 PCs (Sales, Engineering, Admin)
- 1 Web Server (Admin VLAN)
- 1 Kali Attacker (Sales VLAN)

2. Configured VLANs on Switch

- VLAN 10: Sales (Fa0/2, Fa0/6)
- VLAN 20: Engineering (Fa0/3)
- VLAN 30: Admin (Fa0/4, Fa0/5)
- Trunk port on Gi0/1 to router

3. Configured Router-on-a-Stick

- Sub-interface Gi0/0.10 → 192.168.10.1
- Sub-interface Gi0/0.20 → 192.168.20.1
- Sub-interface Gi0/0.30 → 192.168.30.1

4. Configured DHCP for all VLANs

- Pool SALES: 192.168.10.0/24
- Pool ENGINEERING: 192.168.20.0/24
- Pool ADMIN: 192.168.30.0/24

5. Configured DHCP Snooping on Switch

- Enabled on VLANs 10, 20, 30
- Trusted port: Gi0/1 (router port)

6. Tested connectivity successfully

- All VLANs can communicate
 - Web server reachable from all VLANs
-

PING TEST RESULTS:

PC1-Sales → Router: 4/4 replies ✓

PC1-Sales → Engineering: 3/4 replies ✓

PC1-Sales → Admin: 3/4 replies ✓

PC1-Sales → Web Server: 3/4 replies ✓

PC2-Engineering → Admin: 4/4 replies ✓

PLAN FOR NEXT WEEK:

- Configure ACL to block Sales from Admin VLAN
- Set up web server on Ubuntu (HTTP)
- Simulate DoS attack from Kali Linux
- Capture attack traffic using Wireshark
- Add mitigation ACL to block attacker IP