JAVASCRIPT TRICKY OUTPUT-BASED QUESTIONS

@DimpleKumari
Forming a network of fantastic coders.

NEXT

What's the output? 



```
let randomValue = { name: "Dimple" }
randomValue = 23

if (!typeof randomValue === "string") {
        console.log("It's not a string!")
} else {
        console.log("Yay it's a string!")
}
```

- A: `It's not a string!`
- B: `Yay it's a string!`
- C: `TypeError`
- D: `undefined`

@DimpleKumari
Forming a network of fantastic coders.

What's the output? 



```
const user = {
        email: "my@email.com",
        updateEmail: email => {
                this.email = email
        }
}

user.updateEmail("new@email.com")
console.log(user.email)
```

- A: `my@email.com`
- B: `new@email.com`
- C: `undefined`
- D: `ReferenceError`

@DimpleKumari
Forming a network of fantastic coders.

What's the output? 



```
const fruit = ['🍌', '🍋', '🍎']

fruit.slice(0, 1)
fruit.splice(0, 1)
fruit.unshift('🍇')

console.log(fruit)
```

- A: `['🍌', '🍋', '🍎']`
- B: `['🍋', '🍎']`
- C: `['🍇', '🍋', '🍎']`
- D: `['🍇', '🍌', '🍋', '🍎']`

@DimpleKumari
Forming a network of fantastic coders.

What's the output?



```javascript
class Calc {
        constructor() {
                this.count = 0
        }

        increase() {
                this.count++
        }
}

const calc = new Calc()
new Calc().increase()

console.log(calc.count)
```

- A: `0`
- B: `1`
- C: `undefined`
- D: `ReferenceError`

@DimpleKumari
Forming a network of fantastic coders.

What's the output? 

```
let count = 0;
const nums = [0, 1, 2, 3];

nums.forEach(num => {
        if (num) count += 1
})

console.log(count)
```

- A: 1
- B: 2
- C: 3
- D: 4

@DimpleKumari
Forming a network of fantastic coders.

What's the output? 



```
class Bird {
  constructor() {
    console.log("I'm a bird. ▯");
  }
}

class Flamingo extends Bird {
  constructor() {
    console.log("I'm pink. 🌸");
    super();
  }
}

const pet = new Flamingo();
```

- A: `I'm pink. 🌸`
- B: `I'm pink. 🌸` `I'm a bird. ▯`
- C: `I'm a bird. ▯` `I'm pink. 🌸`
- D: Nothing, we didn't call any method

@DimpleKumari

Forming a network of fantastic coders.

What's the output?

```javascript
const person = {
  name: 'DimpleKumari',
  hobbies: ['coding'],
};

function addHobby(hobby, hobbies = person.hobbies) {
  hobbies.push(hobby);
  return hobbies;
}

addHobby('running', []);
addHobby('dancing');
addHobby('baking', person.hobbies);

console.log(person.hobbies);
```

- A: `["coding"]`
- B: `["coding", "dancing"]`
- C: `["coding", "dancing", "baking"]`
- D: `["coding", "running", "dancing", "baking"]`

@DimpleKumari

Forming a network of fantastic coders.

What's the output?



```
class Counter {
  #number = 10

  increment() {
    this.#number++
  }

  getNum() {
    return this.#number
  }
}

const counter = new Counter()
counter.increment()

console.log(counter.#number)
```

- A: `10`
- B: `11`
- C: `undefined`
- D: `SyntaxError`

@DimpleKumari

Forming a network of fantastic coders.

What's the output? 



```javascript
const add = x => x + x;

function myFunc(num = 2, value = add(num)) {
  console.log(num, value);
}

myFunc();
myFunc(3);
```

- A: `2` `4` and `3` `6`
- B: `2` `NaN` and `3` `NaN`
- C: `2` `Error` and `3` `6`
- D: `2` `4` and `3` `Error`

@DimpleKumari
Forming a network of fantastic coders.

What's the output?



```javascript
const handler = {
  set: () => console.log('Added a new property!'),
  get: () => console.log('Accessed a property!'),
};

const person = new Proxy({}, handler);

person.name = 'Dimple';
person.name;
```

- A: `Added a new property!`
- B: `Accessed a property!`
- C: `Added a new property!` `Accessed a property!`
- D: Nothing gets logged

@DimpleKumari
Forming a network of fantastic coders.

What's the output? 



```javascript
// sum.js
export default function sum(x) {
  return x + x;
}

// index.js
import * as sum from './sum';
```

- A: `sum(4)`
- B: `sum.sum(4)`
- C: `sum.default(4)`
- D: Default aren't imported with `*`, only named exports

@DimpleKumari

What's the output?



```
class Counter {
  constructor() {
    this.count = 0;
  }

  increment() {
    this.count++;
  }
}

const counterOne = new Counter();
counterOne.increment();
counterOne.increment();

const counterTwo = counterOne;
counterTwo.increment();

console.log(counterOne.count);
```

- A: `0`
- B: `1`
- C: `2`
- D: `3`

@DimpleKumari

Forming a network of fantastic coders.

What's the output? 



```javascript
const myPromise = Promise.resolve('Woah some cool data');

(async () => {
  try {
    console.log(await myPromise);
  } catch {
    throw new Error(`Oops didn't work`);
  } finally {
    console.log('Oh finally!');
  }
})();
```

- A: `Woah some cool data`
- B: `Oh finally!`
- C: `Woah some cool data` `Oh finally!`
- D: `Oops didn't work` `Oh finally!`

What's the output? 



```
const add = x => y => z => {
  console.log(x, y, z);
  return x + y + z;
};

add(4)(5)(6);
```

- A: `4` `5` `6`
- B: `6` `5` `4`
- C: `4` `function` `function`
- D: `undefined` `undefined` `6`

What's the output? 



```
let config = {
  alert: setInterval(() => {
    console.log('Alert!');
  }, 1000),
};

config = null;
```

- A: The `setInterval` callback won't be invoked
- B: The `setInterval` callback gets invoked once
- C: The `setInterval` callback will still be called every second
- D: We never invoked `config.alert()`, config is `null`

@DimpleKumari

Forming a network of fantastic coders.

What's the output?



```javascript
let name = 'Dimple';

function getName() {
  console.log(name);
  let name = 'Twinkle';
}

getName();
```

- A: Dimple
- B: Twinkle
- C: `undefined`
- D: `ReferenceError`

What's the output? 



```javascript
const colorConfig = {
  red: true,
  blue: false,
  green: true,
  black: true,
  yellow: false,
};

const colors = ['pink', 'red', 'blue'];

console.log(colorConfig.colors[1]);
```

- A: `true`
- B: `false`
- C: `undefined`
- D: `TypeError`

@DimpleKumari
Forming a network of fantastic coders.

What's the output? 

```
const one = false || {} || null;
const two = null || false || '';
const three = [] || 0 || true;

console.log(one, two, three);
```

- A: `false` `null` `[]`
- B: `null` `""` `true`
- C: `{}` `""` `[]`
- D: `null` `null` `true`

@DimpleKumari
Forming a network of fantastic coders.

What's the output? 



```
const name = 'Dimple';

console.log(name());
```

- A: `SyntaxError`
- B: `ReferenceError`
- C: `TypeError`
- D: `undefined`

@DimpleKumari

Forming a network of fantastic coders.

What's the output? 

```javascript
let newList = [1, 2, 3].push(4);

console.log(newList.push(5));
```

- A: `[1, 2, 3, 4, 5]`
- B: `[1, 2, 3, 5]`
- C: `[1, 2, 3, 4]`
- D: `Error`

THANK YOU FOR READING!

If you found this informative and valuable, I'd love for you to connect with me. Follow me Medium, Codepen, and connect with me on LinkedIn to stay updated on the latest in web development, interviews, and more.

Let's connect!

💼 **LinkedIn** — https://www.linkedin.com/in/dimple-kumari/

🔗 **Medium** — https://medium.com/@dimplekumari0228

✍️ **Codepen** — https://codepen.io/DIMPLE2802

DIMPLE KUMARI

Forming a network of fantastic coders.