



cognizant

ULTIMATE CHEATSHEET

HTML



Free PDF →



CLUSTER 1



HTML


Structure/layout

CSS

Style

JS

Logic



HTML

Hyper Text Markup Language

HTML is the code that is used to structure a web page and its content.

The component used to design the structure of websites are called **HTML tags**.

First HTML File


index.html

It is the default name for a website's [homepage](#)

HTML Tag

A container for some content or other HTML tags

`<p>` This is a paragraph `</p>`



Basic HTML Page

```
<!DOCTYPE html>
```

tells browser you are using HTML5

```
<html>
```

root of an html document

```
  <head>
```

container for metadata

```
    <title>My First Page</title>
```

page title

```
  </head>
```

```
  <body>
```

```
    </html>
```

```
    <p>Techie  
    CodeBuddy </p>
```

```
  </body>
```

Quick Points

Html tag is parent of head & body tag

Most of html elements have opening & closing tags
with content in between

Some tags have no content in between, eg - `<br>`

We can use inspect element/view page source to edit html

Comments in HTML

This is part of code that should not be parsed.

```
<!-- This is an HTML Comment -->
```

HTML is NOT case sensitive

<html> = <HTML>

<p> = <P>

<head> = <HEAD>

<body> = <BODY>

Basic HTML Tags

HTML Attributes

Attributes are used to add more information to the tag

```
<html lang="en">
```

Heading Tag

Used to display headings in HTML

h1 (most important)

h2

h3

h4

h5

h6 (least important)

Paragraph Tag

Used to add paragraphs in HTML

<p> This is a sample paragraph </p>

Anchor Tag

Used to add links to your page

```
<a href="https://google.com"> Google </a>
```

Image Tag

Used to add images to your page

```

```

↑
relative url

Br Tag

Used to add next line(line breaks) to your page

```
<br>
```

Bold, Italic & Underline Tags

Used to highlight text in your page

`<b> Bold </b>`

`<i> Italic </i>`

`<u> Underline </u>`

Big & Small Tags

Used to display big & small text on your page

`<big> Big </big>`

`<small> Small </small>`

Hr Tag

Used to display a horizontal ruler, used to separate content

```
<hr>
```

Subscript & Superscript Tag

Used to display a horizontal ruler, used to separate content

`<sub> subscript </sub>`



`<sup> superscript </sup>`



Pre Tag

Used to display text as it is (without ignoring spaces & next line)

```
<pre> This  
    is a sample  
    text.  
  
</pre>
```

Page Layout Techniques

using Semantic tags for layout

using the Right Tags

<header>

<main>

<footer>

Inside Main Tag

Section Tag For a section on your page

`<section>`

Article Tag For an article on your page

`<article>`

Aside Tag For content aside main content(ads)

`<aside>`

Revisiting Anchor Tag

```
<a href="https://google.com" target="_main"> Google </a>
```

↑
for new tab

```
<a href="https://google.com">  </a>
```

↑
clickable pic

Revisiting Image Tag



set height



set width

Div Tag

Div is a container used for other HTML elements

Block Element (takes full width)

List : Div Tags

<address>

<article>

<aside>

<blockquote>

<canvas>

<dd>

<div>

<dl>

<dt>

<fieldset>

<figcaption>

<figure>

<footer>

<form>

<h1>-<h6>

<header>

<hr>

<main>

Span Tag

Span is also a container used for other HTML elements

Inline Element (takes width as per size)

List : Span Tags

<a>

<abbr>

<acronym>

<bdo>

<big>

<button>

<cite>

<code>

<dfn>

<i>

<input>

<kbd>

<label>

<map>


<object>

<tt>

<var>

List in HTML

Lists are used to represent real life list data.



unordered

```
<ul>
```

```
<li> Apple </li>
```

```
<li> Mango </li>
```

```
</ul>
```



ordered

```
<ol>
```

```
<li> Apple </li>
```

```
<li> Mango </li>
```

```
</ol>
```

Tables in HTML

Tables are used to represent real life table data.

`<tr>` used to display table row

`<td>` used to display table data

`<th>` used to display table header

Tables in HTML

Name

Roll No

```
<table>
```

```
  <tr>
```

```
    <th> Name </th>
```

```
    <th> Roll No </th>
```

```
  </tr>
```

```
  <tr>
```

```
    <td> Anshika </td>
```

```
    <td> 1804 </td>
```

```
  </tr>
```

```
</table>
```

Caption in Tables

`<caption>` Student Data `</caption>`

Student Data

Name	Roll No
Anshika	1804

thead & tbody in Tables

`<thead>` to wrap table head

`<tbody>` to wrap table body

colspan attribute

`colspan="n"`

used to create cells which spans over multiple columns

Data	
Anshika	1804
Saksh	1890

Form in HTML

Forms are used to collect data from the user

Eg- sign up/login/help requests/contact me

`<form>`

form content

`</form>`

Action in Form

Action attribute is used to define what action needs to be performed when a form is submitted

```
<form action="/action.php" >
```

Form Element : Input

```
<input type="text" placeholder="Enter Name">
```

Label

```
<label for="id1">
```

```
  <input type="radio" value="class X" name="class" id="id1">
```

```
</label>
```

```
<label for="id2">
```

```
  <input type="radio" value="class X" name="class" id="id2">
```

```
</label>
```

Class & Id

```
<div id="id1" class="group1">
```

```
</div>
```

```
<div id="id2"> class="group1">
```

```
</div>
```

Checkbox

```
<label for="id1">
```

```
  <input type="checkbox" value="class X" name="class" id="id1">
```

```
</label>
```

```
<label for="id2">
```

```
  <input type="checkbox" value="class X" name="class" id="id2">
```

```
</label>
```

Textarea

```
<textarea name="feedback" id="feedback" placeholder="Please add Feedback">
```

```
</textarea>
```

Select

```
<select name="city" id="city">  
  <option value="Delhi"> Delhi </option>  
  <option value="Mumbai"> Delhi </option>  
  <option value="Bangalore"> Delhi </option>  
  
</select>
```

iframe Tag

website inside website



```
<iframe src="link"> Link </option>
```

Video Tag

```
<video src="myVid.mp4"> My Video </video>
```

Attributes

- controls
- height
- width
- loop
- autoplay