

Script-Controlled ACL – Restrict Record Access Based on Field Value

Milestone-7: Conclusion

Project Outcome

By completing this lab, learners gain a comprehensive understanding of how script-controlled READ, WRITE, CREATE, and DELETE ACLs enforce record-level security, how user roles and record field values are evaluated together to make access decisions, and how ACLs protect sensitive data from unauthorized viewing, modification, creation, and deletion across forms, lists, and Service Portal interfaces

Script-Controlled ACL – Restrict Record Access Based on Field value

Milestone-6:Creation of Access Control List-DELETE

Creation of ACL-DELETE

Click New to create a new ACL(Delete)

Enter the following details

Type: record

Operation: Delete

Name: u_institution_details

Active: true

In the Requires role related list, add: bb4 (custom role)

No need to add any Data condition

Save the ACL Record

Script-Controlled ACL – Restrict Record Access Based on

Milestone 5-Creation of Access Control List- WRITE

Creation of ACL-Write

Click New to create a new ACL(Write)

Enter the following details

Type: record

Operation: Write

Name: u_institution_details

Active: true

In the Requires role related list, add: bb3 (custom role)

No need to add any Data condition

Save the ACL Record

Script-Controlled ACL – Restrict Record Access Based on Field Value

Milestone-4: Creation of Access Control List-CREATE

Creation of ACL-Create

Click New to create a new ACL(Create)

Enter the following details

Type: record

Operation: create

Name: u_institution_details

Active: true

In the Requires role related list, add: bb2 (custom role)

No need to add any Data condition

Save the ACL Record

Script-Controlled ACL – Restrict Record Access Based on Field Value

Milestone-3: Creation of Access Control List-READ

ACL Configuration

In the Application Navigator, search for System Security !' Access Con

Elevate "Security_admin" role

Click New to create a new ACL.

Enter the following details

Type: record

Operation: read

Name: u_institution_details

Active: true

Advanced: true

In the Requires role related list, add: bb1 (custom role)

Add Data condition as Branch is EEE

In the Script field, add the following script

Save the ACL form

Script-Controlled ACL-Restrict Record Access Based on Field Value

Milestone-2: Tables Creation

Creation of Tables

In the Application Navigator, search for System Definition !' Tables.

Click New and create a custom table with the following details

Label: Institution Details

Name: u_institution_details

Extends for : false`

Save or Submit the form

In the columns tab, user Insert a New row method to create the mentioned fields as shown below picture

The following fields to the u_institution_details table

Student Roll Number– Auto Number

Student Name – Reference- User

Faculty Name – Reference- User

Branch – Choice (ECE, EEE, CSE)

Email– String

Phone Number– String

Description– Multi String

Save the Table

Click on the Show List in the Related Links

Create multiple records in the Student Records table with different branch values (ECE, EEE, CSE).

Script-Controlled ACL – Restrict Record Access Based on Field

Milestone-1 Creation of Users and Roles

Users Creation

Log in to the ServiceNow instance with admin access.

Create a test user:

Navigate to User Administration !' Users

Click New

User ID: EEE User

First name: EEE

Last name: User

Email: eeeuser@gmail.com

Save the record

Roles Creation

Navigate to User Administration !' Roles

Click New

Name: Enter role name as bb1

Description: Brief role purpose

Click Submit

Create other roles also like bb2,bb3,bb4.(follow the same procedure)

Assign all the roles to the EEE User