

## MCQ

1 What will be the output of the following code snippet?

```
def func(a, b):  
    return b if a == 0 else func(b % a, a)  
print(func(30, 75))
```

- a) 10
- b) 20
- ☒ c) 15
- d) 0

```
2 numbers = (4, 7, 19, 2, 89, 45, 72, 22)  
sorted_numbers = sorted(numbers)  
even = lambda a: a % 2 == 0  
even_numbers = filter(even, sorted_numbers)  
print(type(even_numbers))
```

- a) Int
- ☒ b) Filter
- c) List
- d) Tuple

3) As what datatype are the \*args stored, when passed into

- ☒ a) Tuple
- b) List
- c) Dictionary
- d) none

```
4) set1 = {14, 3, 55}  
set2 = {82, 49, 62}  
set3={99,22,17}
```

**print(len(set1 + set2 + set3))**

- a) 105
- b) 270
- c) 0
- ☒ d) Error

5) What keyword is used in Python to raise exceptions?

☒ a) raise

b) try

c) goto

d) except

6) Which of the following modules need to be imported to handle date time computations in Python?

a) timedata

b) date

☒ c) datetime

d) time

7) What will be the output of the following code snippet?

**print(4\*\*3 + (7 + 5)\*\*(1 + 1))**

- a) 248
- b) 169
- ☒ c) 208
- d) 233

8) Which of the following functions converts date to corresponding time in Python?

☒ a) strptime

b) strftime

c) both a) and b)

d) None

9) The python tuple is \_\_\_\_\_ in nature.

a) mutable

☒ b) immutable

c)unchangeable

d) none

10)

The \_\_\_\_ is a built-in function that returns a range object that consists series of integer numbers, which we can iterate using a for loop.

- ☒ A. range()
- ☐ B. set()
- ☐ C. dictionary{ }
- ☐ D. None of the mentioned above

### Question 11

**Amongst which of the following is a function which does not have any name?**

- ☐ A. Del function
- ☐ B. Show function
- ☒ C. Lambda function
- ☐ D. None of the mentioned above

### Question 12

**The module Pickle is used to \_\_\_\_.**

- ☐ A. Serializing Python object structure
- ☐ B. De-serializing Python object structure
- ☒ C. Both A and B
- ☐ D. None of the mentioned above

### Question 13

**Amongst which of the following is / are the method of convert Python objects for writing data in a binary file?**

- ☐ A. set() method
- ☒ B. dump() method
- ☐ C. load() method
- ☐ D. None of the mentioned above

**Amongst which of the following is / are the method used to unpickling data from a binary file?**

- ☒ A. load()
- ☐ B. set() method
- ☐ C. dump() method
- ☐ D. None of the mentioned above

15.

**A text file contains only textual information consisting of \_\_\_\_.**

- ☐ A. Alphabets
- ☐ B. Numbers
- ☐ C. Special symbols
- ☒ D. All of the mentioned above

16

Which Python code could replace the ellipsis (...) below to get the following output? (Select all that apply.)

```
captains = {
```

```
    "Enterprise": "Picard",
```

```
    "Voyager": "Janeway",
```

```
    "Defiant": "Sisko",
```

```
}
```

```
Enterprise Picard,
```

```
Voyager Janeway
```

```
Defiant Sisko
```

a) `for ship, captain in captains.items():`

```
    print(ship, captain)
```

b) `for ship in captains:`

```
    print(ship, captains[ship])
```

c) `for ship in captains:`

```
print(ship, captains)
```

d) both a and b

17)

Which of the following lines of code will create an empty dictionary named `captains`?

- a) `captains = {dict}`
- b) `type(captains)`
- c) `captains.dict()`
- d) `captains = { }`

18) Now you have your empty dictionary named `captains`. It's time to add some data!

Specifically, you want to add the key-value pairs `"Enterprise": "Picard"`, `"Voyager": "Janeway"`, and `"Defiant": "Sisko"`.

Which of the following code snippets will successfully add these key-value pairs to the existing `captains` dictionary?

a) `captains{"Enterprise" = "Picard"}`

`captains{"Voyager" = "Janeway"}`

`captains{"Defiant" = "Sisko"}`

b) `captains["Enterprise"] = "Picard"`

`captains["Voyager"] = "Janeway"`

`captains["Defiant"] = "Sisko"`

c) `captains = {`

`"Enterprise": "Picard",`

`"Voyager": "Janeway",`

`"Defiant": "Sisko",`

`}`

d) None of the above

**19 )** You're really building out the Federation Starfleet now! Here's what you have:

```
captains = {  
    "Enterprise": "Picard",  
    "Voyager": "Janeway",  
    "Defiant": "Sisko",  
    "Discovery": "unknown",
```

} Now, say you want to display the ship and captain names contained in the dictionary, but you also want to provide some additional context. How could you do it?

- a) `for item in captains.items():`  
`print(f"The [ship] is captained by [captain].")`
- b) `for ship, captain in captains.items():`  
`print(f"The {ship} is captained by {captain}.")`
- c) `for captain, ship in captains.items():`  
`print(f"The {ship} is captained by {captain}.")`
- d) All are correct

**20 )**

You've created a dictionary, added data, checked for the existence of keys, and iterated over it with a `for` loop. Now you're ready to delete a key from this dictionary:

```
captains = {  
    "Enterprise": "Picard",  
    "Voyager": "Janeway",  
    "Defiant": "Sisko",  
    "Discovery": "unknown",  
}
```

What statement will remove the entry for the key "Discovery"?

- a) `del captains`
- b) `captains.remove()`
- c) `del captains["Discovery"]`
- d) `captains["Discovery"].pop()`