Task Interference and Transfer in Weight-Space Merging of Fine-Tuned Small Language Models

A Mini Project Report

U23ADS705 – Mini Project

Submitted by

ARUN M **(61782323110014)**

ARUN PRASATH S **(61782323110016)**

BILAL AHAMED A **(61782323110024)**

In partial fulfillment for the award of the degree

of

BACHELOR OF TECHNOLOGY

in

ARTIFICIAL INTELLIGENCE AND DATA SCIENCE

SONA COLLEGE OF TECHNOLOGY (AUTONOMOUS),

SALEM– 636005

ANNA UNIVERSITY: CHENNAI 600 025

NOVEMBER 2026

SONACOLLEGE OF TECHNOLOGY
(AUTONOMOUS) ANNA UNIVERSITY:
CHENNAI – 600 025

BONAFIDE CERTIFICATE

Certified that this Project titled "**Task Interference and Transfer in Weight-Space Merging of Fine-Tuned Small Language Models**" is the bonafide work of "**ARUN M (61782323110014), ARUNPRASATH S (61782323110016), BILAL AHAMED A (61782323110024)**" who carried out the project work **U23ADS705 - MINI PROJECT** under my supervision.

Signature of the Supervisor	**Head of the Department**
Ms.S.M.C.Subashini	Dr. J. Akilandeswari, M.E., Ph.D.
Associate Professor	Professor
Information Technology	Information Technology
Sona College of Technology,	Sona College of Technology,
Salem – 636005	Salem – 636005

Submitted for the Mini Project Viva-Voce Examination held on

INTERNAL EXAMINER **EXTERNAL EXAMINER**

Sona College of Technology

Department of Information Technology

U23ADS705 - MINIPROJECT - DECLARATION FORM

Declaration by the Students

We hereby declare that the project titled "**Task Interference and Transfer in Weight-Space Merging of Fine-Tuned Small Language Models**" is an original work carried out by us under the guidance of Ms.S.M.C.Subashini. This project has not been submitted elsewhere for the award of any degree.

We also affirm that all the data and information used in this project are genuine and properly acknowledged. This project work is carried out with reference to the **United Nations Sustainable Development SDG 9: Industry, Innovation and Infrastructure, SDG 10: Reduced Inequalities and SDG 12: Responsible Consumption and Production.**

S.No	Register Number	Name	Signature
1.	**61782323110014**	**ARUN M**	
2.	**61782323110016**	**ARUN PRASATH S**	
3.	**61782323110024**	**BILAL AHAMED A**	

Date: _____

Place: Sona College of Technology

ACKNOWLEDGEMENT

First and foremost, we thank the Almighty for showing us inner peace and for all the blessings. We express our special gratitude to our parents for their constant support and love.

We express our sincere thanks to our Chairman, **Sri. C. Valliappa**, and our Principal, **Dr. S. R. R. Senthilkumar**, for providing the facilities needed to complete this project.

We are immensely grateful to our Head of the Department of Information Technology, **Dr. J. Akilandeswari**, for her continued encouragement.

We heartfully thank our Project Coordinator, **Dr. P. Ilanchezhian**, for his support and guidance throughout this project. His leadership has been instrumental in our success.

We express our heartfelt thanks to our Project Supervisor, **Ms.S.M.C.Subashini**, for his valuable guidance and fruitful discussions throughout the project.

We are proud to share this success with our department faculty, staff members, and friends who helped us directly or indirectly in completing this project successfully.

ABSTRACT

Weight-space model merging is an efficient approach to combining the capabilities of multiple fine-tuned language models into a single model without additional training. It is particularly useful for Small Language Models (SLMs), as it reduces the need to store and deploy multiple task-specific models. However, merging task-specific parameter updates may introduce task interference, leading to performance degradation when updates conflict in the shared parameter space.

This project presents a controlled study of task interference and transfer in weight-space merging of fine-tuned SLMs at the 1.5-billion-parameter scale. Qwen2.5-1.5B-Instruct is used as the common base model to develop four task-specialized LoRA adapters for text-to-SQL generation, mathematical reasoning, Tamil-to-English translation, and schema-constrained JSON extraction. Consistent base-model versions, prompts, adapter configurations, training data budgets, and decoding strategies ensure a fair comparison.

Five merging techniques—Linear Merging, TIES-Merging, DARE-TIES, DARE-Linear, and Magnitude Pruning—are evaluated across eleven combinations of the four specialized adapters, producing 55 merged models and five control models. Performance is assessed using task-specific metrics, including SQL abstract syntax tree equivalence, exact numerical matching for mathematical reasoning, corpus-level chrF++ for translation, and schema validation with per-field F1 for JSON extraction.

The study systematically analyses task retention, interference, and cross-task transfer when combining specialized adapters. Through controlled experiments and reproducible evaluation procedures, this project aims to identify the effectiveness, limitations, and practical applicability of weight-space model merging for small language models.

TABLE OF CONTENTS

SECTION NO	TITLE	PAGE NO
	DECLARATION	**iii**
	ACKNOWLEDGMENT	**iv**
	ABSTRACT	**v**
	LIST OF FIGURES	**ix**
	LIST OF TABLES	**x**
	LIST OF ABBREVIATIONS	**xi**
1	**INTRODUCTION**	**1**
1.1	Background of the Project	1
1.2	Problem Statement	2
1.3	Motivation	3
1.4	Objectives	3
1.5	Scope of the Project	4
2	**LITERATURE REVIEW**	**5**
2.1	Introduction	5
2.2	Review of Related Studies	5
2.3	Techniques and Technologies Used in Existing Systems	7
2.4	Research Gap	9
2.5	Summary	10
3	**CHAPTER 1 – NEED FOR PROPOSED TECHNIQUE**	**11**
3.1	Existing Techniques	11
3.2	Limitations of Existing Techniques	13
3.3	Proposed Technique	13
3.4	Objectives of the Proposed Technique	14
3.5	Advantages of the Proposed Technique	15

SECTION NO	TITLE	PAGE NO
4	**CHAPTER 2 – DESIGN OF PROPOSED SYSTEM AND ITS IMPLEMENTATION**	**16**
4.1	Introduction	16
4.2	System Requirements	16
4.2.1	Hardware Requirements	16
4.2.2	Software Requirements	16
4.3	System Architecture	17
4.4	System Components/Modules	18
4.4.1	Module 1: Configuration and Common Utilities (common.py)	18
4.4.2	Module 2: Data Preparation (data/prepare.py)	18
4.4.3	Module 3: LoRA Training (train/run.py)	19
4.4.4	Module 4: Model Merging (merge/build.py)	20
4.4.5	Module 5: Interactive Web Frontend Studio (index.html)	21
4.4.6	Module 6: Asynchronous FastAPI Backend Server (server.py)	22
4.4.7	Module 7: Analytical Datastore and Storage Architecture	24
4.5	Proposed Methodology	25
4.6	System Workflow	26
4.7	Algorithms/Techniques Used	27
4.8	Dataset/Data Collection	28
4.9	Data Preprocessing	29
4.10	Model/System Development	30
4.11	System Design Diagrams	31
4.12	Implementation	32
4.13	Coding/Program Implementation	33

SECTION NO	TITLE	PAGE NO
4.14	User Interface / System Execution Screens	35
4.14.1	Graphical Web Studio Interface Execution Screens	37
4.14.2	Cross-Model Benchmark Arena & Prompt Testing Interface	42
4.15	Chapter Summary	44
5	**CHAPTER 3 – RESULTS AND DISCUSSION**	**46**
5.1	Introduction	46
5.2	Experimental Setup	46
5.3	Evaluation Metrics	46
5.4	Experimental Results	47
5.4.1	Individual Adapter Specialist Performance	49
5.4.2	Comprehensive 5-Method Multi-Task Merging Results	50
5.4.3	Retention Degradation Across Task Arities (2, 3, and 4 Tasks)	51
5.4.4	Task Fragility and Synergistic Cross-Task Transfer	51
5.4.5	Weight Coefficient Sweep Analysis	53
5.4.6	Independent Cross-Check via Mergekit	53
5.4.7	Edge Deployment & Local Runtime Benchmark	54
5.5	Comparison with Existing Techniques and Discussion of Results	54
5.6	Chapter Summary	55
6	**CHAPTER 4 – CONCLUSION AND FUTURE SCOPE**	**56**
6.1	Summary of the Project	56
6.2	Conclusion	56
6.3	Future Scope	58
	SUSTAINABLE DEVELOPMENT GOALS (SDG)	**60**
	REFERENCES	**62**

LIST OF FIGURES

FIGURE NO	TITLE	PAGE NO
3.1	LoRA (Low-Rank Adaptation) Architecture	11
3.2	Comparison of Five Weight-Space Merging Methods	13
4.1	System Architecture of the SLM Merging Study	17
4.2	Frontend Studio Architecture (Interactive SPA Web Studio)	22
4.3	FastAPI Backend Server & Asynchronous Subprocess Orchestration Architecture	24
4.4	Analytical Datastore, Repository and Model Storage Architecture	27
4.5	Experimental Pipeline Workflow	29
4.6	Dataset Distribution Across Tasks	30
4.7	Evaluation Framework for Multi-Task NLP System	33
4.8	Merge Grid Heatmap: 5 Methods × 11 Combinations	34
4.9	Terminal Execution: LoRA Fine-Tuning of Qwen2.5-1.5B with GPU Telemetry	35
4.10	Terminal Execution: Weight-Space Model Merging via TIES Pipeline	37
4.11	Terminal Evaluation: Multi-Task Performance Matrix and AST Retention	38
4.12	Web Studio Interface — Studio Dashboard and Merging Wizard	39
4.13	Web Studio Interface — Automated Strategy Advisor & Conflict Engine	40
4.14	Web Studio Interface — Empirical Analysis and Radar Visualizations	41
4.15	Web Studio Interface — Interactive Playground and AST Verification	42
5.1	Final Training Loss After 2 Epochs for LoRA Fine-Tuned Models	46

FIGURE NO	TITLE	PAGE NO
5.2	Empirical Multi-Task Retention Comparison Across 5 Merging Algorithms and Retention Degradation by Task Arity	48
5.3	Empirical Multi-Task Retention Comparison Across 5 Merging Algorithms and Retention Degradation by Task	52

LIST OF TABLES

TABLE NO	TITLE	PAGE NO
1.1	Base Model Specifications	1
2.1	Summary of Literature Review	8
3.1	Comparison of Existing Multi-Task Techniques	11
4.1	Hardware Requirements	15
4.2	Software Requirements	15
4.3	LoRA Configuration Parameters (Identical Across All Adapters)	18
4.4	Training Hyperparameters (Identical Across All Tasks)	18
4.5	Task Descriptions and Datasets	26
4.6	Dataset Statistics After Preprocessing	28
4.7	Merge Grid Configuration	30
4.8	Cross-Model Benchmark Arena Performance Metrics Across 8 Models	43
5.1	Evaluation Metrics per Task	45
5.2	Individual Adapter Training Results	46
5.3	Merge Grid Summary	47
5.4	Individual Adapter Specialist Training and Benchmark Results	49

TABLE NO	TITLE	PAGE NO
5.5	Empirical Multi-Task Retention Comparison Across 5 Merging Algorithms (144 Cells)	49
5.6	Mean Retention Degradation Across Task Arities (2, 3, and 4 Tasks)	50
5.7	Task-Specific Retention and Fragility Matrix Across Merging Algorithms	50

LIST OF ABBREVIATIONS

Abbreviation	Full Forms
SLM	Small Language Model
LLM	Large Language Model
LoRA	Low-Rank Adaptation
PEFT	Parameter-Efficient Fine-Tuning
TIES	Trim, Elect Sign, and Merge
DARE	Drop And REscale
NLP	Natural Language Processing
SQL	Structured Query Language
JSON	JavaScript Object Notation
AST	Abstract Syntax Tree
chrF++	Character F-score with Word Bigrams
GPU	Graphics Processing Unit
VRAM	Video Random Access Memory
GGUF	GPT-Generated Unified Format
API	Application Programming Interface
HF	Hugging Face
bf16	Brain Floating Point 16-bit

SDG	Sustainable Development Goal
F1	F1 Score (Harmonic Mean of Precision and Recall)
BLEU	Bilingual Evaluation Understudy

1. INTRODUCTION

1.1 Background of the Project

The rapid advancement of Large Language Models (LLMs) has revolutionized natural language processing across diverse domains. However, deploying multiple task-specific LLMs in production environments presents significant challenges in terms of computational resources, memory requirements, and operational costs. Small Language Models (SLMs), typically with fewer than 3 billion parameters, offer a compelling alternative by providing reasonable performance while being deployable on consumer-grade hardware.

Parameter-Efficient Fine-Tuning (PEFT) methods, particularly Low-Rank Adaptation (LoRA), have emerged as a practical approach to adapting pre-trained models to specific tasks without modifying the full parameter set. LoRA introduces trainable low-rank decomposition matrices alongside frozen pre-trained weights, reducing the number of trainable parameters by orders of magnitude while maintaining competitive performance.

Weight-space model merging is a technique that combines multiple fine-tuned models into a single model by operating directly on the model parameters in weight space, without requiring additional training data or compute. This approach is particularly attractive because it enables creating multi-task models from task-specific experts at essentially zero marginal training cost.

Table 1.1: Base Model Specifications

Property	Value
Model	Qwen/Qwen2.5-1.5B-Instruct

Parameters	1.5 Billion
Revision (Pinned)	989aa7980e...aa306
Precision	bfloat16 (no quantization)
Architecture	Transformer (Decoder-only)

1.2 Problem Statement

When multiple task-specific LoRA adapters are merged in weight space, the resulting model may suffer from task interference — a phenomenon where the parameter updates from different tasks conflict with each other, causing degradation in the performance of one or more tasks. Conversely, task transfer may occur when combining complementary tasks leads to improved generalization beyond what each specialist achieves individually.

The challenge lies in understanding the conditions under which merging produces beneficial transfer versus destructive interference. Existing studies on model merging have primarily focused on large-scale models (7B+ parameters) and have often lacked controlled experimental designs that isolate the effect of the merging method from confounding factors such as different base models, inconsistent LoRA configurations, or varying data budgets.

This project addresses the following key research questions: (1) How do different weight-space merging methods compare in preserving task-specific performance while enabling cross-task generalization? (2) What is the relationship between the number and diversity of merged tasks and the resulting performance? (3) Which merging techniques best mitigate task interference at the SLM scale?

1.3 Motivation

The motivation for this project stems from several practical and theoretical considerations:

1. Deployment Efficiency: Maintaining multiple task-specific models requires proportional memory and storage. A single merged model serving all tasks reduces deployment costs significantly, especially for resource-constrained environments.

2. SLM-Scale Gap: Most model merging research targets 7B–70B parameter models. The behavior at the 1.5B scale is understudied and may differ qualitatively due to reduced parameter redundancy and lower model capacity.

3. Controlled Methodology: Many existing studies lack strict experimental controls, making it difficult to attribute observed effects to the merging method rather than confounding factors. A controlled study design is needed to produce reliable, interpretable results.

4. Practical Impact: Understanding which merging methods work best for different task combinations directly informs practitioners choosing between deployment strategies for multi-task SLM applications.

1.4 Objectives

1. To fine-tune four task-specialized LoRA adapters on a pinned Qwen2.5-1.5B-Instruct base model for SQL generation, mathematical reasoning, Tamil-to-English translation, and JSON extraction.

2. To implement and apply five weight-space merging techniques (Linear, TIES, DARE-TIES, DARE-Linear, and Magnitude Pruning) across eleven adapter combinations.

3. To develop task-specific evaluation metrics including AST equivalence for SQL, exact numeric match for math, corpus-level chrF++ for translation, and schema-validated per-field F1 for JSON extraction.

4. To systematically measure and analyse task retention, interference, and cross-task transfer across 55 merged models and 5 control models.

5. To provide reproducible experimental evidence for the effectiveness and limitations of weight-space merging at the SLM scale.

1.5 Scope of the Project

This project focuses on the systematic study of weight-space merging at the 1.5-billion-parameter scale using a single base model (Qwen2.5-1.5B-Instruct). The scope includes four diverse NLP tasks spanning structured output generation (SQL, JSON), reasoning (Math), and sequence transduction (Translation). Five merging methods are evaluated across all possible combinations of the four task adapters.

The project does not include: (a) comparison across different base model architectures or sizes, (b) training-based multi-task learning approaches, (c) deployment and inference optimization beyond the merging step, or (d) evaluation on held-out benchmarks beyond the project-specific evaluation sets.

2. LITERATURE REVIEW

2.1 Introduction

This chapter reviews the existing literature on model merging, parameter-efficient fine-tuning, and multi-task learning in the context of language models. The review establishes the theoretical foundations, identifies key techniques, and highlights the research gaps that motivate the current study.

2.2 Review of Related Studies

Hu et al. [1] introduced Low-Rank Adaptation (LoRA) as a method for adapting large pre-trained language models to downstream tasks. Their key insight was that the weight updates during fine-tuning have a low intrinsic rank, allowing them to be represented as the product of two low-rank matrices. This reduces the number of trainable parameters by up to 10,000× while maintaining or improving performance compared to full fine-tuning. LoRA has since become the de facto standard for parameter-efficient fine-tuning.

Ilharco et al. [2] proposed Task Arithmetic, demonstrating that task-specific weight vectors (the difference between fine-tuned and pre-trained weights) can be combined through simple arithmetic operations. By adding task vectors, they showed that a single model can perform multiple tasks. Conversely, by negating task vectors, undesirable behaviors can be removed. This work established the foundation for weight-space merging as a practical technique.

Yadav et al. [3] introduced TIES-Merging (Trim, Elect Sign, and Merge), which addresses the problem of parameter interference when merging multiple task vectors. TIES operates in three steps: (1) trimming

low-magnitude parameters to reduce noise, (2) resolving sign conflicts by electing the majority sign for each parameter, and (3) merging only the parameters that agree in sign. This approach significantly outperforms simple averaging when task vectors have conflicting updates.

Yu et al. [4] proposed DARE (Drop And REscale), a method that randomly drops a fraction of delta parameters and rescales the remaining ones to maintain the expected value. When combined with TIES (DARE-TIES) or linear merging (DARE-Linear), DARE enables merging models with more diverse or potentially conflicting task specializations. The stochastic nature of DARE provides a form of regularization during merging.

Yang et al. [5] conducted a comprehensive survey on model merging in large language models, covering weight-space methods, routing-based approaches, and alignment-based techniques. Their survey highlighted the growing importance of model merging as a zero-cost alternative to multi-task learning and identified key challenges including task interference, scalability, and evaluation methodology.

Qwen Team [6] released the Qwen2.5 family of models, including the 1.5B-parameter instruction-tuned variant used in this study. The Qwen2.5-1.5B-Instruct model represents a state-of-the-art small language model with strong capabilities across multiple tasks, making it an ideal base model for studying the effects of fine-tuning and merging.

Dettmers et al. [7] demonstrated that 4-bit quantized models can match the performance of 16-bit models when combined with LoRA fine-tuning (QLoRA). While this study uses full bfloat16 precision to avoid quantization noise in the merge study, QLoRA's insights on low-rank adaptation efficiency inform the adapter design choices.

Wortsman et al. [8] explored model soups — simple averaging of multiple fine-tuned models — and demonstrated that greedy interpolation in weight space can improve both in-distribution and out-of-distribution accuracy. Their work provided early evidence that weight-space operations can be beneficial for model combination.

Matena and Raffel [9] introduced Fisher Merging, which uses Fisher Information to weight the importance of different parameters when combining models. While more principled than simple averaging, Fisher Merging requires computing second-order statistics, making it computationally expensive for large models.

Huang et al. [10] developed MergeKit, a toolkit for merging transformer models using various strategies. MergeKit supports full-checkpoint merging and has been widely adopted by the open-source community for creating merged models.

2.3 Techniques and Technologies Used in Existing Systems

Existing model merging systems primarily employ the following techniques: (1) Linear Interpolation, which computes a weighted average of model parameters; (2) Task Arithmetic, which operates on task vectors derived from fine-tuning deltas; (3) TIES-Merging, which resolves sign conflicts before merging; (4) DARE, which introduces stochastic dropout of parameters before merging; and (5) Magnitude Pruning, which retains only the highest-magnitude parameters from each task vector.

The technology stack for model merging research typically includes: Hugging Face Transformers for model loading and inference, PEFT library for LoRA adapter management, PyTorch for tensor operations, and various evaluation frameworks for task-specific metrics. Hardware requirements

range from consumer GPUs (8-12 GB VRAM) for SLMs to multi-GPU clusters for larger models.

Table 2.1: Summary of Literature Review

Study	Technique	Scale	Key Findings
Hu et al. [1]	LoRA	Various	Low-rankupdates match full fine-tuning
Ilharco et al. [2]	Task Arithmetic	ViT, CLIP	Taskvectors are additive
Yadav et al. [3]	TIES-Merging	7B–13B	Sign resolution reducesinterference
Yu et al. [4]	DARE	7B–13B	Stochasticdropout enables merging
Yang et al. [5]	Survey	Various	Taxonomy of mergingmethods
Qwen Team [6]	Qwen2.5	0.5B–72B	State-of-artSLM family
Wortsman et al. [8]	Model Soups	ViT	Averagingimproves robustness
Matena & Raffel [9]	Fisher Merging	Various	Fisher-weighted combination

2.4 Research Gap

The literature review reveals several important gaps that this project aims to address:

1. Scale Gap: Most merging studies target 7B+ parameter models. The behavior of weight-space merging at the 1.5B scale is understudied, yet this scale is practically important for edge deployment.

2. Control Gap: Existing studies often vary multiple factors simultaneously (different base models, LoRA configurations, data budgets), making it difficult to attribute results to the merging method alone.

3. Task Diversity Gap: Few studies combine tasks from fundamentally different NLP domains (structured output, reasoning, translation, extraction) in a single controlled experiment.

4. Evaluation Gap: Many studies rely on generic metrics or single-task evaluations, while program-level metrics (AST equivalence, schema validation) provide more meaningful comparisons for structured output tasks.

5. Reproducibility Gap: Inconsistent experimental setups and unreleased code make it difficult to reproduce and compare results across studies.

2.5 Summary

The literature review establishes that weight-space model merging is a promising technique for creating multi-task models at zero marginal training cost. However, significant gaps exist in understanding the behavior of merging at the SLM scale, particularly under controlled experimental conditions with diverse tasks and rigorous evaluation metrics. This project addresses these gaps through a systematic study design that isolates the effect of the merging method from confounding factors.

3. CHAPTER 1 – NEED FOR PROPOSED TECHNIQUE

3.1 Existing Techniques

Several approaches exist for creating multi-task language models. This section describes the working principles, architectures, and trade-offs of each approach.

Multi-Task Learning (MTL): Traditional multi-task learning trains a single model on multiple tasks simultaneously. The model shares a common backbone and has task-specific output heads. While effective, MTL requires all training data to be available during training and often suffers from negative transfer when tasks are dissimilar. MTL also requires significant computational resources for joint training.

Adapter Routing: Mixture-of-Experts (MoE) and routing-based approaches maintain separate adapters and use a learned router to select which adapter(s) to activate for each input. While this avoids destructive interference, it requires training a routing mechanism and may not fully leverage cross-task knowledge.

Knowledge Distillation: A multi-task student model is trained to mimic the outputs of multiple task-specific teacher models. This requires generating training data from each teacher and training the student, which incurs significant computational cost.




Figure 3.1: LoRA (Low-Rank Adaptation) Architecture

LoRA (Low-Rank Adaptation): As shown in Figure 3.1, LoRA augments frozen pre-trained weights W with low-rank matrices A and B. During fine-tuning, only A and B are updated, reducing trainable parameters dramatically. The forward pass computes h = Wx + (α/r)BAx, where α is the scaling factor and r is the rank. LoRA adapters are small (~71 MB for rank-16 on 1.5B model) and can be combined in weight space without retraining.

Table 3.1: Comparison of Existing Multi-Task Techniques

Technique	Training Cost	Inference Cost	Multi Task	Task isolation
Full Fine-Tuning	High	Per-Model	No	Full
Multi-Task Learning	High	Single Model	Yes	None
Adapter Routing	Medium	Router + Adapters	Yes	Partial

Knowledge Distillation	High	Single Model	Yes	None
Weight-Space	Zero (post-train)	Single Model	Yes	Partial

3.2 Limitations of Existing Techniques

1. Multi-Task Learning requires simultaneous access to all task datasets and joint training, which is infeasible when tasks are developed independently or when compute budgets are limited.

2. Adapter Routing introduces inference overhead due to the routing mechanism and does not consolidate knowledge into a single parameter set, limiting deployment on constrained hardware.

3. Knowledge Distillation requires generating pseudo-labels from teacher models and training a student, adding significant pipeline complexity and compute cost.

4. Simple Linear Merging (averaging) does not account for parameter interference, leading to performance degradation when task updates conflict in the shared parameter space.

5. Existing merging studies lack controlled experimental designs at the SLM scale, making it difficult to recommend specific methods for practical deployment.

3.3 Proposed Technique

This project proposes a controlled experimental framework for studying weight-space merging of LoRA adapters trained on a Qwen2.5-1.5B-Instruct base model. The proposed approach evaluates five merging methods (Linear, TIES, DARE-TIES, DARE-Linear, Magnitude Pruning) across all possible combinations of four task-specialized adapters, producing 55 merged models plus 5 control models (base + 4 individual adapters).




Figure 3.2: Comparison of Five Weight-Space Merging Methods

As shown in Figure 3.2, each method handles parameter conflicts differently. Linear Merging computes a simple weighted average. TIES-Merging trims small values, resolves sign conflicts, and merges only agreeing parameters. DARE-TIES applies random dropout before TIES. DARE-Linear applies dropout before linear averaging. Magnitude Pruning retains only the highest-magnitude parameters before merging.

3.4 Objectives of the Proposed Technique

The proposed framework addresses identified limitations through the following design choices:

1. Identical base model (pinned to exact HuggingFace commit) eliminates base model variation as a confound.

2. Identical LoRA configuration (r=16, α=32, dropout=0.05, same target modules) ensures merging operates on geometrically compatible adapters.

3. Equal data budget (8,000 training examples per task) prevents data imbalance from affecting the comparison.

4. Identical prompt template (only the task instruction string differs) ensures format consistency.

5. Greedy decoding (do_sample=false) ensures reproducible evaluation across all models.

6. Program-level metrics (AST equivalence, schema validation) provide meaningful evaluation beyond surface-level text matching.

3.5 Advantages of the Proposed Technique

1. Zero additional training cost: Weight-space merging operates purely on adapter parameters, requiring no GPU compute beyond the initial fine-tuning.

2. Controlled comparison: By fixing all confounding factors, any performance difference is attributable to the merging method alone.

3. Comprehensive coverage: The full grid of 5 methods × 11 combinations provides a complete picture of merging behavior across varying task diversity.

4. Practical relevance: The 1.5B scale and 8 GB VRAM constraint directly addresses the deployment needs of edge and resource-constrained applications.

5. Reproducibility: Pinned model revision, deterministic seeding, and config-driven design ensure exact reproducibility.

4. CHAPTER 2 – DESIGN OF PROPOSED SYSTEM AND ITS IMPLEMENTATION

4.1 Introduction

This chapter presents the detailed design, architecture, and implementation of the proposed experimental framework for studying weight-space merging in Small Language Models. The system comprises four major stages: data preparation, adapter training, model merging, and evaluation. Each stage is implemented as a modular Python package with a unified configuration system.

4.2 System Requirements

4.2.1 Hardware Requirements

Table 4.1: Hardware Requirements

Components	Specification Used
GPU	NVIDIA GeForce RTX 4070 Laptop
VRAM	8 GB
System RAM	16 GB minimum
Storage	20 GB free (adapters + merged models)
CPU	Modern multi-core processor

4.2.2 Software Requirements

Table 4.2: Software Requirements

Software	Version	Purpose
Python	3.10+	Programming language

Software	Version	Purpose
PyTorch	2.6+	Deep learning framework
Transformers	Latest	Model loading and inference
PEFT	0.19+	LoRA adapter management
TRL	1.9+	Training utilities
Datasets	5.0+	Data loading (HuggingFace)
sqlglot	Latest	SQL AST parsing
sacrebleu	Latest	chrF++ metric
jsonschema	Latest	JSON schema validation
CUDA	12.4	GPU acceleration
FastAPI	0.115+	Asynchronous RESTful backend web server and pipeline execution orchestrator
Uvicorn	0.32+	High-performance ASGI server handling concurrent request event loops
Chart.js	4.4+	Interactive client-side multi-task radar charts and retention visualizations
llama.cpp	b3900+	High-speed C++ quantized GGUF local inference server (`llama-server.exe`)
psutil	6.1+	Real-time hardware telemetry engine for CPU, RAM, and GPU memory monitoring
sqlglot	26.0+	AST-level SQL syntax parsing, dialect normalization, and execution validator

4.3 System Architecture

The system follows a pipeline architecture where each stage produces artifacts consumed by the next stage. A single config.yaml file serves as the source of truth for all hyperparameters, paths, and experimental settings. The architecture is designed for reproducibility and modularity.




Figure 4.1: System Architecture of the SLM Merging Study

4.4 System Components/Modules

4.4.1 Module 1: Configuration and Common Utilities (common.py)

The common.py module provides shared utilities used across all stages of the pipeline. It implements: (1) Configuration loading from config.yaml using PyYAML, (2) Global seed setting across torch, numpy, random, and transformers for reproducibility (seed=42), (3) Model revision stamping for version pinning, and (4) Overlap hashing using SHA-256 to guarantee zero train/eval contamination.

4.4.2 Module 2: Data Preparation (data/prepare.py)

The data preparation module handles downloading, processing, and splitting datasets for all four tasks. It downloads HuggingFace datasets for SQL (b-mc2/sql-create-context), Math (openai/gsm8k), and Translation (ai4bharat/samanantar Tamil subset). For JSON extraction, it generates synthetic data deterministically from 10 predefined schemas (product, person, event, book, restaurant, weather, job posting, movie, flight, health

record). Each task receives up to 8,000 training examples and 300 evaluation examples, with deduplication and overlap checking enforced via content hashing.

Table 4.3: LoRA Configuration Parameters (Identical Across All Adapters)

Parameter	Value	Description
r (Rank)	16	Rank of the low-rank decomposition
α (Alpha)	32	LoRA scaling factor (α/r = 2.0)
Dropout	0.05	LoRA dropout rate
Target Modules	q,k,v,o,gate,up,down	All attention +MLP projections
Bias	None	No bias terms in LoRA

4.4.3 Module 3: LoRA Training (train/run.py)

The training module fine-tunes LoRA adapters on each task using the Hugging Face Trainer. The prompt template (train/prompt_templates.py) is the load-bearing experimental control: all four adapters use an identical Qwen chat-format structure with only the task-specific instruction string varying. Loss is computed only on the assistant turn (prompt tokens are masked to -100), ensuring the model learns to generate task outputs, not reproduce prompts.

Table 4.4: Training Hyperparameters (Identical Across All Tasks)

Parameter	Value
Epochs	2

Learning Rate	2.0×10^{-4}
Scheduler	Cosine
Warmup Ratio	0.03
Per-Device Batch Size	2
Gradient Accumulation Steps	16
Effective Batch Size	32
Max Sequence Length	1024
Precision	bfloat16
Gradient Checkpointing	Enabled
Optimizer	AdamW

4.4.4 Module 4: Model Merging (merge/build.py)

The merging module implements the main experimental grid. It uses PEFT's add_weighted_adapter API to combine adapters in weight space. The grid.py module defines the enumeration: 6 pairs + 4 triples + 1 quadruple = 11 combinations × 5 methods = 55 merged models. Key implementation details include:

1. GPU-free merging: All operations are arithmetic on rank-16 A/B factors (~71 MB each), not the 2.9 GB base model weights. The entire 55-model grid completes in approximately 1 minute.

2. Deterministic stochastic methods: DARE-TIES and DARE-Linear use per-merge seeding derived from hash(seed, method, combo, weights) to ensure byte-reproducibility independent of build order.

3. Geometry gate: The system refuses to merge adapters with mismatched LoRA configurations (r, alpha, dropout, bias, target_modules), preventing confounded results.

4. Staged writes: Output is written to a .partial directory and atomically moved into place, preventing corrupted adapters from interrupted builds.

5. Density parameter: Set to 0.5 (50% of delta entries retained) for all pruning-based methods to avoid confounding the method comparison.

4.4.5 Module 5: Interactive Web Frontend Studio (index.html)

The interactive web frontend studio is architected as a high-performance Single-Page Application (SPA) providing an intuitive graphical environment for end-to-end model fine-tuning, weight-space merging simulation, dynamic conflict diagnosis, and real-time inference playground benchmarking. Built strictly with modern semantic HTML5, Vanilla CSS3 utilizing CSS custom property design tokens, and Vanilla JavaScript ES6+, the interface operates without external bloated JavaScript frameworks, ensuring sub-100ms load times and seamless cross-browser responsiveness. Dynamic multidimensional visualizations are powered by Chart.js 4.4, providing interactive 4-axis multi-task capability radar charts and retention degradation bar plots across task arities.

The frontend studio incorporates five primary functional views accessible via a reactive tab navigation controller: (a) Header & Telemetry Status Bar, which continuously polls the backend specs endpoint (`/api/system/specs`) every 3 seconds to stream live GPU VRAM allocation, CPU thread utilization, physical RAM overhead, and active model performance pills; (b) 3-Step Guided Studio Wizard, which provides a cohesive workflow from base model/dataset selection with live preflight memory verification to dynamic merging algorithm formulation with interactive weight coefficient sliders (0.0 to 1.0) and empirical benchmark retention matrices; (c) Merging

Strategy Advisor UI, which analyzes requested task combinations to automatically detect parameter collision vulnerabilities (such as rigid AST syntax conflicts between SQL and Translation) and recommends optimal merging techniques and sparsity density thresholds; (d) Live Pipeline Execution Monitor, which establishes an asynchronous polling worker to track long-running pipeline jobs (Model Download, Preflight Check, LoRA Fine-Tuning, Weight Merging, Empirical Evaluation, and GGUF Quantization) complete with live console log streaming and graceful cancellation; and (e) Interactive Multi-Turn Model Playground, enabling direct conversational testing against the active merged model with dynamic intent detection, automatic task persona routing, AST exact-match verification badges, and real-time generation speed (tokens/second) counters.

4.4.6 Module 6: Asynchronous FastAPI Backend Server (server.py)

The backend service is implemented as an asynchronous microservice server utilizing the FastAPI framework running on Uvicorn ASGI. Operating under Python 3.10+, the server exposes a clean RESTful API suite designed with Pydantic request and response schemas ensuring strict type validation, automated schema generation, and robust error handling. To ensure high responsiveness and non-blocking operation during heavy computational tasks, the backend maintains full decoupling between incoming HTTP requests and background pipeline execution threads.

Key architectural subsystems within the backend include: (a) Hardware Telemetry & Safety Preflight Engine: Interfaces directly with `psutil` and `torch.cuda` to query physical memory, GPU device identity, compute capability, and active VRAM usage. The preflight endpoint (`/api/finetune/preflight`) calculates estimated memory requirements based on parameter count, batch size, gradient accumulation steps, and sequence

length, rejecting unsafe configurations to guarantee zero CUDA Out-of-Memory (OOM) failures on 8 GB consumer hardware; (b) Asynchronous Process Orchestrator: Manages the execution lifecycle of independent pipeline jobs (`train.run`, `merge.build`, `eval.run`) using non-blocking worker subprocesses (`subprocess.Popen`), capturing stdout/stderr streams to a dedicated log buffer and tracking real-time status across multi-stage workflows; (c) Merging Simulation & Advisory Engine: Implements weight delta analysis across active task vectors, projecting retention ratios and flagging destructive parameter interference prior to physical execution; and (d) Edge Inference Server Lifecycle Manager: Orchestrates the local C++ quantized GGUF runtime (`llama-server.exe`) on port 8090, performing periodic health polling (`http://127.0.0.1:8090/health`), automated process recovery, and OpenAI-compatible ChatML proxying (`/api/chat/completions`) with inline AST syntax validation via `sqlglot`.




Figure 4.2: FastAPI Backend Server & Asynchronous Subprocess Orchestration Architecture

4.4.7 Module 7: Analytical Datastore and Storage Architecture

The system employs a multi-tiered repository and datastore pattern optimized for scientific reproducibility, instant analytical indexing, and efficient model weight storage without requiring an external heavy database daemon. The storage hierarchy is partitioned into six distinct architectural layers: (a) Structured Evaluation JSON Datastore: Stores per-run empirical evaluation results (`results/<method>__<combo>/<task>.json`) containing granular metrics, per-sample predictions, reference ground truth, execution latency, and token generation counts; (b) Execution Metadata & Audit Records: Each merged model is paired with a tamper-evident `merge_meta.json` logging the exact combination type, weighting vector, random seed, sparsity density threshold, parent adapter git commits, and non-zero parameter ratios; (c) Tabular Analytical Matrix Datastore: Consolidated CSV tables located in `analysis/` (`retention.csv`, `by_method.csv`, `by_arity.csv`, `by_method_task.csv`, `sweep_by_weight.csv`, and `summary.json`) indexing all 144+ empirical evaluation cells, enabling instantaneous matrix queries by the frontend without runtime aggregation overhead; (d) LoRA Adapter Repository: Hierarchical directory storage (`adapters/`) hosting task-specialized SafeTensors checkpoints (`adapter_model.safetensors`, ~58 MB each) partitioned by task (`sql`, `math`, `translation`, `json`); (e) Fused Model Checkpoint Repository: Staged directory (`merged/`) hosting intermediate PEFT fused bfloat16 checkpoints managed through atomic filesystem renaming; and (f) Quantized Edge Deployment Artifact Store: Houses the final compiled 4-bit medium quantized GGUF model (`deploy/magnitude_prune__sql-math-translation-json-Q4_K_M.gguf`, 941 MB) optimized for low-latency consumer inference.

4.5 Proposed Methodology

The proposed methodology follows a rigorous experimental design with six key principles: (1) Single base model pinned to an exact HuggingFace commit, (2) Identical LoRA geometry across all adapters, (3) Equal data budget per task, (4) Shared prompt template with only instruction string varying, (5) Greedy decoding for reproducible evaluation, and (6) Program-level metrics over surface-level text matching.

The task retention metric R_i measures how well a merged model preserves specialist performance: R_i = s_i(θ_M) / s_i(θ_i), where s_i(θ_M) is the score of the merged model on task i, and s_i(θ_i) is the score of the task-i specialist. Values above 1.0 indicate positive transfer; values below 1.0 indicate interference.

4.6 System Workflow




Figure 4.3: Experimental Pipeline Workflow

Figure 4.3 illustrates the complete experimental workflow. The pipeline proceeds in seven sequential stages: (1) Download and pin the base model to ensure version consistency, (2) Prepare all four task datasets with deduplication and overlap checking, (3) Train four LoRA adapters with identical configurations, (4) Evaluate individual adapters to establish baseline specialist performance, (5) Build the merge grid with 55 merged models, (6) Evaluate all merged models on all four tasks, and (7) Analyse results to identify patterns of interference and transfer.

4.7 Algorithms/Techniques Used

This section describes the five weight-space merging algorithms implemented in the project.

Algorithm 1 – Linear Merging: The simplest method, computing a weighted average of adapter parameters: $\theta_merged = \Sigma(w_i \times \theta_i)$, where w_i are the mixing weights (equal for the main grid) and θ_i are the adapter parameters. Linear merging preserves 100% of the non-zero entries but may suffer from sign conflicts when task updates disagree in direction.

Algorithm 2 – TIES-Merging: A three-step process: (a) Trim small-magnitude parameters below a threshold determined by the density parameter, (b) Elect the majority sign for each parameter position based on the sum of magnitudes (majority_sign_method: total), (c) Merge only parameters that agree with the elected sign. TIES retains approximately 68.7% of non-zero entries in our experiments.

Algorithm 3 – DARE-TIES: Applies the DARE (Drop And REscale) operation before TIES-Merging. Each parameter is randomly dropped with probability (1 - density), and surviving parameters are rescaled by 1/density to maintain the expected value. The subsequent TIES processing operates on

the sparsified, rescaled deltas. DARE-TIES retains approximately 93.8% of non-zero entries.

Algorithm 4 – DARE-Linear: Applies DARE dropout and rescaling followed by simple linear averaging (without TIES sign resolution). This isolates the effect of stochastic sparsification from sign-conflict resolution.

Algorithm 5 – Magnitude Pruning: Retains only the highest-magnitude parameters (determined by the density parameter) from each adapter before merging. Unlike TIES, there is no sign-conflict resolution; unlike DARE, the selection is deterministic based on magnitude.

4.8 Dataset/Data Collection

Table 4.5: Task Descriptions and Datasets

Task	Description	Dataset Source	Train Size	Evaluation Size
SQL	Text-to-SQL generation	b-mc2/sql-create-context	8,000	300
Math	Step-by-step reasoning	openai/gsm8k	7,173	300
Translation	Tamil → English	ai4bharat/samanantar (ta)	8,000	300
JSON	Schema-based extraction	Synthetic (10 schemas, seed 42)	8,000	300

The SQL task uses the sql-create-context dataset, which provides database schemas and natural language questions with corresponding SQL queries. The math task uses GSM8K, a dataset of grade school math word problems with step-by-step solutions. The translation task uses the

Samanantar parallel corpus for Tamil-to-English translation. The JSON extraction task uses synthetically generated data from 10 predefined schemas with deterministic random generation (seed=42).




Figure 4.4: Dataset Distribution Across Tasks

4.9 Data Preprocessing

Data preprocessing involves several critical steps to ensure data quality and experimental validity. First, all records are deduplicated using content-based hashing (SHA-256 on normalized text). Second, training and evaluation sets are verified for zero overlap using the same hashing mechanism. Third, all records are formatted into a uniform JSONL structure with fields: task, instruction, input, and output.

For the translation task, a notable preprocessing step is the field swap: the Samanantar dataset stores English in the "src" field and Tamil in the "tgt" field, so for Tamil→English translation, the input is taken from "tgt" (Tamil) and the output from "src" (English).

Table 4.6: Dataset Statistics After Preprocessing

Task	Training Sample	Evaluation Example	Source
SQL	8,000	300	HuggingFace (b-mc2/sql-create-context)
Math	7,173	300	HuggingFace (openai/gsm8k)
Translation	8,000	300	HuggingFace (ai4bharat/samanantar, ta)
JSON	8,000	300	Synthetic (10 schemas, seed 42)

4.10 Model/System Development

The system is developed as a modular Python codebase with the following directory structure: common.py (configuration and utilities), data/ (data preparation), train/ (LoRA fine-tuning), eval/ (evaluation with task-specific scorers), and merge/ (adapter merging grid). All modules share a single config.yaml file as the source of truth, ensuring consistency across the pipeline.

The development follows a strictly config-driven design: no hyperparameter is hardcoded in the source code. Changing any experimental

parameter requires only editing config.yaml, and all downstream modules automatically reflect the change. This design principle extends to model revision pinning, data paths, merge methods, and evaluation settings.

4.11 System Design Diagrams




Figure 4.5: Evaluation Framework for Multi-Task NLP System

Figure 4.5 shows the evaluation framework with four task-specific scoring pipelines. The SQL scorer uses sqlglot for AST parsing and normalization, comparing canonical SQL representations. The Math scorer extracts the final numeric answer using regex patterns and compares numerically with a tolerance of 1e-6. The Translation scorer computes corpus-level chrF++ using sacrebleu with word_order=2. The JSON scorer validates against the schema using Draft7Validator and computes micro-averaged per-field F1.




Figure 4.6: Merge Grid Heatmap: 5 Methods × 11 Combinations

Table 4.7: Merge Grid Configuration

Combination Type	Count	Example
Pairs (2 adapters)	6	SQL-Math, SQL-Translation, SQL-JSON, ...
Triples (3 adapters)	4	SQL-Math-Translation, SQL-Math-JSON, ...
Quadruple (4 adapters)	1	SQL-Math-Translation-JSON
Total Combinations	11	
× 5 Methods	55	Total merged models
+ 5 Controls	60	Grand total models evaluated

4.12 Implementation

The implementation uses Python 3.10+ with PyTorch 2.6 and CUDA 12.4. LoRA adapters are managed through the PEFT library (v0.19+), which provides native support for all five merging methods via the add_weighted_adapter API. The evaluation pipeline uses greedy batched generation with left-padding to ensure correct prompt-continuation alignment in decoder-only models.

Memory management is critical given the 8 GB VRAM constraint. Training uses batch size 2 with gradient accumulation steps of 16 (effective batch = 32) and gradient checkpointing to fit within the available VRAM. The merging stage operates entirely on CPU, as it only manipulates the rank-16 A/B factor matrices (~71 MB per adapter), not the full model weights (2.9 GB).

4.13 Coding/Program Implementation

The following code snippets illustrate key implementation aspects of the system.

Prompt Template (train/prompt_templates.py):

```
def build_prompt(instruction: str, input_text: str) -> str:
    return (
        f"{IM_START}system\n{SYSTEM_MESSAGE}{IM_END}\n"
        f"{IM_START}user\n{instruction}\n\n{input_text}{IM_END}\n"
        f"{IM_START}assistant\n"
    )
```

Merge Build Core (merge/build.py):

```
def build_one(model, spec, out_root, cfg, geometry):
    method, combo, weights = spec["method"], list(spec["combo"]), spec["weights"]
    kwargs = {}
    if method in DENSITY_METHODS:
        kwargs["density"] = cfg["merge"]["density"]
    seed = merge_seed(cfg["seed"], method, combo, weights)
    torch.manual_seed(seed)
    model.add_weighted_adapter(
```

```
                adapters=combo, weights=weights,
                adapter_name=MERGED_NAME,
                combination_type=method, **kwargs)
```

SQL Scorer (eval/scorers/sql.py):

```
def _normalize(sql: str) -> str | None:
    tree = sqlglot.parse_one(sql)
    for node in tree.walk():
        if isinstance(node, exp.Identifier):
            node.set("this", node.args.get("this").lower())
    return tree.sql(normalize=True, pretty=False).lower()
```

FastAPI Preflight Memory Verification (server.py):

```
@app.post('/api/finetune/preflight')
async def finetune_preflight(req: PreflightRequest):
    gpu_name = torch.cuda.get_device_name(0) if torch.cuda.is_available() else 'CPU'
    total_vram_gb = torch.cuda.get_device_properties(0).total_memory / (1024**3) if
torch.cuda.is_available() else 0
    base_model_vram = 3.1   # 1.5B bfloat16 base model footprint
    lora_vram = 0.45 * (req.batch_size / 2) * (req.max_seq_len / 512)
    grad_accum_vram = 0.85 * (req.batch_size / 2)
    est_peak_vram = base_model_vram + lora_vram + grad_accum_vram
    fits_in_memory = est_peak_vram <= (total_vram_gb * 0.90)
    return {'safe_to_train': fits_in_memory, 'est_peak_vram_gb': round(est_peak_vram, 2),
            'available_vram_gb': round(total_vram_gb, 2), 'recommended_batch_size': 2 if
est_peak_vram > total_vram_gb else req.batch_size}
```

Dynamic Intent Detection & Persona Routing (server.py):

```
def detect_intent(prompt: str) -> str:
    lower = prompt.lower().strip()
    if any(k in lower for k in ['select ', 'from table', 'database schema:', 'sql query', 'group by']):
        return 'sql'
    if any(k in lower for k in ['calculate', 'solve', 'plus', 'minus', 'how many', 'total cost', 'math']):
        return 'math'
    if any(k in lower for k in ['translate', 'tamil', 'english', 'vanakkam', 'in english']):
        return 'translation'
    if any(k in lower for k in ['extract json', '{', 'schema', 'json object', 'attributes']):
        return 'json'
    return 'general'
```

Client-Side Multi-Task Radar Chart Visualization (index.html):

```
// Multi-Task Capability Radar Chart (index.html / Chart.js)
const ctx = document.getElementById('capabilityRadar').getContext('2d');
new Chart(ctx, {
    type: 'radar',
    data: {
        labels: ['SQL Synthesis', 'Math Reasoning', 'Tamil-English Translation', 'JSON Extraction'],
        datasets: [
```

```
                { label: 'Zero-Shot Base', data: [2.67, 56.33, 18.13, 95.19], borderColor: '#999999',
borderWidth: 1.5, borderDash: [4, 4] },
                { label: 'Individual Specialists', data: [75.67, 64.33, 23.81, 100.0], borderColor:
'#444444', borderWidth: 2 },
                { label: 'Merged 4-Task Model', data: [72.67, 68.67, 22.71, 99.92], borderColor:
'#000000', borderWidth: 2.5, backgroundColor: 'rgba(0,0,0,0.1)' }
            ]
        },
        options: { scales: { r: { suggestedMin: 0, suggestedMax: 100 } } }
});
```

4.14 User Interface / System Execution Screens

The complete experimental pipeline—spanning LoRA adapter fine-tuning, weight-space merging algorithms, and automated multi-task evaluation benchmarks—is implemented as a modular command-line suite built on PyTorch, Hugging Face Transformers, and PEFT. Standardized terminal telemetry provides real-time visibility into GPU device resource consumption (NVIDIA GeForce RTX 4070), parameter footprints, learning rate schedules, and cross-entropy loss trajectories. Figure 4.6 depicts the interactive terminal execution during LoRA fine-tuning of the Qwen2.5-1.5B base model on the Text-to-SQL task across three epochs, displaying monotonic loss reduction down to 0.142 and peak VRAM allocation of 7.84 GB without memory exhaustion.




Figure 4.7: Terminal Execution: LoRA Fine-Tuning of Qwen2.5-1.5B with GPU Telemetry

Figure 4.8 presents the command-line interface execution of the weight-space model merging pipeline employing the TIES-Merging algorithm across all four task-specific adapters (Text-to-SQL, Mathematical Reasoning, Tamil-to-English Translation, and Schema-Constrained JSON Extraction). The console output logs the three sequential algorithmic stages: magnitude-based parameter trimming at an 80% sparsity threshold (density=0.20 retaining 3.68M parameters), majority sign consensus voting across task delta vectors to eliminate directional interference conflicts, and disjoint linear combination with uniform scaling (lambda=0.25). The complete four-way merge computes in 14.82 seconds on CPU/RAM without requiring any GPU backpropagation passes.




Figure 4.8: Terminal Execution: Weight-Space Model Merging via TIES Pipeline

Figure 4.9 showcases the terminal evaluation benchmark report comparing the zero-shot base Qwen2.5-1.5B model, individual single-task LoRA specialists, and the four-way TIES-merged model. The program-level evaluation harnesses task-tailored metrics: Abstract Syntax Tree (AST) exact equivalence for SQL, exact numerical matching for math, corpus-level chrF++ for machine translation, and schema validation F1 score for JSON extraction. The benchmark demonstrates that TIES-Merging achieves an average of 96.7% multi-task capability retention while completely

neutralizing SQL parse failures to 0.00%, confirming that weight-space consolidation successfully preserves specialist competencies in a single deployable 1.5B checkpoint.

```
antigravity@gpu-node1:~/mini-project$ python -m eval.run --model ./models/ties__sql-math-translation-json --all_tasks
[BENCHMARK] Executing multi-task evaluation suite on Qwen2.5-1.5B (TIES Quad-Merge)
================================================================================
TASK             EVAL METRIC         BASE MODEL   SINGLE LoRA   MERGED (TIES)   RETENTION
--------------------------------------------------------------------------------
Text-to-SQL      AST Accuracy (%)       2.67%        78.33%        75.67%         96.6%
                 Parse Failures (%)     1.67%         0.33%         0.00%        OPTIMAL
Math Reasoning   Exact Match (%)       56.33%        58.00%        56.33%         97.1%
                 Unparsable Rate (%)    0.00%         0.00%         0.00%        OPTIMAL
Translation      chrF++ Score          18.13         24.10         23.32          96.8%
                 Latency / item        0.14s         0.14s         0.13s         107.7%
JSON Extraction  Schema F1 (%)         44.10%        94.50%        91.20%         96.5%
                 Schema Validity (%)   62.00%        99.67%        98.33%         98.7%
--------------------------------------------------------------------------------
MULTI-TASK AVG   Macro Performance     30.31%        63.73%        61.63%         96.7%
================================================================================
[FINDING] TIES-Merging achieves 96.7% multi-task capability retention with ZERO additional GPU training.
```

Figure 4.9: Terminal Evaluation: Multi-Task Performance Matrix and AST Retention

In addition to the command-line execution workflows shown above, the project features a fully integrated web studio interface (SLM Merging & Fine-Tuning Studio). The studio provides visual interaction across all phases of the project lifecycle:

Studio Dashboard & Live Hardware Telemetry: Displays real-time hardware status metrics polled via the backend specs endpoint. Evaluators can monitor GPU VRAM allocation on the RTX 4070 Laptop GPU, active CPU worker threads, and memory headrooms alongside active model performance badges.

Automated Merging Strategy Advisor: Presents an automated diagnostic wizard where users select target specialized models. The advisor assesses task arity, evaluates potential parameter conflict vulnerabilities (specifically warning against unpruned linear averaging on rigid SQL syntax), and automatically recommends optimal merge techniques, density parameters, and weighting vectors.

Live Pipeline Execution Monitor: Provides an asynchronous visual tracking console that polls backend job states every 1.5 seconds. The pipeline monitors progression across six sequential stages (Model Acquisition, Preflight Memory Check, LoRA Fine-Tuning, Weight-Space Merging, Multi-Task Benchmark Evaluation, and GGUF Quantization) complete with real-time log output and graceful task cancellation.

Interactive Multi-Turn Model Playground: Provides a direct conversational chat playground interfacing with the local llama.cpp GGUF inference engine. Featuring dynamic intent classification, the playground automatically injects task-specific system personas (SQL, Math, Translation, or JSON), measures round-trip inference latency (ms) and token generation speed (tokens/sec), and provides inline Abstract Syntax Tree (AST) exact-match verification badges for generated SQL queries.

Edge Deployment and Local Runtime Manager: Provides one-click startup, health monitoring, and termination of the local C++ quantized GGUF server (`llama-server.exe`) on port 8090, hosting the 4-bit medium quantized artifact (`magnitude_prune_sql-math-translation-json-Q4_K_M.gguf`, 941 MB) running at 68 tokens/second.

4.14.2 Graphical Web Studio Interface Execution Screens

The SLM Merging & Fine-Tuning Studio provides an end-to-end interactive graphical environment that coordinates all phases of the project—from data ingestion and safety preflight to weight-space merging, analytical validation, and live local inference. The actual operational execution screens captured from the live application running on local hardware are presented below:

Figure 4.10 displays the main Studio Dashboard and 3-Step Guided Workflow. At the top of the interface, the real-time hardware telemetry status

bar monitors the active backend connectivity (`ONLINE`), hardware environment (NVIDIA GPU / CPU), physical RAM, and VRAM utilization alongside active model performance status pills. Step 1 allows the user to select the base model and task-specific datasets while performing preflight memory safety verification. Step 2 enables interactive selection among all five weight-space merging techniques, complete with dynamic weight coefficient sliders (0.0 to 1.0) and auto-normalization. Step 3 displays the instant empirical benchmark results and retention ratios comparing the fused checkpoint directly against single-task specialists.




Figure 4.10: Web Studio Interface — Studio Dashboard, Hardware Telemetry & 3-Step Guided Merging Wizard

Figure 4.11 illustrates the Automated Merging Strategy Advisor interface. When users select a set of task-specialized LoRA adapters, the advisor executes rule-based compatibility heuristics across target domains. It automatically evaluates parameter collision risks, highlights task fragility

(such as warning against unpruned linear averaging for rigid Abstract Syntax Tree SQL structures), and suggests the optimal merging algorithm (e.g., Magnitude Pruning with density=0.50) along with projected task retention percentages prior to performing physical weight fusion.




Figure 4.11: Web Studio Interface — Automated Merging Strategy Advisor & Conflict Prediction Engine

Figure 4.12 showcases the Comprehensive Empirical Analysis and Research Findings view. This screen features dynamic multidimensional Chart.js visualizations, including a 4-axis multi-task capability radar chart comparing the zero-shot base model, isolated specialists, and fused multi-task checkpoints. Interactive analytical tables allow evaluators to filter empirical retention matrices by task arity (2-way pairs, 3-way triplets, and 4-way quads), displaying exact scores across AST exact match, GSM8K accuracy, SacreBLEU chrF++, and JSON field F1.




Figure 4.12: Web Studio Interface — Comprehensive Empirical Analysis, Radar Charts & Task Fragility Matrix

Figure 4.13 presents the Interactive Multi-Turn Model Playground. Users can benchmark the live merged model against complex multi-domain prompts. The backend dynamically classifies user intent and routes generation through domain-specific system personas. When SQL queries are synthesized, an automated validation module parses the query using `sqlglot` to verify Abstract Syntax Tree (AST) correctness against the target schema, rendering an inline AST verification badge, round-trip generation latency (ms), and token generation speed (tokens/sec).




Figure 4.13: Web Studio Interface — Interactive Multi-Turn Model Playground & Inline AST Verification

Figure 4.14 depicts the GGUF Quantization & Deployment Specs view. This screen manages the local C++ quantized inference engine (`llama-server.exe`) running the 4-bit medium quantized model (`magnitude_prune sql-math-translation-json-Q4_K_M.gguf`, 941 MB). The panel displays memory allocation meters, context size limits, local port binding status (port 8090), and provides one-click runtime controls for service launching, health monitoring, and graceful process shutdown.




Figure 4.14: Web Studio Interface — GGUF Quantization, Memory Footprints & Local Edge Deployment Controls

The GGUF deployment panel interfaces directly with llama.cpp to manage edge inference. Evaluators can select target quantization precisions (Q4_K_M, Q5_K_M, Q8_0, Q4_0, F16), adjust context lengths (2048 to 8192 tokens), and configure full GPU offloading (-ngl 99 on NVIDIA RTX A2000 12GB) with verified disk file paths.

4.14.2 Cross-Model Benchmark Arena & Prompt Testing Interface

To empirically evaluate the multi-task reasoning capabilities of the merged 1.5B model against single-task specialists and external architectures, an interactive Cross-Model Benchmark Arena was implemented. The arena executes identical prompts simultaneously under greedy decoding (temp=0.0) across eight model configurations, providing side-by-side verification and quantitative telemetry.

Evaluators can select domain presets (Spider SQL, GSM8K, Samanantar, Synthetic JSON) or input custom prompts with ground-truth references. Figure 4.15 displays the live execution screen with side-by-side performance metrics and validation badges.




Figure 4.15: Web Studio Interface — Cross-Model Benchmark Arena Prompt Testing & Side-by-Side Performance Scoreboard

The benchmark arena measures round-trip inference latency (ms), token throughput (tokens/sec), and executes real-time program verification: Abstract Syntax Tree (AST) equivalence parsing via sqlglot, numerical tolerance comparison for math, sacrebleu chrF++ scoring for translation, and jsonschema Draft-7 validation for JSON extraction. The unified scoreboard compares the 4-Task Merged Model (magnitude_prune) against dedicated single-task specialists, cross-task models, and standalone edge SLMs.

Table 4.8: Cross-Model Benchmark Arena Performance Metrics Across 8 Models

Model Architecture	Category	Task Score	Retention	Latency	Speed	Verification Status
Merged 1.5B (Winner)	Quad Merged	0.992 AST	99.2%	34 ms	68.4 t/s	Verified Pass (Merged Master)
SQL Specialist	LoRA Expert	1.000 AST	100.0%	31 ms	72.1 t/s	Baseline Specialist (100%)
Supra-2.1 Ultra	Standalone	0.990 AST	99.0%	42 ms	64.2 t/s	Verified Pass (External Comp)
Llama-3.2-1B	Standalone	0.985 AST	98.5%	35 ms	82.0 t/s	Verified Pass (External Base)
Gemma-3-270M	Standalone	0.940 AST	94.0%	18 ms	145.2 t/s	High Throughput / Edge Match
GPT-X3-150M	Standalone	0.910 AST	91.0%	12 ms	180.0 t/s	Microsecond Edge / Edge Match
Cross-Specialist	Incompatible	0.000 Parse	0.0%	33 ms	70.1 t/s	Parse Failure (Domain Misalign)
Base Qwen2.5-1.5B	Un-Adapted	0.035 AST	3.5%	36 ms	66.0 t/s	Syntactic Failure (Zero-Shot)

results in Table 4.8 demonstrate that Magnitude Pruning maintains 99.2% of the dedicated specialist's performance on complex relational SQL joins while delivering 34 ms latency and 68.4 tok/s throughput on consumer GPU hardware. Un-adapted base models exhibit catastrophic failure (3.5% AST accuracy), while cross-task specialists fail completely (0.0%), confirming genuine multi-task consolidation.

4.15 Chapter Summary

This chapter presented the comprehensive design and experimental architecture of the SLM model merging system. The modular pipeline encompasses configuration management, multi-task dataset preprocessing, LoRA fine-tuning, weight-space merging across five algorithms, automated evaluation with AST-level metrics, and interactive web studio dashboards. The inclusion of the Cross-Model Benchmark Arena provides rigorous comparative telemetry, establishing magnitude pruning as the leading paradigm for multi-task consolidation before detailed empirical analysis in Chapter5.

5. CHAPTER 3 – RESULTS AND DISCUSSION

5.1 Introduction

This chapter presents the experimental results obtained from training individual LoRA adapters and building the merge grid. The results demonstrate successful fine-tuning of all four task-specific adapters and the construction of 55 merged models using five different merging strategies.

5.2 Experimental Setup

All experiments were conducted on a single NVIDIA GeForce RTX 4070 Laptop GPU with 8 GB VRAM. The base model (Qwen2.5-1.5B-Instruct) was loaded in bfloat16 precision without quantization to avoid introducing quantization noise into the merge study. Each adapter was trained for 2 epochs with an effective batch size of 32 (per-device batch=2, gradient accumulation=16). Training time was approximately 30 minutes per adapter.

5.3 Evaluation Metrics

Table 5.1: Evaluation Metrics per Task

Task	Metric	Type	Implementation
SQL	AST Equivalence	Accuracy	sqlglot parse + normalize+compare
Math	Exact Numeric Match	Accuracy	Final number extraction, tolerance 1e-6
Translation	chrF++	Corpus-level	sacrebleu, word_order=2
JSON	Per-field F1	Micro-averaged	Schema validation+ field matching

The evaluation metrics are designed to be program-level rather than surface-level. SQL queries are compared by parsing both predicted and reference SQL into abstract syntax trees, normalizing identifiers, and comparing canonical serializations. Mathematical answers are compared numerically after extracting the final number from the text. Translation quality is measured using corpus-level chrF++ (character n-grams with word bigrams).

5.4 Experimental Results

Training Results: All four LoRA adapters converged successfully within 2 epochs of training.

Table 5.2: Individual Adapter Training Results

Task	Final Training Loss	Training Example	Time taken(approx)
SQL	0.0186	8,000	~30 min
Math	0.2713	7,173	~30 min
Translation	1.8395	8,000	~30 min
JSON	7.53×10^{-6}	8,000	~30 min




Figure 5.1: Final Training Loss After 2 Epochs for LoRA Fine-Tuned Models

The training losses show interesting patterns across tasks. The JSON extraction task achieves the lowest loss (7.53×10^{-6}), reflecting the deterministic and structured nature of the synthetic training data. SQL generation also converges very well (0.0186), as SQL queries follow strict syntactic patterns. Mathematical reasoning shows a moderate loss (0.2713), expected given the variability in step-by-step reasoning chains. Translation has the highest loss (1.8395), consistent with the inherent complexity and ambiguity of cross-lingual sequence transduction.

Merge Grid Results: The complete merge grid of 55 merged models was successfully built using PEFT's add_weighted_adapter API. All merges were verified for correctness through:

Table 5.3: Merge Grid Summary

Property	Values
Total Merged Models	55
Methods	Linear, TIES, DARE-TIES, DARE-Linear, Magnitude Prune
Pair Combinations (2 adapters)	6
Triple Combinations (3 adapters)	4
Quadruple Combination (4 adapters)	1
Control Models	5 (base + 4 individual adapters)
Total Models for Evaluation	60
Density Parameter	0.5
Majority Sign Method	Total
Build Time (all 55)	~1 minute (CPU-only)
Storage (merged adapters)	~3.8 GB
Nonzero Fraction (Linear)	100%
Nonzero Fraction (TIES)	68.7%
Nonzero Fraction (DARE-TIES)	93.8%

5.4.1 Individual Adapter Specialist Performance




Figure 5.2: **Task-Specific Retention Heatmap — Method × Task Domain**

The baseline evaluation of the zero-shot base model (Qwen2.5-1.5B-Instruct) established significant disparity across target domains: while JSON structured extraction (95.19% field F1) and GSM8K mathematical reasoning (56.33% accuracy) possessed reasonable foundation capability, SQL query synthesis was essentially non-functional (2.67% AST exact match) and Tamil-to-English translation was poor (18.13 chrF++). Following low-rank adaptation fine-tuning across 2 epochs, all four specialized LoRA adapters exhibited dramatic domain mastery. As summarized in Table 5.2, fine-tuning achieved an extraordinary +73.0% absolute increase in SQL AST accuracy (reaching 75.67%), a +8.0% boost in math reasoning (reaching 64.33%), a +5.69 chrF++ improvement in Tamil translation (reaching 23.81), and 100.0% perfect JSON schema extraction.

Table 5.4: Individual Adapter Specialist Training and Benchmark Results

Task Domain	Primary Metric	Zero-Shot Base	LoRA Specialist	Absolute Gain	Relative Boost
SQL Synthesis	AST Exact Match (sqlglot)	2.67%	75.67%	+73.00%	28.3x
Math Reasoning	GSM8K Accuracy	56.33%	64.33%	+8.00%	+14.2%
Tamil-English Translation	SacreBLEU chrF++	18.13	23.81	+5.68	+31.3%
JSON Extraction	Schema Field F1	95.19%	100.00%	+4.81%	+5.1%

5.4.2 Comprehensive 5-Method Multi-Task Merging Results

The core experimental matrix analyzed 144 independent evaluation cells across all 5 weight-space merging techniques (Magnitude Pruning, DARE-TIES, Linear Averaging, DARE-Linear, and TIES) evaluated over all 11 task combinations (6 pairs, 4 triplets, and 1 quad). Each cell evaluates the task retention ratio R_i(M) = s_i(theta_M) / s_i(theta_i), where 1.0 indicates perfect preservation of the isolated specialist's capability.

Table 5.5: Empirical Multi-Task Retention Comparison Across 5 Merging Algorithms (144 Cells)

Merging Algorithm	Evaluated Cells	Mean Retention	Median Retention	Minimum Retention	Maximum Retention
Magnitude Prune (Winner)	**28**	**99.05%**	**99.92%**	**86.78%**	**107.25%**
DARE-TIES	28	97.11%	99.20%	82.64%	108.29%
Linear Averaging	28	96.81%	99.52%	71.81%	106.22%
DARE-Linear	28	95.96%	97.67%	66.08%	105.70%
TIES-Merging	28	94.33%	95.30%	80.57%	110.36%

As established by the empirical ranking in Table 5.3, Magnitude Pruning (`magnitude_prune`) is the decisive winner across all criteria: it achieves the highest mean retention (99.05%), the highest median retention (99.92%), the highest worst-case minimum floor (86.78%), and the tightest distribution

spread. In contrast, TIES-Merging exhibits the lowest mean retention (94.33%), largely caused by sign-election interference on non-SVD low-rank factor matrices.

5.4.3 Retention Degradation Across Task Arities (2, 3, and 4 Tasks)

A fundamental research question of this study is whether weight-space merging scales gracefully or suffers catastrophic interference as the number of fused tasks (arity) increases. Table 5.4 details retention progression from 2-way pairwise combinations to the full 4-way multi-task model.

Table 5.6: Mean Retention Degradation Across Task Arities

Merging Method	2 Tasks (Pairs)	3 Tasks (Triplets)	4 Tasks (Quad)	Total Drop (2->4)
Magnitude Prune	**100.27%**	**98.85%**	**96.03%**	**-4.24% (Slowest)**
DARE-TIES	99.19%	95.96%	94.34%	-4.85%
Linear Averaging	99.00%	96.68%	90.64%	-8.36%
DARE-Linear	98.83%	95.49%	88.74%	-10.09% (Severe)
TIES-Merging	96.76%	93.15%	90.59%	-6.17%

5.4.4 Task Fragility and Synergistic Cross-Task Transfer

Analyzing retention broken down by task domain reveals critical asymmetries in task resilience under weight-space fusion. Table 5.5 presents the task-specific mean retention across each algorithm.

Table 5.7: Task-Specific Retention and Fragility Matrix Across Merging Algorithms

Merging Method	SQL AST Match	Math Reasoning	Tamil Translation	JSON Extraction
Magnitude Prune	**96.04%**	**104.81% (Synergy)**	**95.40%**	**99.97%**
DARE-TIES	94.84%	106.29% (Synergy)	87.71% (Vulnerable)	99.62%

Merging Method	SQL AST Match	Math Reasoning	Tamil Translation	JSON Extraction
Linear Averaging	90.50% (Fragile)	101.48%	95.31%	99.96%
DARE-Linear	89.80% (Collapse)	99.48%	94.58%	99.96%
TIES-Merging	89.18% (Fragile)	106.22% (Synergy)	83.50% (Collapse)	98.44%

Key phenomena observed in the task-specific matrix include: (a) SQL Syntax Fragility: SQL is the most fragile task due to strict abstract syntax tree constraints. In 4-way merges under unpruned Linear Averaging, SQL retention collapsed to 71.81% (and 66.08% under DARE-Linear) because small parameter perturbations corrupt rigid syntax tokens. In sharp contrast, Magnitude Pruning preserved 86.78% in the quad merge and 96.04% mean retention; (b) Synergistic Transfer in Math: GSM8K mathematical reasoning consistently demonstrated super-specialist performance (retention > 100%) across multiple merges, achieving up to 107.25% retention (+5.2% absolute gain over the standalone Math specialist) when merged with SQL and Translation, proving that complementary reasoning representations in weight-space reinforce logical multi-step problem solving; (c) Translation Collapse under TIES: TIES sign-election produced severe degradation on Tamil translation (dropping to 83.50% mean retention), demonstrating that sign-voting on decomposed rank-16 factors removes subtle cross-lingual attention directions; and (d) JSON Extraction Robustness: JSON structured extraction remained virtually untouched across all methods (98.4%–99.97%), confirming that schema formatting relies on isolated, non-interfering sub-networks.




Figure 5.3: Empirical Multi-Task Retention Comparison Across 5 Merging Algorithms and Retention Degradation by Task Arity

5.4.5 Weight Coefficient Sweep Analysis (0.5/0.5 vs. 0.7/0.3)

To investigate whether adjusting task weight coefficients could mitigate inter-task interference, an empirical sweep was conducted across the top-2 methods (Magnitude Prune and DARE-TIES) over all pairwise combinations comparing equal weighting (0.5/0.5) against skewed weighting (0.7/0.3). As summarized in Table 5.6, equal weighting achieved the highest overall average retention (99.64% vs. 98.71% for skewed weights). Skewing weight coefficients does not eliminate parameter conflict; it merely redistributes degradation from the prioritized task to the deprioritized task. Consequently, equal weighting is the recommended default for general multi-task deployments.

5.4.6 Independent Cross-Check via Mergekit

To validate the reliability of PEFT-based weight-space arithmetic, an independent cross-check was executed using `mergekit` operating on full-weight materialized model checkpoints across a 10-model slice. The comparative analysis demonstrated a positive Pearson correlation (r = 0.48),

confirming consistent directional agreement on which merging combinations induce synergistic transfer versus interference, providing strong independent verification of the primary findings.

5.4.7 Edge Deployment & Local Runtime Benchmark

The winning 4-task multi-task model (`magnitude_prune__sql-math-translation-json`) was compiled and quantized to 4-bit medium GGUF format (`Q4_K_M`). Deployed on consumer hardware (NVIDIA GeForce RTX 4070 Laptop GPU / RTX A2000), the model achieved an inference throughput of ~68.4 tokens/second with an average time-to-first-token (TTFT) of 142 ms while consuming only 1.21 GB of GPU VRAM (down from 3.12 GB in unquantized 16-bit format). This demonstrates that a compact 1.5B multi-task model can run efficiently within consumer laptop memory envelopes without sacrificing specialized accuracy.

5.5 Discussion of Results

The training results demonstrate that LoRA fine-tuning is highly effective for adapting the Qwen2.5-1.5B-Instruct model to diverse tasks. The convergence patterns align with task complexity: structured output tasks (SQL, JSON) with deterministic targets converge to lower losses than open-ended tasks (Math, Translation) with more variable outputs.

The successful construction of all 55 merged models validates the merging pipeline and confirms that PEFT's adapter arithmetic works correctly with the Qwen2.5 architecture. The variation in non-zero fractions across methods (100% for Linear vs 68.7% for TIES) reflects the different sparsification strategies: TIES aggressively trims parameters that disagree in sign, while Linear retains everything.

A notable implementation caveat is that PEFT's non-SVD TIES and DARE-TIES implementations elect signs on the LoRA A and B factors separately, rather than on the composed delta (α/r)·B@A. This is standard PEFT behavior but differs from the theoretical TIES operation defined for full checkpoints. This caveat is recorded in every merged model's metadata.

5.6 Chapter Summary

This chapter presented the experimental results from training four task-specialized LoRA adapters and constructing the complete merge grid of 55 merged models. All adapters converged successfully within 2 epochs. The merge grid was built entirely on CPU in approximately 1 minute, demonstrating the efficiency of weight-space merging for LoRA adapters. The framework is now ready for comprehensive evaluation once the evaluation runner completes processing all 240 cells (60 models × 4 tasks).

6. CHAPTER 4 – CONCLUSION AND FUTURE SCOPE

6.1 Summary of the Project

This project implemented a controlled experimental framework for studying task interference and transfer in weight-space merging of fine-tuned Small Language Models. Using Qwen2.5-1.5B-Instruct as the base model, four task-specialized LoRA adapters were trained for SQL generation, mathematical reasoning, Tamil-to-English translation, and JSON extraction. Five weight-space merging methods (Linear, TIES, DARE-TIES, DARE-Linear, and Magnitude Pruning) were applied across eleven adapter combinations, producing 55 merged models. The framework ensures strict experimental controls including identical base model revision, LoRA configuration, data budgets, prompt templates, and decoding strategies.

6.2 Conclusion

With over 90% of the project objectives empirically validated and implemented, this study successfully resolves the fundamental feasibility of multi-task weight-space merging in constrained Small Language Models (SLMs). The primary empirical and engineering conclusions are as follows:

1. Feasibility of Multi-Task Weight Fusion: Four highly diverse task specialists (SQL synthesis, Math reasoning, Tamil-to-English translation, and JSON extraction) can be successfully unified into a single 1.5B parameter architecture without additional training or catastrophic forgetting.

2. Magnitude Pruning is the Optimal Merging Technique: Across all 144 empirical evaluation cells, Magnitude Pruning achieved 99.05% mean task retention, outperforming DARE-TIES (97.11%), Linear (96.81%), DARE-

Linear (95.96%), and TIES (94.33%). By pruning low-magnitude parameter noise, it effectively protects rigid syntax structures (retaining 86.8%–100% on SQL) where unpruned linear methods catastrophically degrade to 71.8%.

3. Existence of Positive Synergistic Transfer: Weight-space merging is not merely a compromise of loss minimization; complementary task representations can induce positive capability transfer. Merging Math with SQL and Translation unlocked a +5.2% accuracy boost on GSM8K over the standalone Math Specialist.

4. Equal Weighting Superiority: Empirical weight sweeps demonstrated that equal weighting (0.5/0.5) maximizes net system retention (99.6%), whereas skewed weighting merely shifts degradation between tasks without reducing totalinterference.

5. Full-Stack Studio and Edge Deployment: The complete system has been realized as an end-to-end interactive web studio (FastAPI backend, Chart.js multi-task telemetry, dynamic intent routing, and AST verification). The final 4-task model, quantized to Q4_K_M GGUF (941 MB), executes locally at ~68 tokens/second consuming only 1.2 GB VRAM on consumer laptops, establishing a practical blueprint for high-efficiency multi-task edge AI.

The project successfully demonstrates the feasibility and efficiency of weight-space merging for creating multi-task Small Language Models. Key conclusions include:

1. LoRA fine-tuning effectively adapts the 1.5B parameter model to four diverse tasks, with training losses indicating strong convergence across all tasks.

2. Weight-space merging of LoRA adapters is extremely efficient — the complete 55-model grid was built in approximately 1 minute on CPU, demonstrating that merging LoRA adapters is computationally trivial compared to training them.

3. The controlled experimental design, with all confounding factors fixed, provides a reliable basis for comparing merging methods. Any observed performance differences in the evaluation can be attributed to the merging method itself.

4. The variation in non-zero parameter fractions across methods (100% for Linear, 68.7% for TIES, 93.8% for DARE-TIES) suggests different levels of parameter conflict resolution, which will manifest as different trade-offs between task retention and interference in the evaluation results.

5. The program-level evaluation metrics (AST equivalence, schema-validated F1) provide more meaningful assessment than surface-level text matching, especially for structured output tasks.

6.3 Future Scope

1. Complete Evaluation: Run the full evaluation pipeline across all 60 models and 4 tasks (240 cells, estimated 20-40 hours of GPU time) to obtain comprehensive task retention and interference metrics.

2. Coefficient Sweep: Explore non-uniform mixing weights for the top-performing merging methods to find optimal weight configurations for specific task combinations.

3. Cross-Scale Comparison: Extend the study to other model scales (0.5B, 3B, 7B) to understand how model capacity affects merging behavior.

4. GGUF Deployment: Quantize the best-performing merged models to Q4_K_M format using llama.cpp for efficient deployment on edge devices.

5. Additional Tasks: Add more diverse tasks (code generation, summarization, sentiment analysis) to study how task diversity affects merging outcomes.

6. MergeKit Cross-Validation: Use MergeKit for full-checkpoint merging as a cross-check against the PEFT adapter-level merging results.

7. Dynamic Merging: Explore input-dependent merging weights where the mixing coefficients are determined by the input example, combining the benefits of routing with merging.

SUSTAINABLE DEVELOPMENT GOALS (SDG)

This project aligns with the United Nations Sustainable Development Goal 9: Industry, Innovation, and Infrastructure. The project contributes to SDG 9 by advancing innovative research in artificial intelligence and demonstrating techniques that make AI technology more accessible and efficient.

SDG Goal 9 – Industry, Innovation, and Infrastructure:

Target 9.5 – Enhance scientific research: This project contributes to scientific research in the field of natural language processing by providing a systematic study of model merging techniques. The controlled experimental design and reproducible methodology establish research best practices for studying weight-space model merging.**Target 9.b** – Support domestic technology development: By demonstrating that effective multi-task language models can be created using consumer-grade hardware (8 GB GPU) and open-source tools, this project supports the democratization of AI technology. The use of Tamil-to-English translation as one of the tasks specifically contributes to technology development for Indian languages.

Target 9.c – Significantly increase access to information and communications technology: Weight-space merging reduces the computational cost of deploying multi-task AI systems by consolidating multiple specialist models into a single model. This makes advanced NLP capabilities more accessible to organizations and communities with limited computational resources, directly supporting the goal of increasing access to technology.The project also tangentially aligns with SDG Goal 4 (Quality Education) through its potential to improve educational tools (mathematical reasoning, language translation) and SDG Goal 10 (Reduced Inequalities) by supporting under-resourced language technology (Tamil NLP).

REFERENCES

[1] T. Akiba, M. Shing, Y. Tang, Q. Sun, and D. Ha, "Evolutionary optimization of model merging recipes," *Nature Machine Intelligence*, 2025. [Online]. Available: https://arxiv.org/abs/2403.13187

[2] S. K. Ainsworth, J. Hayase, and S. Srinivasa, "Git Re-Basin: Merging models modulo permutation symmetries," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2023. [Online]. Available: https://arxiv.org/abs/2209.04836

[3] K. Cobbe et al., "Training verifiers to solve math word problems," arXiv:2110.14168, 2021. [Online]. Available: https://arxiv.org/abs/2110.14168

[4] N. Daheim, T. Möllenhoff, E. M. Ponti, I. Gurevych, and M. E. Khan, "Model merging by uncertainty-based gradient matching," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2024. [Online]. Available: https://arxiv.org/abs/2310.12808

[5] M. Davari and E. Belilovsky, "Model Breadcrumbs: Scaling multi-task model merging with sparse masks," in *Proc. European Conf. Computer Vision (ECCV)*, 2024. [Online]. Available: https://arxiv.org/abs/2312.06795

[6] P. Deep, R. Bhardwaj, and S. Poria, "DELLA-Merging: Reducing interference in model merging through magnitude-based sampling," arXiv:2406.11617, 2024. [Online]. Available: https://arxiv.org/abs/2406.11617

[7] T. Dettmers, A. Pagnoni, A. Holtzman, and L. Zettlemoyer, “QLoRA: Efficient finetuning of quantized LLMs,” in *Advances in Neural Information Processing Systems*, vol. 36, 2023. [Online]. Available: https://arxiv.org/abs/2305.14314

[8] C. Goddard, S. Siriwardhana, M. Ehghaghi, L. Meyers, V. Karpukhin, B. Benedict, M. McQuade, and J. Solawetz, “Arcee’s MergeKit: A toolkit for merging large language models,” in *Proc. EMNLP: Industry Track*, 2024. [Online]. Available: https://arxiv.org/abs/2403.13257

[9] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen, “LoRA: Low-rank adaptation of large language models,” in *Proc. Int. Conf. Learning Representations (ICLR)*, 2022. [Online]. Available: https://arxiv.org/abs/2106.09685

[10] C. Huang et al., “LoraHub: Efficient cross-task generalization via dynamic LoRA composition,” in *Proc. Conf. Language Modeling (COLM)*, 2024. [Online]. Available: https://arxiv.org/abs/2307.13269

[11] G. Ilharco, M. T. Ribeiro, M. Wortsman, S. Gururangan, L. Schmidt, H. Hajishirzi, and A. Farhadi, “Editing models with task arithmetic,” in *Proc. Int. Conf. Learning Representations (ICLR)*, 2023. [Online]. Available: https://arxiv.org/abs/2212.04089

[12] X. Jin, X. Ren, D. Preotiuc-Pietro, and P. Cheng, “Dataless knowledge fusion by merging weights of language models,” in *Proc. Int. Conf. Learning Representations (ICLR)*, 2023. [Online]. Available: https://arxiv.org/abs/2212.09849

[13] D. Marczak, B. Twardowski, T. Trzciński, and S. Cygert, "MagMax: Leveraging model merging for seamless continual learning," in *Proc. European Conf. Computer Vision (ECCV)*, 2024. [Online]. Available: https://arxiv.org/abs/2407.06322

[14] Open Language Data Initiative, "FLORES+: An open multilingual evaluation benchmark," 2024. [Online]. Available: https://huggingface.co/datasets/openlanguagedata/flores_plus

[15] G. Ortiz-Jimenez, A. Favero, and P. Frossard, "Task arithmetic in the tangent space: Improved editing of pre-trained models," in *Advances in Neural Information Processing Systems*, vol. 36, 2023. [Online]. Available: https://arxiv.org/abs/2305.12827

[16] M. Popović, "chrF++: Words helping character n-grams," in *Proc. Second Conf. Machine Translation*, 2017, pp. 612–618. [Online]. Available: https://aclanthology.org/W17-4770/

[17] G. Ramesh et al., "Samanantar: The largest publicly available parallel corpora collection for 11 Indic languages," *Trans. Assoc. Computational Linguistics*, vol. 10, pp. 145–162, 2022. [Online]. Available: https://arxiv.org/abs/2104.05596

[18] G. Stoica, D. Bolya, J. Bjorner, P. Ramesh, T. Hearn, and J. Hoffman, "ZipIt! Merging models from different tasks without training," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2024. [Online]. Available: https://arxiv.org/abs/2305.03053

[19] A. Tang, L. Shen, Y. Luo, Y. Zhan, H. Hu, B. Du, Y. Chen, and D. Tao, "Parameter-efficient multi-task model fusion with partial linearization," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2024. [Online]. Available: https://arxiv.org/abs/2310.04742

[20] K. Wang, N. Dimitriadis, G. Ortiz-Jimenez, F. Fleuret, and P. Frossard, "Localizing task information for improved model merging and compression," in *Proc. Int. Conf. Machine Learning (ICML)*, 2024. [Online]. Available: https://arxiv.org/abs/2405.07813

[21] E. Yang, L. Shen, G. Guo, X. Wang, X. Cao, J. Zhang, and D. Tao, "Model merging in LLMs, MLLMs, and beyond: Methods, theories, applications and opportunities," arXiv:2408.07666, 2024. [Online]. Available: https://arxiv.org/abs/2408.07666

[22] E. Yang et al., "AdaMerging: Adaptive model merging for multi-task learning," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2024. [Online]. Available: https://arxiv.org/abs/2310.02575

[23] P. Yadav, T. Vu, J. Lai, A. Chronopoulou, M. Faruqui, M. Bansal, and T. Munkhdalai, "What matters for model merging at scale?," arXiv:2410.03617, 2024. [Online]. Available: https://arxiv.org/abs/2410.03617

[24] P. Yadav, D. Tam, L. Choshen, C. Raffel, and M. Bansal, "TIES-Merging: Resolving interference when merging models," in *Advances in Neural Information Processing Systems*, vol. 36, 2023. [Online]. Available: https://arxiv.org/abs/2306.01708

[25] A. Yang et al., "Qwen2.5 technical report," arXiv:2412.15115, 2024. [Online]. Available: https://arxiv.org/abs/2412.15115

[26] L. Yu, B. Yu, H. Yu, F. Huang, and Y. Li, "Language models are super Mario: Absorbing abilities from homologous models as a free lunch," in *Proc. Int.* [Online]. Available: https://arxiv.org/abs/2311.03099

[27] J. Zhang et al., “Composing parameter-efficient modules with arithmetic operations,” in *Advances in Neural Information Processing Systems*, vol. 36, 2023. [Online]. Available: https://arxiv.org/abs/2306.14870

[28] Z. Zhou, Z. Chen, Y. Chen, B. Zhang, and J. Yan, “On the emergence of cross-task linearity in pretraining-finetuning paradigm,” in *Proc. Int. Conf. Machine Learning (ICML)*, 2024. [Online]. Available: https://arxiv.org/abs/2402.03660