

SAFETY DATA SHEET

Section 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name or designation

of the mixture

WHITE FUSED ALUMINUM OXIDE

Registration number 01-2119529248-35-0141

AL, ALSD, ALHD, ALLD, ALZD and ALC **Synonyms**

Date of first issue 01-February-2012

Version number 01 **Revision date** Supersedes date

Relevant identified uses of the substance or mixture and uses advised against

Identified uses Abrasives, Ceramics, Flooring, Surface Treatment and Refractory.

Uses advised against

Details of the supplier of the safety data sheet

Company identification ELFUSA GERAL DE ELETROFUSÃO LTDA

501, Julio Michelazzo,

São João da Boa Vista, São Paulo - Brazil ZIP CODE 13872-900

Telephone +55.19.3634.2300

Person responsible for the

MSDS

Contact

Telephone

qualidade@elfusa.com.br

Commercial comercial@elfusa.com.br www.elfusa.com.br Homepage

Person Responsible for commercial introduction of

the substance within

Elfusa Trading SL.

European Community

Mijas

Malaga - Spain Mr. Ruben Sinato +55.11.9973.8421

ruben.sinato@grupocurimbaba.com.br e-mail

1-760-476-3961 **Emergency telephone**

Access Code: 333691

Section 2: Hazards identification

Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

This substance does not meet the criteria for classification according to Directive 67/548/EEC as amended.

Classification according to Regulation (EC) No 1272/2008 as amended

This substance does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Hazard summary

Physical hazards Not classified for physical hazards.

Health hazards Not classified for health hazards. However, occupational exposure to the mixture or substance(s)

may cause adverse health effects.

Environmental hazards Not classified for hazards to the environment.

Specific hazards Dust may cause eye, skin and respiratory tract irritation. Prolonged and repeated overexposure to

dust can lead to pneumoconiosis.

Main symptoms Irritation of eyes and mucous membranes. Irritation of nose and throat.

Label elements

WHITE FUSED ALUMINUM OXIDE

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard statements The mixture does not meet the criteria for classification.

Precautionary statements

Observe good industrial hygiene practices. Prevention

Response Wash hands after handling

Storage Store away from incompatible materials.

Dispose of waste and residues in accordance with local authority requirements. Disposal

Supplemental label information None

Other hazards Not a PBT or vPvB substance or mixture.

Section 3: Composition/information on ingredients

General information

CAS-No. / EC No. REACH Registration No. INDEX No. **Chemical name** % **Notes** Aluminium oxide ≥ 99 1344-28-1 01-2119529248-35-0141 # 215-691-6 Classification: DSD: -CLP: Impurities: ≤ 1 N/A SiO2+Fe2O3+Na2O+CaO+MgO+T Classification: DSD: -

#: This substance has workplace exposure limit(s).

CLP: -

Composition comments This product is registered under the REACH Regulation 1907/2006 as a mono-constituent

> substance. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. For more detailed chemical composition, refer to the

certificate of analysis.

Section 4: First aid measures

General information Get medical attention if any discomfort develops.

Description of first aid measures

Inhalation Move to fresh air. Get medical attention if any discomfort continues.

Skin contact Wash with soap and water. Get medical attention if irritation develops or persists.

Eye contact Flush eyes thoroughly with water for at least 15 minutes. Get medical attention if irritation

develops or persists.

Ingestion Immediately rinse mouth and drink plenty of water. Get medical attention if irritation develops and

persists.

Most important symptoms and effects, both acute and delayed Irritation of eyes and mucous membranes. Irritation of nose and throat.

Indication of any immediate medical attention and special Treat symptomatically.

treatment needed

Section 5: Firefighting measures

General fire hazards The product is not flammable.

Extinguishing media

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing No restrictions known.

media

Special hazards arising from None known.

the substance or mixture

Advice for firefighters

Special protective Self-contained breathing apparatus, operated in positive pressure mode and full protective

equipment for firefighters clothing must be worn in case of fire.

Special firefighting Move containers from fire area if you can do it without risk.

procedures

WHITE FUSED ALUMINUM OXIDE

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency Ensure adequate ventilation. Avoid inhalation of dust and contact with skin and eyes. Wear

personnel protective clothing as described in section 8 of this safety data sheet.

For emergency responders Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Recover and recycle, if practical. Sweep up or vacuum up spillage and collect in suitable containment and cleaning up

filter.

Reference to other sections For personal protection, see section 8. For waste disposal, see section 13.

Section 7: Handling and storage

Precautions for safe handling Provide adequate ventilation. Use work methods which minimise dust production. Avoid inhalation

of dust and contact with skin and eyes. Wear appropriate personal protective equipment. Do not

add wet alumina to electrolysis cells. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in a dry place.

Specific end use(s) For detailed information, see section 15. Recommendations given in the exposure scenario for the

uses are distributed and annexed as separate documents to this eSDS.

Section 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits

Austria. MAK List Material	Туре	Value	Form
Aluminium oxide	MAK	5 mg/m3	Respirable fume.
(1344-28-1)		F / 2	Desniveble freetien
		5 mg/m3	Respirable fraction.
	OTEL	10 mg/m3	Inhalable fraction.
	STEL	20 mg/m3	Inhalable fraction.
		10 mg/m3	Respirable fume.
		10 mg/m3	Respirable fraction.
Components	Туре	Value	Form
Aluminium oxide (1344-28-1)	MAK	5 mg/m3	Respirable fume.
		5 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
	STEL	20 mg/m3	Inhalable fraction.
		10 mg/m3	Respirable fume.
		10 mg/m3	Respirable fraction.
Belgium. Exposure Limit Values.			
Material	Туре	Value	
Aluminium oxide (1344-28-1)	TWA	10 mg/m3	
Components	Туре	Value	

Components	Type	Value	
Aluminium oxide (1344-28-1)	TWA	10 mg/m3	
Bulgaria. OELs. Regulation N	lo 13 on protection of workers aga	inst risks of exposure to che	mical agents at work
Material	Туре	Value	Form
Aluminium oxide (1344-28-1)	TWA	10 mg/m3	Dust.
		1,5 mg/m3	Respirable fraction.
Components	Туре	Value	Form
Aluminium oxide (1344-28-1)	TWA	10 mg/m3	Dust.
()		1,5 mg/m3	Respirable fraction.
Czech Republic. OELs. Gover	rnment Decree 361		
Material .	Туре	Value	Form
Aluminium oxide (1344-28-1)	TWA	0,1 mg/m3	Respirable dust.
Components	Туре	Value	Form
Aluminium oxide (1344-28-1)	TWA	0,1 mg/m3	Respirable dust.

906325 Version No.: 01 Revision date: 01-February-2012 Print date: 01-February-2012

Туре	Value	Form
TLV	5 mg/m3	Total
Turna	2 mg/m3	Respirable.
		Form
TLV	· ·	Total
Exposure Limits of Hazardous Substance	J	Respirable. on No. 293 of 18 Septeml
Type	Value	Form
TWA		Respirable dust.
	· ·	Total dust.
Туре	Value	Form
TWA	4 mg/m3	Respirable dust.
	10 mg/m3	Total dust.
es (VLEP) for Occupational Exposure to C	•	NRS ED 984
Туре	Value	
VME	10 mg/m3	
Туре	Value	
VME	10 mg/m3	
isony OELs). Commission for the Investig	ation of Hoolth Horse	de of Chamical Campair
		us of Chemical Compour
Туре	Value	Form
TWA	4 mg/m3	Inhalable dust.
_	1,5 mg/m3	Respirable dust.
		Form
ΙΛΛ/Δ	4 mg/m3	Inhalable dust.
IWA		
	1,5 mg/m3	Respirable dust.
llues in the Ambient Air at the Workplace	1,5 mg/m3	·
llues in the Ambient Air at the Workplace Type	1,5 mg/m3 Value	Form
llues in the Ambient Air at the Workplace	1,5 mg/m3 Value 3 mg/m3	Form Respirable dust.
alues in the Ambient Air at the Workplace Type AGW	1,5 mg/m3 Value 3 mg/m3 10 mg/m3	Form Respirable dust. Inhalable dust.
alues in the Ambient Air at the Workplace Type AGW Type	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value	Form Respirable dust. Inhalable dust. Form
alues in the Ambient Air at the Workplace Type AGW	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3	Form Respirable dust. Inhalable dust. Form Respirable dust.
Alues in the Ambient Air at the Workplace Type AGW Type AGW	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value	Form Respirable dust. Inhalable dust. Form
Alues in the Ambient Air at the Workplace Type AGW Type AGW AGW 71999, as amended)	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3 10 mg/m3	Form Respirable dust. Inhalable dust. Form Respirable dust. Inhalable dust.
Alues in the Ambient Air at the Workplace Type AGW Type AGW	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3	Form Respirable dust. Inhalable dust. Form Respirable dust.
Alues in the Ambient Air at the Workplace Type AGW Type AGW AGW 71999, as amended) Type	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3 10 mg/m3 Value 5 mg/m3	Form Respirable dust. Inhalable dust. Form Respirable dust. Inhalable dust. Form Inhalable
Type AGW Type AGW Type AGW 71999, as amended) Type TWA	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3	Form Respirable dust. Inhalable dust. Form Respirable dust. Inhalable dust. Form Inhalable Respirable.
Alues in the Ambient Air at the Workplace Type AGW Type AGW AGW 71999, as amended) Type	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3 10 mg/m3 Value 5 mg/m3	Form Respirable dust. Inhalable dust. Form Respirable dust. Inhalable dust. Form Inhalable
Alues in the Ambient Air at the Workplace Type AGW Type AGW /1999, as amended) Type TWA Type	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 Value 5 mg/m3	Form Respirable dust. Inhalable dust. Form Respirable dust. Inhalable dust. Form Inhalable Respirable. Form Inhalable
Type AGW Type AGW Type AGW /1999, as amended) Type TWA Type TWA	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 Value	Form Respirable dust. Inhalable dust. Form Respirable dust. Inhalable dust. Form Inhalable Respirable. Form
Alues in the Ambient Air at the Workplace Type AGW Type AGW /1999, as amended) Type TWA Type	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 Value 5 mg/m3	Form Respirable dust. Inhalable dust. Form Respirable dust. Inhalable dust. Form Inhalable Respirable. Form Inhalable
AGW Type AGW AGW Type AGW /1999, as amended) Type TWA Type TWA Type TWA On Chemical Safety of Workplaces	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 10 mg/m3	Form Respirable dust. Inhalable dust. Form Respirable dust. Inhalable dust. Form Inhalable Respirable. Form Inhalable Respirable. Form Respirable. Form
AGW Type AGW AGW Type AGW AGW AGW Type AGW Type TWA Type TWA Type TWA Type TWA Type TWA TWA TYPE TWA TWA	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 Value 5 mg/m3	Form Respirable dust. Inhalable dust. Form Respirable dust. Inhalable dust. Form Inhalable Respirable. Form Inhalable Respirable. Form Respirable. Respirable.
AGW Type AGW Type AGW AGW /1999, as amended) Type TWA Type TWA On Chemical Safety of Workplaces Type TWA Type TWA Type TWA Type	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 Value 6 mg/m3 Value	Form Respirable dust. Inhalable dust. Form Respirable dust. Inhalable dust. Form Inhalable Respirable. Form Inhalable Respirable. Form Respirable. Form Respirable.
AGW Type AGW AGW Type AGW AGW AGW Type AGW Type TWA Type TWA Type TWA Type TWA Type TWA TWA TYPE TWA TWA	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 Value 5 mg/m3	Form Respirable dust. Inhalable dust. Form Respirable dust. Inhalable dust. Form Inhalable Respirable. Form Inhalable Respirable. Form Respirable. Respirable.
AGW Type AGW Type AGW AGW /1999, as amended) Type TWA Type TWA On Chemical Safety of Workplaces Type TWA Type TWA Type TWA Type	1,5 mg/m3 Value 3 mg/m3 10 mg/m3 Value 3 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 Value 6 mg/m3 Value	Form Respirable dust. Inhalable dust. Form Respirable dust. Inhalable dust. Form Inhalable Respirable. Form Inhalable Respirable. Form Respirable. Form Respirable.
	TLV Type TLV Exposure Limits of Hazardous Substance Type TWA Type TWA Ses (VLEP) for Occupational Exposure to Occupat	TLV 5 mg/m3 2 mg/m3 Yalue TLV 5 mg/m3 2 mg/m3 2 mg/m3 Exposure Limits of Hazardous Substances. (Annex of Regulation of Regulation of Hazardous Substances.) Type Value TWA 4 mg/m3 10 mg/m3 Yalue TWA 4 mg/m3 10 mg/m3

WHITE FUSED ALUMINUM OXIDE

SDS EU

Components	54/1999 on occupational exposure li Type	Value	
Aluminium oxide	TWA	10 mg/m3	
1344-28-1)		•	
eland. Occupational Expos laterial		Value	Form
Juminium oxide	Type TWA		
1344-28-1)	IVVA	4 mg/m3	Respirable dust.
·		10 mg/m3	Total inhalable dust.
Components	Туре	Value	Form
luminium oxide	TWA	4 mg/m3	Respirable dust.
1344-28-1)		10 mg/m3	Total inhalable dust.
taly. OELs		•	
laterial	Туре	Value	Form
luminium oxide	TWA	1 mg/m3	Respirable fraction.
1344-28-1) Components	Туре	Value	Form
Juminium oxide	TWA	1 mg/m3	Respirable fraction.
1344-28-1)	IWA	i ilig/ilio	Respirable fraction.
-	exposure limit values of chemical su		ent
laterial	Туре	Value	Form
luminium oxide	TWA	6 mg/m3	Decomposition aeroso
1344-28-1)		4 mg/m3	
Components	Туре	4 mg/m3 Value	Form
luminium oxide	TWA	6 mg/m3	Decomposition aeroso
1344-28-1)			, , , , , , , , , , , , , , , , , , ,
		4 mg/m3	
	ies for Chemical Substances, Genera		
laterial	Туре	Value	Form
lluminium oxide 1344-28-1)	TWA	5 mg/m3	Inhalable fraction.
1011 20 1)		2 mg/m3	Respirable fraction.
Components	Туре	Value	Form
luminium oxide	TWA	5 mg/m3	Inhalable fraction.
1344-28-1)		2 mg/m3	Respirable fraction.
January Administrative Nor	me for Contominants in the Worknie	-	respirable fraction.
Material	ms for Contaminants in the Workpla Type	Value	
Juminium oxide	TLV	10 mg/m3	
1344-28-1)		·	
Components	Туре	Value	
Numinium oxide 1344-28-1)	TLV	10 mg/m3	
•	about and Social Policy Pogarding	Maximum Allowable Concent	trations and Intonsitios in
Paland MACa Minister of L	about and Social Policy Regarding i	waxiiiluiii Allowable Conceil	trations and intensities in
Vorking Environment	Туре	Value	Form
Vorking Environment Material Numinium oxide	Type TWA	Value 2,5 mg/m3	Form Fume, total dust.
Vorking Environment Material Numinium oxide		2,5 mg/m3	Fume, total dust.
Poland. MACs. Minister of L Norking Environment Material Numinium oxide 1344-28-1)			Fume, total dust. Respirable dust and/or
Vorking Environment laterial luminium oxide 1344-28-1)		2,5 mg/m3	Fume, total dust.
Vorking Environment laterial lluminium oxide 1344-28-1) components	TWA	2,5 mg/m3 1,2 mg/m3	Fume, total dust. Respirable dust and/or fume.
Vorking Environment Material Iduminium oxide 1344-28-1) Components Iduminium oxide	TWA Type	2,5 mg/m3 1,2 mg/m3 Value 2,5 mg/m3	Fume, total dust. Respirable dust and/or fume. Form Fume, total dust.
Vorking Environment Material Iduminium oxide 1344-28-1) Components Iduminium oxide	TWA Type	2,5 mg/m3 1,2 mg/m3 Value	Fume, total dust. Respirable dust and/or fume. Form Fume, total dust. Respirable dust and/or
Vorking Environment Platerial Juminium oxide 1344-28-1) Components Juminium oxide 1344-28-1)	TWA Type TWA	2,5 mg/m3 1,2 mg/m3 Value 2,5 mg/m3 1,2 mg/m3	Fume, total dust. Respirable dust and/or fume. Form Fume, total dust.
Vorking Environment Material Juminium oxide 1344-28-1) Components Juminium oxide 1344-28-1) Portugal. VLEs. Norm on oc	TWA Type TWA TWA ccupational exposure to chemical ago	2,5 mg/m3 1,2 mg/m3 Value 2,5 mg/m3 1,2 mg/m3	Fume, total dust. Respirable dust and/or fume. Form Fume, total dust. Respirable dust and/or
Vorking Environment Material Juminium oxide 1344-28-1) Components Juminium oxide 1344-28-1) Cortugal. VLEs. Norm on och	TWA Type TWA	2,5 mg/m3 1,2 mg/m3 Value 2,5 mg/m3 1,2 mg/m3 ents (NP 1796)	Fume, total dust. Respirable dust and/or fume. Form Fume, total dust. Respirable dust and/or
Vorking Environment Material Juminium oxide 1344-28-1) Components Juminium oxide 1344-28-1) Cortugal. VLEs. Norm on och Material Juminium oxide 1344-28-1)	Type TWA Twa Type Twa Cupational exposure to chemical ago Type TWA	2,5 mg/m3 1,2 mg/m3 Value 2,5 mg/m3 1,2 mg/m3 ents (NP 1796) Value 10 mg/m3	Fume, total dust. Respirable dust and/or fume. Form Fume, total dust. Respirable dust and/or
Vorking Environment Material Illuminium oxide 1344-28-1) Components Illuminium oxide 1344-28-1)	Type TWA TWA cupational exposure to chemical ago Type	2,5 mg/m3 1,2 mg/m3 Value 2,5 mg/m3 1,2 mg/m3 ents (NP 1796) Value	Fume, total dust. Respirable dust and/or fume. Form Fume, total dust. Respirable dust and/or

Material	f workers from exposure to chemi Type	Value	Form
Aluminium oxide (1344-28-1)	STEL	5 mg/m3	Aerosol
(1011201)		1,2 ppm	Aerosol
	TWA	2 mg/m3	Aerosol
		0,5 ppm	Aerosol
Components	Type	Value	Form
Aluminium oxide	STEL	5 mg/m3	Aerosol
(1344-28-1)		1,2 ppm	Aerosol
	TWA	2 mg/m3	Aerosol
		0,5 ppm	Aerosol
Slovakia. OELs. Decree of the agents	e government of the Slovak Repub	olic concerning protection of l	nealth in work with chem
Material	Туре	Value	Form
Aluminium oxide	TWA	4 mg/m3	Inhalable fraction.
(1344-28-1)			
		1,5 mg/m3	Respirable fraction.
Commonante	Time	0,1 mg/m3	Form
Components	Type	Value	
Aluminium oxide (1344-28-1)	TWA	4 mg/m3	Inhalable fraction.
		1,5 mg/m3 0,1 mg/m3	Respirable fraction.
Spain. Occupational Exposur	e Limits	o, r mg/me	
Material	Туре	Value	
Aluminium oxide	TWA	10 mg/m3	
(1344-28-1) Components	Туре	Value	
<u> </u>			
Aluminium oxide (1344-28-1)	TWA	10 mg/m3	
Sweden. Occupational Expos Material	ure Limit Values Type	Value	Form
Aluminium oxide	TWA	5 mg/m3	Total dust.
(1344-28-1)	IVVA	•	
Components	Туре	2 mg/m3 Value	Respirable dust. Form
Aluminium oxide	TWA	5 mg/m3	Total dust.
(1344-28-1)	IWA	•	
		2 mg/m3	Respirable dust.
Switzerland. SUVA Grenzwert	te am Arbeitsplatz Type	Value	Form
Material			Fume and resnirable
Material Aluminium oxide	STEL	24 mg/m3	Fume and respirable dust.
Material Aluminium oxide			
Material Aluminium oxide	STEL	24 mg/m3	dust. Respirable dust. Fume and respirable
Material Aluminium oxide (1344-28-1)	STEL TWA	24 mg/m3 3 mg/m3 3 mg/m3	dust. Respirable dust. Fume and respirable dust.
Material Aluminium oxide (1344-28-1) Components	STEL TWA Type	24 mg/m3 3 mg/m3 3 mg/m3 Value	dust. Respirable dust. Fume and respirable dust. Form
Material Aluminium oxide (1344-28-1) Components Aluminium oxide	STEL TWA	24 mg/m3 3 mg/m3 3 mg/m3	dust. Respirable dust. Fume and respirable dust. Form Fume and respirable
Material Aluminium oxide (1344-28-1) Components Aluminium oxide	STEL TWA Type STEL	24 mg/m3 3 mg/m3 3 mg/m3 Value 24 mg/m3	dust. Respirable dust. Fume and respirable dust. Form Fume and respirable dust.
Material Aluminium oxide (1344-28-1) Components Aluminium oxide	STEL TWA Type	24 mg/m3 3 mg/m3 3 mg/m3 Value 24 mg/m3 3 mg/m3	dust. Respirable dust. Fume and respirable dust. Form Fume and respirable dust. Respirable dust.
Material Aluminium oxide (1344-28-1) Components	STEL TWA Type STEL	24 mg/m3 3 mg/m3 3 mg/m3 Value 24 mg/m3	dust. Respirable dust. Fume and respirable dust. Form Fume and respirable dust.
Material Aluminium oxide (1344-28-1) Components Aluminium oxide (1344-28-1)	STEL TWA Type STEL TWA	24 mg/m3 3 mg/m3 3 mg/m3 Value 24 mg/m3 3 mg/m3	dust. Respirable dust. Fume and respirable dust. Form Fume and respirable dust. Respirable dust. Fume and respirable
Material Aluminium oxide (1344-28-1) Components Aluminium oxide (1344-28-1) UK. EH40 Workplace Exposur	STEL TWA Type STEL TWA TWA Te Limits (WELs)	24 mg/m3 3 mg/m3 3 mg/m3 Value 24 mg/m3 3 mg/m3	dust. Respirable dust. Fume and respirable dust. Form Fume and respirable dust. Respirable dust. Fume and respirable
Material Aluminium oxide (1344-28-1) Components Aluminium oxide (1344-28-1) UK. EH40 Workplace Exposur	STEL TWA Type STEL TWA TWA TWA Te Limits (WELs) Type	24 mg/m3 3 mg/m3 3 mg/m3 Value 24 mg/m3 3 mg/m3 3 mg/m3	dust. Respirable dust. Fume and respirable dust. Form Fume and respirable dust. Respirable dust. Fume and respirable dust. Fume and respirable dust. Form
Material Aluminium oxide (1344-28-1) Components Aluminium oxide (1344-28-1) UK. EH40 Workplace Exposul	STEL TWA Type STEL TWA TWA Te Limits (WELs)	24 mg/m3 3 mg/m3 3 mg/m3 Value 24 mg/m3 3 mg/m3 3 mg/m3	dust. Respirable dust. Fume and respirable dust. Form Fume and respirable dust. Respirable dust. Fume and respirable dust. Fume and respirable dust.
Material Aluminium oxide (1344-28-1) Components Aluminium oxide (1344-28-1) UK. EH40 Workplace Exposur Material Aluminium oxide (1344-28-1)	STEL TWA Type STEL TWA TWA Te Limits (WELs) Type TWA	24 mg/m3 3 mg/m3 3 mg/m3 Value 24 mg/m3 3 mg/m3 3 mg/m3 10 mg/m3	dust. Respirable dust. Fume and respirable dust. Form Fume and respirable dust. Respirable dust. Fume and respirable dust. Fume and respirable dust. Form Respirable dust. Inhalable dust.
Material Aluminium oxide (1344-28-1) Components Aluminium oxide (1344-28-1) UK. EH40 Workplace Exposur Material Aluminium oxide (1344-28-1) Components	STEL TWA Type STEL TWA TWA Te Limits (WELs) Type TWA Type	24 mg/m3 3 mg/m3 3 mg/m3 Value 24 mg/m3 3 mg/m3 3 mg/m3 Value 4 mg/m3 10 mg/m3 Value	dust. Respirable dust. Fume and respirable dust. Form Fume and respirable dust. Respirable dust. Fume and respirable dust. Fume and respirable dust. Inhalable dust. Form
Material Aluminium oxide (1344-28-1) Components Aluminium oxide (1344-28-1) UK. EH40 Workplace Exposur Material Aluminium oxide (1344-28-1)	STEL TWA Type STEL TWA TWA Te Limits (WELs) Type TWA	24 mg/m3 3 mg/m3 3 mg/m3 Value 24 mg/m3 3 mg/m3 3 mg/m3 10 mg/m3	dust. Respirable dust. Fume and respirable dust. Form Fume and respirable dust. Respirable dust. Fume and respirable dust. Fume and respirable dust. Form Respirable dust. Inhalable dust.

906325 Version No.: 01 Revision date: 01-February-2012 Print date: 01-February-2012

DNEL

Material	Туре	Route	Value	Form
Aluminium oxide (1344-28-1)	Workers	Oral	3,29 mg/kg/day	Long term exposure systemic effects
		Inhalation	15,63 mg/m3	Long term exposure local effects
Components	Type	Route	Value	Form
Aluminium oxide (1344-28-1)	Workers	Oral	3,29 mg/kg/day	Long term exposure systemic effects
		Inhalation	15,63 mg/m3	Long term exposure local effects

PNEC

Material	Туре	Route	Value
Aluminium oxide (1344-28-1)	Aqua (freshwater)	Not applicable	79,4 μg/l
	Sewage Treatment Plant	Not applicable	20 mg/l
Components	Type	Route	Value
Components	туре	Noute	
Aluminium oxide (1344-28-1)	Aqua (freshwater)	Not applicable	79,4 µg/l

Exposure controls

Appropriate engineering

controls

Provide sufficient ventilation for operations causing dust formation. If engineering measures are not sufficient to maintain concentrations of dust particulates below the OEL (occupational

exposure limit), suitable respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protective equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection

Skin protection

Wear goggles/face shield.

- Hand protection Wear protective gloves. Suitable gloves can be recommended by the glove supplier.

- Other Wear suitable protective clothing.

Respiratory protection In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory equipment

with particle filter (type P2). Seek advice from local supervisor.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Wash hands after handling. Routinely wash work clothing and protective equipment to remove

contaminants. Handle in accordance with good industrial hygiene and safety practices. Follow up

on any medical surveillance requirements.

Environmental exposure

controls

Contain spills and prevent releases and observe national regulations on emissions.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

White powder. **Appearance**

Physical state Solid. Powder. **Form** Colour White. Odour Odourless. **Odour threshold** Not available. Not applicable. 2040 °C (3704 °F) Melting point/freezing

point

Not available.

Boiling point, initial boiling point, and boiling range

Not applicable. Flash point **Auto-ignition temperature** Not applicable. Non flammable. Flammability (solid, gas) Flammability limit - lower Not available.

(%)

Flammability limit - upper

(%)

Not available.

Oxidising properties

Not oxidizing. **Explosive properties** Not explosive. **Explosive limit** Not applicable. Not applicable. Vapour pressure Not applicable. Vapour density **Evaporation rate** Not applicable. Relative density 3.97 at 20 °C Solubility (water) Insoluble Not applicable. **Partition coefficient**

(n-octanol/water)

Decomposition

Not available.

temperature

Bulk density Not applicable. **Viscosity** Not applicable. Percent volatile Not available.

Other information No relevant additional information available.

Section 10: Stability and reactivity

Reactivity The product is non reactive under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Hazardous polymerisation does not occur. Hazardous reactions do not occur.

Conditions to avoid Moisture. Contact with incompatible materials.

Incompatible materials None known.

Hazardous decomposition

products

No hazardous decomposition products are known.

Section 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Ingestion may cause irritation and malaise. Ingestion Dust may irritate respiratory system. Inhalation

Dust may irritate skin. Skin contact Eye contact Dust may irritate the eyes.

Symptoms Irritation of eyes and mucous membranes. Irritation of nose and throat.

Information on toxicological effects

Dust may cause eye, skin and respiratory tract irritation. Acute toxicity

Product Test results

Aluminium oxide (1344-28-1) Acute Inhalation LC50 Rat: > 2,3 mg/l 4 hours

Acute Oral LD50 Rat: > 5000 mg/kg

May cause irritation through mechanical abrasion. Skin corrosion/irritation

Serious eye damage/eye

irritation

May cause irritation through mechanical abrasion.

Not classified. Respiratory sensitisation Skin sensitisation Not a skin sensitiser.

Germ cell mutagenicity Test data conclusive but not sufficient for classification. Test data conclusive but not sufficient for classification. Carcinogenicity Test data conclusive but not sufficient for classification. Reproductive toxicity

Specific target organ toxicity - single exposure Test data conclusive but not sufficient for classification.

Specific target organ toxicity - repeated

Test data conclusive but not sufficient for classification.

exposure

Not classified. Aspiration hazard

WHITE FUSED ALUMINUM OXIDE

SDS FU

Mixture versus substance

information

Not available.

Other information

Prolonged and repeated overexposure to dust can lead to pneumoconiosis.

Section 12: Ecological information

Toxicity

Product	Test results
Aluminium oxide (1344-28-1)	EC50 Daphnia magna: > 100 mg/l 48 hours
	EC50 Green algae (Selenastrum capricornutum): > 100 mg/l 72 hours
	LC50 Salmo trutta: > 100 mg/l 96 hours

Persistence and degradability

The product is not biodegradable.

Bioaccumulative potential The product is not bioaccumulating. **Mobility** The product is insoluble in water.

Environmental fate -Partition coefficient

Not applicable.

Mobility in soil Aluminum oxide is not mobile in the environment, unless it comes into contact with an aqueous

environment with a pH below 5,5 or above 8,5.

Results of PBT and vPvB assessment

Not a PBT or vPvB substance or mixture.

Other adverse effects Not expected to be harmful to aquatic organisms.

Section 13: Disposal considerations

Waste treatment methods

Residual waste Recover and recycle, if practical. Dispose of in accordance with local regulations.

Contaminated packaging Offer rinsed packaging material to local recycling facilities. Dispose of in accordance with local

regulations.

EU waste code 16 05 09

Disposal methods/information Dispose in accordance with all applicable regulations.

Section 14: Transport information

ADR

The product is not covered by international regulation on the transport of dangerous goods.

The product is not covered by international regulation on the transport of dangerous goods.

The product is not covered by international regulation on the transport of dangerous goods.

The product is not covered by international regulation on the transport of dangerous goods.

The product is not covered by international regulation on the transport of dangerous goods.

Transport in bulk according to Annex II of MARPOL73/78 and

No information available.

the IBC Code

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 2037/2000 on substances that deplete the ozone layer, Annex I

Regulation (EC) No. 2037/2000 on substances that deplete the ozone layer, Annex II

Regulation (EC) No. 850/2004 on persistent organic pollutants, Annex I

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1

Not listed

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V

Not listed.

Directive 96/61/EC concerning integrated pollution prevention and control (IPPC): Article 15, European Pollution Emission Registery (EPER)

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1). Candidate List

Not listed.

Other regulations This substance does not meet the criteria for classification according to Regulation (EC)

1272/2008 (CLP Regulation) and Directive 67/548/EEC and their amendments respectively. This

Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations Follow national regulation for work with chemical agents.

Chemical safety assessment For this substance a chemical safety assessment has been carried out.

Section 16: Other information

List of abbreviations DNEL: Derived No-Effect Level.

PNEC: Predicted No-Effect Concentration.
PBT: Persistent, bioaccumulative and toxic.
vPvB: Very Persistent and very Bioaccumulative.

DSD: Directive 67/548/EEC. CLP: Regulation No. 1272/2008. LD50: Lethal Dose, 50%. LC50: Lethal Concentration, 50%.

References IUCLID

Chemical safety report.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

Full text of any statements or R-phrases and H-phrases under Sections 2 to 15 None.

Training information Follow training instructions when handling this material.

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available.

Issue date01-February-2012Revision date01-February-2012Print date01-February-2012

WHITE FUSED ALUMINUM OXIDE

906325 Version No.: 01 Revision date: 01-February-2012 Print date: 01-February-2012