Proceedings of 2024 International Conference on Cognitive Robotics and Intelligent Systems (ICC - ROBINS 2024)
IEEE Xplore Part Number: CFP24UD1-ART; ISBN: 979-8-3503-7274-8

Classification and Regression Algorithms for Brain Computer Interfacing

Mr. P. Yogendra Prasad
Assistant Professor, Dept of CSSE
Mohan Babu University (Erstwhile Sree Vidyanikethan Engineering College),
Tirupati, India
yogendraprasad.p@vidyanikethan.edu

Mr. M. Ramu
Assistant Professor, Dept of CSSE
Annamacharya Institute of Technology & Sciences,
Tirupati, India
ramucsse20@gmail.com

Gangavaram Sree Varshini
UG Scholar, Department of CSSE
Mohan Babu University (Erstwhile Sree Vidyanikethan engineering College),
Tirupati, India
sreevarshini25@gmail.com

Dasari Keerthi
UG Scholar, Department of CSSE
Mohan Babu University (Erstwhile Sree Vidyanikethan Engineering College),
Tirupati, India
dkeerthi425@gmail.com

Kaduru Jyothsna
UG Scholar , Department of CSSE
Mohan Babu University (Erstwhile Sree Vidyanikethan Engineering College),
Tirupati, India
jyothsnakaduru@gmail.com

Chirangi K Neeraja
UG Scholar, Department of CSSE
Moha Babu Uniersity (Erstwhile Sree Vidyanikethan Engineering College),
Tirupati, India
chirangineeraja2002@gmail.com

2024 International Conference on Cognitive Robotics and Intelligent Systems (ICC - ROBINS) | 979-8-3503-7274-8/24/$31.00 ©2024 IEEE | DOI: 10.1109/ICC-ROBINS60238.2024.10533915

Abstract— **The Brain-Computer Interface (BCI) stands as a groundbreaking technology, establishing a direct communication channel linking the human brain and external devices, enabling seamless interaction and control. This project focuses on the development of a BCI system utilizing machine learning techniques, specifically classification and regression algorithms. The brain-computer interface (BCI) facilitates a connection between the brain and the external world by interpreting physiological information generated during cognitive activities. Recent progress in neuroscience and machine learning has catalyzed transformative developments in BCI technology. This research study explores the implementation of advanced algorithms, specifically focusing on classification and regression techniques to enhance the performance and accuracy of BCI systems.**

Keywords— Brain Computer Interface (BCI), Machine Learning, Classification Algorithms, Regression Algorithms, EEG (Electroencephalogram), Human-Machine Interaction, Real-time Applications.

I. INTRODUCTION

Brain-Computer Interfacing (BCI) is a rapidly advancing technology where researchers are dedicated to establishing a direct link between the person mind and computers. BCI involves the collaboration of the brain with mechanical devices, integrating them seamlessly into the body's representation. Unlike traditional communication systems relying on peripheral nerves and muscles, Brain-Machine Interface (BMI) utilizes brain activity for direct control, command, actuation, and communication with the external world. While the human brain is a remarkable asset, the absence of a proper interface can impede its functionality. BCI addresses this gap, bridging the divide between humans and machines, opening the door to diverse applications.

The BCI system with the processing steps shown in figure 1 demonstrates heightened precision when decoding movements at disparate speeds compared to scenarios where speeds remain constant. This observation opens up new possibilities for enhancing the versatility and adaptability of BCI, indicating potential breakthroughs in the optimization of real and simulated motor functions. This introduction sets the stage for a deeper exploration into the dynamic relationship between BCI technology and the intricacies of human movement.




Fig 1: Processing steps of BCI

II. BRAIN-COMPUTER INTERFACING ALGORITHMS

Numerous studies have been undertaken by researchers on brain computer interfacing. Some of them are discussed below.

A. Multiscale Principal Component Analysis

The MSPCA incorporates distinctive aspects of both PCA (Principal Component Analysis) and wavelet analysis. In cases where the noise exhibits characteristics beyond white noise, the approach involves creating a unique PCA model at

Authorized licensed use limited to: COLLEGE OF ENGINEERING - Pune. Downloaded on January 08,2026 at 11:49:12 UTC from IEEE Xplore. Restrictions apply.

for a better noise reduction. It is implemented with the help of thresholding. It enables the selection of the most pertinent wavelet coefficients for the process. Instead, additional criteria such as mutual correlation on wavelet coefficients can be utilized for the purpose of sorting the coefficients. This methodology facilitates the construction of an efficient model, starting with the most crucial coefficients and concluding at a point determined through cross-validation. Models developed using this approach exhibit enhanced accuracy in estimating system parameters and improved predictive capabilities.

B. Wavelet Packed Decomposition

Wavelet transform is employed for the process of decomposing a signal into a set of wavelets. In comparison to the Short Time Fourier Transform (STFT) this method offers superior temporal resolution for the decomposed signal. dilations and translations are utilized for deriving wavelets from the single function. The Wavelet Packet Decomposition (WPD) serves as an extension of the Discrete Wavelet Transform (DWT). While the DWT utilizes only the low-frequency components, the WPD distinguishes itself by incorporating both the low and high-frequency components. An advantageous feature of the WPD lies in its utilization of diverse levels of decomposition to reconstruct the original signal.

C. *Artificial Neural Network (ANN)*

An Artificial Neural Network (ANN) comprises interconnected input/output units, with each connection characterized by an associated weight. During the learning phase, the network adapts by adjusting these weights to effectively classify test data. The inherent parallel nature of ANN algorithms allows for the application of parallelization techniques, expediting the decision-making process [10]. However, it's worth noting that ANNs generally necessitate a more extended training period compared to alternative classifiers such as nearest neighbor, decision tree, random forest, and others. Despite this, ANNs offer distinct advantages, including the ability to do unknown classification and larger noise tolerance. Consequently, they prove to be suitable model for classifications where the connection between classes or attributes were not clearly defined [10].

D. k-Nearest Neighbors (KNN)

The KNN under consideration operates by discerning resemblances, primarily through the comparison of a given training data with test data. The given training data is characterized by n features, defining an object or image in an n-dimensional space. This approach facilitates the representation of all the given training data within an n-dimensional pattern. The K-Nearest Neighbors (KNN) classifier then assesses these patterns for the k-nearest training data sets. Classification decisions are rendered based on the vote count from these K-Nearest Neighbors, ultimately assigning the unidentified object to the most prevalent class with its k nearest neighbors.

E. Naive Bayes

Naive Bayes, classification technique is a model based technique designed from the Bayes algorithm, has witnessed widespread use in various applications since the 1950s, owing to technological advancements. This classification algorithm is scalable and relatively fast, relying on a straightforward count-based approach. It is versatile, accommodating both binary and multiclass classifications efficiently, making it a particularly effective choice for addressing text classification challenges. However, Naive Bayes assumes all object features to be unrelated, which can limit its effectiveness in handling large and complex data problems, as it does not capture relationships among different features. During classification, it predicts the belonging probabilities of an object to each class, with the final assignment determined by the class associated with the highest probability. Naive Bayes classifiers are further categorized based on the distribution of attribute values in classes, leading to types such as Gaussian Naive Bayes, Multinomial Naive Bayes, and Bernoulli Naive Bayes.

F. Support Vector Machines (SVMs)

Support Vector Machines (SVMs) are versatile in classifying both linear and nonlinear data. In essence, SVMs the original data is transformed into a higher dimension through a nonlinear mapping. While the training time for SVMs may be comparatively higher than some alternative algorithms, they compensate by offering superior accuracy. This enhanced accuracy is attributed to their ability to model intricate nonlinear decision boundaries effectively.

G. EEG Database

The EEG dataset IVa from BCI Competition III serves as the foundation for the analysis. This dataset involves the execution of fundamental brain activities, specifically moving the right foot or hand. Each movement is performed for a duration of 3.5 seconds, with a 2-second interval between maneuvers to allow for brief breaks for the subjects. The dataset is created from five healthy subjects, and signals from 118 EEG channels undergo bandpass filtering with a sampling at 1 kHz of frequency.

H. Linear Regression:

Initially, feature selection techniques are used to identify the most relevant physiological signals for linear regression-based BCI. Then the optimization models are used to improve prediction accuracy and reduce overfitting. The real-time adaptive linear regression models are developed to adjust to the changes in the user's cognitive state during BCI interactions. Finally, the multiple sources of physiological data (e.g., EEG, EMG) will be integrated into the linear regression model to enhance its performance and perform a more comprehensive data analysis.

I. Decision Tree:

The ensemble techniques for decision trees, such as Random Forests or Gradient Boosting are used to improve the robustness and accuracy of BCI predictions. The decision tree-based BCI models are more interpretable for end-users

Authorized licensed use limited to: COLLEGE OF ENGINEERING - Pune. Downloaded on January 08,2026 at 11:49:12 UTC from IEEE Xplore. Restrictions apply.

in order to visualize decision boundaries and important features. Decision trees can also dynamically adjust their structure based on changes in the user's cognitive state. Moreover, decision trees can be effectively used in handling non-stationarity BCI signals.

J. Random Forest:

In the random forest model, the temporal aspects of BCI signals are used to investigate how Random Forests (RF) can handle time-series data to predict changes in user intent over time. To enhance the Random Forest model's performance for BCI, optimizing hyperparameters such as the number of trees and tree depth is crucial. A systematic exploration of these parameters is necessary to achieve the best accuracy and generalization. Furthermore, the feature importance scores provided by Random Forests helps to understand the contribution of different physiological signals to the BCI predictions.

III. OVERALL ARCHITECTURE OF BCI

In the brain-computer fusion system, the Brain-Computer Interface (BCI) serves as a vital interactive interface method for information exchange. It is widely implemented in recent years for the hybrid intelligence and human-computer interaction. A typical BCI system comprises four essential components: signal acquisition, processing, control, and feedback. The processing component, encompassing preprocessing of the input signal, along with feature extraction, and feature classification, plays a key role in performing pattern recognition within brain signals. The general architecture of a BCI system is depicted in Figure 2.




FIG 2: General BCI System Architecture

Categorized based on the pathways of information transmission, Brain-Computer Interface (BCI) can be broadly delineated into three modalities. As shown in Figure 3, BCI is typically classified as non-invasive (external to the brain), invasive, and semi-invasive, based on the distinction of whether or not it involves the invasion of the brain.




FIG 3: Three Types of BCI's in general context

IV. IMPLEMENTATION OF FEATURE CLUSTERING ALGORITHMS:

Feature clustering, an unsupervised machine learning technique, can be applied to segregate the features of the EEG dataset into homogeneous groups.

A. PCA

The Principal Component Analysis (PCA) [32] is a widely used unsupervised dimensionality reduction method applied across various fields. In this study, PCA is utilized to minimize the dimensionality of the EEG feature set. The original data consists of sample vectors from all samples, represented as 1,……n, where i is the row vector of the participant, and n is the number of participants. The covariance matrix is expressed as:

$$S=\sum i=1N(\mathbf{x}i-\bar{\mathbf{x}})(\mathbf{x}i-\bar{\mathbf{x}})T$$

$$\bar{\mathbf{x}}=N1\sum i=1N\,\mathbf{x}i$$

a) K-means Algorithm

The K-means algorithm is among the most widely utilized and straightforward clustering algorithms [31]. Its primary objective is to minimize cluster variance. Notably, diverse initializations may result in varied final clustering outcomes, as K-means converges to a local minimum. To address this, a strategy involves running the K-means algorithm for a specified value of k with multiple distinct initial partitions and selecting the partition associated with the smallest squared error.

V. SYMMETRICAL UNCERTAINITY BASED TRANSFER LEARNING ALGORITHM(SUTL):

The SUTL method employs feature selection based on correlation measurement. The correlation between two variables can be effectively and quantitatively gauged using the Symmetrical Uncertainty (SU) metric, introduced by Hall and Smith. This metric is grounded in the information theoretical concept of entropy. Figure 4 depicts the SUTL

Authorized licensed use limited to: COLLEGE OF ENGINEERING - Pune. Downloaded on January 08,2026 at 11:49:12 UTC from IEEE Xplore. Restrictions apply.

process. The SU value between two variables, X and Y, is defined as follows:

$$SU(X,Y)= (2 * I(X|Y)) / (H(X)+H(Y))$$

.




Fig. 4: Flow chart of SUTL Process

Symmetrical Uncertainty-based Transfer Learning within the framework of Brain-Computer Interface (BCI) represents a novel strategy designed to improve the performance and adaptability of BCI systems across varied datasets. This innovative approach relies on the utilization of symmetrical uncertainty, a metric measuring the mutual dependency between variables. Its primary objective is to enable the effective transfer of knowledge from a source domain to a target domain in the context of BCI applications.

The core concept driving this approach is to recognize and leverage the shared information or dependencies existing between the source and target domains. Symmetrical uncertainty serves as a metric to quantify the commonality between feature sets, allowing for a more informed selection of relevant features that contribute to the transferability of knowledge. By focusing on the variables with high symmetrical uncertainty, the transfer learning model can prioritize features that are both discriminative and consistent across different datasets.

Transfer learning in BCI is crucial due to the inherent variability in brain signals across individuals and sessions. Traditional machine learning models may struggle to generalize well to new datasets, making transfer learning an attractive solution to enhance adaptability. Symmetrical uncertainty-based transfer learning provides a principled framework to identify and transfer relevant knowledge, potentially leading to improved BCI performance in novel scenarios. Figure 5 provides an overall view of the SUTL process by highlighting both the source and target domain.




FIG 5: SUTL Overview with source domain and target domain

This symmetrical uncertainty-based transfer learning paradigm has the potential to address the individual variability challenges in BCI, promoting a more robust and adaptable interface for diverse user populations.

VI. COMPARATIVE ANALYSIS

When assessing the effectiveness of various machine learning algorithms for the implementation of Brain-Computer Interface (BCI), we observed varying levels of accuracy. The linear regression model achieved an accuracy of 70%, while the decision tree classifier exhibited a slightly higher accuracy at 75%. The random forest classifier demonstrated the highest accuracy among the three, reaching 78%. These accuracy scores provide a quantitative measure of the models' effectiveness in correctly

Accuracy Comparison:
Linear Regression: 70%
Decision Tree Classifier: 75%
Random Forest Classifier: 78%

In the context of BCI for actual and imagined movements, the results highlight the importance of algorithm selection based on the specific characteristics of the physiological signals. From the ROC curve depicted in Figure 6, it is evident that the Linear regression might be suitable for simpler relationships, while decision tree and random forest classifiers prove advantageous for capturing intricate patterns. However, achieving a balance between accuracy and interpretability remains a key challenge.

Authorized licensed use limited to: COLLEGE OF ENGINEERING - Pune. Downloaded on January 08,2026 at 11:49:12 UTC from IEEE Xplore. Restrictions apply.




Fig 6: Receiver Operating Characteristic (ROC) Curve

VI. CONCLUSION

To conclude, this study has analyzed the Brain-Computer Interface (BCI) implementations with linear regression, decision tree, and random forest classifiers and analyzed its distinct advantages and limitations. The linear regression model has achieved a moderate accuracy with its inherent complexity in analyzing physiological signals linked to actual and imagined movements. Decision tree and random forest classifiers demonstrated higher accuracy, attributed to their adeptness in handling non-linearities and intricate decision boundaries. However, the decision tree's accuracy comes at the cost of interpretability due to its complex structures. The random forest, acting as an ensemble, alleviates interpretability concerns but demands hyperparameters tuning. This study has highlighted the algorithm selection process for implementing any BCI applications by balancing accuracy, interpretability, and model complexity. In the near future, a real-time algorithmic implementation can be done for BCI applications.

REFERENCES

[1] [1] U. Hoffmann, J. M. Vesin, T. Ebrahimi, and K.

[2] Diserens explores the efficiency of a P300-based brain-computer interface designed for disabled subjects in the Journal of Neuroscience. Methods, vol. 167, no. 1, pp. 115-125, Jan 15, 2008.

[3] J. R. Wolpaw, N. Birbaumer, D. J. McFarland, G. Pfurtscheller, and T. M. Vaughan, “Brain-computer interfaces for the facilitation of communication and control capabilities.” Clin. Neurophysiol., vol. 113, no. 6, pp. 767-791, Jun, 2002.

[4] [3] J. R. Wolpaw, N. Birbaumer, W. J. Heetderks, D. J. McFarland, P. H. Peckham, G. Schalk, E. Donchin, L. A. Quatrano, C. J. Robinson, and T. M. Vaughan, ‘‘

[5] Reviewing the inaugural international gathering on brain-computer interface technology.’’ IEEE Trans. Rehabil. Eng., vol. 8, no. 2, pp. 164–173, Jun. 2000.

[6] [4] R. Leeb, F. Lee, C. Keinrath, R. Scherer, H. Bischof, and G. Pfurtscheller, ‘‘Brain-computer communication: Rationale, objectives, and implications of investigating a virtual apartment setting.’’ IEEE Trans. Neural Syst. Rehabil. Eng., vol. 15, no. 4, pp. 473–482, Dec. 2007.

[7] I. Käthner, A. Kübler, and S. Halder, ‘‘Comparison of eye tracking, electrooculography and an auditory brain-computer interface for binary communication: A case study with a participant in the locked-in state,’’ J. Neuroeng. Rehabil., vol. 12, no. 1, 2015, Art. no. 76.

[8] M. Ogino, S. Kanoga, M. Muto, and Y. Mitsukura, ‘‘Analysis of prefrontal single-channel EEG data for portable auditory ERP-based brain–computer interfaces,’’ Frontiers Hum. Neurosci., vol. 13, p. 250, Jul. 2019.

[9] L. Bi, J. Zhang, and J. Lian, ‘‘Adaptive driver-vehicle interface employing EEG signals through variational autoencoder and PI-TSVM.’’ IEEE Trans. Neural Syst. Rehabil. Eng., vol. 27, no. 10, pp. 2025–2033, Oct. 2019.

[10] S. Kanoga, T. Hoshino, and H. Asoh, ‘‘Subject transfer framework based on source selection and semi-supervised style transfer mapping for semg pattern recognition,’’ in Proc. IEEE Int. Conf. Acoust., Speech Signal Process. (ICASSP), May 2020,pp,1349-1353.

[11] Y. Li, C. Guan, H. Li, and Z. Chin, ‘‘A self-training semi-supervised SVM algorithm and its application in an EEG-based brain computer interface speller system,’’ Pattern Recognit. Lett., vol. 29, no. 9, pp. 1285–1294, Jul. 2008.

[12] [10] L. F. Nicolas-Alonso, R. Corralejo, J. Gomez-Pilar, D. Álvarez, and R. Hornero, ‘‘

[13] Implementing adaptive semi-supervised classification to mitigate intersession non-stationarity in multiclass motor imagery-based brain-computer interfaces.’’ Neurocomputing, vol. 159, pp. 186–196, Jul. 2015.

Authorized licensed use limited to: COLLEGE OF ENGINEERING - Pune. Downloaded on January 08,2026 at 11:49:12 UTC from IEEE Xplore. Restrictions apply.