



3. Maximum Operations

ALL

Given a string s of lowercase English characters, the following operation can be performed on it any number of times.

- Choose three consecutive characters $s[i]$, $s[i+1]$ and $s[i+2]$ where $(1 \leq i \leq |s| - 2, 1\text{-based indexing})$ such that $s[i] = s[i+1]$ and $s[i+1] \neq s[i+2]$. Replace $s[i+2]$ with $s[i]$.
- For example, if $s = "abc"$, then after the operation at $i = 1$, $s = "aac"$.

1

Find the maximum number of operations that can be applied to s .

2

Example

Consider $s = "accept"$.

3

The following operations are performed. Bold indicates the changed character.

4

- In the original string, start at $i = 2$, $"cce"$. The new string $s' = "acc**pt**"$.

5

- Start at $i = 3$, $s' = "acc**cc**t"$.

- Start at $i = 4$ $s' = "acc**ccc**"$.

6

There is no other selection available. The operation can be applied a maximum of 3 times.

7

Function Description

Complete the function `getMaximumOperations` in the editor below.

8

`getMaximumOperations` has the following parameters:

string s: the string to transform

9

Returns

long_int: the maximum number of times the **operation** can be applied

10

Constraints

- $3 \leq |s| \leq 2 \cdot 10^5$
- The string s only contains lowercase English letters.

► **Input Format For Custom Testing**

