

# Skeleton Key for RNAseq analysis

*Written By: Ciera Martinez*

## libraries

```
library(edgeR)
```

## Read in YAML guide

```
library(yaml)
yaml1 <- yaml.load_file("./de.yml")
```

```
sample1 <- yaml1$sample1
sample2 <- yaml1$sample2

sample1
```

```
## [1] "wtaother"
```

```
sample2
```

```
## [1] "wtcother"
```

## Read in Data

Read in raw count data per gene.

```
counts <- read.delim("../sam2countsResults.tsv",row.names=1)

#check the file
head(counts)
summary(counts)
colnames(counts)
#need to convert NA to 0 counts
counts[is.na(counts)] <- 0
```

## Subset per DE experiment

I am going to start by subsetting the particular treatments I am looking at.

```
colnames(counts)
```

```
## [1] "tf2ambr1"      "tf2ambr3"      "tf2ambr4"      "tf2ambr6"
## [5] "tf2aother1"    "tf2aother2"    "tf2aother4"    "tf2aother7"
## [9] "tf2bmr2"       "tf2bmr5"       "tf2bmr6"       "tf2bmr1"
## [13] "tf2bmr3"       "tf2bmr4"       "tf2bmr6"       "tf2cmbr1.4"
## [17] "tf2cmbr3"      "tf2cmbr6"      "tf2cmbr7"      "tf2cother2"
## [21] "tf2cother5"    "tf2cother6"    "tf2cother7"    "wtambr2"
## [25] "wtambr4"       "wtambr5"       "wtambr8"       "wtambr5"
## [29] "wtambr6"       "wtambr7"       "wtambr8"       "wtbmr2"
## [33] "wtbmr3"       "wtbmr6"       "wtbmr8"       "wtbmr1.4"
## [37] "wtbmr3"       "wtbmr5"       "wtbmr8"       "wtcmbr10"
## [41] "wtcmbr1.4.6"   "wtcmbr2"       "wtcmbr3"       "wtcmbr7"
## [45] "wtcmbr9"       "wtcother1.3.4" "wtcother2"     "wtcother6"
```

```
counts1 <- counts[,grep(sample1, colnames(counts), value = TRUE)]
count1Len <- length(colnames(counts1)) #used in to specify library group in next step.

counts2 <- counts[,grep(sample2, colnames(counts), value = TRUE)]
count2Len <- length(colnames(counts2)) #used to specify library group in next step.

counts <- cbind(counts1, counts2)

head(counts)
```

```
##          wtaother1 wtaother5 wtaother6 wtaother7 wtaother8
## Solyc00g005040.2.1      1      1      1      0      2
## Solyc00g005050.2.1     17     16      9      2      3
## Solyc00g005060.1.1      0      0      0      0      2
## Solyc00g005070.1.1      8      6      5      5      6
## Solyc00g005080.1.1     18     37      6     10      7
## Solyc00g005150.1.1      2      5      0      0      2
##          wtcother1.3.4 wtcother2 wtcother6
## Solyc00g005040.2.1      0      0     12
## Solyc00g005050.2.1      2      6     37
## Solyc00g005060.1.1     13      0      0
## Solyc00g005070.1.1    169      6     24
## Solyc00g005080.1.1     11     26     35
## Solyc00g005150.1.1      2      1      5
```

## Add column specifying library Group

Make a vector called group that will be used to make a new column named group to identify library region type.

```
group <- c(rep(sample1, count1Len), rep(sample2, count2Len))
d <- DGEList(counts=counts,group=group)
```

```
d$samples
```

```
##          group lib.size norm.factors
## wtaother1  wtaother  929017      1
## wtaother5  wtaother 1555921      1
## wtaother6  wtaother  498294      1
```

```
## wtaother7      wtaother    479003      1
## wtaother8      wtaother    510148      1
## wtcother1.3.4  wtcother    197345      1
## wtcother2      wtcother    319043      1
## wtcother6      wtcother    1525172     1
```

```
cpm.d <- cpm(d)
d <- d[rowSums(cpm.d>5)>=3,] #change to 5
d <- estimateCommonDisp(d,verbose=T)
```

```
## Disp = 0.287 , BCV = 0.5358
```

```
d <- calcNormFactors(d)
d <- estimateCommonDisp(d)
```

```
DEtest <- exactTest(d,pair=c(sample1,sample2))
head(DEtest$table)
```

```
##              logFC logCPM   PValue
## Solyc00g005050.2.1  0.76915  4.057 2.788e-01
## Solyc00g005070.1.1  5.38653  7.065 1.184e-16
## Solyc00g005080.1.1  1.60087  5.056 8.115e-03
## Solyc00g005160.1.1  1.70235  3.295 3.466e-02
## Solyc00g005440.1.1  0.28819  4.802 7.631e-01
## Solyc00g005840.2.1 -0.03526  4.886 9.759e-01
```

```
results <- topTags(DEtest, n=Inf)
head(results)
```

```
## Comparison of groups: wtcother-wtaother
##              logFC logCPM   PValue   FDR
## Solyc01g022780.1.1  8.302  8.536 1.702e-29 2.668e-25
## Solyc10g050260.1.1  7.476 10.450 7.060e-29 5.535e-25
## Solyc07g039270.2.1  7.552  9.782 1.321e-28 6.906e-25
## Solyc10g036800.1.1  7.390  9.791 3.543e-28 1.389e-24
## Solyc10g052420.1.1  7.406  9.823 4.887e-28 1.532e-24
## Solyc11g020560.1.1  7.162 11.675 6.253e-28 1.634e-24
```

```
dim(results$table)
```

```
## [1] 15678      4
```


```
sum(results$table$FDR<.05) # How many are DE genes?
```

```
## [1] 378
```

```
summary(decideTestsDGE(DEtest,p.value=.05))
```

```
##      [,1]
## -1      31
## 0     15300
## 1       347
```

```
sig.genes <- rownames(results$table[results$table$FDR<0.05,]) # outputs just significant gene names
plotSmea(d,de.tags=sig.genes)
```



Subset by all the ones with a significant score

```
results.sig <- subset(results$table, results$table$FDR < 0.05)
```

What are the genes that are misexpressed? For this we need to add some annotation

Essentially we are merging two annotations files to 1.) only sig genes 2.) all genes

```
annotation1<- read.delim("../ITAG2.3_all_Arabidopsis_ITAG_annotations.tsv", header=FALSE) #Changed to
colnames(annotation1) <- c("ITAG", "SGN_annotation")
annotation2<- read.delim("../ITAG2.3_all_Arabidopsis_annotated.tsv")
annotation <- merge(annotation1,annotation2, by = "ITAG")

#Making the only significant gene table
results.sig$ITAG <- rownames(results.sig) #change row.names to ITAG for merging
results.sig.annotated <- merge(results.sig,annotation,by = "ITAG") #This is merging to only sig genes

#Making all table
results$table$ITAG <- rownames(results$table)
results.all.annotated <- merge(results$table, annotation,by = "ITAG")
```

Write table with results

```
write.table(results.all.annotated, file=paste(sample1,"_",sample2,"_", "DE_all.txt",sep=""),sep="\t",row
write.table(results.sig.annotated, file=paste(sample1,"_",sample2,"_", "DE_sig.txt",sep=""),sep="\t",row
```

```
library(rmarkdown)
render("skeletonDE.Rmd", "pdf_document", output_file = paste(sample1,"_",sample2,"_", "DE.pdf", sep=""))
```