



Page Rank



Simple Recursive Formulation

- Each link's vote is proportional to the importance of its source page
- If page j with importance r_j has n out-links, each link gets r_j/n votes
- Page j 's own importance is the sum of the votes on its in-links

$$r_j = r_i/3 + r_k/4$$




PageRank: The “Flow” Model

- A “vote” from an important page is worth more
- A page is important if it is pointed to by other important pages
- Define a “rank” r_j for page j

$$r_j = \sum_{i \rightarrow j} \frac{r_i}{d_i}$$

d_i ... out-degree of node i



What is the flow equation?

- 3 equations, 3 unknowns,
no constants

Flow equations:

$$r_y = r_y/2 + r_a/2$$

$$r_a = r_y/2 + r_m$$

$$r_m = r_a/2$$

⇒ No unique solution

■ All solutions equivalent modulo the scale factor

- Additional constraint forces uniqueness:

$$\Rightarrow r_y + r_a + r_m = 1$$

$$\Rightarrow \text{Solution: } r_y = \frac{2}{5}, r_a = \frac{2}{5}, r_m = \frac{1}{5}$$

- Gaussian elimination method works for small examples, but we need a better method for large web-size graphs
- We need a new formulation!

PageRank: Matrix Formulation

- **Stochastic adjacency matrix M**

- Let page i has d_i out-links

- If $i \rightarrow j$, then $M_{ji} = \frac{1}{d_i}$ else $M_{ji} = 0$

- M is a **column stochastic matrix**

- Columns sum to **1**

- **Rank vector r :** vector with an entry per page

- r_i is the importance score of page i

- $\sum_i r_i = 1$

- **The flow equations can be written**


$$r = M \cdot r$$

$$r_j = \sum_{i \rightarrow j} \frac{r_i}{d_i}$$

- Remember the flow equation: $r_j = \sum_{i \rightarrow j} \frac{r_i}{d_i}$
- Flow equation in the matrix form

$$M \cdot r = r$$

- Suppose page i links to 3 pages, including j



Eigenvector Formulation

- The flow equations can be written


$$\underline{r} = M \cdot r$$

- So the rank vector r is an eigenvector of the stochastic web matrix M
 - In fact, its first or principal eigenvector, with corresponding eigenvalue 1
 - Largest eigenvalue of M is 1 since M is column stochastic
 - Why? We know r is a stochastic vector and each column of M sums to one, so $Mr \leq 1$
- We can now efficiently solve for r !
The method is called Power iteration

NOTE: x is an eigenvector with the corresponding eigenvalue λ if:

$$Ax = \lambda x$$

Flow equations and Matrix



$$M = \begin{matrix} & \begin{matrix} y & a & m \end{matrix} \\ \begin{matrix} y \\ a \\ m \end{matrix} & \begin{bmatrix} 1/2 & 1/2 & 0 \\ 1/2 & 0 & 1 \\ 0 & 1/2 & 0 \end{bmatrix} \end{matrix}$$

$$r = M \cdot r$$

$$\begin{aligned} r_y &= r_y/2 + r_a/2 \\ r_a &= r_y/2 + r_m \\ r_m &= r_a/2 \end{aligned}$$

$$\begin{bmatrix} y \\ a \\ m \end{bmatrix} = \begin{bmatrix} 1/2 & 1/2 & 0 \\ 1/2 & 0 & 1 \\ 0 & 1/2 & 0 \end{bmatrix} \begin{bmatrix} y \\ a \\ m \end{bmatrix}$$

Power Iteration Method

- Given a web graph with N nodes, where the nodes are pages and edges are hyperlinks
- **Power iteration:** a simple iterative scheme

- Suppose there are N web pages

- Initialize: $\mathbf{r}^{(0)} = [1/N, \dots, 1/N]^T$

- Iterate: $\mathbf{r}^{(t+1)} = \mathbf{M} \cdot \mathbf{r}^{(t)}$

- Stop when $\|\mathbf{r}^{(t+1)} - \mathbf{r}^{(t)}\|_1 < \varepsilon$

$$r_j^{(t+1)} = \sum_{i \rightarrow j} \frac{r_i^{(t)}}{d_i}$$

d_i out-degree of node i


$\|\mathbf{x}\|_1 = \sum_{1 \leq i \leq N} |x_i|$ is the L_1 norm

Can use any other vector norm, e.g., Euclidean

PageRank: How to solve?

■ Power Iteration:

- Set $r_j = 1/N$
- 1: $r'_j = \sum_{i \rightarrow j} \frac{r_i}{d_i}$
- 2: $r = r'$
- If not converged: goto 1



	y	a	m
y	$\frac{1}{2}$	$\frac{1}{2}$	0
a	$\frac{1}{2}$	0	1
m	0	$\frac{1}{2}$	0

$$r_y = r_y/2 + r_a/2$$

$$r_a = r_y/2 + r_m$$

$$r_m = r_a/2$$

■ Example:

$$\begin{bmatrix} r_y \\ r_a \\ r_m \end{bmatrix} = \begin{bmatrix} 1/3 & 1/3 & 5/12 & 9/24 & & 6/15 \\ 1/3 & 3/6 & 1/3 & 11/24 & \dots & 6/15 \\ 1/3 & 1/6 & 3/12 & 1/6 & & 3/15 \end{bmatrix}$$

Iteration 0, 1, 2, ...