



Chapter 4

Recursion

Principle of Recursion

- A recursion is a process of defining a problem (or solution to a problem) in terms of (a simple version of) itself.
- A **recursive algorithm** is one expressed in terms of itself. In other words, at least one step of a recursive algorithm is a “call” to itself.
- In programming, a **recursive function** is one that calls itself. We use recursive function to implement recursive algorithms in programming languages
- A recursive algorithm is more elegant and easier to understand but it is less efficient (extra calls consume time and space).

Principle of Recursion

- Given a recursive algorithm, how can we sure that it terminates?
- The algorithm must have:
 - ❖ one or more “easy” cases or stopping conditions
 - ❖ one or more “hard” cases or recursive calls
- In a stopping condition, the algorithm must give a direct answer without calling itself.
- In a recursive call, the algorithm may call itself, but only to deal with an “easier” case.

Example: Factorial

■ Algorithm:

$n! = 1$ if $n = 0$

$n! = n * (n - 1)!$ If $n > 0$

■ C-Function:

```
int factorial(int n)
{
    if(n == 0)
        return 1;
    else
        return n * factorial(n - 1);
}
```

Example: Fibonacci Number

■ Algorithm:

$\text{fib}(n) = n$ if $n = 0$ or $n = 1$

$\text{fib}(n) = \text{fib}(n - 1) + \text{fib}(n - 2)$ If $n > 1$

■ C-Function:

```
int fibo(int n)
{
    if(n <= 1)
        return n;
    else
        return fibo(n - 1) + fibo(n - 2);
}
```

Example: Greatest Common Divisor

■ Algorithm:

$\text{gcd}(p, q) = q$ if q exactly divides p

$\text{gcd}(p, q) = \text{gcd}(q, p \bmod q)$ if q does not exactly divide p

■ C-Function:


```
int gcd(int p, int q)
{
    if(p % q == 0)
        return q;
    else
        return gcd(q, p % q);
}
```

Example: Tower of Hanoi

- Three vertical poles (A, B, C) are mounted on a platform.
- A number of differently-sized disks are threaded on to pole A, forming a tower with the largest disk at the bottom and the smallest disk at the top.
- We may move **one** disk at a time, from any pole to any other pole, but we must never place a larger disk on top of a smaller disk.
- Problem: Move the tower of disks from pole A to pole B.

Example: Tower of Hanoi

- **Algorithm**: To move n disks from A to C, using B as auxiliary
 1. If $n = 1$, move the single disk from A to C and stop.
 2. Move the top $n - 1$ disks from A to B using C as auxiliary.
 3. Move the remaining disk from A to C.
 4. Move then $n - 1$ disks from B to C using A as auxiliary.



Example: Tower of Hanoi

■ C-Function:

```
void towers(int n, char frompeg, char topeg, char auxpeg)
{
    if(n == 1)
    {
        printf("\nMove disk 1 from peg %c to peg %c", frompeg, topeg);
        return;
    }
    towers(n - 1, frompeg, auxpeg, topeg);
    printf("\nMove disk %d from peg %c to peg %c", n, frompeg, topeg);
    towers(n - 1, auxpeg, topeg, frompeg);
}
```

Recursion vs. Iteration

■ Recursion:

- ❖ Recursion uses selection structure.
- ❖ Infinite recursion occurs if the recursive step does not reduce the problem in a manner that converges on some condition (base case) and Infinite recursion can crash the system.
- ❖ Recursion terminates when a base case is recognized.
- ❖ Recursion is usually slower than iteration due to the overhead of maintaining the stack.
- ❖ Recursion uses more memory than iteration.
- ❖ Recursion makes the code smaller.

Recursion vs. Iteration

■ Iteration:

- ❖ Iteration uses repetition structure.
- ❖ An infinite loop occurs with iteration if the loop condition test never becomes false and Infinite looping uses CPU cycles repeatedly.
- ❖ An iteration terminates when the loop condition fails.
- ❖ An iteration does not use the stack so it's faster than recursion.
- ❖ Iteration consumes less memory.
- ❖ Iteration makes the code longer.

Efficiency of Recursion

- Nonrecursive version of a program executes more efficiently in terms of time and space than a recursive version because extra calls in recursive programs consume time and space
- Overhead involved in entering and exiting a block is avoided in the nonrecursive version
- In a nonrecursive program stacking activity can be eliminated
- Sometimes a recursive solution is the most natural way of solving a problem because recursive solution flows directly from the recursive definitions