

- `useState` is a react hook that re-renders the state of a component when a user interacts or changes it
 - State represents the react data or variable that will change over time with user interaction
- `useEffect` is the function you use when you want to make a backend call to grab data when you're loading a page.
 - It best used for functions that are not pure, meaning if you input a value into that function it will not always return the same output
 - It's used for syncing React UI with things outside of react
 - In the call `useEffect(() => {},[])`, the second parameter determines when it gets called.
 - If there's no second parameter it gets called every time it renders,
 - If there's a second parameter that's just brackets, it gets called once
 - If there's a parameter with a value in it, the value can be an item that changes (i. e. an variable that contains the currently selected id of an element).
 - Note - you can't use this inside of a function as react restricts it
- `useNavigate` helps you navigate pages
 - Assign `useNavigate` to a constant variable
 - Pass an object with one field named `state` that contains another data object with fields to pass data into another component
- `onClick` is the property where you assign functions that you want to be called when clicking a button or text element
 - The return type of the function type you pass has to be void, but you can pass in a functional object that's void but the function contains another function that contains parameters
- Create an `axios` object inside a component, then export that component so it can be used throughout the react application.
 - `baseUrl`: the url to the backend application you're sending and receiving data from
 - `Headers`: this is where you set properties like the content type of the data that you're sending or receiving back
- If you're trying to send back a data object in React to a Spring Boot application, make sure that in the controller method for adding new records to databases, you set the id value to null
 - Apparently, when Hibernate executes the sql query to add or modify data in a table, if the data object sent back has a value for the ID, it will assume it's updating a record instead of adding a new one, which will throw an error when it tries to do so.
- `onChange` property in the input tag is what updates the value of the form that you're entering data into. You assign the function you want to be called when the value of that field updates
- If you're trying to use a class for css styling, know that bootstrap actually overwrites the .css file to an extent

- If you are trying to set a class for a row or item element in a table, set the class on the parent element, but in the css styling add a new css styling element that has the title of the class followed by a space and the name of the child element.
- CSS properties
 - Flex - a property used to control how a child element grows and shrinks
 - Do not apply this to elements concerning tables as it will break the alignment with column headers and rows
 - Width - controls horizontal size of element
 - Use a percentage amount to determine the amount of space you want an element to take up relative to the parent element (i. e. if you set the width to 20% that element will take up 20 percent of the space the parent element takes up)