

Decision Trees

July 2, 2019

Introduction

- ▶ We will now study our first Machine Learning tools : Decision Trees

Introduction

- ▶ We will now study our first Machine Learning tools : Decision Trees
- ▶ They can be used for **classification** and for **regression**.

Problem statement

- ▶ We have a dataset of samples, that have several **features**. Each sample also has a class.

Problem statement

- ▶ We have a dataset of samples. Each sample also has a class. Each sample also has several **features**.
- ▶ For instance we study two types of fishs : the possible classes are **tuna** and **salmon**.
- ▶ Each fish has two features : its weight and its length.

Problem statement


- ▶ We have a dataset of samples. Each sample also has a class. Each sample also has several **features**.
- ▶ For instance we study two types of fishs : the possible classes are **tuna** and **salmon**.
- ▶ Each fish has two features : its weight and its length.
- ▶ The question is : are we able to **predict the class by looking at the features ?**

Problem statement

- ▶ The **Decision Tree** is a classifier that we will build from the data that will help us to **predict the class of a new datapoint**.

Problem statement

- ▶ When the tree is built, it will look like this. Let us analyze what this means :



Building a tree

- ▶ We are interested in a method that would automatically build the tree for us.

Building a tree

- ▶ We are interested in a method that would automatically build the tree for us.
- ▶ Let us try to design such a method.

Segmentation variable

- ▶ We start from a simple tree with only one node.

Segmentation





Figure: segmentation

Segmentation variable

- ▶ We start from a simple tree with only one node.



- ▶ We want to find the feature that helps us to predict the class of the fish with most certainty.

Segmentation variable

- ▶ We start from a simple tree with only one node.
- ▶ We want to find the feature that helps us to predict the class of the fish with most certainty.
- ▶ We then need a measure of the informativeness of the feature on the class.

Segmentation variable

- ▶ We start from a simple tree with only one node.
- ▶ We want to find the feature that helps us to predict the class of the fish with most certainty.
- ▶ We then need a measure of the informativeness of the feature on the class.
- ▶ There are several possible measures :
 - ▶ Gini factor
 - ▶ Information gain
 - ▶ Misclassification probability

Notion of Entropy

- ▶ Let us discuss the concept of entropy and information.

Notion of Entropy

- ▶ Let us discuss the concept of entropy and information.
- ▶ Let X be a random variable, that can take the values a_k with probability p_k .

Notion of Entropy

- ▶ Let us discuss the concept of entropy and information.
- ▶ Let X be a random variable, that can take the values a_k with probability p_k .
- ▶ Its entropy is then

$$H = - \sum_{i=1}^n p_k \log p_k \quad (1)$$

Dataset

- ▶ Let us look at our dataset

Dataset

- ▶ Let us look at our dataset
- ▶ We have a database of 800 fishes (tunas and salmon).

Dataset

- ▶ Let us look at our dataset
- ▶ We have a database of 800 fishes (tunas and salmon).
- ▶ the features of the fishes are stored in **numpy arrays**.

Dataset : ipython demo


```
In [44]: np.load("fish_features.npy")
```

```
Out[44]:
```


```
array([[53.75892579,  0.27022806],  
       [43.5530757 ,  5.39964379],  
       [48.71780521,  0.57694348],  
       ...,  
       [27.63229236,  4.86565666],  
       [24.64053512,  5.5411517 ],  
       [35.20792985,  4.22064417]])
```

```
In [45]: █
```

Dataset : histograms



Dataset : histograms



Exercise 1

- ▶ Given the number n of datapoints, what is the maximal number of nodes in the tree ?

Implementation

- ▶ We will use **sklearn** to build decision trees.
- ▶ `https://scikit-learn.org/stable/modules/generated/sklearn.tree.DecisionTreeClassifier.html`
- ▶ `https://scikit-learn.org/stable/modules/tree.html`

Implementation

- ▶ **pip install sklearn**
- ▶ We will also need
 - ▶ **numpy**
 - ▶ **matploblib**

Exercise 2

- ▶ Use the file **fish_tree.py** in order to build your decision tree and plot it.
- ▶ Try to use different depths !

Exercise 3

- Uncomment the end of the file **fish_tree.py** in order to predict the class for new fishes.

Exercise 4

- ▶ Modify the file **fish_dataset.py** in order to modify the dataset by **adding a new feature to the fishes**.

Exercise 5

- ▶ Use the files **fish_tree_blurred.py** and **fish_dataset_blurred.py** so that the obtained tree has a smaller number of nodes.
- ▶ You can use the documentation <https://scikit-learn.org/stable/modules/generated/sklearn.tree.DecisionTreeClassifier.html>
- ▶ You can modify :
 - ▶ the distributions
 - ▶ the value of the parameters **min_samples_split** and **min_impurity_decrease**

Exercise 6

- ▶ We can apply what we learned to a famous dataset, the **iris dataset**.
- ▶ please use the file **iris.py** in order to build several decision trees with different number of nodes, by changing the specifications given to sklearn.

Discussion

- ▶ The design of a decision tree has many variants.

Discussion

- ▶ The design of a decision tree has many variants.
- ▶ When the variable to predict is continuous, we build a **regression** tree.

Discussion

- ▶ The design of a decision tree has many variants.
- ▶ When the variable to predict is continuous, we build a **regression** tree.
- ▶ Sometimes the rule used to predict the variable at a leaf node is not the **majority rule**.

Discussion

- ▶ The design of a decision tree has many variants.
- ▶ When the variable to predict is continuous, we build a **regression** tree.
- ▶ Sometimes the rule used to predict the variable at a leaf node is not the **majority rule**.
- ▶ The χ^2 test can also be used to choose to split a node or not.

Overfitting

- ▶ Overfitting can easily happen with a decision tree

Overfitting

- ▶ Overfitting can easily happen with a decision tree
- ▶ To handle it, **pruning** is often performed. It consists in **removing nodes from the tree**.

Overfitting

- ▶ Overfitting can easily happen with a decision tree
- ▶ To handle it, **pruning** is often performed. It consists in **removing nodes from the tree** :
 - ▶ **pre pruning** : while building the tree, we choose not to split some nodes
 - ▶ **post pruning** : after building the tree, we remove some nodes.
 - ▶ in **Exercise 5** we used prepruning.