

# Pandas

```
In [1]: import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

- pandas contains data structures and data manipulation tools designed to make data cleaning and analysis fast and easy in Python.
- pandas is often used in tandem with numerical computing tools like NumPy and SciPy, analytical libraries like statsmodels and scikit-learn, and data visualization libraries like matplotlib.
- pandas adopts significant parts of NumPy's idiomatic style of array-based computing, especially array-based functions and a preference for data processing without *for* loops.
- While pandas adopts many coding idioms from NumPy, the biggest difference is that pandas is designed for working with *tabular* or *heterogeneous* data. NumPy, by contrast, is best suited for working with *homogeneous numerical* array data.

## Introduction to pandas Data Structures

### Series

A **Series** is a one-dimensional array-like object containing a sequence of values (of similar types to NumPy types) and an associated array of data labels, called its *index*. The simplest Series is formed from only an array of data:

```
In [2]: obj = pd.Series([4, 7, -5, 3])
```

```
In [3]: obj
```

```
Out[3]: 0    4
        1    7
        2   -5
        3    3
        dtype: int64
```

Since we did not specify an index for the data, a default one consisting of the integers 0 through N - 1 (where N is the length of the data) is created. You can get the array representation and index object of the Series via its **values** and **index** attributes, respectively:

```
In [4]: obj.values
```

```
Out[4]: array([ 4,  7, -5,  3], dtype=int64)
```

```
In [5]: obj.index
```

```
Out[5]: RangeIndex(start=0, stop=4, step=1)
```

Often it will be desirable to create a Series with an **index** identifying each data point with a label:

```
In [6]: obj2 = pd.Series([4, 7, -5, 3], index=['d', 'b', 'a', 'c'])
```

```
In [7]: obj2
```

```
Out[7]: d      4  
       b      7  
       a     -5  
       c      3  
       dtype: int64
```

```
In [8]: obj2.index
```

```
Out[8]: Index(['d', 'b', 'a', 'c'], dtype='object')
```

You can use labels in the index when selecting single values or a set of values:

```
In [9]: obj2['a']
```

```
Out[9]: -5
```

```
In [10]: obj2['d'] = 6
```

```
In [11]: obj2
```

```
Out[11]: d      6  
       b      7  
       a     -5  
       c      3  
       dtype: int64
```

```
In [12]: obj2[['c', 'a', 'd']]
```

```
Out[12]: c      3  
       a     -5  
       d      6  
       dtype: int64
```

Using NumPy functions or NumPy-like operations, such as filtering with a boolean array, scalar multiplication, or applying math functions, will preserve the index-value link:

```
In [13]: obj2[obj2 > 0]
```

```
Out[13]: d      6  
       b      7  
       c      3  
       dtype: int64
```

```
In [14]: obj2 * 2
```

```
Out[14]: d     12  
       b     14  
       a    -10  
       c      6  
       dtype: int64
```

```
In [15]: np.exp(obj2)
```

```
Out[15]: d      403.428793
         b    1096.633158
         a      0.006738
         c     20.085537
         dtype: float64
```

Another way to think about a Series is as a fixed-length, *ordered dict*, as it is a mapping of index values to data values. It can be used in many contexts where you might use a **dict**:

```
In [16]: 'b' in obj2
```

```
Out[16]: True
```

```
In [17]: 'e' in obj2
```

```
Out[17]: False
```

You can create a Series from it by passing the dict:

```
In [18]: sdata = {'Ohio': 35000, 'Texas': 71000, 'Oregon': 16000, 'Utah': 5000}
```

```
In [19]: obj3 = pd.Series(sdata)
```

```
In [20]: obj3
```

```
Out[20]: Ohio      35000
         Oregon   16000
         Texas    71000
         Utah     5000
         dtype: int64
```

When you are only passing a *dict*, the index in the resulting Series will have the *dict's keys in sorted order*. You can override this by passing the dict keys in the order you want them to appear in the resulting Series:

```
In [21]: states = ['California', 'Ohio', 'Oregon', 'Texas']
```

```
In [22]: obj4 = pd.Series(sdata, index=states)
```

```
In [23]: obj4
```

```
Out[23]: California      NaN
         Ohio           35000.0
         Oregon          16000.0
         Texas           71000.0
         dtype: float64
```

The **isnull** and **notnull** functions in pandas should be used to detect missing data:

```
In [24]: pd.isnull(obj4)
```

```
Out[24]: California    True
         Ohio          False
         Oregon         False
         Texas          False
         dtype: bool
```

```
In [25]: pd.notnull(obj4)
```

```
Out[25]: California    False
         Ohio          True
         Oregon         True
         Texas          True
         dtype: bool
```

Series also has these as instance methods:

```
In [26]: obj4.isnull()
```

```
Out[26]: California    True
         Ohio          False
         Oregon         False
         Texas          False
         dtype: bool
```

```
In [27]: obj4.notnull()
```

```
Out[27]: California    False
         Ohio          True
         Oregon         True
         Texas          True
         dtype: bool
```

A useful Series feature for many applications is that it *automatically aligns by index label* in arithmetic operations:

```
In [28]: obj3
```

```
Out[28]: Ohio          35000
         Oregon         16000
         Texas          71000
         Utah           5000
         dtype: int64
```

```
In [29]: obj4
```

```
Out[29]: California    NaN
         Ohio          35000.0
         Oregon         16000.0
         Texas          71000.0
         dtype: float64
```

```
In [30]: obj3 + obj4
```

```
Out[30]: California    NaN
         Ohio          70000.0
         Oregon         32000.0
         Texas         142000.0
         Utah           NaN
         dtype: float64
```

Both the *Series object itself* and its *index* have a **name** attribute, which integrates with other key areas of pandas functionality:

```
In [31]: obj4
```

```
Out[31]: California      NaN
         Ohio            35000.0
         Oregon          16000.0
         Texas           71000.0
         dtype: float64
```

```
In [32]: obj4.name = 'population'
```

```
In [33]: obj4.index.name = 'state'
```

```
In [34]: obj4
```

```
Out[34]: state
         California      NaN
         Ohio            35000.0
         Oregon          16000.0
         Texas           71000.0
         Name: population, dtype: float64
```

A Series's index can be altered in-place by assignment:

```
In [35]: obj
```

```
Out[35]: 0      4
         1      7
         2     -5
         3      3
         dtype: int64
```

```
In [36]: obj.index = ['Bob', 'Steve', 'Jeff', 'Ryan']
```

```
In [37]: obj
```

```
Out[37]: Bob          4
         Steve         7
         Jeff        -5
         Ryan         3
         dtype: int64
```

## DataFrame

- A DataFrame represents a rectangular table of data and contains an ordered collection of columns, each of which can be a different value type (numeric, string, boolean, etc.).
- The DataFrame has both a row and column index; it can be thought of as a dict of Series all sharing the same index.
- The data is stored as one or more two-dimensional blocks rather than a list, dict, or some other collection of one-dimensional arrays.
- While a DataFrame is physically two-dimensional, you can use it to represent higher dimensional data in a tabular format using hierarchical indexing.

There are many ways to construct a DataFrame, though one of the most common is from a dict of equal-length lists or NumPy arrays:

```
In [38]: data = {'state':  
    ['Ohio', 'Ohio', 'Ohio', 'Nevada', 'Nevada', 'Nevada'],  
    'year': [2000, 2001, 2002, 2001, 2002, 2003],  
    'pop': [1.5, 1.7, 3.6, 2.4, 2.9, 3.2]}  
frame = pd.DataFrame(data)
```

```
In [39]: frame
```

```
Out[39]:
```

	pop	state	year
0	1.5	Ohio	2000
1	1.7	Ohio	2001
2	3.6	Ohio	2002
3	2.4	Nevada	2001
4	2.9	Nevada	2002
5	3.2	Nevada	2003

For large DataFrames, the **head** method selects only the first five rows:

```
In [40]: frame.head()
```

```
Out[40]:
```

	pop	state	year
0	1.5	Ohio	2000
1	1.7	Ohio	2001
2	3.6	Ohio	2002
3	2.4	Nevada	2001
4	2.9	Nevada	2002

```
In [41]: frame.head(2)
```

```
Out[41]:
```

	pop	state	year
0	1.5	Ohio	2000
1	1.7	Ohio	2001

If you specify a sequence of **columns**, the DataFrame's columns will be arranged in that order:

```
In [43]: pd.DataFrame(data, columns=['year', 'state', 'pop'])
```

```
Out[43]:
```

	year	state	pop
0	2000	Ohio	1.5
1	2001	Ohio	1.7
2	2002	Ohio	3.6
3	2001	Nevada	2.4
4	2002	Nevada	2.9
5	2003	Nevada	3.2

If you pass a column that isn't contained in the dict, it will appear with missing values in the result:

```
In [44]: data
```

```
Out[44]: {'pop': [1.5, 1.7, 3.6, 2.4, 2.9, 3.2],
          'state': ['Ohio', 'Ohio', 'Ohio', 'Nevada', 'Nevada', 'Nevada'],
          'year': [2000, 2001, 2002, 2001, 2002, 2003]}
```

```
In [45]: frame2 = pd.DataFrame(data, columns=['year', 'state', 'pop', 'debt'],
                                index=['one', 'two', 'three', 'four', 'five', 'six'])
```

```
In [46]: frame2
```

```
Out[46]:
```

	year	state	pop	debt
one	2000	Ohio	1.5	NaN
two	2001	Ohio	1.7	NaN
three	2002	Ohio	3.6	NaN
four	2001	Nevada	2.4	NaN
five	2002	Nevada	2.9	NaN
six	2003	Nevada	3.2	NaN

A column in a DataFrame can be retrieved as a *Series* either by *dict-like* notation or by *attribute*:

```
In [47]: frame2['state']
```

```
Out[47]: one      Ohio
         two      Ohio
         three    Ohio
         four    Nevada
         five    Nevada
         six     Nevada
         Name: state, dtype: object
```

```
In [48]: frame2.state
```

```
Out[48]: one      Ohio
         two      Ohio
         three    Ohio
         four    Nevada
         five    Nevada
         six      Nevada
         Name: state, dtype: object
```

Note that the returned Series have the *same index* as the DataFrame, and their name attribute has been appropriately set.

**The column returned from indexing a DataFrame is a view on the underlying data, not a copy. Thus, any in-place modifications to the Series will be reflected in the DataFrame. The column can be explicitly copied with the Series's `copy` method.**

Rows can also be retrieved by position or name with the special `.loc` attribute:

```
In [50]: frame2.loc['three']
```

```
Out[50]: year      2002
         state     Ohio
         pop       3.6
         debt      NaN
         Name: three, dtype: object
```

Columns can be modified by assignment. For example, the empty 'debt' column could be assigned a scalar value or an array of values:

```
In [51]: frame2['debt'] = 16.5
```

```
In [52]: frame2
```

```
Out[52]:
```

	year	state	pop	debt
one	2000	Ohio	1.5	16.5
two	2001	Ohio	1.7	16.5
three	2002	Ohio	3.6	16.5
four	2001	Nevada	2.4	16.5
five	2002	Nevada	2.9	16.5
six	2003	Nevada	3.2	16.5

```
In [53]: frame2['debt'] = np.arange(6.)
```



```
In [54]: frame2
```

```
Out[54]:
```

	year	state	pop	debt
<b>one</b>	2000	Ohio	1.5	0.0
<b>two</b>	2001	Ohio	1.7	1.0
<b>three</b>	2002	Ohio	3.6	2.0
<b>four</b>	2001	Nevada	2.4	3.0
<b>five</b>	2002	Nevada	2.9	4.0
<b>six</b>	2003	Nevada	3.2	5.0

When you are assigning lists or arrays to a column, the value's length must match the length of the DataFrame. If you assign a Series, its labels will be realigned exactly to the DataFrame's index, inserting missing values in any holes:

```
In [60]: val = pd.Series([-1.2, -1.5, -1.7], index=['two', 'four', 'five'])
```

```
In [61]: frame2['debt'] = val
```

```
In [62]: frame2
```

```
Out[62]:
```

	year	state	pop	debt	eastern
<b>one</b>	2000	Ohio	1.5	NaN	True
<b>two</b>	2001	Ohio	1.7	-1.2	True
<b>three</b>	2002	Ohio	3.6	NaN	True
<b>four</b>	2001	Nevada	2.4	-1.5	False
<b>five</b>	2002	Nevada	2.9	-1.7	False
<b>six</b>	2003	Nevada	3.2	NaN	False

Assigning a column that doesn't exist will create a new column. The **del** keyword will delete columns as with a dict.

```
In [63]: frame2['eastern'] = frame2.state == 'Ohio'
```

```
In [64]: frame2
```

```
Out[64]:
```

	year	state	pop	debt	eastern
<b>one</b>	2000	Ohio	1.5	NaN	True
<b>two</b>	2001	Ohio	1.7	-1.2	True
<b>three</b>	2002	Ohio	3.6	NaN	True
<b>four</b>	2001	Nevada	2.4	-1.5	False
<b>five</b>	2002	Nevada	2.9	-1.7	False
<b>six</b>	2003	Nevada	3.2	NaN	False

```
In [65]: del frame2['eastern']
```

```
In [66]: frame2.columns
```

```
Out[66]: Index(['year', 'state', 'pop', 'debt'], dtype='object')
```

```
In [67]: frame2
```

```
Out[67]:
```

	year	state	pop	debt
one	2000	Ohio	1.5	NaN
two	2001	Ohio	1.7	-1.2
three	2002	Ohio	3.6	NaN
four	2001	Nevada	2.4	-1.5
five	2002	Nevada	2.9	-1.7
six	2003	Nevada	3.2	NaN

Another common form of data is a nested dict of dicts:

```
In [68]: pop = {'Nevada': {2001: 2.4, 2002: 2.9},  
               'Ohio': {2000: 1.5, 2001: 1.7, 2002: 3.6}}
```

pandas will interpret the *outer dict* keys as the *columns* and the *inner keys* as the row indices:

```
In [69]: frame3 = pd.DataFrame(pop)
```

```
In [70]: frame3
```

```
Out[70]:
```

	Nevada	Ohio
2000	NaN	1.5
2001	2.4	1.7
2002	2.9	3.6

You can transpose the DataFrame (swap rows and columns) with similar syntax to a NumPy array:

```
In [71]: frame3.T
```

```
Out[71]:
```

	2000	2001	2002
Nevada	NaN	2.4	2.9
Ohio	1.5	1.7	3.6

If a DataFrame's index and columns have their *name* attributes set, these will also be displayed:

```
In [72]: frame3.index.name = 'year'; frame3.columns.name = 'state'
```

```
In [73]: frame3
```

```
Out[73]:
```

state	Nevada	Ohio
year		
2000	NaN	1.5
2001	2.4	1.7
2002	2.9	3.6

As with Series, the **values** attribute returns the data contained in the DataFrame as a two-dimensional ndarray:

```
In [74]: frame3.values
```

```
Out[74]: array([[nan, 1.5],
                [2.4, 1.7],
                [2.9, 3.6]])
```

## Index Objects

pandas's *Index* objects are responsible for holding the axis labels and other metadata (like the axis name or names). Any array or other sequence of labels you use when constructing a Series or DataFrame is internally converted to an Index:

```
In [75]: obj = pd.Series(range(3), index=['a', 'b', 'c'])
```

```
In [76]: obj
```

```
Out[76]: a    0
         b    1
         c    2
         dtype: int64
```

```
In [77]: index = obj.index
```

```
In [78]: index
```

```
Out[78]: Index(['a', 'b', 'c'], dtype='object')
```

```
In [79]: index[1:]
```

```
Out[79]: Index(['b', 'c'], dtype='object')
```

Index objects are immutable and thus can't be modified by the user:

Immutability makes it safer to share Index objects among data structures:

```
In [81]: labels = pd.Index(np.arange(3))
```

```
In [82]: labels
```

```
Out[82]: Int64Index([0, 1, 2], dtype='int64')
```

```
In [83]: obj2 = pd.Series([1.5, -2.5, 0], index=labels)
```

```
In [84]: obj2.index is labels
```

```
Out[84]: True
```

In addition to being array-like, an Index also behaves like a fixed-size set:

```
In [85]: frame3
```

```
Out[85]:
```

state	Nevada	Ohio
year		
2000	NaN	1.5
2001	2.4	1.7
2002	2.9	3.6

```
In [86]: frame3.columns
```

```
Out[86]: Index(['Nevada', 'Ohio'], dtype='object', name='state')
```

```
In [87]: 'Ohio' in frame3.columns
```

```
Out[87]: True
```

Unlike Python sets, a pandas Index can contain duplicate labels:

```
In [88]: dup_labels = pd.Index(['foo', 'foo', 'bar', 'bar'])
```

```
In [89]: dup_labels
```

```
Out[89]: Index(['foo', 'foo', 'bar', 'bar'], dtype='object')
```

Selections with duplicate labels will select all occurrences of that label.

Each Index has a number of methods and properties for set logic, which answer other common questions about the data it contains.

*Table 5-2. Some Index methods and properties*

Method	Description
<code>append</code>	Concatenate with additional Index objects, producing a new Index
<code>difference</code>	Compute set difference as an Index
<code>intersection</code>	Compute set intersection
<code>union</code>	Compute set union
<code>isin</code>	Compute boolean array indicating whether each value is contained in the passed collection
<code>delete</code>	Compute new Index with element at index <code>i</code> deleted
<code>drop</code>	Compute new Index by deleting passed values
<code>insert</code>	Compute new Index by inserting element at index <code>i</code>
<code>is_monotonic</code>	Returns <code>True</code> if each element is greater than or equal to the previous element
<code>is_unique</code>	Returns <code>True</code> if the Index has no duplicate values
<code>unique</code>	Compute the array of unique values in the Index

## Essential Functionality

### Reindexing

An important method on pandas objects is **reindex**, which means to create a new object with the data conformed to a new index. Consider an example:

```
In [90]: obj = pd.Series([4.5, 7.2, -5.3, 3.6], index=['d', 'b', 'a', 'c'])
```

```
In [91]: obj
```

```
Out[91]: d      4.5  
         b      7.2  
         a     -5.3  
         c      3.6  
         dtype: float64
```

Calling **reindex** on this Series rearranges the data according to the new index, introducing missing values if any index values were not already present:

```
In [94]: obj2 = obj.reindex(['a', 'b', 'c', 'd', 'e'])
```

```
In [95]: obj2
```

```
Out[95]: a    -5.3  
        b     7.2  
        c     3.6  
        d     4.5  
        e     NaN  
        dtype: float64
```

For ordered data like time series, it may be desirable to do some interpolation or fill- ing of values when reindexing. The `method` option allows us to do this, using a method such as **ffill**, which forward-fills the values:

```
In [96]: obj3 = pd.Series(['blue', 'purple', 'yellow'], index=[0, 2, 4])
```

```
In [97]: obj3
```

```
Out[97]: 0      blue  
        2    purple  
        4    yellow  
        dtype: object
```

```
In [98]: obj3.reindex(range(6), method='ffill')
```

```
Out[98]: 0      blue  
        1      blue  
        2    purple  
        3    purple  
        4    yellow  
        5    yellow  
        dtype: object
```

With **DataFrame**, `reindex` can alter either the (row) index, columns, or both. When passed only a sequence, it reindexes the rows in the result:

```
In [99]: frame = pd.DataFrame(np.arange(9).reshape((3, 3)),  
                             index=['a', 'c', 'd'],  
                             columns=['Ohio', 'Texas', 'California'])
```

```
In [100]: frame
```

```
Out[100]:
```

	Ohio	Texas	California
a	0	1	2
c	3	4	5
d	6	7	8

```
In [101]: frame2 = frame.reindex(['a', 'b', 'c', 'd'])
```

```
In [102]: frame2
```

```
Out[102]:
```

	Ohio	Texas	California
a	0.0	1.0	2.0
b	NaN	NaN	NaN
c	3.0	4.0	5.0
d	6.0	7.0	8.0

The columns can be reindexed with the **columns** keyword:

```
In [103]: states = ['Texas', 'Utah', 'California']
```

```
In [104]: frame.reindex(columns=states)
```

```
Out[104]:
```

	Texas	Utah	California
a	1	NaN	2
c	4	NaN	5
d	7	NaN	8

You can reindex more succinctly by label-indexing with `loc`, and many users prefer to use it exclusively:

```
In [105]: frame.loc[['a', 'b', 'c', 'd'], states]
```

```
C:\Users\User\Anaconda3\lib\site-packages\ipykernel_launcher.py:1: FutureWarning
:
Passing list-likes to .loc or [] with any missing label will raise
KeyError in the future, you can use .reindex() as an alternative.
```

See the documentation here:

<http://pandas.pydata.org/pandas-docs/stable/indexing.html#deprecate-loc-reindex-listlike>

```
"""Entry point for launching an IPython kernel.
```

```
Out[105]:
```

	Texas	Utah	California
a	1.0	NaN	2.0
b	NaN	NaN	NaN
c	4.0	NaN	5.0
d	7.0	NaN	8.0

Table 5-3. *reindex* function arguments

Argument	Description
<code>index</code>	New sequence to use as index. Can be Index instance or any other sequence-like Python data structure. An Index will be used exactly as is without any copying.
<code>method</code>	Interpolation (fill) method; 'ffill' fills forward, while 'bfill' fills backward.
<code>fill_value</code>	Substitute value to use when introducing missing data by reindexing.
<code>limit</code>	When forward- or backfilling, maximum size gap (in number of elements) to fill.
<code>tolerance</code>	When forward- or backfilling, maximum size gap (in absolute numeric distance) to fill for inexact matches.
<code>level</code>	Match simple Index on level of MultiIndex; otherwise select subset of.
<code>copy</code>	If True, always copy underlying data even if new index is equivalent to old index; if False, do not copy the data when the indexes are equivalent.

## Dropping Entries from an Axis

**drop** method will return a new object with the indicated value or values deleted from an axis:

```
In [106]: obj = pd.Series(np.arange(5.), index=['a', 'b', 'c', 'd', 'e'])
```

```
In [107]: obj
```

```
Out[107]: a    0.0
          b    1.0
          c    2.0
          d    3.0
          e    4.0
          dtype: float64
```

```
In [108]: new_obj = obj.drop('c')
```

```
In [109]: new_obj
```

```
Out[109]: a    0.0
          b    1.0
          d    3.0
          e    4.0
          dtype: float64
```

```
In [110]: obj.drop(['d', 'c'])
```

```
Out[110]: a    0.0
          b    1.0
          e    4.0
          dtype: float64
```

With DataFrame, index values can be deleted from either axis. To illustrate this, we first create an example DataFrame:



```
In [113]: data = pd.DataFrame(np.arange(16).reshape((4, 4)),  
                              index=['Ohio', 'Colorado', 'Utah', 'New York'],  
                              columns=['one', 'two', 'three', 'four'])
```

```
In [114]: data
```

```
Out[114]:
```

	one	two	three	four
Ohio	0	1	2	3
Colorado	4	5	6	7
Utah	8	9	10	11
New York	12	13	14	15

```
In [115]: data.drop(['Colorado', 'Ohio'])
```

```
Out[115]:
```

	one	two	three	four
Utah	8	9	10	11
New York	12	13	14	15

You can drop values from the columns by passing `axis=1` or `axis='columns'`:

```
In [116]: data.drop('two', axis=1)
```

```
Out[116]:
```

	one	three	four
Ohio	0	2	3
Colorado	4	6	7
Utah	8	10	11
New York	12	14	15

```
In [117]: data.drop(['two', 'four'], axis='columns')
```

```
Out[117]:
```

	one	three
Ohio	0	2
Colorado	4	6
Utah	8	10
New York	12	14

Many functions, like `drop`, which modify the size or shape of a Series or DataFrame, can manipulate an object **in-place** without returning a new object:

```
In [118]: obj.drop('c', inplace=True)
```

```
In [119]: obj
Out[119]: a      0.0
          b      1.0
          d      3.0
          e      4.0
          dtype: float64
```

## Indexing, Selection, and Filtering

Series indexing (`obj[...]`) works analogously to NumPy array indexing, except you can use the Series's index values instead of only integers. Here are some examples of this:

```
In [120]: obj = pd.Series(np.arange(4.), index=['a', 'b', 'c', 'd'])
```

```
In [121]: obj['b']
```

```
Out[121]: 1.0
```

```
In [122]: obj[1]
```

```
Out[122]: 1.0
```

```
In [123]: obj[2:4]
```

```
Out[123]: c      2.0
          d      3.0
          dtype: float64
```

```
In [124]: obj[['b', 'a', 'd']]
```

```
Out[124]: b      1.0
          a      0.0
          d      3.0
          dtype: float64
```

```
In [125]: obj[[1, 3]]
```

```
Out[125]: b      1.0
          d      3.0
          dtype: float64
```

```
In [126]: obj[obj < 2]
```

```
Out[126]: a      0.0
          b      1.0
          dtype: float64
```

Slicing with labels behaves differently than normal Python slicing in that the endpoint is **inclusive**:

```
In [127]: obj['b':'c']
```

```
Out[127]: b      1.0
          c      2.0
          dtype: float64
```

```
In [128]: obj['b':'c'] = 5
```

```
In [129]: obj
```

```
Out[129]: a      0.0  
         b      5.0  
         c      5.0  
         d      3.0  
         dtype: float64
```

Indexing into a DataFrame is for retrieving one or more columns either with a single value or sequence:

```
In [130]: data = pd.DataFrame(np.arange(16).reshape((4, 4)),  
                             index=['Ohio', 'Colorado', 'Utah', 'New York'],  
                             columns=['one', 'two', 'three', 'four'])
```

```
In [131]: data
```

```
Out[131]:
```

	one	two	three	four
Ohio	0	1	2	3
Colorado	4	5	6	7
Utah	8	9	10	11
New York	12	13	14	15

```
In [132]: data['two']
```

```
Out[132]: Ohio      1  
         Colorado   5  
         Utah       9  
         New York   13  
         Name: two, dtype: int32
```

```
In [133]: data[['three', 'one']]
```

```
Out[133]:
```

	three	one
Ohio	2	0
Colorado	6	4
Utah	10	8
New York	14	12

Indexing like this has a few special cases. First, slicing or selecting data with a boolean array:

```
In [134]: data[:2]
```

```
Out[134]:
```

	one	two	three	four
Ohio	0	1	2	3
Colorado	4	5	6	7

```
In [135]: data[data['three'] > 5]
```

```
Out[135]:
```

	one	two	three	four
Colorado	4	5	6	7
Utah	8	9	10	11
New York	12	13	14	15

The row selection syntax `data[2]` is provided as a convenience. Passing a single element or a list to the `[]` operator selects *\*columns*.

Another use case is in indexing with a boolean DataFrame, such as one produced by a scalar comparison:

```
In [136]: data < 5
```

```
Out[136]:
```

	one	two	three	four
Ohio	True	True	True	True
Colorado	True	False	False	False
Utah	False	False	False	False
New York	False	False	False	False

```
In [137]: data[data < 5] = 0
```

```
In [138]: data
```

```
Out[138]:
```

	one	two	three	four
Ohio	0	0	0	0
Colorado	0	5	6	7
Utah	8	9	10	11
New York	12	13	14	15

## Selection with loc and iloc

**loc** and **iloc** enable you to select a subset of the rows and columns from a DataFrame with NumPy-like notation using either axis labels (**loc**) or integers (**iloc**).

```
In [139]: data.loc['Colorado', ['two', 'three']]
```

```
Out[139]: two      5
          three    6
          Name: Colorado, dtype: int32
```

```
In [140]: data.iloc[2, [3, 0, 1]]
```

```
Out[140]: four      11
          one       8
          two       9
          Name: Utah, dtype: int32
```

```
In [141]: data.iloc[2]
```

```
Out[141]: one       8
          two       9
          three     10
          four     11
          Name: Utah, dtype: int32
```

```
In [142]: data.iloc[[1, 2], [3, 0, 1]]
```

```
Out[142]:
```

	four	one	two
Colorado	7	0	5
Utah	11	8	9

Both indexing functions work with slices in addition to single labels or lists of labels:

```
In [143]: data.loc[:, 'Utah', 'two']
```

```
Out[143]: Ohio      0
          Colorado   5
          Utah       9
          Name: two, dtype: int32
```

```
In [144]: data.iloc[:, :3]
```

```
Out[144]:
```

	one	two	three
Ohio	0	0	0
Colorado	0	5	6
Utah	8	9	10
New York	12	13	14

```
In [145]: data.iloc[:, :3][data.three > 5]
```

```
Out[145]:
```

	one	two	three
Colorado	0	5	6
Utah	8	9	10
New York	12	13	14

## Indexing options with DataFrame

Type	Notes
<code>df[val]</code>	Select single column or sequence of columns from the DataFrame; special case conveniences: boolean array (filter rows), slice (slice rows), or boolean DataFrame (set values based on some criterion)
<code>df.loc[val]</code>	Selects single row or subset of rows from the DataFrame by label
<code>df.loc[:, val]</code>	Selects single column or subset of columns by label
<code>df.loc[val1, val2]</code>	Select both rows and columns by label
<code>df.iloc[where]</code>	Selects single row or subset of rows from the DataFrame by integer position
<code>df.iloc[:, where]</code>	Selects single column or subset of columns by integer position
<code>df.iloc[where_i, where_j]</code>	Select both rows and columns by integer position
<code>df.at[label_i, label_j]</code>	Select a single scalar value by row and column label
<code>df.iat[i, j]</code>	Select a single scalar value by row and column position (integers)
reindex method	Select either rows or columns by labels
get_value, set_value methods	Select single value by row and column label

## Integer Indexes

Working with pandas objects indexed by integers is something that often trips up new users due to some differences with indexing semantics on built-in Python data structures like lists and tuples. For example, you might not expect the following code to generate an error:

```
In [146]: ser = pd.Series(np.arange(3.))
```

```
In [147]: ser
```

```
Out[147]: 0    0.0
          1    1.0
          2    2.0
          dtype: float64
```

```
In [148]: #ser[-1] error
```

```
In [149]: ser.iloc[-1]
```

```
Out[149]: 2.0
```

On the other hand, with a non-integer index, there is no potential for ambiguity:

```
In [150]: ser2 = pd.Series(np.arange(3.), index=['a', 'b', 'c'])
```

```
In [151]: ser2[-1]
```

```
Out[151]: 2.0
```

To keep things consistent, if you have an axis index containing integers, data selection will always be label-oriented. For more precise handling, use `loc` (for labels) or `iloc` (for integers):

```
In [152]: ser[:1]
```

```
Out[152]: 0    0.0  
          dtype: float64
```

```
In [153]: ser.loc[:1]
```

```
Out[153]: 0    0.0  
          1    1.0  
          dtype: float64
```

```
In [154]: ser.iloc[:1]
```

```
Out[154]: 0    0.0  
          dtype: float64
```

## Arithmetic and Data Alignment

An important pandas feature for some applications is the behavior of arithmetic between objects with different indexes. When you are adding together objects, if any index pairs are not the same, the respective index in the result will be the union of the index pairs. For users with database experience, this is similar to an automatic outer join on the index labels. Let's look at an example:

```
In [155]: s1 = pd.Series([7.3, -2.5, 3.4, 1.5], index=['a', 'c', 'd', 'e'])
```

```
In [156]: s1
```

```
Out[156]: a    7.3  
          c   -2.5  
          d    3.4  
          e    1.5  
          dtype: float64
```

```
In [157]: s2 = pd.Series([-2.1, 3.6, -1.5, 4, 3.1], index=['a', 'c', 'e', 'f', 'g'])
```

```
In [158]: s2
```

```
Out[158]: a   -2.1  
          c    3.6  
          e   -1.5  
          f    4.0  
          g    3.1  
          dtype: float64
```

```
In [159]: s1 + s2
```

```
Out[159]: a    5.2  
          c    1.1  
          d   NaN  
          e    0.0  
          f   NaN  
          g   NaN  
          dtype: float64
```

In the case of DataFrame, alignment is performed on both the rows and the columns:

```
In [160]: df1 = pd.DataFrame(np.arange(9.).reshape((3, 3)), columns=list('bcd'), index=['Ohio', 'Texas', 'Colorado'])
df2 = pd.DataFrame(np.arange(12.).reshape((4, 3)), columns=list('bde'), index=['Utah', 'Ohio', 'Texas', 'Oregon'])
```

```
In [161]: df1
```

```
Out[161]:
```

	b	c	d
Ohio	0.0	1.0	2.0
Texas	3.0	4.0	5.0
Colorado	6.0	7.0	8.0

```
In [162]: df2
```

```
Out[162]:
```

	b	d	e
Utah	0.0	1.0	2.0
Ohio	3.0	4.0	5.0
Texas	6.0	7.0	8.0
Oregon	9.0	10.0	11.0

```
In [163]: df1 + df2
```

```
Out[163]:
```

	b	c	d	e
Colorado	NaN	NaN	NaN	NaN
Ohio	3.0	NaN	6.0	NaN
Oregon	NaN	NaN	NaN	NaN
Texas	9.0	NaN	12.0	NaN
Utah	NaN	NaN	NaN	NaN

## Arithmetic methods with fill values

In arithmetic operations between differently indexed objects, you might want to fill with a special value, like 0, when an axis label is found in one object but not the other:

```
In [164]: df1 = pd.DataFrame(np.arange(12.).reshape((3, 4)), columns=list('abcd'))
df2 = pd.DataFrame(np.arange(20.).reshape((4, 5)), columns=list('abcde'))
```



```
In [165]: df1
```

```
Out[165]:
```

	a	b	c	d
0	0.0	1.0	2.0	3.0
1	4.0	5.0	6.0	7.0
2	8.0	9.0	10.0	11.0

```
In [166]: df2
```

```
Out[166]:
```

	a	b	c	d	e
0	0.0	1.0	2.0	3.0	4.0
1	5.0	6.0	7.0	8.0	9.0
2	10.0	11.0	12.0	13.0	14.0
3	15.0	16.0	17.0	18.0	19.0

```
In [167]: df2.loc[1, 'b'] = np.nan
```

```
In [168]: df2
```

```
Out[168]:
```

	a	b	c	d	e
0	0.0	1.0	2.0	3.0	4.0
1	5.0	NaN	7.0	8.0	9.0
2	10.0	11.0	12.0	13.0	14.0
3	15.0	16.0	17.0	18.0	19.0

```
In [169]: df1 + df2
```

```
Out[169]:
```

	a	b	c	d	e
0	0.0	2.0	4.0	6.0	NaN
1	9.0	NaN	13.0	15.0	NaN
2	18.0	20.0	22.0	24.0	NaN
3	NaN	NaN	NaN	NaN	NaN

Using the **add** method on df1, I pass df2 and an argument to **fill\_value**:

```
In [172]: df1
```

```
Out[172]:
```

	a	b	c	d
0	0.0	1.0	2.0	3.0
1	4.0	5.0	6.0	7.0
2	8.0	9.0	10.0	11.0

```
In [173]: df2
```

```
Out[173]:
```

	a	b	c	d	e
0	0.0	1.0	2.0	3.0	4.0
1	5.0	NaN	7.0	8.0	9.0
2	10.0	11.0	12.0	13.0	14.0
3	15.0	16.0	17.0	18.0	19.0

```
In [175]: df1.add(df2, fill_value=0)
```

```
Out[175]:
```

	a	b	c	d	e
0	0.0	2.0	4.0	6.0	4.0
1	9.0	5.0	13.0	15.0	9.0
2	18.0	20.0	22.0	24.0	14.0
3	15.0	16.0	17.0	18.0	19.0

```
In [176]: 1 / df1
```

```
Out[176]:
```

	a	b	c	d
0	inf	1.000000	0.500000	0.333333
1	0.250000	0.200000	0.166667	0.142857
2	0.125000	0.111111	0.100000	0.090909

Relatedly, when reindexing a Series or DataFrame, you can also specify a different fill value:

```
In [178]: df1
```

```
Out[178]:
```

	a	b	c	d
0	0.0	1.0	2.0	3.0
1	4.0	5.0	6.0	7.0
2	8.0	9.0	10.0	11.0

```
In [179]: df2
```

```
Out[179]:
```

	a	b	c	d	e
0	0.0	1.0	2.0	3.0	4.0
1	5.0	NaN	7.0	8.0	9.0
2	10.0	11.0	12.0	13.0	14.0
3	15.0	16.0	17.0	18.0	19.0

```
In [180]: df1.reindex(columns=df2.columns, fill_value=0)
```

```
Out[180]:
```

	a	b	c	d	e
0	0.0	1.0	2.0	3.0	0
1	4.0	5.0	6.0	7.0	0
2	8.0	9.0	10.0	11.0	0

## Operations between DataFrame and Series

```
In [181]: arr = np.arange(12.).reshape((3, 4))
```

```
In [182]: arr
```

```
Out[182]: array([[ 0.,  1.,  2.,  3.],
                 [ 4.,  5.,  6.,  7.],
                 [ 8.,  9., 10., 11.]])
```

```
In [183]: arr[0]
```

```
Out[183]: array([0., 1., 2., 3.])
```

```
In [184]: arr - arr[0]
```

```
Out[184]: array([[0., 0., 0., 0.],
                 [4., 4., 4., 4.],
                 [8., 8., 8., 8.]])
```

```
In [185]: frame = pd.DataFrame(np.arange(12.).reshape((4, 3)), columns=list('bde'),
                                index=['Utah', 'Ohio', 'Texas', 'Oregon'])
```

```
In [186]: series = frame.iloc[0]
```

```
In [187]: frame
```

```
Out[187]:
```

	b	d	e
Utah	0.0	1.0	2.0
Ohio	3.0	4.0	5.0
Texas	6.0	7.0	8.0
Oregon	9.0	10.0	11.0

```
In [188]: series
```

```
Out[188]: b    0.0
           d    1.0
           e    2.0
           Name: Utah, dtype: float64
```

```
In [189]: frame - series
```

```
Out[189]:
```

	<b>b</b>	<b>d</b>	<b>e</b>
<b>Utah</b>	0.0	0.0	0.0
<b>Ohio</b>	3.0	3.0	3.0
<b>Texas</b>	6.0	6.0	6.0
<b>Oregon</b>	9.0	9.0	9.0

If an index value is not found in either the DataFrame's columns or the Series's index, the objects will be reindexed to form the union:

```
In [193]: series2 = pd.Series(range(3), index=['b', 'e', 'f'])
```

```
In [194]: frame
```

```
Out[194]:
```

	<b>b</b>	<b>d</b>	<b>e</b>
<b>Utah</b>	0.0	1.0	2.0
<b>Ohio</b>	3.0	4.0	5.0
<b>Texas</b>	6.0	7.0	8.0
<b>Oregon</b>	9.0	10.0	11.0

```
In [195]: series2
```

```
Out[195]: b      0
          e      1
          f      2
          dtype: int64
```

```
In [177]: frame + series2
```

```
Out[177]:
```

	<b>b</b>	<b>d</b>	<b>e</b>	<b>f</b>
<b>Utah</b>	0.0	NaN	3.0	NaN
<b>Ohio</b>	3.0	NaN	6.0	NaN
<b>Texas</b>	6.0	NaN	9.0	NaN
<b>Oregon</b>	9.0	NaN	12.0	NaN

If you want to instead broadcast over the columns, matching on the rows, you have to use one of the arithmetic methods. For example:

```
In [196]: series3 = frame['d']
```

```
In [197]: frame
```

```
Out[197]:
```

	<b>b</b>	<b>d</b>	<b>e</b>
<b>Utah</b>	0.0	1.0	2.0
<b>Ohio</b>	3.0	4.0	5.0
<b>Texas</b>	6.0	7.0	8.0
<b>Oregon</b>	9.0	10.0	11.0

```
In [198]: series3
```

```
Out[198]: Utah      1.0  
Ohio      4.0  
Texas     7.0  
Oregon    10.0  
Name: d, dtype: float64
```

```
In [199]: frame.sub(series3, axis='index')
```

```
Out[199]:
```

	<b>b</b>	<b>d</b>	<b>e</b>
<b>Utah</b>	-1.0	0.0	1.0
<b>Ohio</b>	-1.0	0.0	1.0
<b>Texas</b>	-1.0	0.0	1.0
<b>Oregon</b>	-1.0	0.0	1.0

## Function Application and Mapping

NumPy ufuncs (element-wise array methods) also work with pandas objects:

```
In [200]: frame = pd.DataFrame(np.random.randn(4, 3), columns=list('bde'),  
                               index=['Utah', 'Ohio', 'Texas', 'Oregon'])
```

```
In [201]: frame
```

```
Out[201]:
```

	<b>b</b>	<b>d</b>	<b>e</b>
<b>Utah</b>	-1.153553	-2.476836	0.490014
<b>Ohio</b>	0.143545	1.054801	-0.372301
<b>Texas</b>	0.143501	1.299873	-0.655373
<b>Oregon</b>	-0.222918	-0.488328	1.177951

```
In [202]: np.abs(frame)
```

```
Out[202]:
```

	b	d	e
Utah	1.153553	2.476836	0.490014
Ohio	0.143545	1.054801	0.372301
Texas	0.143501	1.299873	0.655373
Oregon	0.222918	0.488328	1.177951

Another frequent operation is applying a function on one-dimensional arrays to each column or row. DataFrame's **apply** method does exactly this:

```
In [203]: f = lambda x: x.max() - x.min()
```

```
In [204]: frame.apply(f)
```

```
Out[204]: b      1.297098
          d      3.776709
          e      1.833324
          dtype: float64
```

Here the function `f`, which computes the difference between the maximum and minimum of a Series, is invoked once on each column in frame. The result is a Series having the columns of frame as its index.

If you pass `axis='columns'` to `apply`, the function will be invoked once per row instead:

```
In [205]: frame.apply(f, axis='columns')
```

```
Out[205]: Utah      2.966850
          Ohio      1.427102
          Texas      1.955245
          Oregon     1.666279
          dtype: float64
```

Many of the most common array statistics (like **sum** and **mean**) are DataFrame methods, so using `apply` is not necessary.

Element-wise Python functions can be used, too. Suppose you wanted to compute a formatted string from each floating-point value in frame. You can do this with **applymap**:

```
In [206]: format = lambda x: '%.2f' % x
```

```
In [207]: frame.applymap(format)
```

```
Out[207]:
```

	b	d	e
Utah	-1.15	-2.48	0.49
Ohio	0.14	1.05	-0.37
Texas	0.14	1.30	-0.66
Oregon	-0.22	-0.49	1.18

The reason for the name **applymap** is that Series has a **map** method for applying an element-wise function:

```
In [208]: frame['e'].map(format)
```

```
Out[208]: Utah      0.49
Ohio      -0.37
Texas     -0.66
Oregon     1.18
Name: e, dtype: object
```

## Sorting and Ranking

To sort lexicographically by row or column index, use the *sort\_index* method, which returns a new, sorted object:

```
In [191]: obj = pd.Series(range(4), index=['d', 'a', 'b', 'c'])
```

```
In [192]: obj
```

```
Out[192]: d      0
a      1
b      2
c      3
dtype: int64
```

```
In [193]: obj.sort_index()
```

```
Out[193]: a      1
b      2
c      3
d      0
dtype: int64
```

```
In [209]: frame = pd.DataFrame(np.arange(8).reshape((2, 4)),
                                index=['three', 'one'],
                                columns=['d', 'a', 'b', 'c'])
```

```
In [210]: frame.sort_index()
```

```
Out[210]:
```

	d	a	b	c
one	4	5	6	7
three	0	1	2	3

```
In [211]: frame.sort_index(axis=1)
```

```
Out[211]:
```

	a	b	c	d
three	1	2	3	0
one	5	6	7	4

```
In [212]: frame.sort_index(axis=1, ascending=False)
```

```
Out[212]:
```

	d	c	b	a
three	0	3	2	1
one	4	7	6	5

To sort a Series by its values, use its **sort\_values** method:

```
In [213]: obj = pd.Series([4, 7, -3, 2])
```

```
In [214]: obj.sort_values()
```

```
Out[214]: 2    -3
          3     2
          0     4
          1     7
          dtype: int64
```

Any missing values are sorted to the end of the Series by default:

```
In [215]: obj = pd.Series([4, np.nan, 7, np.nan, -3, 2])
```

```
In [216]: obj.sort_values()
```

```
Out[216]: 4    -3.0
          5     2.0
          0     4.0
          2     7.0
          1    NaN
          3    NaN
          dtype: float64
```

When sorting a DataFrame, you can use the data in one or more columns as the sort keys. To do so, pass one or more column names to the **by** option of **sort\_values**:

```
In [217]: frame = pd.DataFrame({'b': [4, 7, -3, 2], 'a': [0, 1, 0, 1]})
```



```
In [218]: frame
```

```
Out[218]:
```

	a	b
0	0	4
1	1	7
2	0	-3
3	1	2

```
In [219]: frame.sort_values(by='b')
```

```
Out[219]:
```

	a	b
2	0	-3
3	1	2
0	0	4
1	1	7

```
In [220]: frame.sort_values(by=['a', 'b'])
```

```
Out[220]:
```

	a	b
2	0	-3
0	0	4
3	1	2
1	1	7

```
In [221]: frame.sort_values(by=['b', 'a'])
```

```
Out[221]:
```

	a	b
2	0	-3
3	1	2
0	0	4
1	1	7

Ranking assigns ranks from one through the number of valid data points in an array. The **rank** methods for Series and DataFrame are the place to look; by default rank breaks ties by assigning each group the mean rank (Equal values are assigned a rank that is the average of the ranks of those values):

```
In [222]: obj = pd.Series([7, -5, 7, 4, 2, 0, 4])
```

```
In [223]: obj.rank()
```

```
Out[223]: 0    6.5
          1    1.0
          2    6.5
          3    4.5
          4    3.0
          5    2.0
          6    4.5
          dtype: float64
```

DataFrame can compute ranks over the rows or the columns:

```
In [224]: frame = pd.DataFrame({'b': [4.3, 7, -3, 2], 'a': [0, 1, 0, 1], 'c': [-2, 5, 8, -2.5]})
```

```
In [225]: frame
```

```
Out[225]:
```

	a	b	c
0	0	4.3	-2.0
1	1	7.0	5.0
2	0	-3.0	8.0
3	1	2.0	-2.5

```
In [227]: frame.rank()
```

```
Out[227]:
```

	a	b	c
0	1.5	3.0	2.0
1	3.5	4.0	3.0
2	1.5	1.0	4.0
3	3.5	2.0	1.0

## Axis Indexes with Duplicate Labels

While many pandas functions (like `reindex`) require that the labels be unique, it's not mandatory. Let's consider a small Series with duplicate indices:

```
In [228]: obj = pd.Series(range(5), index=['a', 'a', 'b', 'b', 'c'])
```

```
In [229]: obj
```

```
Out[229]: a    0
          a    1
          b    2
          b    3
          c    4
          dtype: int64
```

The index's **is\_unique** property can tell you whether its labels are unique or not:

```
In [230]: obj.index.is_unique
```

```
Out[230]: False
```

Data selection is one of the main things that behaves differently with duplicates. Indexing a label with multiple entries returns a **Series**, while single entries return a scalar value:

```
In [231]: obj['a']
```

```
Out[231]: a    0
          a    1
          dtype: int64
```

```
In [232]: obj['c']
```

```
Out[232]: 4
```

The same logic extends to indexing rows in a **DataFrame**:

```
In [233]: df = pd.DataFrame(np.random.randn(4, 3), index=['a', 'a', 'b', 'b'])
```

```
In [234]: df
```

```
Out[234]:
```

	0	1	2
a	-0.952965	0.285869	-0.900695
a	-2.178218	-0.122389	-0.741050
b	-0.130731	-0.522613	-0.630387
b	-0.664129	1.190639	-0.983794

```
In [235]: df.loc['b']
```

```
Out[235]:
```

	0	1	2
b	-0.130731	-0.522613	-0.630387
b	-0.664129	1.190639	-0.983794

## Summarizing and Computing Descriptive Statistics

```
In [237]: df = pd.DataFrame([[1.4, np.nan], [7.1, -4.5],
                             [np.nan, np.nan], [0.75, -1.3]],
                             index=['a', 'b', 'c', 'd'],
                             columns=['one', 'two'])
```

```
In [238]: df
```

```
Out[238]:
```

	one	two
a	1.40	NaN
b	7.10	-4.5
c	NaN	NaN
d	0.75	-1.3

Calling `DataFrame`'s `sum` method returns a `Series` containing column sums:

```
In [239]: df.sum()
```

```
Out[239]: one      9.25  
         two     -5.80  
         dtype: float64
```

Passing `axis='columns'` or `axis=1` sums across the columns instead:

```
In [240]: df.sum(axis='columns')
```

```
Out[240]: a      1.40  
         b      2.60  
         c      0.00  
         d     -0.55  
         dtype: float64
```

NA values are excluded unless the entire slice (row or column in this case) is NA. This can be disabled with the **`skipna`** option:

```
In [241]: df.mean(axis='columns', skipna=False)
```

```
Out[241]: a      NaN  
         b      1.300  
         c      NaN  
         d     -0.275  
         dtype: float64
```

List of common options for each reduction method:

- `axis`: Axis to reduce over; 0 for `DataFrame`'s rows and 1 for columns
- `skipna`: Exclude missing values; True by default

Some methods, like **`idxmin`** and **`idxmax`**, return indirect statistics like the index value where the minimum or maximum values are attained:

```
In [225]: df.idxmax()
```

```
Out[225]: one      b  
         two      d  
         dtype: object
```

Another type of method is neither a reduction nor an accumulation. `describe` is one such example, producing multiple summary statistics in one shot:

```
In [242]: df.describe()
```

```
Out[242]:
```

	one	two
count	3.000000	2.000000
mean	3.083333	-2.900000
std	3.493685	2.262742
min	0.750000	-4.500000
25%	1.075000	-3.700000
50%	1.400000	-2.900000
75%	4.250000	-2.100000
max	7.100000	-1.300000

On non-numeric data, **`describe`** produces alternative summary statistics:

```
In [243]: obj = pd.Series(['a', 'a', 'b', 'c'] * 4)
```

```
In [244]: obj.describe()
```

```
Out[244]: count      16
           unique       3
           top         a
           freq         8
           dtype: object
```

*Table 5-8. Descriptive and summary statistics*

Method	Description
<code>count</code>	Number of non-NA values
<code>describe</code>	Compute set of summary statistics for Series or each DataFrame column
<code>min, max</code>	Compute minimum and maximum values
<code>argmin, argmax</code>	Compute index locations (integers) at which minimum or maximum value obtained, respectively
<code>idxmin, idxmax</code>	Compute index labels at which minimum or maximum value obtained, respectively
<code>quantile</code>	Compute sample quantile ranging from 0 to 1
<code>sum</code>	Sum of values
<code>mean</code>	Mean of values
<code>median</code>	Arithmetic median (50% quantile) of values
<code>mad</code>	Mean absolute deviation from mean value
<code>prod</code>	Product of all values
<code>var</code>	Sample variance of values
<code>std</code>	Sample standard deviation of values
<code>skew</code>	Sample skewness (third moment) of values
<code>kurt</code>	Sample kurtosis (fourth moment) of values
<code>cumsum</code>	Cumulative sum of values
<code>cummin, cummax</code>	Cumulative minimum or maximum of values, respectively
<code>cumprod</code>	Cumulative product of values
<code>diff</code>	Compute first arithmetic difference (useful for time series)
<code>pct_change</code>	Compute percent changes

## Unique Values, Value Counts, and Membership

**unique** which gives you an array of the unique values in a Series:

```
In [245]: obj = pd.Series(['c', 'a', 'd', 'a', 'a', 'b', 'b', 'c', 'c'])
```

```
In [246]: uniques = obj.unique()
```

```
In [247]: uniques
```

```
Out[247]: array(['c', 'a', 'd', 'b'], dtype=object)
```

**value\_counts** computes a Series containing value frequencies:

```
In [248]: obj.value_counts()
```

```
Out[248]: c      3
          a      3
          b      2
          d      1
          dtype: int64
```

**value\_counts** is also available as a top-level pandas method that can be used with any array or sequence:

```
In [249]: pd.value_counts(obj.values, sort=False)
```

```
Out[249]: b      2
          a      3
          c      3
          d      1
          dtype: int64
```

**isin** performs a vectorized set membership check and can be useful in filtering a dataset down to a subset of values in a Series or column in a DataFrame:

```
In [250]: obj
```

```
Out[250]: 0      c
          1      a
          2      d
          3      a
          4      a
          5      b
          6      b
          7      c
          8      c
          dtype: object
```

```
In [251]: mask = obj.isin(['b', 'c'])
```

```
In [252]: mask
```

```
Out[252]: 0      True
          1     False
          2     False
          3     False
          4     False
          5      True
          6      True
          7      True
          8      True
          dtype: bool
```

```
In [253]: obj[mask]
```

```
Out[253]: 0      c
          5      b
          6      b
          7      c
          8      c
          dtype: object
```