

### Set 1: Installation

Which tool is commonly used to install CentOS or RHEL?

- a) apt-get
- b) yum
- c) pacman
- d) dpkg

Answer: b) yum

Which file contains the boot loader configuration in a standard RHEL installation?

- a) /etc/grub.conf
- b) /boot/grub2/grub.cfg
- c) /etc/fstab
- d) /etc/inittab

Answer: b) /boot/grub2/grub.cfg

What is the default installation directory for applications installed from RPM packages?

- a) /var
- b) /etc
- c) /usr/local
- d) /opt

Answer: c) /usr/local

Which command can be used to install software during the CentOS installation process?

- a) dnf
- b) yum install
- c) rpm -i
- d) kickstart

Answer: d) kickstart

### Set 2: Booting Process

Which file is used by the Linux kernel during the boot process to mount file systems?

- a) /etc/fstab
- b) /boot/grub/grub.conf
- c) /etc/inittab
- d) /etc/rc.local

Answer: a) /etc/fstab

Which of the following is the first process started by the Linux kernel at boot time?

- a) init
- b) systemd
- c) bash
- d) cron

Answer: b) systemd

What command is used to change the runlevel in CentOS/RHEL?

- a) init
- b) runlevel
- c) systemctl
- d) telinit

Answer: c) systemctl

In RHEL/CentOS, the bootloader used by default is called?

- a) LILO
- b) GRUB2
- c) syslinux
- d) Bootmgr

Answer: b) GRUB2

Set 3: Linux Usage Basics

Which command is used to display the current working directory?

- a) pwd
- b) whoami

c) ls

d) cd

Answer: a) pwd

How can you list hidden files in a directory using the ls command?

a) ls -a

b) ls -l

c) ls -h

d) ls -r

Answer: a) ls -a

What does the cd command do?

a) Changes the directory

b) Copies files

c) Creates a directory

d) Deletes files

Answer: a) Changes the directory

Which of the following commands displays a calendar?

a) cal

b) date

c) time

d) cat

Answer: a) cal

Set 4: Linux File System

Which of the following directories is used to store system-wide configuration files?

a) /bin

b) /etc

c) /usr

d) /var

Answer: b) /etc

What command is used to display the file system disk space usage?

- a) df
- b) du
- c) free
- d) fdisk

Answer: a) df

What is the default file system used in CentOS 7 and RHEL 7?

- a) ext3
- b) ext4
- c) xfs
- d) btrfs

Answer: c) xfs

Which command is used to check a file's type?

- a) file
- b) type
- c) stat
- d) check

Answer: a) file

#### Set 5: Package Management

Which of the following is the package manager used in RHEL 8?

- a) apt
- b) rpm
- c) yum
- d) dnf

Answer: d) dnf

What command is used to install a package using the rpm tool?

- a) rpm -i
- b) rpm -install
- c) rpm -add
- d) rpm --install

Answer: a) rpm -i

Which command lists all installed RPM packages?

- a) yum list installed
- b) rpm -qa
- c) dnf list installed
- d) apt list --installed

Answer: b) rpm -qa

How do you remove a package using yum?

- a) yum erase
- b) yum remove
- c) yum uninstall
- d) yum delete

Answer: b) yum remove

Set 6: Standard I / O Pipes

Which symbol is used to redirect output to a file in Linux?

- a) |
- b) &
- c) >
- d) #

Answer: c) >

How can you redirect the output of one command to the input of another?

- a) Using the pipe |

- b) Using >
- c) Using &
- d) Using #

Answer: a) Using the pipe |

What is the purpose of the tee command?

- a) Redirect input to a file
- b) Split output to both a file and display
- c) Append to a file
- d) Concatenate two files

Answer: b) Split output to both a file and display

Which command concatenates files and outputs to the standard output?

- a) cat
- b) tee
- c) more
- d) tail

Answer: a) cat

#### Set 7: Basic System Configuration Tools

Which tool is commonly used to manage services in RHEL 7 and later?

- a) chkconfig
- b) systemctl
- c) service
- d) init

Answer: b) systemctl

What is the main configuration file for the network in CentOS/RHEL?

- a) /etc/sysconfig/network-scripts/ifcfg-\*
- b) /etc/hosts
- c) /etc/resolv.conf

d) /etc/network/interfaces

Answer: a) /etc/sysconfig/network-scripts/ifcfg-\*

Which command shows the current IP address of your machine?

a) ip addr

b) ifconfig

c) netstat

d) hostname

Answer: a) ip addr

How can you restart the network service on CentOS/RHEL 8?

a) systemctl restart network

b) service network restart

c) systemctl restart NetworkManager

d) networkctl restart

Answer: c) systemctl restart NetworkManager

Set 8: Essential System Administration Tools

Which command is used to check the disk usage of a directory?

a) du

b) df

c) lsblk

d) blkid

Answer: a) du

What is the command to monitor real-time system processes?

a) top

b) ps

c) kill

d) htop

Answer: a) top

How can you list all running processes on a system?

- a) ps -ef
- b) top
- c) htop
- d) free

Answer: a) ps -ef

Which tool provides a dynamic, real-time view of running processes?

- a) top
- b) vmstat
- c) sar
- d) uptime

Answer: a) top

#### Set 9: Network Clients

Which of the following commands is used to check network connectivity by sending ICMP requests?

- a) ping
- b) netstat
- c) traceroute
- d) telnet

Answer: a) ping

How can you resolve a domain name to an IP address?

- a) nslookup
- b) ping
- c) traceroute
- d) wget

Answer: a) nslookup

Which command is used to transfer files via FTP?



- a) ftp
- b) scp
- c) rsync
- d) wget

Answer: a) ftp

Which file contains the list of DNS servers on a Linux system?

- a) /etc/resolv.conf
- b) /etc/hosts
- c) /etc/hostname
- d) /etc/network/interfaces

Answer: a) /etc/resolv.conf

Set 10: Network Configuration

Which command is used to display active network connections?

- a) netstat
- b) iptables
- c) ip addr
- d) dig

Answer: a) netstat

How can you bring up a network interface in RHEL/CentOS?

- a) ifup
- b) ifconfig
- c) ip addr
- d) systemctl start network

Answer: a) ifup

What is the purpose of /etc/hosts?

- a) Maps IP addresses to hostnames
- b) Resolves domain names

c) Stores network interface configurations

d) Configures the firewall

Answer: a) Maps IP addresses to hostnames

Which command can be used to trace the route packets take to a destination?

a) traceroute

b) ping

c) netstat

d) nslookup

Answer: a) traceroute