## 《保姆级教程》第四集 简单的库存扣减功能开 发

#### 1.创建 SeckillOverSellService 类



# 2. 添加@Service注解 & 注入 SeckillActivityDao 对象 & 简单的库存扣减方法


```
| Die Leit Yew Bewigne Code Analyze Befactor Build Run Took VCS Window Belp sexbill day2 beckilled by the main jume) com jumbumg ) Ease colling to the project of the proj
```

```
@Autowired
private SeckillActivityDao seckillActivityDao;

public String processSeckill(long activityId) {
    SeckillActivity seckillActivity =
    seckillActivityDao.querySeckillActivityById(activityId);
    long availableStock = seckillActivity.getAvailableStock();
    String result;
    if (availableStock > 0) {
```

```
result = "恭喜,抢购成功";
System.out.println(result);
availableStock = availableStock - 1;
seckillActivity.setAvailableStock(new Integer("" + availableStock));
seckillActivityDao.updateSeckillActivity(seckillActivity);
} else {
    result = "抱歉,抢购失败,商品被抢完了";
    System.out.println(result);
}
return result;
}
```

### 3. web 下面创建 SeckillOverSellController 类 & 添加 @Controller 注解



# 4. 注入 SeckillOverSellService 对象 & 添加处理抢购请求的处理方法

```
| Figure | Second | Controller | Controller
```

```
@Autowired
private SeckilloverSellService seckilloverSellService;

/**


* 简单 处理抢购请求

* @param seckillActivityId


* @return

*/
@ResponseBody
@RequestMapping("/seckill/{seckillActivityId}")
public String seckil(@PathVariable long seckillActivityId){
    return seckillOverSellService.processSeckill(seckillActivityId);
}
```


#### 5. 设置活动的可用库存




#### 6. 进入启动类, 点击 "绿色箭头" 启动项目




#### 7.清除控制台信息




8.进入 jmeter 安装目录的 bin 下,双击 jmeter.bat 启动 jmeter




### 9. 设置 jmeter 参数





#### 10. 点击 "绿色箭头" 进行测试



#### 11. 测试结果

