

CSE 238/2038/2138 Systems Programming
Project 1
Binary Data Converter
Due: 07.04.2022 11:59PM

The purpose of this assignment is to become more familiar with bit-level representations of integers and floating point numbers.

In this project, you will implement an application, in C or Java programming language; that takes

- a file containing numbers
- the byte ordering type (Little Endian or Big Endian),
- the data type to be converted, and
- the size of the floating point data type (the size of both signed and unsigned integers are 2 bytes),

as input and converts the contents of the file to hexadecimal according to the predefined format and gives the converted data as output.

The data type can be any of the following:

- signed integer
- unsigned integer
- floating point number

The size of the data type can be 1, 2, 3 or 4 bytes

- The signed integers are written as normal integers in the file (e.g., 3, -5, etc.).
 - The unsigned integers are written as integers followed by the letter u (e.g., 3u, 5u, etc.).
 - The floating point numbers are written with a decimal point (e.g., 3.0, -5.987, etc.).
- If the read data type is signed integer, your program will convert the numbers in the input file using 2's complement representation.
- If the read data type is unsigned integer, numbers will be converted using unsigned integer representation.
- If the read data type is floating point number, you will use IEEE-like format. The number of exponent bits according to given data size will be like the following:
 - o if 1 byte (i.e., 8 bits), 3 bits will be used for exponent part
 - o if 2 bytes (i.e., 16 bits), 8 bits will be used for exponent part
 - o if 3 bytes (i.e., 24 bits), 10 bits will be used for exponent part
 - o if 4 bytes (i.e., 32 bits), 12 bits will be used for exponent part
 - o While calculating the mantissa to get the floating point value, you will only use the first 13 bits of the fraction part. You will use "round to even" method for rounding fraction bits to 13 bits.

Details about the program are listed below:

- At the beginning of the execution, your program will prompt for the input file.

- The format of the input file will be like the following:
 - In the input file, each line will include a single number.

Example: input.txt

```
29.109375
4u
-9
6u
0
-63.0
```

- After a valid input file is taken as input, the user will be prompted for the byte ordering type and size:

Example:

```
Byte ordering: l
Floating point size: 2
```

- You program will calculate the hexadecimal value of the file content with the given information:

Example:

The byte ordering is Little Endian, and the floating point is 2 byte.

- First, your program will read the first number of the file. For our "input.txt" the first number is: **29.109375**
- This is a floating point number.

$$29.109375 = 11101.000111 = 1.1101000111 * 2^4$$
- Mantissa is **1.1101000111**. However, for 2 bytes we have 7 bits of fraction part, so we need to round it. **1.1101000111** \approx **1.1101001**. The fraction part is **1101001**.
- E = 4. Exponent is E = exp - Bias, where Bias = $2^{8-1} - 1 = 127$. Therefore the equation is 4 = exp - 127. exp = 131 which is **1000011**.
- The number is positive, so the sign bit is 0.
- The number at total is **010000011101001** which is **0x41E9** in hexadecimal.
- Byte ordering is little endian, so the float point is represented as **E9 41**. So the first line of the output line has to be **E9 41**.

Example 2:

- If the program reads the following number:
4u
- This is an unsigned integer. Unsigned integers are 2 bytes:
4 = 0000000000000100
- 0000000000000100** is **0x004** in hexadecimal.
- The byte ordering is little endian, so the unsigned integer will be represented as **00 04**.

- You cannot use library functions for the binary to decimal conversions.

This is a group project. You will submit the source code of your program using the Canvas service. The file name should include your names and surname, e.g., *betuldemirozboz_fatmacorutergin_lokmanaltin_zuhalaltuntas.c*. If you submit multiple files in a zip file, you need to name both zip file and the file containing your main function/method like this.

(*betuldemirozboz_fatmacorutergin_lokmanaltin_zuhalaltuntas.zip* file containing multiple files one of which has the name *betuldemirozboz_fatmacorutergin_lokmanaltin_zuhalaltuntas.c*)

Keep in mind that the due date will not be extended. So, please start early.

IMPORTANT

- The project will be done in groups of 4 people. (Mandatory!)
- Your project will be graded with an auto grader. Here are the rules you should follow for the auto grader to correctly grade your programs:
 - The name of the output file is always output.txt.
 - The format of the input and output files are exactly given above. (No redundant spaces and newlines! Write **AB CD**, not **ab cd** nor **abcd**.)
 - The inputs should be taken in the order: inputFileName, byteOrderig (l or b), size
 - You should not put any spaces in the name of your program or zip file.
 - You should not use Turkish characters anywhere. (Inside programs or as filenames)
 - When extracted, make sure that your program files are directly under the extracted directory. (the extracted directory should not contain any subdirectory)
 - If your program does not follow these rules, it cannot be graded.
- Project from previous years will get 0 grade!