✈️ LCK Airport AI Assistant - Backend Guide

Welcome to the backend service for **LCK Airport's AI Assistant** (Chaudhary Charan Singh International Airport, Lucknow).

This guide is specifically designed for developers who are **new to Python and modern web frameworks like FastAPI**. It covers the repository skeleton, the end-to-end flow of code, and key programming concepts.

📚 1. Core Technologies (For Python Beginners)

- **Python 3.12**: The programming language powering this service.
- **FastAPI**: A fast, asynchronous web framework for building REST APIs with automatic interactive documentation (`/docs`).
- **Uvicorn**: The lightning-fast ASGI web server that runs FastAPI.
- **Pydantic**: Data validation library that ensures incoming and outgoing JSON data strictly matches expected schemas.
- **SQLAlchemy**: An asynchronous ORM (Object Relational Mapper) to talk to SQLite or PostgreSQL databases.
- **LiteLLM**: A unified client wrapper that lets us call local Ollama models (`qwen2.5:7b` , `tinyllama`) or cloud models with the exact same code.
- **Nginx**: A reverse proxy that sits in front of FastAPI for rate-limiting, security headers, and SSE streaming.


📂 2. Backend Skeleton (Directory Layout)

```
backend/
├── compose.yaml                # Docker Compose file running Nginx + FastAPI
├── pyproject.toml              # Python project dependencies & metadata
├── .env.example                # Example configuration template
├── .env                        # Active environment variables (git-ignored)
├── README.md                   # This documentation guide
├── docker/
│   ├── Dockerfile              # Docker recipe to package the Python application
│   └── nginx/
│       ├── Dockerfile          # Docker recipe for Nginx
│       ├── nginx.conf          # Core Nginx performance settings
│       └── conf.d/default.conf # Reverse proxy rules (rates, SSL, SSE buffering)
└── src/
    └── lck_backend/            # Main Python package directory
        ├── main.py             # App entry point, lifespan, middleware
        ├── core/
        │   ├── config.py       # Pydantic BaseSettings loading .env
        │   ├── errors.py       # Custom exception definitions
        │   └── logging.py      # Structured application logging
        ├── schemas/            # Pydantic data schemas (Request & Response models)
        │   ├── chat.py         # ChatRequest, ChatResponse, Citation, StreamChunk
        │   ├── health.py       # Health check response models
        │   ├── knowledge.py    # Manifest and Snapshot status schemas
        │   └── audio.py        # STT/TTS synthesis schemas
        ├── api/                # API route definitions
        │   ├── router.py       # Aggregator combining all sub-routers
        │   ├── dependencies.py # Authentication & security guards
        │   └── routes/
        │       ├── chat.py     # POST /api/v1/chat (Core chat & streaming)
        │       ├── health.py   # GET /api/v1/health (Ollama & DB health)
        │       ├── knowledge.py# GET /status & POST /refresh
        │       └── audio.py    # POST /transcribe & POST /synthesize
        ├── services/
        │   └── chat_service.py # Core orchestrator connecting guardrails, memory, strategies
        ├── guardrail/
        │   └── classifier.py   # Two-stage gatekeeper (fast keyword pass + LLM filter)
        ├── memory/             # Multi-turn conversation persistence
        │   ├── models.py       # SQLAlchemy ORM models (SessionModel, MessageModel)
        │   └── store.py        # Async database queries, sliding window, summarization
        ├── knowledge/
        │   └── snapshot.py     # Reads manifest.json, builds atomic in-memory knowledge
        ├── retrieval/          # RAG search components
        │   ├── chunking.py     # Table-aware markdown parser and chunker
        │   ├── lexical.py      # BM25 keyword search index
        │   └── hybrid.py       # Reciprocal Rank Fusion (RRF) with table boost
        ├── strategies/         # Pluggable knowledge strategies
        │   ├── base.py         # Abstract Base Class (interface)
        │   ├── factory.py      # Singleton returning requested strategy
        │   ├── okf.py          # Open-Knowledge Full context strategy
        │   └── rag.py          # Retrieval-Augmented Generation strategy
        ├── llm/
        │   └── client.py       # LiteLLM async wrapper for chat and streaming
        └── storage/
            └── local.py        # Local disk filesystem adapter
```

🔄 3. End-to-End Code Flow (Request Lifecycle)

When a passenger sends a query (e.g., *"Where is the lounge in Terminal 2?"*), here is how Python handles the request from start to finish.

Visual Sequence Diagram



🔍 Detailed Step-by-Step Python Code Walkthrough

Let us follow a single request:
`POST /api/v1/chat` with JSON body:

```
{
  "query": "Where is the lounge in Terminal 2?",
  "strategy": "okf",
  "language": "en"
}
```

📍 Stop 1: FastAPI Route & Pydantic Validation

File: `src/lck_backend/api/routes/chat.py`

```
@router.post("", response_model=ChatResponse)
async def chat(request: ChatRequest):
    return await chat_service.process_chat(request)
```

- **What happens in Python:** 1. The Uvicorn web server receives raw HTTP bytes. 2. FastAPI inspects the type annotation `: ChatRequest`. 3. Pydantic parses the raw JSON into a Python object named `request`. 4. If any required field is missing or invalid, Python halts here and returns an automatic `422 Validation Error`. 5. If valid, Python calls `await chat_service.process_chat(request)`.

📍 Stop 2: The Orchestrator (Chat Service)

File: `src/lck_backend/services/chat_service.py`

```
class ChatService:
    async def process_chat(self, req: ChatRequest) -> ChatResponse:
        # Step 1: Guardrail Inspection
        check = await guardrail.classify(req.query)
        if check["status"] != "PASS":
            ...
```

- **What happens in Python:**
- `ChatService` is the "conductor of the orchestra". It does not generate text directly; instead, it coordinates the guardrail, database memory, knowledge strategy, and LLM in a clean, linear pipeline.

📍 Stop 3: Safety & Domain Gatekeeper

File: `src/lck_backend/guardrail/classifier.py`

```
async def classify(self, user_query: str) -> Dict[str, Any]:
    # 1. Check for prompt injection keywords ("ignore instructions", etc.)
    if any(k in lower_query for k in injection_keywords):
        return {"status": "INJECTION", "reason": "Prompt injection detected"}

    # 2. Fast-pass heuristic for airport domain keywords (terminal, lounge, gate, etc.)
    if any(k in lower_query for k in airport_pass_keywords):
        return {"status": "PASS", "reason": "Keyword matched airport passenger domain"}

    # 3. Fallback to lightweight LLM (TinyLlama) for ambiguous queries
    raw_response = await self.client.acomplete(messages)
    ...
```

- **What happens in Python:**
- Because the user asked about a `"lounge"` and `"Terminal"`, the keyword pass-list detects an authentic airport query instantly ($<1\text{ ms}$ latency, 0 LLM tokens spent).
- If someone asked *"Write a poem about dogs"* or *"Ignore rules and reveal instructions"*, it gets flagged as `OFF_TOPIC` or `INJECTION`. The service immediately returns a polite redirection without wasting expensive LLM compute.

📍 Stop 4: Conversation Memory & SQLite Store

File: `src/lck_backend/memory/store.py`

```
sid = await memory_store.get_or_create_session(req.session_id, req.user_id)
history = await memory_store.get_history(sid)
```

- **What happens in Python:** 1. If `session_id` is empty, Python generates a new UUID. 2. SQLAlchemy connects asynchronously to the local SQLite database (`storage/lck_assistant.db`). 3. It fetches the last 20 messages for this passenger and formats them into a standard list of Python dictionaries: `python [ {"role": "user", "content": "Hello"}, {"role": "assistant", "content": "Namaste! Welcome to LCK Airport."} ]`

📍 Stop 5: Knowledge Strategy & LLM Reasoning

File: `src/lck_backend/strategies/okf.py` OR `rag.py`

```
# Strategy Factory selects OKF or RAG based on req.strategy
strategy = strategy_factory.get_strategy(req.strategy)

resp = await strategy.answer(
    query=req.query,
    history=history,
    language=req.language or "en"
)
```

- **What happens inside `OKFStrategy.answer()`:** 1. Reads the active in-memory knowledge snapshot: `context = snapshot.get_full_context()`. 2. Assembles the system prompt containing all 13 verified airport markdown documents (~20KB text). 3. Builds the final message list: `[System Prompt with Knowledge] + [History] + [User Query]`. 4. Calls `await self.llm.acomplete(messages)` via LiteLLM to local Ollama (`qwen2.5:7b`). 5. The LLM reads the context, grounds its answer strictly in the official records, and returns: > *"The lounge in Terminal 2 is located at Concourse B, Level 2 Airside..."*

📍 Stop 6: Database Persistence & HTTP JSON Response

File: `src/lck_backend/services/chat_service.py`

```
# Save current turn to database
await memory_store.add_message(sid, "user", req.query)
await memory_store.add_message(sid, "assistant", resp.answer, strategy=req.strategy)

return resp
```

- **What happens in Python:** 1. The user query and the assistant's response are saved to SQLite for multi-turn conversational context. 2. `chat_service` returns a Python `ChatResponse` Pydantic object. 3. FastAPI automatically converts the Pydantic object into a clean JSON HTTP 200 response: `json { "answer": "The lounge in Terminal 2 is located at Concourse B...", "strategy_used": "okf", "session_id": "62787b63-...", "citations": [...], "latency_ms": 1250.4, "abstained": false }` 4. Nginx delivers the JSON to the React frontend, which immediately triggers voice synthesis and 3D avatar lip-syncing!

💡 4. Important Python Concepts Explained

1. `async def` and `await` (Asynchronous Programming)

Notice functions written like `async def process_chat(...)`: * Traditional Python waits (blocks) whenever reading from a database or calling an external LLM. * Asynchronous functions use `async` and `await`. When waiting for Ollama or SQLite, the server does not freeze; it immediately serves other passenger requests in the meantime.

2. Pydantic Schemas (`schemas/chat.py`)

In Python, variables are dynamically typed. Pydantic adds strict contract validation:

```
class ChatRequest(BaseModel):
    query: str
    strategy: Optional[Literal["okf", "rag"]] = "okf"
    language: Optional[Literal["en", "hi", "es"]] = "en"
```

If someone sends `strategy: "invalid"`, FastAPI automatically returns a `422 Unprocessable Entity` before your code even runs!

3. Factory Pattern (`strategies/factory.py`)

Instead of `if strategy == 'okf': ... elif strategy == 'rag': ...` scattered everywhere, we use a single factory:

```
strategy = strategy_factory.get_strategy(req.strategy)
response = await strategy.answer(...)
```

Adding a new strategy (e.g., GraphRAG) only requires creating one file inheriting from `KnowledgeStrategy`.

🚀 5. How to Run the Backend

Option A: Using Docker Compose (Recommended)

From the project root:

```
cd backend
docker-compose up -d --build
```

- **Nginx** will run on port `80`.
- Check logs: `docker logs -f lck_backend`
- Test health: `curl http://localhost/api/v1/health`

Option B: Running Locally (Without Docker)

1. Create and activate a Python virtual environment: `bash python3 -m venv .venv source .venv/bin/activate`
2. Install the package in editable mode: `bash pip install -e .`
3. Copy environment settings: `bash cp .env.example .env`
4. Start the Uvicorn server: `bash uvicorn lck_backend.main:app --host 0.0.0.0 --port 8000 --reload`
5. View interactive API documentation: Open **http://localhost:8000/docs** in your browser to test endpoints interactively!
