

DELIVERABLE 1.2

Atomic Design System Manual

Pangasinan Heritage Digital Showcase

Implementation-aligned component and interface guide

Updated for the current Next.js application

System at a glance

This manual reflects the current code in **source-code/src**. The application presents Pangasinan destinations through a responsive, image-led interface with four public routes: Home, Heritage Sites, Plan a Visit, and About. The design system follows Atomic Design where practical, while page-specific visual compositions remain close to their routes.

Layer	Implemented units	Purpose
Atoms	ColorTokens, Typography, Button, Icon, Image	Reusable visual primitives and media behavior.
Molecules	NavigationItem, SearchForm, HeritageCard	Small, task-focused compositions.
Organisms	HeaderNavigation, HeritageGallery, HeritageGrid, DestinationHighlights, TipCard, DestinationDetailModal	Feature-level interface areas.
Routes	/, /sites, /plan-a-visit, /about, /style-guide	Editorial layouts that compose organisms and page-local content.

The live **/style-guide** route remains the component reference. It documents the original Atomic set and can be used alongside this manual when reviewing visual primitives.

Implemented interaction model

Feature	Current behavior	Accessibility / responsive note
Primary navigation	Route-aware links, sticky header or hero overlay; mobile panel opens from a labelled menu button.	aria-current, aria-expanded, and aria-controls are supplied; desktop navigation begins at md.
Search	Ranks matching destinations by name, municipality, keywords, and description; selecting a result opens the destination dialog.	Visible screen-reader label, clear control, Escape handling, and click-outside closure.
Gallery	Searches and filters all four destinations by category, with responsive masonry-style columns.	Search clear affordance and no-results state are present.
Destination dialog	Provides image, municipality, description, and close action from header search.	role=dialog, aria-modal, labelled title, Escape close, initial close-button focus, and scroll lock.

Color, typography, and responsive rules

The visual language is coastal and heritage-led: deep sea surfaces create contrast, sand supports long-form reading, coral carries high-value actions, and moss marks supporting location or ecological context.

Token	Value	Implemented use
sea / sea-900	#0F3D3E / #081F1F	Hero overlays, navigation, dark panels, heading text.
sand-100 / sand	#FAF7F0 / #E8DFC8	Page ground and light surfaces.
coral / coral-600	#E4572E / #C94620	Primary calls to action, focus outline, active emphasis.
moss / moss-700	#4C7A5E / #3A5F49	Location metadata and secondary emphasis.
ink	#16231F	Body copy and low-level contrast.
warm gold	#F3B75C	Hero labels and dark-surface actions.

Type roles

Role	Family	Where used
Display	Fraunces	Hero statements, editorial page headings, feature titles.
Sans	Public Sans	Body copy, controls, metadata, navigation.
Mono	IBM Plex Mono	Eyebrows and compact all-caps labels.

Fonts are loaded in the root layout through next/font/google and assigned as CSS variables. Tailwind maps them to font-display, font-sans, and font-mono.

Responsive contract

Breakpoint	Layout behavior
Base / mobile	Single-column stacks, full-width search and compact hero padding. The mobile header has a labelled menu control.
sm (640px)	Larger type, two-column content where appropriate, horizontal action groups, and wider gutters.
md (768px)	Desktop primary navigation becomes visible; mobile navigation control is hidden.
lg (1024px)	Three- and four-column editorial grids, two-column feature panels, and desktop image sizing.
xl (1280px)	Header search is shown inline beside desktop navigation.

Reusable primitives

ColorTokens. A typed color map and swatch renderer provide the documented palette. Tailwind's matching theme extension is used throughout production pages.

Typography. Heading supports levels 1-4 with a mobile-first scale; Eyebrow applies compact monospaced uppercase labelling; Text provides sm, base, and lg body sizes with a muted treatment.

Button. Primary, secondary, and ghost variants use a rounded-pill form and disabled state. Global focus-visible styling supplies a coral 3px ring. Use page-specific Link buttons for route transitions and Button for in-place behavior.

Icon. The local icon atom exposes search, pin, menu, close, and chevron-right SVG paths. The application also uses lucide-react for the richer editorial icon set. Decorative icons are hidden from assistive technology; icon-only controls supply a label.

Image. A wrapper around next/image provides a required alt prop, aspect-ratio container, responsive sizes, and optional rounding. Route-level editorial images use next/image directly with similarly explicit alt and sizes values.

Representative implementation

Heading: text-3xl sm:text-4xl md:text-5xl leading-[1.1]

Image sizing: (min-width: 1024px) 33vw, (min-width: 640px) 50vw, 100vw

Global focus: outline: 3px solid #e4572e; outline-offset: 2px

Composed interactions

Molecule	Composition	Current implementation details
NavigationItem	Next Link + route state	Uses usePathname upstream to mark the active route. Active item receives a warm underline; inactive items animate a subtle underline.
SearchForm	Controlled search, destination data, dialog	Client component with ranked results, thumbnail previews, clear button, Esc and outside-click closure, and a selected DestinationDetailModal.
HeritageCard	Image + Typography + Icon + Button	Reusable vertical preview card. It remains available in the style guide; the About route currently uses the animated HeritageGrid card presentation.

Search ranking order

Priority	Match
1	Exact destination name
2	Destination name starts with query
3	Destination name contains query
4	Municipality contains query
5	Keywords contain query
6	Description contains query

The destination data source is `src/lib/heritage-sites.ts`. It holds four entries - Hundred Islands National Park, Cape Bolinao Lighthouse, Balungao Hot Spring & Adventure Park, and Urduja House - each with a slug, municipality, description, image, and searchable keywords.

Feature blocks, routes, and validation

Organism	Where it appears	Key behavior
HeaderNavigation	All public routes	Hero overlay or sticky sea header; responsive nav; XL inline search; mobile collapsible panel.
HeritageGallery	/sites	Client-side free-text search plus all/natural/cultural/other filters; 1/2/3 responsive columns and empty state.
HeritageGrid	/about and style guide	1, 2, then 3 columns; IntersectionObserver fades each card upward as it enters view.
DestinationHighlights	Home	Four responsive destination previews, 1/2/4 columns with image overlays.
TipCard	/plan-a-visit	Animated travel-guidance cards with image, contextual icon, and hover elevation.
DestinationDetailModal	Header search	Portal dialog with accessible name, Escape close, backdrop close, focus placement, and body scroll lock.

Page composition

Route	Primary content
/	Immersive hero, tourism reasons, planning feature, destination highlights, story section, CTA, and full footer.
/sites	Heritage hero, gallery search/filter controls, destination image cards, and compact footer.
/plan-a-visit	Travel hero, four guidance cards, essentials grid, and image-led CTA.
/about	Showcase purpose, feature points, animated selected-site grid, and compact footer.
/style-guide	Component reference for colors, type, buttons, icons, image wrapper, molecules, and organisms.

Validation summary

The current source was checked with **npm run build** and completed compilation plus type validation successfully under Next.js 14.2.35. The implementation is mobile-first, provides visible keyboard focus styling, includes responsive image sizes, and uses semantic headings and labelled interactions. Before production publication, perform device and screen-reader testing against the target deployment and real content.

Maintenance guidance

Add destinations in the shared data module before extending presentation components. Preserve token names and font roles when modifying themes. Keep interaction-heavy features as client components, but leave static layout and content as server components where possible. When a reusable route action is added, choose semantic Link for navigation and Button for in-place behavior.