

```

import csv
import sqlite3

def create_tables(cursor):
    cursor.execute("""
        CREATE TABLE IF NOT EXISTS shipping_data_0 (
            origin_warehouse TEXT,
            destination_store TEXT,
            product TEXT,
            on_time TEXT,
            product_quantity INTEGER,
            driver_identifier TEXT
        )
    """)

    cursor.execute("""
        CREATE TABLE IF NOT EXISTS shipping_data_1 (
            shipment_identifier TEXT,
            product TEXT,
            on_time TEXT,
            origin_warehouse TEXT,
            destination_store TEXT
        )
    """)

def insert_shipping_data_0(cursor):
    with open('data/shipping_data_0.csv', 'r') as file:
        csv_reader = csv.reader(file)
        next(csv_reader)
        for row in csv_reader:
            origin_warehouse, destination_store, product, on_time,
            product_quantity, driver_identifier = row
            cursor.execute("INSERT INTO shipping_data_0 (origin_warehouse,
            destination_store, product, on_time, product_quantity, driver_identifier) VALUES
            (?, ?, ?, ?, ?, ?)",
                           (origin_warehouse, destination_store, product,
            on_time, product_quantity, driver_identifier))

def insert_shipping_data_2(cursor):
    with open('data/shipping_data_2.csv', 'r') as file:
        csv_reader = csv.reader(file)
        next(csv_reader)
        shipping_data_2_rows = [row for row in csv_reader]

    with open('data/shipping_data_1.csv', 'r') as file:

```

```

        csv_reader = csv.reader(file)
        next(csv_reader)
        for row in csv_reader:
            shipment_idenfifier, product, on_time = row
            matching_rows = [r for r in shipping_data_2_rows if r[0] ==
shipment_idenfifier]
                if matching_rows:
                    origin_warehouse, destination_store, driver_idenfifier =
matching_rows[0][1], matching_rows[0][2], matching_rows[0][3]
                    cursor.execute("INSERT INTO shipping_data_1 (shipment_idenfifier,
product, on_time, origin_warehouse, destination_store) VALUES (?, ?, ?, ?, ?)",
                                (shipment_idenfifier, product, on_time,
origin_warehouse, destination_store))

if __name__ == "__main__":
    conn = sqlite3.connect('shipment_database.db')
    cursor = conn.cursor()

    create_tables(cursor) # Create the necessary tables

    insert_shipping_data_0(cursor)
    insert_shipping_data_2(cursor)

    conn.commit()
    conn.close()

```