queries.sql

```sql
CREATE TABLE Student (
    StudentName VARCHAR(50),
    Age INT,
    Course VARCHAR(30)
);

DELIMITER $$

CREATE PROCEDURE GetStudents()
BEGIN
    SELECT * FROM Student;
END $$

CREATE PROCEDURE InsertStudent(
    IN p_ID INT,
    IN p_Name VARCHAR(50),
    IN p_Age INT,
    IN p_Course VARCHAR(30)
)
BEGIN
    INSERT INTO Student
    VALUES (p_ID, p_Name, p_Age, p_Course);
END $$

CREATE PROCEDURE UpdateStudent(
    IN p_ID INT,
    IN p_Age INT
)
BEGIN
    UPDATE Student
    SET Age = p_Age
    WHERE StudentID = p_ID;
END $$

CREATE PROCEDURE DeleteStudent(
    IN p_ID INT
)
BEGIN
    DELETE FROM Student
    WHERE StudentID = p_ID;
END $$

DELIMITER ;

CALL InsertStudent(1, 'Rahul', 20, 'BCA');
CALL InsertStudent(2, 'Priya', 21, 'BSc');
```

I/O | AI Agent | 84 ms

STDIN

Input for the program (Optional)

Output:

```
+-----------+-------------+------+--------+
| StudentID | StudentName | Age  | Course |
+-----------+-------------+------+--------+
|         1 | Rahul       |   20 | BCA    |
|         2 | Priya       |   21 | BSc    |
+-----------+-------------+------+--------+
+-----------+-------------+------+--------+
| StudentID | StudentName | Age  | Course |
+-----------+-------------+------+--------+
|         1 | Rahul       |   22 | BCA    |
|         2 | Priya       |   21 | BSc    |
+-----------+-------------+------+--------+
+-----------+-------------+------+--------+
| StudentID | StudentName | Age  | Course |
+-----------+-------------+------+--------+
|         1 | Rahul       |   22 | BCA    |
+-----------+-------------+------+--------+
```