



Divide and Conquer




Divide-and-Conquer

The most-well known algorithm design strategy:

1. Divide instance of problem into two or more smaller instances
2. Solve smaller instances recursively
3. Obtain solution to original (larger) instance by combining these solutions



Divide-and-Conquer Technique (cont.)



Divide-and-Conquer Examples

- Sorting: mergesort and quicksort
- Binary tree traversals
- Binary search
- Multiplication of large integers
- Matrix multiplication: Strassen's algorithm
- Closest-pair and convex-hull algorithms



General Divide-and-Conquer Recurrence

$$T(n) = aT(n/b) + f(n) \quad \text{where } f(n) \in \Theta(n^d), \quad d \geq 0$$

Master Theorem:

- If $a < b^d$, $T(n) \in \Theta(n^d)$
- If $a = b^d$, $T(n) \in \Theta(n^d \log n)$
- If $a > b^d$, $T(n) \in \Theta(n^{\log_b a})$

Note: The same results hold with O instead of Θ .



Mergesort

- Split array $A[0..n-1]$ in two about equal halves and make copies of each half in arrays B and C
- Sort arrays B and C recursively
- Merge sorted arrays B and C into array A as follows:
 - Repeat the following until no elements remain in one of the arrays:
 - compare the first elements in the remaining unprocessed portions of the arrays
 - copy the smaller of the two into A, while incrementing the index indicating the unprocessed portion of that array
 - Once all elements in one of the arrays are processed, copy the remaining unprocessed elements from the other array into A.



Pseudocode of Mergesort

ALGORITHM *Mergesort*($A[0..n - 1]$)

//Sorts array $A[0..n - 1]$ by recursive mergesort

//Input: An array $A[0..n - 1]$ of orderable elements

//Output: Array $A[0..n - 1]$ sorted in nondecreasing order

if $n > 1$

copy $A[0..\lfloor n/2 \rfloor - 1]$ to $B[0..\lfloor n/2 \rfloor - 1]$

copy $A[\lfloor n/2 \rfloor..n - 1]$ to $C[0..\lceil n/2 \rceil - 1]$

Mergesort($B[0..\lfloor n/2 \rfloor - 1]$)

Mergesort($C[0..\lceil n/2 \rceil - 1]$)

Merge(B, C, A)



Pseudocode of Merge

ALGORITHM *Merge*($B[0..p-1]$, $C[0..q-1]$, $A[0..p+q-1]$)

//Merges two sorted arrays into one sorted array

//Input: Arrays $B[0..p-1]$ and $C[0..q-1]$ both sorted

//Output: Sorted array $A[0..p+q-1]$ of the elements of B and C

$i \leftarrow 0$; $j \leftarrow 0$; $k \leftarrow 0$

while $i < p$ **and** $j < q$ **do**

if $B[i] \leq C[j]$

$A[k] \leftarrow B[i]$; $i \leftarrow i + 1$

else $A[k] \leftarrow C[j]$; $j \leftarrow j + 1$

$k \leftarrow k + 1$


if $i = p$

 copy $C[j..q-1]$ to $A[k..p+q-1]$

else copy $B[i..p-1]$ to $A[k..p+q-1]$



Mergesort Example



Analysis of Mergesort

- All cases have same efficiency: $\Theta(n \log n)$
- Number of comparisons in the worst case is close to theoretical minimum for comparison-based sorting:


$$\lceil \log_2 n! \rceil \approx n \log_2 n - 1.44n$$

- Space requirement: $\Theta(n)$ (not in-place)
- Can be implemented without recursion (bottom-up)



Quicksort

- Select a *pivot* (partitioning element) – here, the first element
- Rearrange the list so that all the elements in the first s positions are smaller than or equal to the pivot and all the elements in the remaining $n-s$ positions are larger than or equal to the pivot (see next slide for an algorithm)



Exchange the pivot with the last element in the first (i.e., \leq) subarray — the pivot is now in its final position

- Sort the two subarrays recursively



Partitioning Algorithm

```
Algorithm Partition( $A[l..r]$ )
//Partitions a subarray by using its first element as a pivot
//Input: A subarray  $A[l..r]$  of  $A[0..n - 1]$ , defined by its left and right
//       indices  $l$  and  $r$  ( $l < r$ )
//Output: A partition of  $A[l..r]$ , with the split position returned as
//        this function's value
 $p \leftarrow A[l]$ 
 $i \leftarrow l; j \leftarrow r + 1$ 
repeat
    repeat  $i \leftarrow i + 1$  until  $A[i] \geq p$ 
    repeat  $j \leftarrow j - 1$  until  $A[j] < p$ 
    swap( $A[i], A[j]$ )
until  $i \geq j$ 
swap( $A[i], A[j]$ ) //undo last swap when  $i \geq j$ 
swap( $A[l], A[j]$ )
return  $j$ 
```



Quicksort Example

5 3 1 9 8 2 4 7



Analysis of Quicksort

- Best case: split in the middle — $\Theta(n \log n)$
- Worst case: sorted array! — $\Theta(n^2)$
- Average case: random arrays — $\Theta(n \log n)$
- Improvements:
 - better pivot selection: median of three partitioning
 - switch to insertion sort on small subfiles
 - elimination of recursionThese combine to 20-25% improvement
- Considered the method of choice for internal sorting of large files ($n \geq 10000$)

