




## Unit III

### Floyd's Algorithm



# Floyd's Algorithm: All pairs shortest paths


- **Problem:** In a weighted (di)graph, find shortest paths between every pair of vertices
- **Same idea:** construct solution through series of matrices  $D^{(0)}, \dots, D^{(n)}$  using increasing subsets of the vertices allowed as intermediate
- **Example:**




# Floyd's Algorithm (matrix generation)

- On the  $k$ -th iteration, the algorithm determines shortest paths between every pair of vertices  $i, j$  that use only vertices among  $1, \dots, k$  as intermediate

- $D^{(k)}[i,j] = \min \{D^{(k-1)}[i,j], D^{(k-1)}[i,k] + D^{(k-1)}[k,j]\}$



# Floyd's Algorithm (example)



$$D^{(0)} = \begin{bmatrix} 0 & \infty & 3 & \infty \\ 2 & 0 & \infty & \infty \\ \infty & 7 & 0 & 1 \\ 6 & \infty & \infty & 0 \end{bmatrix}$$

$$D^{(1)} = \begin{bmatrix} 0 & \infty & 3 & \infty \\ 2 & 0 & \mathbf{5} & \infty \\ \infty & 7 & 0 & 1 \\ 6 & \infty & \mathbf{9} & 0 \end{bmatrix}$$

$$D^{(2)} = \begin{bmatrix} 0 & \infty & 3 & \infty \\ 2 & 0 & 5 & \infty \\ \mathbf{9} & 7 & 0 & 1 \\ 6 & \infty & 9 & 0 \end{bmatrix}$$

$$D^{(3)} = \begin{bmatrix} 0 & \mathbf{10} & 3 & \mathbf{4} \\ 2 & 0 & 5 & \mathbf{6} \\ 9 & 7 & 0 & 1 \\ 6 & \mathbf{16} & 9 & 0 \end{bmatrix}$$

$$D^{(4)} = \begin{bmatrix} 0 & 10 & 3 & 4 \\ 2 & 0 & 5 & 6 \\ \mathbf{7} & 7 & 0 & 1 \\ 6 & 16 & 9 & 0 \end{bmatrix}$$

# Floyd's Algorithm (pseudocode and analysis)

**ALGORITHM** *Floyd*( $W[1..n, 1..n]$ )

//Implements Floyd's algorithm for the all-pairs shortest-paths problem

//Input: The weight matrix  $W$  of a graph with no negative-length cycle

//Output: The distance matrix of the shortest paths' lengths

$D \leftarrow W$  //is not necessary if  $W$  can be overwritten

**for**  $k \leftarrow 1$  **to**  $n$  **do**

---

**for**  $i \leftarrow 1$  **to**  $n$  **do**

**for**  $j \leftarrow 1$  **to**  $n$  **do**

$D[i, j] \leftarrow \min\{D[i, j], D[i, k] + D[k, j]\}$

**return**  $D$

**Time efficiency:**  $\Theta(n^3)$

**Space efficiency:** Matrices can be written over their predecessors

**Note:** Shortest paths themselves can be found, too

