

UIT2504 Artificial Intelligence

Markov Chain Simulations in Bayesian Networks

C. Aravindan
<AravindanC@ssn.edu.in>

Professor of Information Technology
SSN College of Engineering

November 07, 2024

- *Monte Carlo Markov Chain (MCMC) algorithms* randomly modify the current state to generate a random next state; the initial state is fixed randomly

- *Monte Carlo Markov Chain (MCMC) algorithms* randomly modify the current state to generate a random next state; the initial state is fixed randomly
- Note that there is no need to sample the variables in topological order

- *Monte Carlo Markov Chain (MCMC) algorithms* randomly modify the current state to generate a random next state; the initial state is fixed randomly
- Note that there is no need to sample the variables in topological order
- Further, sampling of a variable need not depend upon its parents alone

- *Monte Carlo Markov Chain (MCMC) algorithms* randomly modify the current state to generate a random next state; the initial state is fixed randomly
- Note that there is no need to sample the variables in topological order
- Further, sampling of a variable need not depend upon its parents alone
- Since evidence variables are fixed, the state space is formed by nonevidence variables only; that means, one of the nonevidence variables is randomly sampled to generate the next state


- *Monte Carlo Markov Chain (MCMC) algorithms* randomly modify the current state to generate a random next state; the initial state is fixed randomly
- Note that there is no need to sample the variables in topological order
- Further, sampling of a variable need not depend upon its parents alone
- Since evidence variables are fixed, the state space is formed by nonevidence variables only; that means, one of the nonevidence variables is randomly sampled to generate the next state
- In general, *Markov Chain* refers to a random process that generates a sequence of states

Markov Chain: Example

- In the sprinkler example, consider $Sprinkler = true$ and $WetGrass = true$ as evidences. A state space for Markov chain, where nonevidence variables $Cloudy$ and $Rain$ can be modified, is as shown below:

Markov Chain: Example

- In the sprinkler example, consider $Sprinkler = true$ and $WetGrass = true$ as evidences. A state space for Markov chain, where nonevidence variables $Cloudy$ and $Rain$ can be modified, is as shown below:



- Start with an arbitrary state (consistent with the evidence variables) and generate a next state by randomly sampling a value for one of the nonevidence variables X_i

Gibbs Sampling


- Start with an arbitrary state (consistent with the evidence variables) and generate a next state by randomly sampling a value for one of the nonevidence variables X_i
- Gibbs sampling for X_i means sampling conditioned on the current values of the variables in its Markov blanket

Gibbs Sampling

- Start with an arbitrary state (consistent with the evidence variables) and generate a next state by randomly sampling a value for one of the nonevidence variables X_i
- Gibbs sampling for X_i means sampling conditioned on the current values of the variables in its Markov blanket
- The algorithm wanders randomly around the state space flipping one variable at a time (but keeping the evidence variables fixed)


Gibbs Sampling: Example

- Consider the query $\mathbf{P}(R|s, w)$




Gibbs Sampling: Example

- Consider the query $\mathbf{P}(R|s, w)$
- Nonevidence variables C and R are randomly initialized to, say, *true* and *false*, giving the state $[true, \mathbf{true}, false, \mathbf{true}]$




Gibbs Sampling: Example



- Consider the query $\mathbf{P}(R|s, w)$
- Nonevidence variables C and R are randomly initialized to, say, *true* and *false*, giving the state [*true*, **true**, *false*, **true**]
- Choose a nonevidence variable randomly, say C . Markov blanket of C is S, R . So, sample from $\mathbf{P}(C|s, \neg r)$. Suppose we get *Cloudy* = *false*, the new state is [*false*, **true**, *false*, **true**]

Gibbs Sampling: Example



- Consider the query $\mathbf{P}(R|s, w)$
- Nonevidence variables C and R are randomly initialized to, say, *true* and *false*, giving the state $[true, \mathbf{true}, false, \mathbf{true}]$
- Choose a nonevidence variable randomly, say C . Markov blanket of C is S, R . So, sample from $\mathbf{P}(C|s, \neg r)$. Suppose we get *Cloudy* = *false*, the new state is $[false, \mathbf{true}, false, \mathbf{true}]$
- Suppose R is chosen next. Markov blanket of R is C, S, W . So, sample from $\mathbf{P}(R|\neg c, s, w)$. Suppose this yields *Rain* = *true*, the next state is

Gibbs Sampling Algorithm

function GIBBS-ASK(X, \mathbf{e}, bn, N) **returns** an estimate of $\mathbf{P}(X | \mathbf{e})$
 local variables: \mathbf{C} , a vector of counts for each value of X , initially zero
 \mathbf{Z} , the nonevidence variables in bn
 \mathbf{x} , the current state of the network, initialized from \mathbf{e}

 initialize \mathbf{x} with random values for the variables in \mathbf{Z}
 for $k = 1$ **to** N **do**
 choose any variable Z_i from \mathbf{Z} according to any distribution $\rho(i)$
 set the value of Z_i in \mathbf{x} by sampling from $\mathbf{P}(Z_i | mb(Z_i))$
 $\mathbf{C}[j] \leftarrow \mathbf{C}[j] + 1$ where x_j is the value of X in \mathbf{x}
 return NORMALIZE(\mathbf{C})

- How do we get the Markov blanket distribution, $\mathbf{P}(X_i|mb(X_i))$, of a nonevidence variable X_i ?

- How do we get the Markov blanket distribution, $\mathbf{P}(X_i|mb(X_i))$, of a nonevidence variable X_i ?

$$P(x_i|mb(X_i)) = \alpha P(x_i|parents(X_i)) \prod_{Y_j \in Children(X_i)} P(y_j|parents(Y_j))$$

- How do we get the Markov blanket distribution, $\mathbf{P}(X_i|mb(X_i))$, of a nonevidence variable X_i ?

$$P(x_i|mb(X_i)) = \alpha P(x_i|parents(X_i)) \prod_{Y_j \in Children(X_i)} P(y_j|parents(Y_j))$$

- In our sprinkler example, We can calculate $\mathbf{P}(C|s, \neg r)$ as follows

$$P(c|s, \neg r) = \alpha P(c)P(s|c)P(\neg r|c) = \alpha \times 0.5 \times 0.1 \times 0.2$$

$$P(\neg c|s, \neg r) = \alpha P(\neg c)P(s|\neg c)P(\neg r|\neg c) = \alpha \times 0.5 \times 0.5 \times 0.8$$

- How do we get the Markov blanket distribution, $\mathbf{P}(X_i|mb(X_i))$, of a nonevidence variable X_i ?

$$P(x_i|mb(X_i)) = \alpha P(x_i|parents(X_i)) \prod_{Y_j \in Children(X_i)} P(y_j|parents(Y_j))$$

- In our sprinkler example, We can calculate $\mathbf{P}(C|s, \neg r)$ as follows

$$P(c|s, \neg r) = \alpha P(c)P(s|c)P(\neg r|c) = \alpha \times 0.5 \times 0.1 \times 0.2$$

$$P(\neg c|s, \neg r) = \alpha P(\neg c)P(s|\neg c)P(\neg r|\neg c) = \alpha \times 0.5 \times 0.5 \times 0.8$$

- So, the sampling distribution is $\alpha \langle 0.001, 0.020 \rangle \approx \langle 0.048, 0.952 \rangle$

Does Gibbs sampling work?


- Gibbs sampling work as intended (probability estimates converge to true probability values) when the chain is *ergodic* — that is, every state must be reachable from every other and there are no periodic cycles

Does Gibbs sampling work?

- Gibbs sampling work as intended (probability estimates converge to true probability values) when the chain is *ergodic* — that is, every state must be reachable from every other and there are no periodic cycles
- It does not work for cases as follows (where *Rain* is constrained to have the same value as *Cloudy*)

Does Gibbs sampling work?

- Gibbs sampling works as intended (probability estimates converge to true probability values) when the chain is *ergodic* — that is, every state must be reachable from every other and there are no periodic cycles
- It does not work for cases as follows (where *Rain* is constrained to have the same value as *Cloudy*)



Metropolis–Hastings Sampling

- We saw that Gibbs sampling may get stuck to a part of the Markov Chain
- This may be solved by occasional random “restarts” where next state is generated from scratch
- For example, next state generation may be as follows:
 - With probability 0.95, perform a Gibbs sampling step to generate the next state x'
 - Otherwise, generate x' by running likelihood-weighted sampling algorithm
- This is an example of a *Metropolis–Hastings* algorithm, where the next state x' is generated from the current state x from a proposal distribution (an example is shown above)
- The proposed next state may be accepted or rejected according to the acceptance probability (depends on the ratio $\frac{\pi(x')}{\pi(x)}$ which can be computed by $\frac{P(x',e)}{P(x,e)}$)

- We have discussed how knowledge under uncertainty can be represented using Bayesian Networks

What Next?

- Read chapter 13 of the text book!