

# UIT2504 Artificial Intelligence

## Genetic Algorithms

C. Aravindan  
<AravindanC@ssn.edu.in>

Professor of Information Technology  
SSN College of Engineering

August 28, 2024




# Iterative improvement algorithms

- In several problems, the path is irrelevant and a goal-state is a solution we are looking for
- With state space = set of “complete” configurations,
  - Find an optimal configuration (eg. TSP, maximal matching in a bipartite graph, “weights” that minimize error on the examples)
  - Find a configuration that satisfies some constraints (eg. Timetable generation,  $n$ -queens problem, stable matching)
- In such cases, we can use **iterative improvement algorithms** — “keep a single current state and try to improve it”

# Outline of Hill Climbing Algorithm

```
def hill_climbing(problem):  
    current = problem.initial()  
    while True:  
        neighbor = max( problem.children(current) )  
        if problem.value(neighbor) <=  
            problem.value(current):  
            break  
        current = neighbor  
    return current
```

# Hill Climbing Search




# Issues in Greedy Local Search

- **Local maxima / minima**
- **Ridges** — sequence of local maxima that is very difficult for the greedy algorithm to navigate
- **Plateaux** — flat local maximum or a shoulder

## Local maxima is a serious problem

Empirical analysis of 8-queens problem reveals that the greedy hill-climbing algorithm gets stuck 86% of the time

# Ridges



# Variations of Hill Climbing

- **Random sideways moves** — can escape from a shoulder, but gets trapped in a local maxima — number of sideways moves may be limited — number of instances solved for the 8-queens problem increases from 14% to 94%
- **Stochastic Hill Climbing** — chooses at random, among all uphill moves — probability of selection can depend on the steepness of the ascent — example of a **Randomized algorithm**
- **First Choice Hill Climbing** — randomly generate the successors, until one better than the current is generated
- **Random Restart** — enough restarts may make this algorithm complete — if each hill-climbing has a probability  $p$  of success, then  $1/p$  restarts are expected — for 8-queens,  $p \approx 0.14$ , and so roughly 7 restarts are expected

# Simulated Annealing

- One interesting variation of hill climbing is to adopt the concept of **simulated annealing**
- For example, consider a ball set to roll on a state landscape
- The ball simply follows the rules of gravity and moves towards nearby valley
- The ball needs to make some uphill moves to escape from local minima!
- Imagine applying just enough force for it to escape from all local minima but not from global minima
- How to find that “just enough force”?



# Simulated Annealing

- Similar to the metallurgical process of annealing
- Start with a high “temperature” — probability of selecting a bad move is high
- Slowly reduce the “temperature” — probability of selecting a bad move reduces slowly
- “Schedule” of reducing the temperature is very critical

# Simulated Annealing

```
function SIMULATED-ANNEALING(problem, schedule) returns a solution state
  current  $\leftarrow$  problem.INITIAL
  for  $t = 1$  to  $\infty$  do
     $T \leftarrow$  schedule( $t$ )
    if  $T = 0$  then return current
    next  $\leftarrow$  a randomly selected successor of current
     $\Delta E \leftarrow$  VALUE(current) - VALUE(next)
    if  $\Delta E > 0$  then current  $\leftarrow$  next
    else current  $\leftarrow$  next only with probability  $e^{-\Delta E/T}$ 
```

# Questions?

- May be we are too conservative with memory!

- May be we are too conservative with memory! Track  $k$  states rather than just one

# Local Beam Search

- May be we are too conservative with memory! Track  $k$  states rather than just one — **local beam search**

# Local Beam Search

- May be we are too conservative with memory! Track  $k$  states rather than just one — **local beam search**
- At each iteration, generate successors of all  $k$  states

# Local Beam Search

- May be we are too conservative with memory! Track  $k$  states rather than just one — **local beam search**
- At each iteration, generate successors of all  $k$  states
- And choose the best  $k$  among all for the next generation



# Local Beam Search

- May be we are too conservative with memory! Track  $k$  states rather than just one — **local beam search**
- At each iteration, generate successors of all  $k$  states
- And choose the best  $k$  among all for the next generation — useful information is passed among the parallel search threads

# Local Beam Search

- May be we are too conservative with memory! Track  $k$  states rather than just one — **local beam search**
- At each iteration, generate successors of all  $k$  states
- And choose the best  $k$  among all for the next generation — useful information is passed among the parallel search threads
- Different from running  $k$  parallel searches!

# Local Beam Search

- Can still get stuck in local minima

- Can still get stuck in local minima — all  $k$  states may not be diverse enough

# Local Beam Search

- Can still get stuck in local minima — all  $k$  states may not be diverse enough
- Variation called **stochastic beam search** may be used

# Local Beam Search

- Can still get stuck in local minima — all  $k$  states may not be diverse enough
- Variation called **stochastic beam search** may be used — instead of  $k$  best from the frontier, randomly select  $k$  successors with probability directly related to their “fitness”

- Inspired by natural evolution, successors are generated from a pair of parents

- Inspired by natural evolution, successors are generated from a pair of parents — the **crossover** operation



- Inspired by natural evolution, successors are generated from a pair of parents — the **crossover** operation
- States are referred to as **individuals**


- Inspired by natural evolution, successors are generated from a pair of parents — the **crossover** operation
- States are referred to as **individuals** — Each individual is represented as a string over finite alphabet (usually 0 and 1)

- Inspired by natural evolution, successors are generated from a pair of parents — the **crossover** operation
- States are referred to as **individuals** — Each individual is represented as a string over finite alphabet (usually 0 and 1)
- An individual is evaluated by a **fitness function**


- Inspired by natural evolution, successors are generated from a pair of parents — the **crossover** operation
- States are referred to as **individuals** — Each individual is represented as a string over finite alphabet (usually 0 and 1)
- An individual is evaluated by a **fitness function**
- Algorithm maintains a set of, say  $k$ , individuals

- Inspired by natural evolution, successors are generated from a pair of parents — the **crossover** operation
- States are referred to as **individuals** — Each individual is represented as a string over finite alphabet (usually 0 and 1)
- An individual is evaluated by a **fitness function**
- Algorithm maintains a set of, say  $k$ , individuals — referred to as the **population**

# Genetic Algorithms — Representation




# Genetic Algorithms — Representation



- One representation for this could be “16257483”


# Genetic Algorithms — Representation



- One representation for this could be “16257483”
- We may also choose a binary representation for this — 3 bits per column, resulting in a string of 24 bits —  
“000101001100110011111010”




# Genetic Algorithms — Representation




- One representation for this could be “16257483”
- We may also choose a binary representation for this — 3 bits per column, resulting in a string of 24 bits — “000101001100110011111010”
- Does the representation matter?

# Genetic Algorithms — Fitness function




# Genetic Algorithms — Fitness function




- Fitness of this individual may be evaluated using a heuristics

# Genetic Algorithms — Fitness function



- Fitness of this individual may be evaluated using a heuristics — number of pairs of non-attacking queens (for maximization),

# Genetic Algorithms — Fitness function



- Fitness of this individual may be evaluated using a heuristics — number of pairs of non-attacking queens (for maximization), or number of pairs of attacking queens (for minimization)


- Algorithm starts with an **initial population** of random individuals

- Algorithm starts with an **initial population** of random individuals
- **Offsprings** are generated through **selection**, **crossover**, and **mutation**


- Algorithm starts with an **initial population** of random individuals
- **Offsprings** are generated through **selection**, **crossover**, and **mutation**
- **Culling** may be done to eliminate the “unfit” individuals and keep only, say  $k$ , best for the next generation of population




# Genetic Algorithms — Operations



# Genetic Algorithms — Crossover




# Genetic Algorithms — Crossover



- Randomly generate **crossover points**

# Genetic Algorithms — Crossover



- Randomly generate **crossover points**
- Generate an offspring by taking one part of the string from one parent and the other part from the other parent (string)

# Genetic Algorithms

```
function GENETIC-ALGORITHM(population, fitness) returns an individual
  repeat
    weights  $\leftarrow$  WEIGHTED-BY(population, fitness)
    population2  $\leftarrow$  empty list
    for  $i = 1$  to SIZE(population) do
      parent1, parent2  $\leftarrow$  WEIGHTED-RANDOM-CHOICES(population, weights, 2)
      child  $\leftarrow$  REPRODUCE(parent1, parent2)
      if (small random probability) then child  $\leftarrow$  MUTATE(child)
      add child to population2
    population  $\leftarrow$  population2
  until some individual is fit enough, or enough time has elapsed
  return the best individual in population, according to fitness
```

```
function REPRODUCE(parent1, parent2) returns an individual
   $n \leftarrow$  LENGTH(parent1)
   $c \leftarrow$  random number from 1 to  $n$ 
  return APPEND(SUBSTRING(parent1, 1,  $c$ ), SUBSTRING(parent2,  $c + 1$ ,  $n$ ))
```

- General intuition behind genetic algorithms is that the crossover and mutation operations help in exploring a larger landscape

- General intuition behind genetic algorithms is that the crossover and mutation operations help in exploring a larger landscape
- Crossover may preserve useful patterns in most of the fit individuals

- General intuition behind genetic algorithms is that the crossover and mutation operations help in exploring a larger landscape
- Crossover may preserve useful patterns in most of the fit individuals
- **Schema** is a substring where some positions may be left unspecified — for example, “246\*\*\*\*\*”



- General intuition behind genetic algorithms is that the crossover and mutation operations help in exploring a larger landscape
- Crossover may preserve useful patterns in most of the fit individuals
- **Schema** is a substring where some positions may be left unspecified — for example, “246\*\*\*\*\*”
- Several fit individuals in a population may be **instances** of this schema — if the average fitness of a schema is above mean, then several instances may survive in a population

- General intuition behind genetic algorithms is that the crossover and mutation operations help in exploring a larger landscape
- Crossover may preserve useful patterns in most of the fit individuals
- **Schema** is a substring where some positions may be left unspecified — for example, “246\*\*\*\*\*”
- Several fit individuals in a population may be **instances** of this schema — if the average fitness of a schema is above mean, then several instances may survive in a population
- Genetic algorithms work better for problems where such schema make sense

# Questions?

# Continuous State Spaces

- There are infinitely many neighbours when the state space is continuous!

# Continuous State Spaces

- There are infinitely many neighbours when the state space is continuous!
- First-choice hill climbing or simulated annealing may be used because all the successors need not be generated

# Continuous State Spaces

- There are infinitely many neighbours when the state space is continuous!
- First-choice hill climbing or simulated annealing may be used because all the successors need not be generated
- Example: Given a map with cities, find locations for three airports such that sum of squared distances from each city to its nearest airport is minimized

# Continuous State Spaces

- There are infinitely many neighbours when the state space is continuous!
- First-choice hill climbing or simulated annealing may be used because all the successors need not be generated
- Example: Given a map with cities, find locations for three airports such that sum of squared distances from each city to its nearest airport is minimized
- The state space may be defined by the coordinates of the airports:  $[(x_1, y_1), (x_2, y_2), (x_3, y_3)]$

# Continuous State Spaces

- There are infinitely many neighbours when the state space is continuous!
- First-choice hill climbing or simulated annealing may be used because all the successors need not be generated
- Example: Given a map with cities, find locations for three airports such that sum of squared distances from each city to its nearest airport is minimized
- The state space may be defined by the coordinates of the airports:  $[(x_1, y_1), (x_2, y_2), (x_3, y_3)]$
- The evaluation function  $f(s)$  may be easily computed as:

$$f((x_1, y_1), (x_2, y_2), (x_3, y_3)) = \sum_{i=1}^3 \sum_{c \in C_i} (x_i - x_c)^2 + (y_i - y_c)^2$$

where  $C_i$  is the set of cities whose closest airport is airport  $i$





- How do we generate the successor states?

- How do we generate the successor states? — discretize the neighborhood

# Discretization

- How do we generate the successor states? — discretize the neighborhood
- Possible action: Move only one airport at a time in either the  $x$  or  $y$  direction by a fixed amount  $\pm\delta$

- How do we generate the successor states? — discretize the neighborhood
- Possible action: Move only one airport at a time in either the  $x$  or  $y$  direction by a fixed amount  $\pm\delta$
- This gives 12 possible successors for any state

- How do we generate the successor states? — discretize the neighborhood
- Possible action: Move only one airport at a time in either the  $x$  or  $y$  direction by a fixed amount  $\pm\delta$
- This gives 12 possible successors for any state
- Any algorithm that we have discussed so far may be used

- How do we generate the successor states? — discretize the neighborhood
- Possible action: Move only one airport at a time in either the  $x$  or  $y$  direction by a fixed amount  $\pm\delta$
- This gives 12 possible successors for any state
- Any algorithm that we have discussed so far may be used — however, time may be an issue

- How do we generate the successor states? — discretize the neighborhood
- Possible action: Move only one airport at a time in either the  $x$  or  $y$  direction by a fixed amount  $\pm\delta$
- This gives 12 possible successors for any state
- Any algorithm that we have discussed so far may be used — however, time may be an issue — reducing the value of  $\delta$  over time may help

- How do we generate the successor states? — discretize the neighborhood
- Possible action: Move only one airport at a time in either the  $x$  or  $y$  direction by a fixed amount  $\pm\delta$
- This gives 12 possible successors for any state
- Any algorithm that we have discussed so far may be used — however, time may be an issue — reducing the value of  $\delta$  over time may help
- Such approaches are referred to as **empirical gradient** methods



# Gradient Descent

- Use **gradient** of the landscape to find a maximum / minimum

# Gradient Descent

- Use **gradient** of the landscape to find a maximum / minimum
- Gradient of our objective function gives the magnitude and direction of the steepest slope

$$\nabla f = \left( \frac{\partial f}{\partial x_1}, \frac{\partial f}{\partial y_1}, \frac{\partial f}{\partial x_2}, \frac{\partial f}{\partial y_2}, \frac{\partial f}{\partial x_3}, \frac{\partial f}{\partial y_3} \right)$$

# Gradient Descent

- Use **gradient** of the landscape to find a maximum / minimum
- Gradient of our objective function gives the magnitude and direction of the steepest slope

$$\nabla f = \left( \frac{\partial f}{\partial x_1}, \frac{\partial f}{\partial y_1}, \frac{\partial f}{\partial x_2}, \frac{\partial f}{\partial y_2}, \frac{\partial f}{\partial x_3}, \frac{\partial f}{\partial y_3} \right)$$

- Maximum of this function may be found by solving the equation  $\nabla f = 0$

# Gradient Descent

- Use **gradient** of the landscape to find a maximum / minimum
- Gradient of our objective function gives the magnitude and direction of the steepest slope

$$\nabla f = \left( \frac{\partial f}{\partial x_1}, \frac{\partial f}{\partial y_1}, \frac{\partial f}{\partial x_2}, \frac{\partial f}{\partial y_2}, \frac{\partial f}{\partial x_3}, \frac{\partial f}{\partial y_3} \right)$$

- Maximum of this function may be found by solving the equation  $\nabla f = 0$
- Note that local gradient for a given state can be computed, for example, as

$$\frac{\partial f}{\partial x_1} = 2 \sum_{c \in C_1} (x_1 - x_c)$$

# Gradient Descent

- Use **gradient** of the landscape to find a maximum / minimum
- Gradient of our objective function gives the magnitude and direction of the steepest slope

$$\nabla f = \left( \frac{\partial f}{\partial x_1}, \frac{\partial f}{\partial y_1}, \frac{\partial f}{\partial x_2}, \frac{\partial f}{\partial y_2}, \frac{\partial f}{\partial x_3}, \frac{\partial f}{\partial y_3} \right)$$

- Maximum of this function may be found by solving the equation  $\nabla f = 0$
- Note that local gradient for a given state can be computed, for example, as

$$\frac{\partial f}{\partial x_1} = 2 \sum_{c \in C_1} (x_1 - x_c)$$

- Current state vector  $x$  may be updated as

$$x \leftarrow x + \alpha \nabla f(x)$$

where  $\alpha$  is a small constant called the **step size** (learning rate, in the

# Newton-Raphson method

- **Newton-Raphson** technique for solving equations of the form  $g(x) = 0$  may be used

$$x \leftarrow x - \frac{g(x)}{g'(x)}$$

# Newton-Raphson method

- **Newton-Raphson** technique for solving equations of the form  $g(x) = 0$  may be used

$$x \leftarrow x - \frac{g(x)}{g'(x)}$$

- In our context, we need to solve  $\nabla f = 0$

# Newton-Raphson method

- **Newton-Raphson** technique for solving equations of the form  $g(x) = 0$  may be used

$$x \leftarrow x - \frac{g(x)}{g'(x)}$$

- In our context, we need to solve  $\nabla f = 0$

$$x \leftarrow x - H_f^{-1}(x) \nabla f(x)$$



# Newton-Raphson method

- **Newton-Raphson** technique for solving equations of the form  $g(x) = 0$  may be used

$$x \leftarrow x - \frac{g(x)}{g'(x)}$$

- In our context, we need to solve  $\nabla f = 0$

$$x \leftarrow x - H_f^{-1}(x) \nabla f(x)$$

where  $H_f(x)$  is the **Hessian** matrix of second derivatives

# Newton-Raphson method

- **Newton-Raphson** technique for solving equations of the form  $g(x) = 0$  may be used

$$x \leftarrow x - \frac{g(x)}{g'(x)}$$

- In our context, we need to solve  $\nabla f = 0$

$$x \leftarrow x - H_f^{-1}(x) \nabla f(x)$$

where  $H_f(x)$  is the **Hessian** matrix of second derivatives

- Elements  $H_{ij}$  are given by  $\frac{\partial^2 f}{\partial x_i \partial x_j}$

# Questions?