

# UIT2504 Artificial Intelligence

## Rational Agents

C. Aravindan  
<AravindanC@ssn.edu.in>

Professor of Computing  
SSN College of Engineering

July 31, 2024

# AI and Rational Agents

Thinking humanly	Thinking rationally
Acting humanly	Acting rationally

# AI and Rational Agents

Thinking humanly	Thinking rationally
Acting humanly	Acting rationally

The textbook advocates “*Acting Rationally*”


- An agent is anything that can be viewed as perceiving its *environment* through *sensors* and acting upon that environment through *actuators*

- An agent is anything that can be viewed as perceiving its *environment* through *sensors* and acting upon that environment through *actuators*
- *Example — Human agent:* eyes, ears, and other organs for sensors; hands, legs, mouth, and other body parts for actuators

- An agent is anything that can be viewed as perceiving its *environment* through *sensors* and acting upon that environment through *actuators*
- *Example — Human agent:* eyes, ears, and other organs for sensors; hands, legs, mouth, and other body parts for actuators
- *Example — Robotic agent:* cameras, infrared range finders, etc. for sensors; various motors for actuators


- An agent is anything that can be viewed as perceiving its *environment* through *sensors* and acting upon that environment through *actuators*
- *Example — Human agent:* eyes, ears, and other organs for sensors; hands, legs, mouth, and other body parts for actuators
- *Example — Robotic agent:* cameras, infrared range finders, etc. for sensors; various motors for actuators
- *Example — Software agent:* keystrokes, mouse clicks, file contents, network packets, etc. for sensors; display, writing files, sending packets, etc. for actuators

# Agents






# Agents




- The agent function maps from percept sequences to actions:  
 $f : P^* \rightarrow A$

# Agents




- The agent function maps from percept sequences to actions:  
 $f : P^* \rightarrow A$
- An agent program runs on some physical architecture to compute  $f$

# Vacuum-Cleaner World




# Vacuum-Cleaner World




- *Percepts*: pair of location and its contents. Eg. [A, dirty], [B, clean]
- *Actions*: Left, Right, Suck, Noop

# Vacuum-Cleaner World



- *Percepts*: pair of location and its contents. Eg. [A, dirty], [B, clean]
- *Actions*: Left, Right, Suck, Noop
- Given a percept sequence, what is the "right" thing to be done by the agent?

# Vacuum-Cleaner World



- *Percepts*: pair of location and its contents. Eg. [A, dirty], [B, clean]
- *Actions*: Left, Right, Suck, Noop
- Given a percept sequence, what is the "right" thing to be done by the agent?
- Can the agent function be computed by a simple look-up table?

# What is Rationality?

- The "right" action is the one that will cause the agent to be successful

# What is Rationality?

- The "right" action is the one that will cause the agent to be successful
- But, how to measure success?



# What is Rationality?

- The "right" action is the one that will cause the agent to be successful
- But, how to measure success?
- Consequentialism — evaluate an agent's behavior by its consequences

# What is Rationality?

- The "right" action is the one that will cause the agent to be successful
- But, how to measure success?
- Consequentialism — evaluate an agent's behavior by its consequences
- *Performance Measure*: an objective criterion for success of an agent

# What is Rationality?

- The "right" action is the one that will cause the agent to be successful
- But, how to measure success?
- Consequentialism — evaluate an agent's behavior by its consequences
- *Performance Measure*: an objective criterion for success of an agent
- Example: For vacuum-cleaner, performance measures could be amount of dirt cleaned up, time taken, electricity consumed, noise generated etc.

## Rational Agents

For each possible percept sequence, a rational agent should select an action that is expected to maximize its performance measure, given the evidence provided by the percept sequence and whatever built-in knowledge the agent has.

- Rationality is not perfection and it is not omniscience

- Rationality is not perfection and it is not omniscience
- Rational agents can perform actions to gather information (exploration)

- Rationality is not perfection and it is not omniscience
- Rational agents can perform actions to gather information (exploration)
- Rational agents should learn from the percepts

- Rationality is not perfection and it is not omniscience
- Rational agents can perform actions to gather information (exploration)
- Rational agents should learn from the percepts
- Rational agents should be autonomous



- *PEAS*: Performance measure, Environment, Actuators, Sensors

# PEAS Formulation

- *PEAS*: Performance measure, Environment, Actuators, Sensors
- Example: How can we describe an automated taxi driver?

# PEAS Formulation

- *PEAS*: Performance measure, Environment, Actuators, Sensors
- Example: How can we describe an automated taxi driver?
- Performance:

# PEAS Formulation

- *PEAS*: Performance measure, Environment, Actuators, Sensors
- Example: How can we describe an automated taxi driver?
- Performance: Safety, speed, legal, comfort, profits, etc.

- *PEAS*: Performance measure, Environment, Actuators, Sensors
- Example: How can we describe an automated taxi driver?
- Performance: Safety, speed, legal, comfort, profits, etc.
- Environment:

- *PEAS*: Performance measure, Environment, Actuators, Sensors
- Example: How can we describe an automated taxi driver?
- Performance: Safety, speed, legal, comfort, profits, etc.
- Environment: Roads, traffic, police, pedestrians, weather, etc.

- *PEAS*: Performance measure, Environment, Actuators, Sensors
- Example: How can we describe an automated taxi driver?
- Performance: Safety, speed, legal, comfort, profits, etc.
- Environment: Roads, traffic, police, pedestrians, weather, etc.
- Actuators:

- *PEAS*: Performance measure, Environment, Actuators, Sensors
- Example: How can we describe an automated taxi driver?
- Performance: Safety, speed, legal, comfort, profits, etc.
- Environment: Roads, traffic, police, pedestrians, weather, etc.
- Actuators: Steering, accelerator, brake, signal, horn, etc.



- *PEAS*: Performance measure, Environment, Actuators, Sensors
- Example: How can we describe an automated taxi driver?
- Performance: Safety, speed, legal, comfort, profits, etc.
- Environment: Roads, traffic, police, pedestrians, weather, etc.
- Actuators: Steering, accelerator, brake, signal, horn, etc.
- Sensors:

- *PEAS*: Performance measure, Environment, Actuators, Sensors
- Example: How can we describe an automated taxi driver?
- Performance: Safety, speed, legal, comfort, profits, etc.
- Environment: Roads, traffic, police, pedestrians, weather, etc.
- Actuators: Steering, accelerator, brake, signal, horn, etc.
- Sensors: Camera, radar, speedometer, GPS, odometer, engine sensors, etc.

- Another example: How can we describe an Internet shopping agent?

- Another example: How can we describe an Internet shopping agent?
- Performance:

- Another example: How can we describe an Internet shopping agent?
- Performance: Price, quality, appropriateness, efficiency, etc.

- Another example: How can we describe an Internet shopping agent?
- Performance: Price, quality, appropriateness, efficiency, etc.
- Environment:

- Another example: How can we describe an Internet shopping agent?
- Performance: Price, quality, appropriateness, efficiency, etc.
- Environment: Current and future websites, vendors, shippers

- Another example: How can we describe an Internet shopping agent?
- Performance: Price, quality, appropriateness, efficiency, etc.
- Environment: Current and future websites, vendors, shippers
- Actuators:



- Another example: How can we describe an Internet shopping agent?
- Performance: Price, quality, appropriateness, efficiency, etc.
- Environment: Current and future websites, vendors, shippers
- Actuators: Display to user, follow links, fill-up forms, etc.

- Another example: How can we describe an Internet shopping agent?
- Performance: Price, quality, appropriateness, efficiency, etc.
- Environment: Current and future websites, vendors, shippers
- Actuators: Display to user, follow links, fill-up forms, etc.
- Sensors:

- Another example: How can we describe an Internet shopping agent?
- Performance: Price, quality, appropriateness, efficiency, etc.
- Environment: Current and future websites, vendors, shippers
- Actuators: Display to user, follow links, fill-up forms, etc.
- Sensors: Understand HTML pages (text, graphics, scripts)

# PEAS Formulation

Agent Type	Performance Measure	Environment	Actuators	Sensors
Medical diagnosis system	Healthy patient, reduced costs	Patient, hospital, staff	Display of questions, tests, diagnoses, treatments	Touchscreen/voice entry of symptoms and findings
Satellite image analysis system	Correct categorization of objects, terrain	Orbiting satellite, downlink, weather	Display of scene categorization	High-resolution digital camera
Part-picking robot	Percentage of parts in correct bins	Conveyor belt with parts; bins	Jointed arm and hand	Camera, tactile and joint angle sensors
Refinery controller	Purity, yield, safety	Refinery, raw materials, operators	Valves, pumps, heaters, stirrers, displays	Temperature, pressure, flow, chemical sensors
Interactive English tutor	Student's score on test	Set of students, testing agency	Display of exercises, feedback, speech	Keyboard entry, voice

# Properties of task environments

- Fully observable Vs. partially observable
  - Can the agent sense all the relevant aspects of the environment?
  - Example: Chess playing agent
  - Example: Autonomous driving agent

# Properties of task environments

- Fully observable Vs. partially observable
  - Can the agent sense all the relevant aspects of the environment?
  - Example: Chess playing agent
  - Example: Autonomous driving agent
- Single agent Vs. multiagent
  - How do we define other agents?
  - Example: Puzzle solver
  - Example: Chess playing agent
  - Example: Autonomous driving agent

# Properties of task environments

- Deterministic Vs. nondeterministic
  - Is the next state completely defined by the current state and the action executed by the agent?
  - Example: Chess playing agent
  - Example: Autonomous driving agent

# Properties of task environments

- Deterministic Vs. nondeterministic
  - Is the next state completely defined by the current state and the action executed by the agent?
  - Example: Chess playing agent
  - Example: Autonomous driving agent
- Episodic Vs. sequential
  - Does the action taken in one time duration (episode) depend on the actions taken in the previous episodes?
  - Example: Chess playing agent
  - Example: Part-picking robot



# Properties of task environments

- Static Vs. dynamic
  - Does the environment change while the agent is deliberating?
  - Example: Chess playing agent
  - Example: Part-picking robot

# Properties of task environments

- Static Vs. dynamic

- Does the environment change while the agent is deliberating?
- Example: Chess playing agent
- Example: Part-picking robot
- If the environment itself does not change, but the performance score changes, then it is semi-dynamic
- Example: Chess with a clock

# Properties of task environments

- Static Vs. dynamic

- Does the environment change while the agent is deliberating?
- Example: Chess playing agent
- Example: Part-picking robot
- If the environment itself does not change, but the performance score changes, then it is semi-dynamic
- Example: Chess with a clock

- Discrete Vs. continuous

- Can the environment be captured by a set of discrete states? — time is discrete or continuous?
- Example: Chess playing agent
- Example: Part-picking robot

# Properties of task environments

- Static Vs. dynamic

- Does the environment change while the agent is deliberating?
- Example: Chess playing agent
- Example: Part-picking robot
- If the environment itself does not change, but the performance score changes, then it is semi-dynamic
- Example: Chess with a clock

- Discrete Vs. continuous

- Can the environment be captured by a set of discrete states? — time is discrete or continuous?
- Example: Chess playing agent
- Example: Part-picking robot

- Known Vs. unknown

- Does the agent know the “laws of physics” of the environment?

# Properties of task environments

Task Environment	Observable	Agents	Deterministic	Episodic	Static	Discrete
Crossword puzzle	Fully	Single	Deterministic	Sequential	Static	Discrete
Chess with a clock	Fully	Multi	Deterministic	Sequential	Semi	Discrete
Poker	Partially	Multi	Stochastic	Sequential	Static	Discrete
Backgammon	Fully	Multi	Stochastic	Sequential	Static	Discrete
Taxi driving	Partially	Multi	Stochastic	Sequential	Dynamic	Continuous
Medical diagnosis	Partially	Single	Stochastic	Sequential	Dynamic	Continuous
Image analysis	Fully	Single	Deterministic	Episodic	Semi	Continuous
Part-picking robot	Partially	Single	Stochastic	Episodic	Dynamic	Continuous
Refinery controller	Partially	Single	Stochastic	Sequential	Dynamic	Continuous
English tutor	Partially	Multi	Stochastic	Sequential	Dynamic	Discrete

# Questions?

- Read chapter 2 of the textbook!