

```

1  import serial
2  import time
3  import logging
4  from typing import Optional
5
6  # -----
7  # Global file names (as in extern QString)
8  # -----
9  myFileName = "data.txt"
10 logFileName = "serial.log"
11
12 # -----
13 # Logger setup (replacement for Logger.h)
14 # -----
15 logging.basicConfig(
16     filename=logFileName,
17     level=logging.INFO,
18     format="%asctime)s [%s] %(message)s"
19 )
20 logger = logging.getLogger("SerialManager")
21
22
23 class SerialManager:
24     def __init__(self):
25         self.serial_port: Optional[serial.Serial] = None
26         self.isopen = False
27
28         self.ser_data = bytearray(2048)
29         self.user_data = bytearray(2048)
30
31         self.tcp1Data = -100.0
32         self.tcp2Data = -100.0
33         self.tcp3Data = -100.0
34         self.tcp4Data = -100.0
35         self.wing1Data = -100.0
36         self.wing2Data = -100.0
37
38         self.actuatorDataLink = 0
39         self.cguDataLink = 0
40
41     # -----
42     # Utility
43     # -----
44     @staticmethod
45     def hex_fn(a: int, b: int) -> int:
46         return ((b << 8) | a)
47
48     @staticmethod
49     def delay(ms: int):
50         time.sleep(ms / 1000.0)
51
52     # -----
53     # Serial init / close
54     # -----
55     def initSerialPort(self, portName: str) -> int:
56         try:
57             self.serial_port = serial.Serial(
58                 port=portName,
59                 baudrate=9600,
60                 bytesize=serial.EIGHTBITS,
61                 parity=serial.PARITY_NONE,
62                 stopbits=serial.STOPBITS_ONE,
63                 timeout=2
64             )
65             self.isopen = True
66             print(f"Success {portName}")
67             logger.info(f"Opened Successfully {portName}")
68             return 0
69         except Exception as e:
70             self.isopen = False
71             logger.error(str(e))
72             return 1

```

```

73
74 def serclose(self):
75     if self.serial_port and self.serial_port.is_open:
76         self.serial_port.close()
77         self.isopen = False
78         print("closed")
79     else:
80         print("Not Closed")
81
82 def serFlush(self):
83     if self.serial_port:
84         self.serial_port.reset_input_buffer()
85         self.serial_port.reset_output_buffer()
86
87 # -----
88 # TX / RX
89 # -----
90 def serTx(self, data: bytes) -> int:
91     if not self.isopen:
92         return -1
93     self.serFlush()
94     written = self.serial_port.write(data)
95     print("Bytes Written :", written)
96     logger.info("Tx : " + data.hex().upper())
97     return written
98
99 def serTxStr(self, s: str):
100     self.serTx(s.encode("ascii"))
101
102 def serRx(self) -> int:
103     if not self.isopen:
104         return 0
105
106     rx = bytearray()
107     start = time.time()
108     while time.time() - start < 2:
109         if self.serial_port.in_waiting:
110             rx.extend(self.serial_port.read(self.serial_port.in_waiting))
111             time.sleep(0.01)
112
113     if rx:
114         self.user_data[:len(rx)] = rx
115         self.ser_data[:len(rx)] = rx
116         print("rxByte.length", len(rx), "Data:", rx.hex().upper())
117         logger.info("Rx : " + rx.hex().upper())
118         return len(rx)
119
120     print("read timeout")
121     return 0
122
123 def serRxNumber(self, number: int) -> int:
124     length = self.serRx()
125     return number if length == number else length
126
127 # -----
128 # Commands
129 # -----
130 def CMode(self) -> str:
131     serialData = bytearray()
132     self.serFlush()
133
134     self.serTxStr("L")
135
136     time.sleep(1)
137     if self.serial_port.in_waiting:
138         serialData.extend(self.serial_port.read(self.serial_port.in_waiting))
139
140     return serialData.decode(errors="replace")
141
142 def relayOn(self, chan: int) -> int:
143     cmd = bytes([ord('u'), chan, ord('1'), ord('*')])
144     self.serTx(cmd)

```

```

145         status = self.serRx()
146         return 0 if status in (0, 1) else status
147
148     def relayOn_alt(self, chan: int) -> int:
149         cmd = bytes([ord('y'), chan, ord('1'), ord('*')])
150         self.serTx(cmd)
151         return self.serRxNumber(1)
152
153     def relayOnCmd(self, chan: int) -> int:
154         cmd = bytes([ord('r'), chan, ord('1'), ord('*')])
155         self.serTx(cmd)
156         return 1 if self.serRx() >= 1 else 0
157
158     def wingUncage(self) -> int:
159         return 0 if self.relayOnCmd(0) == 1 else 6
160
161     def wingCage(self) -> int:
162         return 0 if self.relayOnCmd(1) == 1 else 7
163
164     def setIpcode(self, ipfreq: int, ipcode: int) -> int:
165         cmd = bytes([ord('p'), 2, ipfreq, ipcode, ord('*')])
166         self.serTx(cmd)
167         status = self.serRxNumber(2)
168         return 1 if status == 2 else 0
169
170     def ipVal(self) -> str:
171         self.serFlush()
172         self.serTxStr("\v*")
173         if self.serRxNumber(7) == 7:
174             return "".join(f"{b:02x}" for b in self.ser_data[:5])
175         return ""
176
177     def cguData(self):
178         self.serFlush()
179         self.serTxStr("c*")
180         if self.serRxNumber(35) == 35:
181             self.cguDataLink = 1
182         else:
183             self.cguDataLink = 0
184
185     def writeTelData(self, inc: int) -> int:
186         cmd = b"t" + (b"I" if inc == 0 else b"D") + b"*"
187         self.serTx(cmd)
188         return 0 if self.serRxNumber(1) == 1 else 1
189
190     def actuatorFeedback(self):
191         self.serFlush()
192         self.serTxStr("f*")
193         if self.serRxNumber(12) == 12:
194             act = []
195             for i in range(0, 12, 2):
196                 v = self.hex_fn(self.ser_data[i], self.ser_data[i+1])
197                 act.append((v - 2048) * 20.0 / 4096.0)
198
199             (
200                 self.tcp1Data,
201                 self.tcp2Data,
202                 self.tcp3Data,
203                 self.tcp4Data,
204                 self.wing1Data,
205                 self.wing2Data,
206             ) = act[:6]
207
208             self.actuatorDataLink = 1
209         else:
210             self.actuatorDataLink = 0
211
212     def actuatorNull(self) -> int:
213         self.serFlush()
214         self.serTxStr("\n*")
215         return 0 if self.serRxNumber(1) == 1 else 9
216

```

```
217 def actuatorCycling(self) -> int:
218     self.serFlush()
219     self.serTxStr("5*")
220     rx = bytearray()
221     end_time = time.time() + 1.3
222
223     while time.time() < end_time:
224         if self.serial_port.in_waiting:
225             rx.extend(self.serial_port.read(self.serial_port.in_waiting))
226             time.sleep(0.01)
227
228     if rx.endswith(b'@'):
229         print("actuatorCycling Completed")
230         return 0
231     return -1
232
233 def skrSetSTABCmd(self) -> int:
234     cmd = bytes([ord('S'), 7, ord('G'), 1, 14, 0x21, 0x00, 0xAA, ord('*')])
235     self.serTx(cmd)
236     self.delay(100)
237     return 0
238
239 def skrSetTrackCmd(self) -> int:
240     cmd = bytes([ord('S'), 7, ord('G'), 1, 14, 0x31, 0x00, 0xAA, ord('*')])
241     self.serTx(cmd)
242     self.delay(100)
243     return 0
244
```