SUMMARY: AGENTS ARCHUTECTURE & DESIGN PATTERNS

Objective:

By the end of this session, you will be able to:

- **Differentiate** between key AI agent architectures, including Logic-based, Reactive, BDI, and Hybrid models.
- **Analyze** the trade-offs of different architectures based on their complexity, performance, and adaptability.
- **Explain** fundamental design patterns for agents, such as Planning, ReAct, Tool Use, and Reflection, and how they contribute to reasoning, action, and quality control.
- **Distinguish** between a purely Reactive agent and an agent using the ReAct pattern for more complex reasoning.
- **Integrate** multiple design patterns to build a basic reactive agent capable of performing tasks.

1. Why Agent Architectures Matter: The Blueprint for Intelligent Systems

Imagine you're building something complex. Would you start nailing boards together randomly, or would you begin with a detailed blueprint? Of course, you'd want the blueprint! An **agent architecture** is precisely that—a **blueprint for an intelligent agent**. It defines the fundamental structure, how its components connect, and the flow of information that dictates how the agent perceives, reasons, and acts.

Think of it as the agent's internal "operating system." A solid architecture is the difference between a clunky, unreliable system and a smart, robust one. This matters for three critical reasons: **scalability**, **efficiency**, and **adaptability**.

This matters for three critical reasons that separate a toy from a tool: scalability, efficiency, and adaptability. Let's explore what each of these means for an intelligent agent.

a. Scalability: From a Small Town to a Megalopolis

Scalability is an agent's ability to handle a growing amount of work or complexity without breaking down. A good architecture ensures the system can grow gracefully.

- **The Analogy: Building a City.** If you build a small town with no plan—narrow roads, random water pipes—it works fine for a few hundred people. But what happens when thousands move in?

You get gridlock, water shortages, and chaos! A well-planned city, however, is built on a grid with wide avenues and scalable infrastructure, allowing it to grow into a thriving metropolis.

- **Real-World Example: Amazon's E-commerce Platform.** In its early days, Amazon's system was simple. But to handle millions of users, products, and transactions per second, they had to build a highly scalable microservices architecture. Each component (user authentication, product search, shopping cart, payment) is a separate service. This allows them to update, fix, or scale one part (like the payment system during a Black Friday sale) without shutting down the entire website. Without this architectural foresight, they couldn't have grown.

A good agent architecture allows you to add more skills, handle more data, or serve more users without having to redesign the entire system from scratch.

b. Efficiency: The Professional Chef's Kitchen

Efficiency is about doing more with less—less time, less computational power, less energy. The agent's internal structure directly impacts how quickly and economically it can achieve its goals.

- **The Analogy:** A Professional Chef vs. a Novice Cook. A master chef, with a perfectly organized kitchen (mise en place), can execute a complex recipe without wasted movement. They don't stop to think where the salt is; they just grab it and continue. A novice, in a messy kitchen, spends most of their time searching for tools and ingredients. The architecture of the chef's workspace is optimized for efficient action. Similarly, an agent's architecture organizes its 'tools' (data, APIs) and 'thought processes' (algorithms) for speed..
- **Real-World Example: Google Maps.** A navigation agent like Google Maps processes an immense amount of real-time data: traffic, road closures, user speed, etc. Its architecture is designed to efficiently query this data, calculate the optimal route using sophisticated algorithms, and deliver it to your phone in seconds. A poorly designed architecture would be too slow, making the app useless for real-time navigation. It efficiently sorts through possibilities to find the best path without getting stuck in "analysis paralysis."

An efficient architecture ensures your agent makes smart decisions quickly and without wasting resources.

c. Adaptability: The Lego Masterpiece

Adaptability is the agent's capacity to change and evolve in response to new information, new goals, or a changing environment. A rigid system is a brittle one.

- **The Analogy: Legos vs. a Model Car.** Imagine a pre-built, glued-together model car. It does one thing perfectly, but you can't change it. If you want to add bigger wheels or turn it into a truck, you can't. Now think of a Lego car. You can easily swap out pieces, add a new engine, or rebuild it into something entirely different. Its modular nature makes it incredibly adaptable.
- **Real-World Example: Personalized News Feeds (e.g., Google News).** These agents must constantly adapt to your changing interests. When you start reading more about AI but less about celebrity gossip, the agent's architecture must allow it to easily adjust its content-recommendation

models. It's not hard-coded to show you one type of news. Its modular design allows it to update its understanding of "you" and modify its behavior accordingly, ensuring the feed remains relevant.

A flexible, modular architecture doesn't just make an agent easier for developers to change; it is the foundational requirement for an agent that can eventually learn and adapt on its own, integrating new knowledge and skills seamlessly—just like adding new Lego blocks to a growing masterpiece

2. Architecture vs. Design Pattern: Blueprint vs. Building Techniques

It's easy to confuse these two terms, but the distinction is vital.

2.1 Architecture: The Big-Picture Structure

Architecture is the high-level, fundamental organization of a system. It's the **blueprint of the entire house**. It defines:

- The main components (the foundation, rooms, floors, roof).
- Their relationships and how they interact (how the plumbing connects rooms, where the stairs go).
- The overall principles guiding its construction (e.g., is it a single-story ranch or a three-story Victorian?).

In an AI agent, the architecture might be a **Subsumption architecture** (layered behaviors) or a **BDI architecture** (Belief-Desire-Intention). It's the grand plan.

1. Types of AI Agent Architecture:

In complex systems, whether it’s a robot navigating a room, a virtual assistant helping a user, or an AI analyzing data, we need a way for these systems to **decide what to do and how to act in different situations**.

Traditionally, agents were designed using **classic architectures** like deliberative planning, reactive behaviors, or hybrid approaches. These worked well for structured environments, predictable rules, and task-specific goals. But as AI has evolved, especially with the rise of **large language models (LLMs)**, the scope of what agents can do has expanded dramatically. Today, agents can **understand language, reason over knowledge, maintain long-term context, and interact in human-like ways**, thanks to LLM-based architectures.

Designing an agent that can handle tasks effectively—whether in the past with classic AI or now with LLMs—requires a clear blueprint. This blueprint is what we call an **agent architecture**, which defines **how an agent perceives, reasons, and acts**.

In this session, we will explore the main types of agent architectures:

1. **Logic / Deliberative Architecture** – for goal-driven, planning-based reasoning.
2. **Reactive Architecture** – for fast, stimulus-response behaviors.
3. **BDI (Belief-Desire-Intention) Architecture** – for human-like goal reasoning.
4. **Layered (Hybrid) Architecture** – combining planning and reaction.
5. **CoALA (Cognitive Architecture for Language Agents)** – specialized for intelligent language interaction using LLMs.

By understanding these architectures, we'll see **how agent design has evolved over time** and get a foundation for building the next generation of intelligent agents.

Now start with the first Architecture i.e Deliberative Architecture:

1.1 Deliberative Architecture:

Imagine a chess grandmaster.
They don't just make the first move that comes to mind. They sit, observe the board (*the world*), think several steps ahead (*plan*), and then execute a move (*act*).
This is the essence of a **deliberative architecture**.

An **LLM-based deliberative agent** works the same way. The LLM is the grandmaster's brilliant, creative brain. Let's map the four key components of a deliberative agent to this chess analogy.

Component	Chess Grandmaster	LLM-Based Agent
World Model	The mental image of the board: where every piece is, their values, and possible threats.	The Context & Memory: The prompt, the conversation history, and the agent's own "thought" scratchpad.
Goal	To achieve checkmate.	To fulfill the user's request (e.g., "Write a report on climate change").

Actions	The legal moves of each chess piece (e.g., *Knight to F3*).	The available Tools & APIs (e.g., search_web, write_file, execute_code).
Planner	The grandmaster's reasoning process: evaluating sequences of moves to find the strongest line.	The LLM itself, using its reasoning to generate a step-by-step plan (a "thought process") before acting.

Here's how we can map the **four key components** of a deliberative agent to an LLM-based agent:

Component 1. A World Model (The Mental Chessboard)

A grandmaster's power comes from their perfect internal model of the game state.
Our LLM agent builds its world model from:

- **The Prompt (The Initial Board Setup):**
  The system prompt ("You are a helpful assistant...") and the user's query ("Book a flight") set the initial state, just like placing the pieces on the board at the start of a game.
- **The "Scratchpad" (The Grandmaster's Calculation):**
  The agent uses a technique like *Chain-of-Thought* to write down its reasoning. This acts as its temporary, evolving mental model.

  Example Thought:
  "The user wants a flight. First, I need the destination and dates. I'll ask for those. My current world model is missing critical information."

- **External Memory (Studying Past Games):**
  To go beyond the current "game," the agent can access a database of past interactions (a vector database). This is like a grandmaster recalling famous strategies from previous matches, enriching their current decision-making.

Component 2. A Set of Goals (The Path to Checkmate)

The goal is clear: win the game. For the agent, the goal is the successful completion of the user's task.
The key to deliberation is breaking this down.

- **Main Goal:**
  "Write a comprehensive market analysis report for product X."

- **Sub-goals (The Sequence of Moves):**
    - *Sub-goal 1:* Research the target market and competitors (the opening).
    - *Sub-goal 2:* Analyze the data and identify key trends (the middlegame).
    - *Sub-goal 3:* Synthesize findings into a well-structured report (the endgame).

Component 3. A Set of Actions (The Moves on the Board)

The grandmaster can only move pieces according to the rules of chess.
The LLM agent can only act using the tools it's given.

- **Tools (The Chess Pieces):**
  Each tool (e.g., web_search, data_analyzer) is a powerful piece with specific capabilities, like a Queen or a Knight.
- **Preconditions and Effects (The Rules of Movement):**
  The LLM learns the "rules" for each tool from its training.
  It knows that before it can write_file (the move), it must first generate_content (the precondition).
  The successful creation of the file is the effect.

Component 4. A Planner (The Grandmaster's Strategy)

The LLM itself is the planner. It doesn't use a formal algorithm; it uses its pattern recognition and reasoning capabilities to simulate a strategy.

- **The "Plan" is the Thought Process:**
  The agent's output is a continuous loop of deliberation expressed in natural language, much like a grandmaster thinking through their options.

Example: The Agent's "Game"

- **User (The Opponent's Move):**
  "Our market share is falling. Analyze why and suggest a strategy."
- **Agent's Deliberation:**
    - **Thought (Plan):** *"This is a complex request. I need to first understand the current market landscape. My first move should be to gather data."*
    - **Action (Move):** *search_web(query="current market share trends for [Industry]")*
    - **Observation (New Board State):** *[Gathers data on competitors and trends]*
    - **Thought (Re-plan):** *"Now I have the data. My next move is to analyze this information for root causes."*
    - **Action (Move):** *analyze_data(trend_data)*
    - **Observation:** *[Identifies key factors like new competitor pricing]*
    - **Thought:** "*Based on this, I can now formulate a strategic response. My final move is to synthesize this into a recommendation."*

Essence of Deliberative Architecture:

This entire process — **Sense (Observe) → Think (Deliberate) → Act (Move)** — is what makes it a deliberative architecture.
The agent is not just reacting; it's *thinking ahead like a grandmaster planning their victory*.

Strengths and Weaknesses of an LLM Deliberative Agent

The transition to an LLM "brain" fundamentally changes the architecture's trade-offs.

Strengths

- **Flexibility and Generalization:** The LLM can handle a vast range of unstructured, complex problems that a classical deliberative agent could never manage. It's not limited to a predefined set of actions and facts.
- **Human-like Reasoning:** The natural language planning process is intuitive and explainable to a human user. You can see *why* the agent chose a particular path, even if it's not always the optimal one.
- **Handling Unforeseen Events:** While still a challenge, an LLM agent is better equipped to handle a wrong or unexpected observation. If a tool call fails, the LLM can "reflect" on the error and attempt to formulate a new plan, instead of just failing.

Weaknesses

- **Hallucination and Unreliability:** The core weakness of LLMs is their tendency to "hallucinate" or generate incorrect information. This can lead to the agent creating a plan based on a flawed "world model" that doesn't reflect reality.
- **Computational Cost and Speed:** LLM inference is far more computationally expensive than symbolic reasoning. The "analysis paralysis" problem of classical agents is replaced by a "cost and latency" problem.
- **The "Black Box" Problem:** While the natural language output is explainable, the underlying reasoning of the LLM is still a black box. You can see *what* it thought, but not *why* it thought it.
- **The "Frame Problem" in a new form:** The LLM's implicit world model is easily outdated. An LLM agent may plan based on information it retrieved moments ago, but if the world changes rapidly, its plan can become obsolete just as a classical agent's would.

In conclusion, LLM-based agents are a modern manifestation of the deliberative architecture. They embody the "Sense -> Plan -> Act" loop, but they replace the rigid, symbolic logic with the flexible, but less predictable, power of a large language model. The "planning" is no longer a search through a state space but a creative, iterative process of generating the next best thought and action using natural language.

Now that we've unpacked deliberative architecture, especially in the context of LLMs, we can see that while it's powerful, it also comes with some critical weaknesses: it can be slow, computationally expensive, and prone to overthinking or hallucination.

This raises a very practical question: ***What if we don't always need such heavy reasoning?***

Imagine a robot that needs to stop instantly when it sees a wall, or a drone that has to dodge a sudden obstacle in midair. In these cases, if the agent paused to 'think,' reason, or plan step by step, it would fail — sometimes with disastrous results.

This is where **reactive architecture** comes in. Unlike deliberative agents, reactive agents don't build detailed world models or plan in advance. Instead, they operate on a direct **stimulus → response** cycle, almost like reflexes in humans.

So, while deliberative agents are like a grandmaster carefully thinking 10 moves ahead, reactive agents are like someone pulling their hand away instantly from a hot stove — fast, direct, and often good enough to survive in dynamic environments.

This brings us to **reactive architecture** — a design where agents respond immediately to their environment, without heavy planning or internal models. Instead of 'thinking first and acting later,' reactive agents are more like reflexes: they sense and act directly, ensuring speed and adaptability.

1.2 Reactive Architecture:

Imagine you touch a hot stove. Do you stop, think about the chemical properties of heat, model the damage to your skin cells, and then plan a response to move your hand? Of course not! You pull your hand away *instantly*. That's a reflex.

At its core, a reactive architecture is designed to give an AI agent that same kind of reflex. It's built on a simple, powerful philosophy that completely contrasts with the slow, thoughtful, deliberative architectures.

The Core Philosophy: "Don't Think, Just Do!"

The motto of a reactive agent is **Sense -> Act**.

That's it. There's no complex "planning" or "modeling" stage in the middle. The agent perceives something in its environment through its sensors and immediately triggers a corresponding action. It's a tight, direct coupling between sensing and acting.

Think of a simple insect, like a cockroach.

- **Senses** a shadow from above -> **Acts** by scurrying away.
- **Senses** a wall with its antennae -> **Acts** by turning.

The cockroach doesn't have a deep internal map of the room or a long-term goal to "cross the kitchen floor." It simply reacts to its immediate surroundings based on a set of pre-programmed survival behaviors. This is the essence of a reactive agent.

How It Works: A World of Simple Rules

A reactive architecture works by breaking down a complex task into a collection of simple, independent behaviors. Each behavior is essentially a rule that looks like this:

IF <this condition is met by a sensor>, THEN <execute this action>

For example:

- IF bumper_sensor == PRESSED, THEN reverse_and_turn()
- IF light_sensor > 70%, THEN move_forward()
- IF battery_level < 10%, THEN activate_find_charger_behavior()

The agent's overall "intelligent" behavior isn't found in one master plan; instead, it **emerges** from the interaction of all these simple rules running at the same time.

The Classic Example: The Subsumption Architecture

The most famous and influential reactive architecture is the **Subsumption Architecture**, developed by Rodney Brooks at MIT in the 1980s. His work was a direct rebellion against the slow, symbolic AI of the time.

The genius of Subsumption is that it organizes simple behaviors into a **hierarchy of layers**.

Let's design a simple robot vacuum cleaner to see how this works:

- **Layer 0: Avoid Obstacles (The Highest Priority)**
  - This is the most basic survival instinct. Its only job is to watch the bumper and sonar sensors.
  - **Rule:** If you're about to hit something, override everything else and turn away.
- **Layer 1: Wander**
  - This layer's job is to make the robot explore.
  - **Rule:** If nothing else is happening, just move forward.
- **Layer 2: Clean**
  - This is the "goal" we actually want.
  - **Rule:** If you are moving, turn on the vacuum suction.

What does "Subsumption" mean?

It means that **higher-priority layers can suppress or *subsume* the outputs of lower-priority layers**.

Imagine our robot is wandering forward (Layer 1) with its vacuum on (Layer 2). Suddenly, its sensor detects a wall. The "Avoid Obstacles" behavior (Layer 0) wakes up and shouts "STOP!" It suppresses the "Wander" layer's command to move forward and takes control of the wheels, forcing the robot to turn. Once the path is clear, Layer 0 goes quiet again, and Layer 1 can resume its job of wandering.

This layering makes the system incredibly robust. Even if the "Clean" layer fails, the robot will still wander around and avoid bumping into things.

Strengths and Weaknesses

Strengths

- **Extremely Fast:** With no time spent on complex planning, these agents can react to dynamic environments in real-time.
- **Robust and Fault-Tolerant:** Since behaviors are simple and independent, the failure of one doesn't usually crash the whole system. The agent can still function at a basic level.
- **Computationally Cheap:** They don't require powerful processors or large amounts of memory.
- **Elegant Simplicity:** They can produce surprisingly complex and effective behavior from very simple rules.

Weaknesses

- **No Long-Term Planning:** The agent is fundamentally **shortsighted**. It cannot make multi-step plans. Our robot vacuum can't plan the most efficient path to clean a room; it just reacts its way through the space.
- **No "World Model":** The agent has no memory or internal understanding of the world. It doesn't know it has cleaned a spot already, so it might clean it again and again.
- **Difficult to Scale:** While the behaviors are simple, predicting how dozens or hundreds of them will interact to produce the desired *emergent behavior* can be extremely difficult for the designer.

In summary, reactive architectures are a powerful and foundational concept, perfect for tasks that require fast, robust responses in dynamic environments. While they lack the deep reasoning of other architectures, their simplicity and efficiency are what make them so brilliant

Now that we've understood both **Deliberative** and **Reactive** architectures in detail, a natural question arises:
"How do we decide which one to use in practice?"

The truth is, neither is universally better—each shines in different situations. Deliberative agents excel when careful planning and reasoning are critical, while reactive agents thrive in fast-changing environments where quick decisions matter more than deep thinking.

To make this distinction clearer, let's break down **when to use which architecture** side by side:

When to Use Which Architecture:

Aspect	Deliberative Architecture	Reactive Architecture
Speed	Slower – requires planning & reasoning	Very fast – direct stimulus → action

Best For	Complex tasks needing foresight, strategy, reasoning	Dynamic, uncertain environments needing quick responses
Example Use Case	Planning a delivery route with traffic optimization	Autonomous car braking to avoid a sudden pedestrian
Strength	Deep reasoning, long-term goal alignment	Robust in real-time, unpredictable scenarios
Weakness	Computationally expensive, prone to "paralysis by analysis"	Lacks foresight, can't handle abstract or long-term goals
Analogy	Chess grandmaster planning 10 moves ahead	Human reflex pulling hand away from fire

This tension—between *thinking too much* and *not thinking enough*—led researchers to look for a middle ground. That's where the **BDI (Belief–Desire–Intention) Architecture** comes in. BDI agents combine the **context-awareness of reactive systems** with the **goal-directed reasoning of deliberative systems**, allowing them to act quickly while still keeping long-term objectives in mind

1.3 Belief–Desire–Intention (BDI) architecture

The Belief–Desire–Intention (BDI) architecture is a hybrid model for intelligent agents that strikes a balance between the extremes of purely **reactive** and purely **deliberative** systems. It achieves this by giving the agent a structured internal "mind" to guide its actions without requiring a full, complex plan for every single step.

The Three Core Components

The BDI model is built on three key mental attitudes that, when combined, allow for flexible and goal-directed behavior.

1. **Beliefs (Informational State):** These are the agent's internal model of the world—its knowledge and assumptions about the environment and its own state. Crucially, these are "beliefs," not "facts," because they may be incomplete or even incorrect. They're constantly updated by the agent's sensors and internal reasoning.
    - **Example:** A rescue robot's beliefs might include at(robot, room_A), obstacle(blocked_door), and victim_location(room_C).
2. **Desires (Motivational State):** These are the agent's high-level goals and objectives. The agent may have multiple desires, some of which may be in conflict with each other. These represent what the agent *wants* to achieve.
    - **Example:** The rescue robot's desires might be to rescue_victim, recharge_battery, and avoid_damage.
3. **Intentions (Deliberative State):** These are a subset of the desires that the agent has committed to pursuing. An intention is a goal that the agent has chosen to act on, along with a plan for how to achieve it. This is the "sweet spot" of the BDI model, as it provides stability. Once an agent forms an intention, it commits to it and doesn't get sidetracked by every new piece of information.
    - **Example:** The robot's intention is to rescue_victim, and its chosen plan is [go_to(room_C), carry(victim), go_to(safe_zone)].

How It Blends Reactivity and Deliberation

The BDI architecture combines the best of both worlds through a continuous **deliberation cycle** that constantly re-evaluates the agent's state.

- **Deliberative Component (The Planner):** The "Desire-to-Intention" process is where deliberation happens. The agent periodically takes a step back to review its current beliefs and desires and then deliberates on which desire is the most important to pursue. It then selects an appropriate plan from its "plan library" (a set of pre-defined procedures) to turn that desire into a firm intention. This is where it engages in complex, goal-oriented reasoning, similar to a purely deliberative agent.
- **Reactive Component (The Executor):** Once a plan is chosen and becomes an intention, the agent enters a reactive execution phase. It focuses on executing the steps of the plan one at a time. This is where it acts more like a reactive agent, responding to immediate changes in the environment that might affect the current step. If a new belief—like a sudden obstacle blocking its path—contradicts its current plan, it doesn't scrap the entire plan; instead, it might find a quick reactive action to handle the immediate problem (e.g., move_around_obstacle). It's only if a major change occurs that it would revisit its entire intention.

This cycle of **perceiving**, **deliberating**, and **acting** provides a powerful balance. The agent isn't paralyzed by a long planning phase like a purely deliberative agent, because it can react to local changes during execution. At the same time, it isn't aimlessly wandering like a purely reactive agent, because its actions are guided by a long-term intention and a high-level goal. The BDI model allows the agent to be purposeful and efficient without being rigid.

Classical BDI agents gave us a powerful way to balance reactive agility with deliberative planning, but they were limited by rigid, pre-programmed rules and a fixed plan library. This worked in well-defined domains (like a rescue robot with a known map), but struggled in open, unpredictable environments.

Now, with LLMs, the same BDI ideas get a new life. Instead of relying on symbolic rules, an LLM can **dynamically form beliefs, infer desires, and generate intentions on the fly**. For example, a travel-planning BDI robot in the past would only know how to book hotels if a rule existed. But an LLM-based agent, when asked *"Plan me a Paris trip"*, can flexibly discover sub-goals (flights, hotels, attractions), retrieve real-time data via APIs, and adapt its intentions as conditions change (like flight cancellations).

The Role of LLMs in the BDI Framework

While classical BDI agents rely on a predefined, symbolic rule set for their "mental states," an LLM-based agent uses the **LLM itself as the central processing unit and knowledge base**. The LLM's vast training data and its ability to reason and generate text enable it to dynamically simulate and manage beliefs, desires, and intentions.

Here is a breakdown of the three key components in this new context:

1. Beliefs: In an LLM-based agent, beliefs are its internal model of the world. They are formed from a combination of several sources:

- **Pre-trained knowledge**: The foundational knowledge the LLM acquired during its training on a massive dataset.
- **Current context**: Information from the user's prompt and the ongoing conversation.
- **Real-time information**: Data retrieved from external tools, such as a search engine, an API, or a database. This is the equivalent of a classical agent's perception of the environment.
- **Memory**: Information stored from past interactions or sessions, often managed by an external memory module (e.g., a vector database) to overcome the LLM's context window limitations.

2. Desires: Desires are the agent's goals or objectives. They represent the states it wants to achieve. In an LLM-based agent, desires are often explicitly defined by the developer through system prompts or directly given by the user's request. For example, a user's prompt "Plan a trip to Paris for me" becomes a core desire for the agent to fulfill. An LLM can also infer sub-desires from a complex request, such as finding flights, booking a hotel, and creating a list of attractions.

3. Intentions: Intentions are the specific plans of action the agent commits to in order to achieve its desires. Unlike classical agents that rely on a pre-programmed "plan library," an LLM agent uses its reasoning capabilities to **dynamically generate a plan**. This process often involves a continuous loop of:

1. **Thinking**: The LLM reasons about the user's request and breaks down a complex goal into smaller, manageable sub-tasks.
2. **Acting**: The LLM calls on a tool (like a web search or a calendar API) to execute a step in the plan.

3. **Observing**: The LLM processes the output from the tool and evaluates its effectiveness. It then decides the next step or corrects its course if the result is not what it expected.

This "think-act-observe" loop, often referred to as a **ReAct** (Reasoning and Acting) framework, gives the LLM agent its ability to autonomously and flexibly solve complex, multi-step problems that were difficult to handle with a rigid, rule-based approach.

Key Differences from Classical Agents:

Feature	Classical BDI Agent	LLM-based AI Agent
Knowledge Base	Explicit symbolic rules and facts.	Pre-trained model weights, current context, and real-time external data.
Reasoning	Rule-based, logical deduction, and formal planning.	Natural language reasoning, pattern recognition, and dynamic plan generation.
Planning	Relies on a pre-defined "plan library" for a known set of problems.	Dynamically generates plans on the fly to adapt to new or unpredictable situations.
Flexibility	Limited to the rules programmed by the developer.	Highly flexible and can generalize to new tasks it was not explicitly trained for.

While BDI improves on purely reactive and deliberative systems, it still has its limits.

- It assumes that an agent can always cleanly separate beliefs, desires, and intentions, but in messy real-world scenarios, these boundaries blur.
- It can also become inefficient when the environment demands both **fast reflexes** and **long-term strategic reasoning** at the same time.

an **LLM-based customer support agent** might manage long-term goals like resolving a user's issue (deliberation) but needs a reactive layer to instantly flag harmful content, avoid hallucinations, or quickly answer simple FAQs without invoking heavy reasoning.

This gap led to the rise of **Layered (Hybrid) Architectures**, which explicitly combine the strengths of different models—reactive speed at the bottom, deliberative reasoning at the top, and coordination in between.

Layered (Hybrid) Architectures

Layered (Hybrid) Architectures are a sophisticated approach to building intelligent agents that combine the strengths of both **reactive** and **deliberative** systems. The core idea is to structure the agent's control system into distinct layers, each responsible for a different level of abstraction and a specific type of behavior.

This layered approach is designed to overcome the primary weaknesses of purely reactive and purely deliberative agents:

- **Reactive agents** are fast and responsive but lack long-term planning and can appear aimless.
- **Deliberative agents** are goal-oriented and can solve complex problems but are slow, computationally expensive, and struggle in dynamic, rapidly changing environments.

By integrating these two paradigms, a hybrid agent can both react instantly to immediate threats and engage in thoughtful, long-term planning to achieve complex goals.

The Three Key Layers

While the specific number and purpose of layers can vary, a common model for layered architectures includes three levels:

1. **The Reactive Layer (The "Instinct"):** This is the lowest and fastest layer. It is directly connected to the agent's sensors and actuators and is responsible for low-level, real-time responses. This layer operates on a simple stimulus-response model, similar to a reactive agent. It handles immediate, time-critical tasks without any complex reasoning.
    - **Example:** For a self-driving car, this layer's job is to apply the brakes instantly if an object suddenly appears in the road. It doesn't need to "think" about why or what the object is; it just reacts.
2. **The Sequencer/Behavioral Layer (The "Habit"):** This middle layer acts as an intermediary, managing routine behaviors and coordinating a sequence of actions to achieve a short-term goal. It operates at a higher level than the reactive layer, but it still doesn't engage in deep, abstract planning. It often uses pre-compiled routines or a simple script to execute a series of steps.
    - **Example:** In the self-driving car, this layer manages the process of a lane change. It handles the sequence of checking the mirrors, signaling, and turning the wheel in a smooth, coordinated manner. It responds to the deliberative layer's command to "change lanes" but handles the tactical execution itself.
3. **The Deliberative Layer (The "Grandmaster"):** This is the highest and slowest layer. It is responsible for long-term strategic planning, complex reasoning, and goal management. This layer maintains a world model, considers multiple options, and formulates a multi-step plan to achieve a high-level goal. It then passes down sub-goals or specific instructions to the lower layers for execution.
    - **Example:** This layer of the self-driving car is responsible for planning the entire route from point A to point B. It considers traffic, road conditions, and fuel stops to create an optimal, long-term plan, which it then delegates to the lower layers to execute.

This creates a robust and reliable agent. The agent is always capable of rapid, instinctive responses while simultaneously pursuing a logical, long-term strategy. This hybrid design is widely used in real-world applications such as robotics, autonomous vehicles, and industrial automation where a balance of speed and intelligence is critical.

In an LLM-based agent, the layered architecture is not about different pieces of code but rather about **different modes of operation** for the large language model itself. The LLM acts as the central brain that can switch its behavior to function in each of the three layers, providing a hybrid approach to problem-solving.

The LLM as the Three Layers

1. **Reactive Layer (The Reflex):** In this mode, the LLM provides an immediate, low-latency response without any deep reasoning or tool use. It's triggered by a specific prompt or a simple check of an external state. The LLM's vast knowledge base allows it to handle these responses, but the process is similar to a simple lookup or a canned response, not a multi-step plan.
    - **Example:** A support bot instantly responds with "I've received your request and will forward it to a human agent" based on a keyword trigger. This is a reflexive, immediate action.
2. **Sequencer/Behavioral Layer (The Routine):** The LLM operates here by following a pre-defined script or a set of instructions to achieve a short-term goal. The LLM is given a plan to follow and simply executes it step by step. This is often seen in frameworks that use a "ReAct" (Reasoning and Acting) loop where the LLM is prompted to think, then choose a tool, then observe the result. The LLM is orchestrating a known routine.
    - **Example:** When a user asks an agent to find a restaurant, the LLM first thinks "I need to find the user's location," then calls a `get_location` tool. After getting the location, it thinks "Now I need to search for restaurants," and calls a `search_restaurants` tool with the location as a parameter. It's following a structured, but not overly complex, plan.
3. **Deliberative Layer (The Strategist):** In this mode, the LLM uses its full reasoning power for long-term strategic planning. It breaks down complex, ambiguous goals into sub-goals, considers multiple options, and formulates a dynamic, multi-step plan from scratch. This is where the LLM's intelligence truly shines, as it can go beyond a simple script and create a novel solution. This layer may even delegate tasks to other, more specialized LLM agents in a "multi-agent" system.
    - **Example:** When a user asks an agent to "plan a summer vacation," the LLM's deliberative layer might reason, "First, I need to know the destination and dates. Then, I should research flights, hotels, and local activities. Finally, I will synthesize all this information into a cohesive itinerary." This is a high-level plan that requires abstract thinking and problem decomposition.

The LLM-Based Flow of Control

The flow between these layers is handled by a sophisticated **orchestration engine**, which is usually code that wraps the LLM. It manages the agent's state, selects tools, and prompts the LLM for the appropriate mode of behavior.

- **Bottom-up Activation:** An urgent observation from a tool (e.g., an error message or an unexpected event) can cause the orchestration engine to bypass the deliberative or behavioral layers and ask the LLM for an immediate, reactive response. This ensures the agent can handle real-world issues on the fly without getting stuck in a planning loop.
- **Top-down Delegation:** The deliberative layer, as the "manager," sets the overall goal and delegates tasks to the behavioral layer. The behavioral layer then uses its tools to execute the steps, and the reactive layer handles any low-level, immediate needs. This allows for a flexible and resilient architecture where the agent can adapt to the unpredictability of the real world while staying focused on its long-term objective.

we saw the Layered architectures, the clever attempt to get the best of both worlds by stacking a fast reactive layer with a deep-thinking deliberative layer

You can't just take a revolutionary jet engine and bolt it onto a horse-drawn carriage. The old blueprints aren't designed to handle this new power source. You need a new architecture, a new airframe, designed from the ground up to harness its unique capabilities.

So while the **LLM is the core in all these cases**, the surrounding “airframe” is outdated. It’s like installing a jet engine inside a carriage—it works, but the design holds it back.


This is precisely where our next topic, **CoALA**, comes in.

CoALA asks the fundamental question: **"If we place a powerful LLM at the very heart of an agent, how do we build the rest of the system—the memory, the actions, the decision-making—around it?"** It’s a modern blueprint for the age of LLMs, drawing inspiration from cognitive science to create a truly intelligent agent.

So, let's dive in and see how CoALA provides the framework for this new generation of AI.

1.4. Cognitive Architectures for Language Agents(CoALA) :

Cognitive Architectures for Language Agents (CoALA) as a framework to organize existing language agents and guide the development of new ones. CoALA positions the LLM as the core component of a larger cognitive architecture.



Under CoALA, a language agent stores information in memory modules , and acts in an action space structured into external and internal parts:
• **External actions** interact with external environments (e.g., control a robot, communicate with a human, navigate a website) through grounding.
• **Internal actions** interact with internal memories. Depending on which memory gets accessed and whether the access is read or write.
internal actions can be further decomposed into three kinds:
retrieval (read from long-term memory), **reasoning** (update the short-term working memory with LLM), and **learning** (write to long-term memory) .

Think of CoALA not as a specific piece of software, but as an **architect's blueprint for building an AI's mind**. It provides a structured framework, inspired by how our own human minds work, to design sophisticated AI agents.

CoALA proposes that to build a capable agent, we need to focus on three key pillars:

1. **Memory:** How does the agent store and recall information?
2. **Actions:** What can the agent actually *do*?
3. **Decisions:** How does the agent choose what to do next

Let's break down each of these pillars.

The Agent's Brain: The Four Memory Modules

An AI agent, just like us, needs different kinds of memory to function effectively. CoALA organizes this into four distinct modules.

- **Working Memory:** The agent's "conscious mind," holding current inputs, goals, and recently retrieved memories—temporary and constantly updated.


- **Episodic Memory:** A diary of past experiences and events, used to provide context and learn from previous situations.

- **Semantic Memory:** An encyclopedia of general knowledge, both pre-loaded and self-learned from reasoning and experiences.

- **Procedural Memory:** "How-to" knowledge for performing actions, stored both in the LLM's weights (implicit) and in explicit code or tools.

The Agent's Hands & Senses: The Action Space

Now that our agent has a brain, how does it interact with the world and its own mind? CoALA splits its abilities into two types of actions.



External Actions: Interacting with the World

These are the actions that connect the agent to an environment outside of its own mind. This is often called **"grounding"** because it grounds the agent in reality.

- **Physical Environments:** An LLM can act as the "brain" for a robot, translating a command like "get the red ball" into the physical movements needed to execute the task.
- **Dialogue with Humans:** The agent can talk to us, ask for clarification, and learn from our feedback.
- **Digital Environments:** This is the most common one today! It includes using "tools" like calling an API, browsing a website, or executing a piece of code.

Internal Actions: Managing Its Own Mind


These are mental actions the agent performs on its own memory.

- **Retrieval:** The act of **"recalling a memory."** The agent pulls information from its long-term Episodic or Semantic memory and places it onto its "workbench" (Working Memory) to think about.

- **Reasoning:** The act of **"thinking."** The agent takes the information in its Working Memory and processes it to generate new insights, summarize observations, or break down a problem.
- **Learning:** The act of **"saving a new memory."** This is crucial! In CoALA, learning is defined as the agent *writing* new information to its long-term memory. This could be adding a new experience to its diary (Episodic), a new fact to its encyclopedia (Semantic), or even a new skill to its code library (Procedural).

The Agent's Thought Process: Decision Making

So, we have an agent with memory and a set of possible actions. How does it decide what to do at any given moment? It follows a continuous decision-making loop, much like a chess player contemplating their next move. This is often a **"Propose-Evaluate-Select"** cycle.



1. **Propose:** The agent first generates one or more potential actions.
    - *Analogy:* A chess player thinks, "Okay, I could move my knight here, or I could advance my pawn."
2. **Evaluate:** It then assesses the quality or potential outcome of each candidate action.
    - *Analogy:* "If I move my knight, I threaten his queen, which is good. If I move my pawn, it weakens my defense, which is bad." The agent can even use its reasoning abilities to simulate the outcome of an action internally.

3. **Select:** Finally, it chooses the best action based on its evaluation.
    - *Analogy:* "Moving the knight is the superior option. I'll do that."

This loop repeats, allowing the agent to deliberate, plan, and choose its actions intelligently rather than just reacting impulsively.

Why This Blueprint Matters: The Big Picture

CoALA gives us a powerful and organized way to think about building smarter AI. It encourages us to:

- **Build with LEGOs:** Design modular agents where we can swap out memory or action components easily.
- **Combine Brains and Brawn:** Use code for structured, logical tasks (like planning) and the LLM for flexible, creative tasks (like generating ideas).
- **Create True Learners:** Design agents that don't just rely on pre-trained knowledge but actively learn and grow by updating their own memories and skills over time.

By using this architectural blueprint, we can move beyond simple chatbots and start building more robust, capable, and genuinely intelligent agents that can tackle complex problems in the real world.

Now that we've explored each architecture one by one — from symbolic deliberation to reactive reflexes, from BDI's balance to hybrid layering, and finally CoALA's LLM-driven cognition — the natural question is:

How do these approaches connect with each other, and how do we decide which one to use in practice?

Just like tools in a toolbox, no single architecture fits every situation. Each emerged as a response to the limitations of the previous one, and each shines in specific contexts. To really understand them, we need to see the bigger picture:

- how they evolved in relation to each other, and
- when it makes sense to choose one over the other.

This brings us to our next section: **"How They Relate and When to Choose."**

2.2 How They Relate and When to Choose

Understanding AI agent architectures isn't just about knowing their definitions — it's about knowing **how they connect** and **when each one is the right tool for the job**.

A. How They Relate

These architectures didn't appear randomly — they **evolved to overcome the limitations of the previous generation**:

1. **Deliberative (Logic-Based):**
    - First attempt at "thinking" machines.
    - Strong in planning but weak in real-time adaptation.
2. **Reactive:**
    - Emerged to fix responsiveness.
    - Great for dynamic environments but lacks foresight.
3. **BDI:**
    - Hybridized both — introducing structured "mental states" (beliefs, desires, intentions).
    - Balanced but can still be rigid when environments get too unpredictable.
4. **Layered (Hybrid):**
    - Added explicit **coordination between layers**.
    - Solves both immediate reactions and long-term planning in a flexible way.
5. **CoALA (Cognitive Architectures for Language Agents):**
    - Modern extension tailored for **LLMs**.
    - Embeds memory, reasoning, tool use, and language understanding natively.

You can think of it like a ladder: each step builds on the last to address **practical gaps in intelligence, flexibility, or efficiency**.

B. When to Choose

Architecture	Best For	Complexity	Performance	Adaptability

Deliberative (Symbolic/Logic)	Structured environments with clear rules (e.g., chess, scheduling).	**High** – needs explicit modeling of states, rules, and planning.	**Low–Medium** – slower due to heavy reasoning.	**Low** – struggles in dynamic, uncertain environments.
Reactive	Real-time, safety-critical, fast response tasks (e.g., obstacle avoidance in robots).	**Low** – simple rules or reflexes.	**High** – very fast responses.	**Low** – cannot adapt to new goals, easily brittle.
BDI	Agents needing goal-driven yet flexible behavior (e.g., rescue robots, multi-task AI assistants).	**Medium–High** – requires belief/desire/intention modeling and plan libraries.	**Medium** – faster than deliberative but slower than reactive.	**Medium** – can adapt to new inputs but bounded by plan library and design.
Layered (Hybrid)	Environments needing both reflexes and strategy (e.g., self-driving cars, customer support AI).	**High** – needs careful design of multiple layers and coordination.	**High** – balances fast reactions with deliberate planning.	**High** – can flexibly handle both short-term changes and long-term goals.

codingninjas

CoALA (Cognitive Architectures for LLM Agents)	Complex, open-ended tasks requiring reasoning + memory + tool use (e.g., research assistants, autonomous AI agents).	**Variable** – complexity managed by LLM + memory integration.	**Medium–High** – depends on LLM efficiency, can be slower on heavy reasoning.	**Very High** – dynamically adapts to novel tasks and unpredictable inputs.

Now that we've explored the different agent architectures—from purely logical planners to reactive reflexes, from goal-driven BDI systems to layered hybrids and even modern LLM-powered cognitive agents—you might notice a common theme: **there's no single architecture that fits every problem.** Each comes with trade-offs in complexity, performance, and adaptability.

This raises an important question: *once you've chosen an architecture, how do you actually structure the internal behavior of your agent so it's reusable, scalable, and easier to extend?*

That's where **Design Patterns** come in.

2.3 Design Pattern: Reusable Strategies Within the Architecture

A **design pattern** is a well-tested, reusable solution to a commonly occurring problem *within* a given architecture. It's a **specific building technique or component design**. It's not the whole blueprint, but a smart, proven way to build a part of it.

Following our house analogy, design patterns would be things like:

- The "kitchen work triangle" (a proven, efficient layout for the sink, stove, and refrigerator).
- A "cross-ventilation" window placement strategy for passive cooling.
- The specific design for a "load-bearing wall" or a "roof truss."

You use these proven patterns to solve smaller problems effectively within your grand architectural plan. In software, examples include the **Singleton pattern** (ensuring only one instance of an object exists) or the **Observer pattern** (allowing objects to subscribe to events). These aren't architectures themselves, but clever strategies you apply while building within an architecture.

In short: **Architecture is the city plan; design patterns are the best-practice designs for traffic intersections, parks, and buildings within that city.**

Why We Need Design Patterns

Architectures give us the *big picture*—how agents are structured and how they "think." But architecture alone doesn't solve recurring, practical challenges.

For example, suppose you're designing a **customer support AI**. Even if you've chosen a hybrid architecture, you'll still face tough questions:

- Should the agent carefully **plan steps** before replying, or respond instantly?
- When should it **call an external API** versus generating the answer itself?
- How can it **avoid hallucinations** while still being flexible?

These challenges appear again and again, regardless of the underlying architecture.

Design patterns are the **reusable strategies** that solve these problems. Just as software engineers use patterns like *Singleton* or *Observer* to organize code, in AI agent design we rely on patterns for **reasoning, interaction, memory, and tool use**.

They don't replace architectures—rather, they **cut across them**, making agents more practical and reliable.

Why Patterns Are Crucial for LLM-based Agents

With **LLM-based agents**, design patterns become even more important. LLMs are powerful but inherently unpredictable. Patterns bring:

- **Structure** → reduce randomness and hallucinations
- **Standardization** → make reasoning steps interpretable
- **Modularity** → allow combining strategies (e.g., Planning + Tool Use + Reflection)

Think of it this way:

- **Architecture** = the blueprint of a house (Colonial, Modern, Minimalist)
- **Design patterns** = the floor plans (open kitchen, central staircase, skylight) that make the house functional and livable

So, moving forward, we'll shift from **architectures** (the "big picture") to **design patterns** (the practical building blocks).

Design Pattern 1: Planning

Planning is a design pattern where the AI model first creates a comprehensive, step-by-step blueprint to solve a problem *before* taking any significant action. Think of it as a chef meticulously writing down every step of a complex recipe before even turning on the stove.

This pattern is built on four key components:

1. **World Model:** The agent's internal representation of the world, including its own state and the state of objects in the environment.
2. **Goals:** A description of the desired final state of the world.
3. **Actions:** A list of available actions, each defined by its preconditions (what must be true to perform the action) and effects (how the world changes after the action).
4. **Planner:** The reasoning engine that searches for a valid sequence of actions (the plan) to bridge the gap between the current state and the goal.

Once the plan is created, the agent executes it step by step. If a step fails, the agent may need to replan

How It Works

1. **Decomposition:** When presented with a complex prompt (e.g., "Summarize the key arguments in the last three research papers by Dr. Geoffrey Hinton on capsule networks"), the model doesn't immediately start searching or writing. Its first goal is to formulate a plan.
2. **Plan Generation:** The model outputs a structured plan, which might look like this:
    - **Step 1:** Identify the three most recent research papers by Geoffrey Hinton that focus on capsule networks.
    - **Step 2:** For the first paper, read the abstract and conclusion to identify the core hypothesis and results.
    - **Step 3:** For the second paper, do the same, and note any evolution from the first paper.
    - **Step 4:** For the third paper, repeat the process, focusing on the most current advancements.
    - **Step 5:** Synthesize the findings from all three papers into a cohesive summary, highlighting the progression of ideas.
3. **Execution:** The model (or an external system orchestrating the model) then executes each step in sequence. The output of one step often becomes the input for the next.

The Core: More Than a Simple Loop

The planning cycle isn't just a simple **Sense → Plan → Act**. It's a continuous, dynamic process that addresses real-world complexity:

- **Sense:** The agent perceives its environment, updating its internal **world model**. This model is often an incomplete, and potentially incorrect, representation of reality. The challenge of keeping this model accurate and up-to-date is known as the **Frame Problem**.
- **Plan:** The agent's planner, a sophisticated algorithm, searches for an optimal sequence of actions. This can involve:
    - **State-Space Search:** Starting from the current state and searching through a graph of possible future states until a goal state is reached. Algorithms like A* search are commonly used here.
    - **Plan-Space Search:** Starting with a high-level plan and iteratively refining it by adding actions and resolving conflicts until a complete, valid plan is formed.

- **Act:** The agent executes the plan one step at a time. This is where the world model is tested against reality.

A crucial aspect of this pattern is **replanning**. If the agent's actions have an unexpected outcome (e.g., a door it thought was open is locked), the world model is updated, and the agent may have to replan from the new, observed state. This makes the agent resilient to real-world uncertainty.

Strengths & Weaknesses

- **Strengths:**
  - **Structured & Predictable:** The process is transparent and easy to follow. You know what the AI is going to do before it does it.
  - **Efficient for Known Problems:** Excellent for tasks where the steps to a solution are well-understood and don't require much trial-and-error.
  - **Reduces Errors:** By thinking through the whole process upfront, it can avoid logical dead-ends.
- **Weaknesses:**
  - **Rigid & Brittle:** The primary drawback. If a crucial early step fails (e.g., a search API is down, or a paper can't be found), the entire plan can be invalidated. It struggles to adapt to unexpected obstacles.
  - **Not for Dynamic Environments:** If the problem space is constantly changing, a pre-made plan can quickly become obsolete.

Design Pattern 2: ReAct (Reasoning and Acting):

The **ReAct (Reasoning and Acting)** design pattern is a fundamental breakthrough in creating truly capable LLM agents. It's much more than just a technique; it's an architectural paradigm that turns a static LLM into a dynamic, problem-solving engine.

The core of ReAct lies in a simple yet profound idea: by interleaving **verbal reasoning** with **action-taking**, an LLM can overcome its inherent limitations and solve complex, multi-step tasks. It's a method of "thinking out loud" that makes the LLM's thought process transparent and allows it to interact with the real world.

The Anatomy of the ReAct Loop

The pattern is based on a cyclical, three-step process that continues until the goal is achieved. This loop is typically driven by a carefully designed prompt that structures the LLM's output.

1. **Thought:** This is the LLM's internal monologue. Before taking any action, the model is prompted to explicitly articulate its reasoning. This step serves several critical functions:
   - **Task Decomposition:** It breaks down a complex problem into smaller, manageable sub-tasks.
   - **Planning & Self-Correction:** It outlines the next step in its plan and allows for real-time adjustments if previous steps failed or returned unexpected results.

    - **Transparency:** It creates an audit trail, making the agent's decision-making process understandable and debuggable.
2. **Action:** Based on its thought, the LLM selects and calls an external **tool**. The LLM doesn't perform the action itself; it generates a structured command that an external orchestrator (like a LangChain **AgentExecutor**) can interpret and execute. The available tools are the agent's "senses" and "limbs," allowing it to access a dynamic, real-world environment. Common tools include search engines, calculators, code interpreters, and API calls.
3. **Observation:** This is the feedback loop. After the tool is executed, its output is returned to the agent. This result becomes a new piece of information that updates the agent's internal state (its "beliefs"). The observation is then included in the prompt for the next loop, enabling the LLM to learn and adapt with each step.

Why ReAct is a Game-Changer

ReAct's power lies in how it overcomes the two biggest limitations of a raw LLM:

- **1. Combating Hallucination:** A core weakness of LLMs is their tendency to confidently "hallucinate" incorrect facts because their knowledge is frozen at the time of training. ReAct directly solves this by forcing the LLM to **validate its reasoning against external facts**. By using a search tool, the agent can ground its conclusions in real-time, verifiable information, dramatically increasing factual accuracy.
- **2. Enabling Multi-Step Reasoning:** LLMs can struggle with complex, multi-step problems that require intermediate steps. By breaking down the task into smaller **Thought-Action** cycles, ReAct provides the LLM with a structured, step-by-step reasoning process. The "thought" component is essentially a verbal form of **Chain-of-Thought (CoT)** prompting, which has been shown to improve reasoning capabilities.

Drawbacks and Challenges

While powerful, **ReAct** has several practical challenges:

1. **Latency and Cost:** Each **Thought → Action → Observation** cycle triggers a **new LLM inference call**, which can slow down response times and increase monetary costs. This is a critical consideration for developers building production-ready agents.

2. **Prompt Engineering Complexity:** The agent's performance depends heavily on the quality of its prompt. Crafting prompts that consistently elicit the correct behavior requires expertise and often involves trial and error.

3. **Brittleness:** A single incorrect observation, hallucinated thought, or parsing error can derail the process. Building robust agents requires sophisticated error handling and recovery mechanisms.

Comparing the **ReAct** and **Planning** design patterns reveals a fundamental difference in how they approach problem-solving: one prioritizes **adaptability** while the other prioritizes **optimality**.

	Planning (Classical Approach)	ReAct (Adaptive Approach)
Core Idea	**Think first, then act.** The agent generates a complete, logical plan upfront and then executes it.	**Think, then act, then think again.** The agent reasons and acts in a continuous, iterative loop.
Execution Style	**Fixed Sequence.** A pre-computed, linear sequence of steps. If a step fails, the entire plan is invalid.	**Dynamic Loop.** The plan is built one step at a time, allowing for real-time adjustments and course correction.
Adaptability	**Brittle.** Struggles in dynamic, unpredictable environments. Replanning is a slow and expensive process.	**Robust.** Handles unexpected observations and tool failures gracefully, making it ideal for the real world.
Efficiency	Can be **computationally expensive** upfront (analysis paralysis). A lot of time is spent planning before any progress is made.	**Incrementally efficient.** The agent makes progress with each step, and the process only continues until the goal is met.
Implementation	Classical planning algorithms (e.g., A* search, STRIPS) working on a symbolic world model.	An LLM-based agent using a **ReAct prompt** and external tools. The LLM acts as both the planner and the executor.
Output	A formal, verified plan as the output of a planning algorithm.	A sequence of Thought, Action, Observation logs that represent the emergent plan.

When to Use Which?

The choice between these two patterns depends entirely on the nature of the problem and the environment.

Use the Planning Pattern When...

- **The environment is static and predictable.** There are no unexpected variables.
    - **Example:** A robotic arm on a factory assembly line. The positions of parts are known, and the steps to assemble them are fixed. A pre-planned sequence is faster and more reliable than a dynamic one.
- **Optimality is paramount.** You need to guarantee the most efficient or shortest path to the solution.

    - **Example:** A logistics system that plans the most fuel-efficient route for a fleet of trucks. The cost of a suboptimal plan is high, so the upfront planning cost is justified.
- **The problem space is closed and well-defined.** All possible actions, states, and goals are known in advance.
    - **Example:** Solving a Rubik's Cube. The problem has a finite set of states and moves, so a planning algorithm can find the optimal solution.

Use the ReAct Pattern When...

- **The environment is dynamic and uncertain.** The agent needs to react to real-time information.
    - **Example:** A customer support chatbot that needs to answer questions, check a knowledge base, and look up a user's order status in a live database. The outcome of each action is unpredictable.
- **The problem is open-ended or requires external information.** You cannot define all possible states and actions beforehand.
    - **Example:** A web research agent tasked with answering a complex question like "What are the latest developments in fusion energy?" It must dynamically decide which search queries to run based on previous results.
- **Flexibility and robustness are more important than guaranteed optimality.** A good-enough, adaptable solution is better than a perfect, brittle one.
    - **Example:** A scientific discovery agent that runs experiments and updates its hypothesis based on the results. Each step is an observation that informs the next action, making a rigid plan impossible.

In a modern context, **ReAct is the more common and powerful pattern** for general-purpose LLM agents because most real-world problems are dynamic and require access to external, real-time data. Classical Planning is often used in very specific, constrained domains where the environment is perfectly modeled.

React Agents vs Reactive Agents:

Reactive agents and **ReAct agents** represent two fundamentally different approaches to building intelligent systems. While both are designed to respond to the environment, they differ in their core architecture, decision-making process, and level of cognitive complexity.

Reactive Agent: The Reflexive System

A **reactive agent** operates on a simple **stimulus-response** loop. It perceives the current state of its environment and immediately performs a predefined action based on a set of simple, hard-coded rules. It has **no memory**, does not maintain an internal model of the world, and cannot plan for the future. Its behavior is entirely reflexive, much like a thermostat turning on the heater when the temperature drops below a certain threshold.

- **Decision-Making:** The agent's actions are determined by a simple mapping from a specific perception to a specific action. (e.g., "IF obstacle in front THEN turn right").

- **Strengths:** They are **fast, efficient,** and computationally lightweight. They are ideal for real-time tasks in predictable environments where quick reflexes are more important than complex reasoning.
- **Weaknesses:** They are **inflexible** and cannot handle new or complex problems. They cannot learn or adapt to an unfamiliar environment.

ReAct Agent: The Thinking System

A **ReAct agent** is a modern, Large Language Model (LLM)-based agent that combines **Reasoning** and **Acting**. Instead of a simple reflex, it operates on a dynamic, iterative **Thought → Action → Observation** loop. The agent's decision-making is a conscious, step-by-step process.

- **Reasoning:** The agent's core is an LLM that serves as its "brain." It verbalizes a **Thought** to plan its next step, break down a complex problem, and decide which external tool to use.
- **Acting:** Based on its **Thought**, the agent calls an external **Tool** (e.g., a search engine, a calculator, an API). This is how the agent interacts with the real world.
- **Observation:** The agent observes the output of the tool, and this new information is fed back into the LLM as part of the next **Thought** loop. This allows the agent to **self-correct** and dynamically adapt its plan.

Comparison Table between Reactive Agent vs ReAct Agent

Feature	**Reactive Agent**	**ReAct Agent**
Core Principle	**Reflexive:** Sense → Act	**Iterative:** Thought → Action → Observation
Cognitive Ability	None. No planning or reasoning.	High. Uses an LLM for complex reasoning.
Memory	None. Stateless.	Has short-term memory (the Thought history) and can use long-term memory.

Environment	Best for static, predictable environments.	Best for dynamic, open-ended environments.
Flexibility	**Rigid.** Cannot handle unforeseen situations.	**Highly adaptable.** Can adjust its plan on the fly.
Example	An obstacle-avoiding robot, a thermostat.	A web research agent, a customer service chatbot.

Design Pattern 3: Tool Use Design Pattern

Both Planning and ReAct are reasoning frameworks, but they are just brains in a vat. **Tool Use** is the pattern that gives these brains hands and eyes to interact with the world. Tools are external programs, APIs, or functions that the AI can call to perform tasks it cannot do internally.

Language models are trained on a static dataset. They don't know the current time, can't browse the internet, and struggle with precise mathematical calculations. Tools bridge this gap by giving the model access to **live data and specialized capabilities**.

How It Works

1. **Tool Availability:** The system defines a set of available tools for the model. Each tool has a name, a clear description of what it does, and the parameters it expects (e.g., get_weather(city: string, unit: 'celsius' | 'fahrenheit')).
2. **Tool Selection:** During its reasoning process (either in a Planning step or a ReAct Thought), the model determines it has a knowledge gap. It reviews the descriptions of the available tools and selects the one that best fits its current need.
3. **Execution & Observation:** The model formulates a call to the selected tool with the correct parameters. The external environment executes this call (e.g., makes an API request to a weather service) and feeds the result back to the model as an "Observation."

Examples Common Tools:

- **Web Search:** To get up-to-date information.
- **Calculator:** For precise mathematical operations.
- **Code Interpreter:** To run Python or other code for complex logic, data analysis, or simulations.
- **Database Query Engine:** To retrieve structured information from a SQL or NoSQL database.

- **Calendar/Email APIs:** To manage schedules or draft communications.

Tool use is the **"Action"** in the ReAct loop and the **"Execution"** of a step in a Planning framework.

a. Tool Use in the Planning Pattern

In the **Planning** pattern, tool use is a **consequence of the plan, not a part of the planning process itself**. The agent's deliberation phase is an internal, symbolic process. It formulates a complete, linear sequence of tool calls based on its internal world model before a single tool is invoked.

- **Role of the tool:** A tool is an **atomic function** with known preconditions and effects. The planner's job is to arrange these functions in the correct order.
- **Execution:** Once the plan is finalized, the agent executes the tool calls in the pre-determined sequence. There is no real-time feedback loop. If a tool call fails, the entire plan may be abandoned, and a new planning cycle must be initiated.
- **Control flow:** This is a **top-down** process. The high-level plan dictates the low-level actions.

Example (Conceptual): A classical planning agent tasked with "getting the current weather in Paris" might have a pre-defined plan:

1. **Plan:**
    - Call get_city_coordinates with "Paris" as the input.
    - Call get_weather_by_coords with the coordinates from the previous step.
2. **Act:** The agent executes these two tool calls sequentially.

b. Tool Use in the ReAct Pattern

In the **ReAct** pattern, **tool use is the central mechanism of the planning process**. The agent's thinking and acting are intertwined in a continuous feedback loop. It dynamically decides which tool to use next based on the observation from the previous tool's output.

- **Role of the tool:** A tool is an **external source of information or an action-taking capability**. The LLM decides what to do with the output of a tool, allowing for dynamic, data-driven decisions.
- **Execution:** The agent executes tools one by one, with each tool's output being immediately fed back to the LLM for the next step of reasoning.
- **Control flow:** This is a **dynamic, adaptive loop**. The agent's next action is always informed by its latest observation.

Example (LangChain-based): An LLM agent using the ReAct pattern for the same task might demonstrate the following behavior:

1. **Thought:** "I need to get the weather in Paris. I can use my web_search tool."
2. **Action:** web_search("current weather in Paris")
3. **Observation:** "The current temperature in Paris is 15°C and it's raining."

4. **Thought:** "I have the temperature and conditions. This is the final answer."
5. **Action:** Final Answer: The current weather in Paris is 15°C and it's raining.

In this example, the agent dynamically decides to perform a single, broad search rather than two specific ones, showing its flexible, on-the-fly planning.

When We Use Which

The choice between the two patterns for tool use depends on the **certainty of the environment and the complexity of the task**.

- **Use Planning:** When the sequence of tool calls is **known and fixed**, and the environment is **static**. This is ideal for simple, repetitive tasks that don't require real-time adaptation. For example, a pre-defined chain in LangChain (SequentialChain) that gets a user's name and then emails them, where the steps are always the same.
- **Use ReAct:** When the required sequence of tool calls is **unknown**, and the agent must **adapt to an unpredictable environment**. This is essential for open-ended, multi-step problems that require real-time information. A single AgentExecutor with a set of tools can handle a vast range of queries, dynamically selecting the right tool at the right time.

Design Pattern 4: Reflection Design Pattern

Reflection is a meta-cognitive pattern where the model critically evaluates its own output to identify flaws, refine its reasoning, and improve the final result. It’s like an author writing a draft and then putting on an editor's hat to review and improve it.

The first attempt at a solution is often imperfect. By adding an explicit reflection step, the model can catch errors, address missed requirements, or find more elegant solutions. It's a mechanism for **self-correction and iterative improvement**.

The Core Mechanics: A Structured Feedback Loop


At its heart, reflection is a specialized feedback loop that operates on the agent's internal reasoning logs. It is distinct from the **ReAct** pattern's **Thought-Action-Observation** loop, as it typically runs *after* a task attempt (or a failure) has concluded.

1. **The Input: The Agent's History** The reflection process doesn't just analyze the final answer; it examines a full, detailed log of the agent's actions, including all **Thoughts**, **Actions**, **Observations**, and any errors that occurred. This history provides the raw data for the agent's self-analysis.

2. **The Reflection Engine: The Critic Prompt** The reflection itself is initiated by a secondary LLM call with a carefully crafted prompt. This prompt instructs the LLM to act as a "critic" or "teacher" and asks targeted questions to guide the self-evaluation. The prompt might ask:
    - "What was the overall goal of the task?"
    - "Based on the log, what was the primary reason for failure?"
    - "Was there a hallucination, a bad tool call, or a logical error?"
    - "What are two concrete 'lessons learned' that could improve performance on a similar task in the future?"
3. **The Output: Structured Self-Knowledge** The output of the reflection engine is a structured text containing the critique. This is not just a free-form summary but often includes distinct sections like:
    - **Critique:** A high-level summary of the flaws.
    - **Reasoning:** A deeper explanation of *why* the flaws occurred.
    - **Lessons Learned:** Generalizable, actionable knowledge that can be stored for later use.

The Reflection Methodology

The process of self-reflection is an iterative cycle of learning from experience. It typically follows these steps:



The Four-Step Learning Cycle:

Step 1: Execution ("Just Do It")

What happens here?
The agent rolls up its sleeves and attempts the task. It follows its initial plan, step-by-step.

Key Action:
The agent keeps a detailed log—like a pilot's flight journal—of everything it thinks, every action it takes, and every result it observes.

Step 2: Evaluation ("The Review Session")

What happens here?
After the task is done (or if it gets stuck), we bring in a "critic." This is often a separate, unbiased AI prompted to act as a teacher.

Key Action:
The critic reads the entire log from Step 1 and performs a structured analysis. It asks critical questions:

- *Was the goal achieved?*
- *Were there unnecessary or inefficient steps?*
- *Where did things go wrong? Was it a logic error, or did a tool fail?*
- *What was the single biggest mistake?*

Step 3: Refinement ("The Study Plan")

What happens here?
Using the critic's feedback from Step 2, the agent now creates a new, improved strategy.

Key Action:
The agent generates a list of "Lessons Learned" or a revised plan. This is its new "study guide" for tackling the problem.

Instructor's Analogy:
The student gets their graded exam back, reads the professor's feedback, and makes a new study plan focused on the concepts they got wrong. They are now preparing for a retake.

Step 4: Integration ("Saving to Memory")

What happens here?
This is the most crucial step for long-term learning. We make sure the lesson isn't forgotten.

Key Action:
The "Lessons Learned" are saved into the agent's long-term memory (like saving a note in a database). This ensures the knowledge can be recalled for future, similar tasks.

How the Cycle Repeats

The power of this methodology is the loop. After **Integration**, the agent goes right back to **Step 1: Execution**.

- **On the same task:** It can immediately make a second, smarter attempt using its new plan.
- **On a new, similar task:** When it faces a new challenge, it can search its long-term memory for relevant *lessons learned* and start from a much more advanced position.

This cycle is not just a way for an agent to *learn* from its experiences. It also highlights a deeper principle that underpins advanced agent design: **Reflection**.

Just as students learn best when they pause, review feedback, and adjust their strategies, agents become smarter and more resilient when they can *reflect* on their own actions and reasoning.

This is where **Reflection in Agent Architectures** comes in. Unlike the four-step cycle, reflection isn't a standalone pattern—it acts as a *booster* inside many different architectures. Whether it's a logic-driven BDI system, a layered hybrid agent, or modern LLM-based agents like CoALA, reflection plays a critical role in ensuring the agent doesn't just react blindly but continuously improves its performance.

Reflection in Agent Architectures

Reflection is not a standalone pattern but an essential component that enhances other architectures.

- **Logic/BDI Architectures:** Reflection maps directly to the **re-evaluation** phase of a BDI agent. When a plan (intention) fails, the agent reflects on its beliefs and desires to form a new intention.
- **Layered (Hybrid) Architectures:** Reflection is a function of the **top deliberative layer**. This layer can periodically review the logs of the lower, reactive layers to identify persistent issues and update the agent's high-level strategy.
- **CoALA/LLM Agents:** This is where the Reflection pattern shines. Techniques like **Reflexion** and **Self-RAG** explicitly incorporate a reflective loop. The agent's reasoning is no longer a single-pass chain of thought but a continuous process of self-correction. For example, a reflective RAG agent can review retrieved documents, determine they are irrelevant, and then use that "reflection" to generate a better search query for the next attempt. This makes the agent far more robust and accurate.

Example in Action

Task: "Explain gravity to a five-year-old."

- **Initial Generation:** "Gravity is a fundamental interaction of nature that causes mutual attraction between all things with mass. It is described by Einstein's theory of general relativity, where it is a consequence of the curvature of spacetime caused by the uneven distribution of mass."

- **Reflection (Critique Prompt):** "Review this explanation. Is it appropriate for a five-year-old?"
- **Critique (Model's Thought):** "This explanation is far too complex. It uses terms like 'fundamental interaction,' 'general relativity,' and 'curvature of spacetime,' which a five-year-old will not understand. The explanation fails to meet the core requirement of the audience."
- **Refined Generation:** "Imagine the world is a big, bouncy trampoline! And you are a big bowling ball sitting on it. You make a big dip, right? Now, if you roll a little marble nearby, it won't go straight—it will roll down into the dip you made. Gravity is like that! Big things like the Earth make a giant, invisible dip that keeps you and everything else from floating away."

By combining these four patterns—**Planning/ReAct** for reasoning, **Tools** for acting, and **Reflection** for quality—you can design AI systems that are not just knowledgeable but are truly capable, adaptive, and reliable problem-solvers.

Comparison table:

Design Pattern	Core Idea	Strengths	Weaknesses	When to Use
Planning	Create a step-by-step plan before acting (like writing a recipe before cooking).	- Structured & predictable- Efficient for known tasks- Reduces logical errors	- Rigid, brittle if environment changes- Struggles in dynamic settings	- Static, predictable environments- When optimality is crucial (e.g., logistics, factory tasks)
ReAct (Reasoning + Acting)	Interleave *Thought* → *Action* → *Observation* in a loop for adaptive reasoning.	- Highly adaptable- Transparent reasoning (audit trail)- Handles dynamic environments	- Higher latency & cost- Sensitive to prompt quality- Can be brittle if a tool fails	- Open-ended, multi-step problems- When environment is uncertain or changing
Tool Use	Extend LLMs with external tools (APIs, functions, databases) for tasks they can't do internally.	- Bridges LLM limitations (math, real-time data, APIs)- Enables richer actions & interactions	- Requires correct tool selection & parameter use- Misuse can cause errors	- When tasks need external info/actions- Examples: search, database queries, code execution

Reflection	Agent critiques its own output after execution, refining via self-feedback.	- Improves quality & accuracy- Learns from mistakes- Enables iterative improvement	- Adds extra inference cost- Risk of over-analysis (“paralysis”)	- When accuracy & reliability matter- Complex reasoning tasks that benefit from self-correction

Conclusion:

- **No Single "Best" Architecture**: There is no one-size-fits-all agent architecture. The choice between a **deliberative** (slow, complex planning), **reactive** (fast, direct response), or **hybrid** approach depends entirely on the specific task's requirements.
- **Hybrid Architectures are the Future**: The most powerful and robust agents are **hybrid** models, which combine the strengths of deliberative and reactive systems. The **Belief-Desire-Intention (BDI)** framework is a prime example of this balanced approach.
- **LLMs Act as a Dynamic Engine**: The rise of large language models (LLMs) has revolutionized agent design. They serve as a flexible "brain" that can handle reasoning, planning, and self-correction, enabling more sophisticated behavior than was previously possible.
- **Design Patterns Enhance Capabilities**: Architectures provide the framework, but **design patterns** like **ReAct** (Reasoning and Acting), **Tool Use**, and **Reflection** are what give an agent its specific abilities. These patterns allow agents to plan dynamically, interact with the external world, and learn from their mistakes.