Address finder UI component

Use the address finder when users need to quickly find and enter an address as part of a form or workflow. This component reduces manual typing, speeds up completion, and helps ensure accurate, standardised address data.

UI component

The address finder component is used to lookup an address using a postcode. In the event an address cannot be found a manual entry link is available to the user.

Anatomy

1. Use existing address checkbox (optional)
2. Address finder search (form input field with suffix and helper text)
3. Tertiary buttons (optional)
4. Search result popover list

Behaviour

- Checking the use existing address checkbox (1) uses an address previously chosen in the workflow.
- Performing a postcode search (2) returns results in a scrollable popover list (4).
- Tertiary buttons are shown inline and wrap when wider than the available space.

Search states

The postcode search uses default form input field states for default, active and error states. Searching and search results states use the popover component.

Address finder search field



Search results popover

The search results popover shows the results of the search and can also contain a header and footer allowing the user to take further action. This is particularly useful when providing contextual guidance, and when other UI elements such as tertiary buttons are hidden by the popover.

Anatomy



1. Popover action bar
2. Text area
3. Action button (optional)
4. Search results

Behaviour

- The popover action bar header always shows at the top of the search results list and scrolls with content.
- The popover action bar footer always shows at the bottom of the search results list and scrolls with content.
- The use of an action button (3) is optional.
- Content in the action bar can be stacked.



Example of a popover action bar footer with an action button | **Example of a stacked action bar footer**

Spacing

Completed address

The completed address is shown as a single, compact line of text. This avoids the the use of multiple input fields and makes it clear that the address can't be edited directly.

Anatomy

1. Address text (body)
2. Actions (optional)

Behaviour

- The address text (1) can be shown alongside optional actions (2).
- When the address is longer than the available space it should wrap onto a new line.
- Actions use the text link with icon component.
- Multiple actions can be shown.

Spacing

Component parts

Component parts are used for Figma components.



Version control:	Date of design update:	Notable updates:
V1 added	17.07.2025	N/A