

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

**“GnanaSangama”, Belgaum -590014,
Karnataka.**



LAB REPORT

on

BIG DATA ANALYTICS

Submitted by

**RAGHAVENDRA R KURDEKAR
(1BM21CS409)**

in partial fulfillment for the award of the degree of
BACHELOR OF ENGINEERING
in
COMPUTER SCIENCE AND ENGINEERING



B.M.S. COLLEGE OF ENGINEERING

(Autonomous Institution under VTU)

BENGALURU-560019

Mar-2023 to July-2023

B. M. S. College of Engineering
Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “LAB COURSE **BIG DATA ANALYTICS** ” was **carried** out by **RAGHAVENDRA R KURDEKAR (1BM21CS409)**, who is a bonafide student of **B. M. S. College of Engineering**. It is in partial fulfillment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum during the year 2023. The Lab report has been approved as it satisfies the academic requirements in respect of a **Big Data Analytics - (20CS6PEBDA)** work prescribed for the said degree.

Dr. Manjunath D R
Assistant Professor

Dr. Jyothi S Nayak
Professor and Head of Department

Index Sheet

Sl. No.	Experiment Title
01	MongoDB Commands
02	Cassandra program for Employee details
03	Cassandra Library Database
04	Hadoop Commands
05	Word Count program in Hadoop
06	Average Temperature in Hadoop
07	Mean Max Temperature in Hadoop
08	Map Reduce Program in Hadoop using Joins
09	Spark program for Word Count
10	Spark program for Word Count greater than 4.

Program 01: MongoDB commands

To execute create, insert, update, find and count commands of MongoDB

```
$mongosh
```

```
test> show dbs; admin
```

```
40.00  KiB config 60.00
```

```
KiB local 72.00 KiB test>
```

```
use database1
```

```
database1> db.createCollection("student"); database1>
db.student.insert({_id:1,StudName:"student1",Sem:6});
{ acknowledged: true, insertedIds: { '0': 1 } } database1>
db.student.insert({_id:2,StudName:"student2",Sem:6});
{ acknowledged: true, insertedIds: { '0': 2 } } database1>
db.student.insert({_id:3,StudName:"student3",Sem:6});
{ acknowledged: true, insertedIds: { '0': 3 } } database1>
db.student.insert({_id:4,StudName:"student4",Sem:6});
{ acknowledged: true, insertedIds: { '0': 4 } } database1>
db.student.insert({_id:5,StudName:"student5",Sem:6});
{ acknowledged: true, insertedIds: { '0': 5 } } database1>
db.student.insert({_id:6,StudName:"student6",Sem:6});
{ acknowledged: true, insertedIds: { '0': 6 } }
database1> show collections student
database1> db.student.find()
```

```
[
  { _id: 1, StudName: 'student1', Sem: 6 },
  { _id: 2, StudName: 'student2', Sem: 6 },
  { _id: 3, StudName: 'student3', Sem: 6 },
  { _id: 4, StudName: 'student4', Sem: 6 },
  { _id: 5, StudName: 'student5', Sem: 6 },
  { _id: 6, StudName: 'student6', Sem: 6 } ]
```

```
database1> db.student.find({StudName:"student1"}); [ { _id: 1,
StudName: 'student1', Sem: 6 } ]
```

```
database1> db.student.count()
```

```
6
```

```
` database1> db.student.find({Sem:6});
```

```
[
  { _id: 1, StudName: 'student1', Sem: 6 },
  { _id: 2, StudName: 'student2', Sem: 6 },
  { _id: 3, StudName: 'student3', Sem: 6 },
  { _id: 4, StudName: 'student4', Sem: 6 },
  { _id: 5, StudName: 'student5', Sem: 6 },
  { _id: 6, StudName: 'student6', Sem: 6 }
]
```

```
database1> db.student.update({_id:4,StudName:"student4"},{$set:{Sem:7}},{upsert:
true});
```

```
database1> db.student.find()
```

```
[
  { _id: 1, StudName: 'student1', Sem: 6 },
  { _id: 2, StudName: 'student2', Sem: 6 },
  { _id: 3, StudName: 'student3', Sem: 6 },
  { _id: 4, StudName: 'student4', Sem: 7 },
  { _id: 5, StudName: 'student5', Sem: 6 },
  { _id: 6, StudName: 'student6', Sem: 6 }
]
```

```
database1> db.student.find().pretty()
```

```
[
  { _id: 1, StudName: 'student1', Sem: 6 },
  { _id: 2, StudName: 'student2', Sem: 6 },
  { _id: 3, StudName: 'student3', Sem: 6 },
  { _id: 4, StudName: 'student4', Sem: 7 },
  { _id: 5, StudName: 'student5', Sem: 6 },
  { _id: 6, StudName: 'student6', Sem: 6 }
]
```

```
database1> db.student.update({_id:5,StudName:"student5"},{$unset:{Sem:6}},{upser
```

```
t:true});
database1> db.student.find().pretty()
```

```
[
  { _id: 1, StudName: 'student1', Sem: 6 },
  { _id: 2, StudName: 'student2', Sem: 6 },
  { _id: 3, StudName: 'student3', Sem: 6 },
  { _id: 4, StudName: 'student4', Sem: 7 },
  { _id: 5, StudName: 'student5' },
  { _id: 6, StudName: 'student6', Sem: 6 }
]
```

```
database1> db.student.update({_id:6},{ $set:{OE:"OR"}},{upsert:true}); database1>
db.student.find()
```

```
[
  { _id: 1, StudName: 'student1', Sem: 6 },
  { _id: 2, StudName: 'student2', Sem: 6 },
  { _id: 3, StudName: 'student3', Sem: 6 },
  { _id: 4, StudName: 'student4', Sem: 7 },
  { _id: 5, StudName: 'student5' },
  { _id: 6, StudName: 'student6', Sem: 6, OE: 'OR' }
]
```

```
database1> db.student.find({OE:"OR"});
[ { _id: 6, StudName: 'student6', Sem: 6, OE: 'OR' } ]
```

```
database1> db.student.count({Sem:6});
4
```

```
database1> db.student.find({Sem:6}).limit(4);
[
  { _id: 1, StudName: 'student1', Sem: 6 },
  { _id: 2, StudName: 'student2', Sem: 6 },
  { _id: 3, StudName: 'student3', Sem: 6 },
  { _id: 6, StudName: 'student6', Sem: 6, OE: 'OR' }
] database1> db.student.find({StudName:"student2",Sem:6}); [ { _id: 2,
StudName: 'student2', Sem: 6 } ]
```

```
database1> db.student.find().sort({StudName:1}).pretty();
```

```
[
  { _id: 1, StudName: 'student1', Sem: 6 },
  { _id: 2, StudName: 'student2', Sem: 6 },
  { _id: 3, StudName: 'student3', Sem: 6 },
  { _id: 4, StudName: 'student4', Sem: 7 },
  { _id: 5, StudName: 'student5' },
  { _id: 6, StudName: 'student6', Sem: 6, OE: 'OR' }
] database1> db.student.find().sort({StudName:-1}).pretty();
```

```
[
  { _id: 6, StudName: 'student6', Sem: 6, OE: 'OR' },
  { _id: 5, StudName: 'student5' },
  { _id: 4, StudName: 'student4', Sem: 7 },
  { _id: 3, StudName: 'student3', Sem: 6 },
  { _id: 2, StudName: 'student2', Sem: 6 },
  { _id: 1, StudName: 'student1', Sem: 6 }
]
```

```
database1> db.student.find().skip(3).pretty()
```

```
[
  { _id: 4, StudName: 'student4', Sem: 7 },
  { _id: 5, StudName: 'student5' },
  { _id: 6, StudName: 'student6', Sem: 6, OE: 'OR' }
]
```

```
database1> db.student.count({Sem:7});
```

```
1
```

Program 02: Cassandra Commands

Perform the following DB operations using Cassandra

1. Create a keyspace by name Employee

```
create keyspace Employee with replication = {  
    ... 'class':'SimpleStrategy',  
    ... 'replication_factor':1 ... }; use  
Employee;
```

2. Create a column family by name Employee-Info with attributes Emp_Id,
Primary Key, Emp_Name, Designation, Date_of_Joining, Salary, Dept_Name

```
create table EmployeeInfo (  
    ... EmplID int PRIMARY KEY,  
    ... EmplName text,  
    ... Designation text,  
    ... DateOfJoining timestamp,  
    ... Salary int,  
    ... DeptName text  
    ... );
```

3. Insert the values into the table in batch

```
begin batch
```

```
insert into EmployeeInfo (EmplID, EmplName,  
Designation, DateOfJoining, Salary, DeptName) values  
(101, 'employee1', 'designation1', '2020-03-29', 40000,  
'dept1')
```

```
insert into EmployeeInfo (EmplID, EmplName,  
Designation, DateOfJoining, Salary, DeptName) values  
(102, 'employee2',
```


'designation2', '2020-06-04', 60000, 'dept1') insert into EmployeeInfo

(EmplID, EmplName, Designation, DateOfJoining, Salary,

DeptName) values (103,

'employee3',

'designation3', '2020-04-21', 75000, 'dept1')

insert into EmployeeInfo (EmplID, EmplName, Designation, DateOfJoining, Salary, DeptName) values (104, 'employee4', 'designation4', '2020-12-02', 90000, 'dept2')

insert into EmployeeInfo (EmplID, EmplName, Designation, DateOfJoining, Salary, DeptName) values (105, 'employee5', 'designation5', '2020-09-11', 15000, 'dept2') apply batch;

	emplid	dateofjoining	deptname	designation	emplname	salary
105	2020-09-10 18:30:00.000000+0000	dept2	designation5	employee5	15000	104 2020-12-01 18:30:00.000000+0000 dept2 designation4 employee4 90000
102	2020-06-03 18:30:00.000000+0000	dept1	designation2	employee2	60000	101 2020-03-28 18:30:00.000000+0000 dept1 designation1 employee1 40000
103	2020-04-20 18:30:00.000000+0000	dept1	designation3	employee3	75000	

4. Update Employee name and Department of Emp-Id 121

insert into EmployeeInfo (EmplID, EmplName, Designation, DateOfJoining, Salary, DeptName) values (121, 'employee6', 'designation6', '2020-10-18', 45000, 'dept1'); select * from

EmployeeInfo;

	emplid	dateofjoining	deptname	designation	emplname	salary
105	2020-09-10 18:30:00.000000+0000	dept2	designation5	employee5	15000	121 2020-10-17 18:30:00.000000+0000 dept1 designation6 employee6 45000
104	2020-12-01 18:30:00.000000+0000	dept2	designation4	employee4	90000	102

```

2020-06-03 18:30:00.000000+0000 | dept1 | designation2 | employee2 | 60000 101 |
2020-03-28 18:30:00.000000+0000 | dept1 | designation1 | employee1 | 40000 103 | 2020-04-20
18:30:00.000000+0000 | dept1 | designation3 | employee3 | 75000
update EmployeeInfo SET EmplName='employee7', DeptName='dept2' where EmplID=121;
select * from EmployeeInfo;

```

	emplid	dateofjoining	deptname	designation	emplname	salary
105	2020-09-10 18:30:00.000000+0000	dept2	designation5	employee5	15000 121	2020-10-17
	18:30:00.000000+0000	dept2	designation6	employee7	45000 104	
	2020-12-01 18:30:00.000000+0000	dept2	designation4	employee4	90000 102	
	2020-06-03 18:30:00.000000+0000	dept1	designation2	employee2	60000 101	
	2020-03-28 18:30:00.000000+0000	dept1	designation1	employee1	40000 103	2020-04-20
	18:30:00.000000+0000	dept1	designation3	employee3	75000	

5. Sort the details of Employee records based on salary

```

select * from Employee_info where Emp_id in(101,102,103,104,121,105)
order by salary desc;

```

	emplid	dateofjoining	deptname	designation	emplname	salary
105	2020-09-10 18:30:00.000000+0000	dept2	designation5	employee5	15000 121	2020-10-17
	18:30:00.000000+0000	dept2	designation6	employee7	45000 104	
	2020-12-01 18:30:00.000000+0000	dept2	designation4	employee4	90000 102	
	2020-06-03 18:30:00.000000+0000	dept1	designation2	employee2	60000 101	
	2020-03-28 18:30:00.000000+0000	dept1	designation1	employee1	40000 103	2020-04-20
	18:30:00.000000+0000	dept1	designation3	employee3	75000	

6. Alter the schema of the table Employee_Info to add a column Projects which stores a set of Projects done by the corresponding Employee.

```

alter table EmployeeInfo add Projects text; select * from

```

```

EmployeeInfo;

```

	emplid	dateofjoining	deptname	designation	emplname	projects	salary
105	2020-09-10 18:30:00.000000+0000	dept2	designation5	employee5	null	15000 121	
	2020-10-17 18:30:00.000000+0000	dept2	designation6	employee7	null	45000 104	
	2020-12-01 18:30:00.000000+0000	dept2	designation4	employee4	null	90000 102	
	2020-06-03 18:30:00.000000+0000	dept1	designation2	employee2	null	60000 101	
	2020-03-28 18:30:00.000000+0000	dept1	designation1	employee1	null	40000 103	
	18:30:00.000000+0000	dept1	designation3	employee3	null	75000	

```
18:30:00.000000+0000 | dept1 | designation2 | employee2 | null | 60000 101 | 2020-03-28 18:30:00.000000+0000 | dept1 | designation1 |  
employee1 | null | 40000 103 | 2020-04-20 18:30:00.000000+0000 | dept1 | designation3 | employee3 | null | 75000
```

7. Create a TTL of 15 seconds to display the values of Employees.

insert into EmployeeInfo (Emp_id, Emp_name, Designation, DOJ, salary, Dept_name) values
(161,'Ryan','Associate professor','2022-05-11',95000,'ISE') using ttl 60;

select ttl(Emp_name) from Employee_info where Emp_id = 161 and salary =
95000;

ttl(emp_name)

53

(1 rows)

11

Program 03: Cassandra Library Database

Perform the following DB operations using Cassandra.

1. Create a keyspace by name Library create

```
keyspace libInfo with replication = {  
    ... 'class':'SimpleStrategy',  
    ... 'replication_factor':1 ... }; use  
libInfo;
```

2. Create a column family by name Library-Info with attributes Stud_Id

```
Primary Key, Counter_value of type Counter create table libInfo (  
    ... studID int,  
    ... studName text, ... bookID  
    int,  
    ... bookName text,  
    ... dateOfIssue timestamp,  
    ... counterValue counter,  
    ... primary key ((studID, bookID), studName, bookName,  
dateOfIssue)  
    ... );
```

3. Insert the values into the table in batch

update libInfo

```
    ... set counterValue=counterValue+1  
    ... where studID = 001 and studName = 'Raj' and bookID  
= 101 and bookName = 'The Midnight Library' and dateOfIssue  
= '2023-05-08';
```

update libInfo

```
    ... set counterValue=counterValue+1  
    ... where studID = 002 and studName = 'Krishna'  
and bookID = 102 and  
bookName = 'The Little Coffee Shop of Kabul' and dateOfIssue = '2023-03-07';  
update libInfo
```

```

... set counterValue=counterValue+1
... where studID = 003 and studName = 'Trupti' and bookID
= 103 and bookName = 'Tokyo Ueno Station' and dateOfIssue
= '2022-12-26';

```

```

update libInfo
... set counterValue=counterValue+1
... where studID = 004 and studName = 'Arya' and
bookID =
104 and bookName = 'A Thousand Splendid Suns' and
dateOfIssue = '2022-10-03';

```

```

update libInfo
... set counterValue=counterValue+1
... where studID = 005 and studName = 'Karan'
and bookID =
105 and bookName = 'Portrait of an Unknown Woman' and dateOfIssue
= '2023-01-28';

```

4. Display the details of the table created and increase the value of the counter select
* from libInfo;

```

studid | bookid | studname | bookname | dateofissue | countervalue
-----+-----+-----+-----+-----+-----
1 | 101 | Raj | The Midnight Library | 2023-05-07 18:30:00.000000+0000 | 1
3 | 103 | Trupti | Tokyo Ueno Station | 2022-12-25 18:30:00.000000+0000 | 1
2 | 102 | Krishna | The Little Coffee Shop of Kabul | 2023-03-06 18:30:00.000000+0000 |
1 5 | 105 | Karan | Portrait of an Unknown Woman | 2023-01-27 18:30:00.000000+0000 | 1
4 | 104 | Arya | A Thousand Splendid Suns | 2022-10-02 18:30:00.000000+0000 | 1

```

```

update libInfo
... set counterValue=counterValue+1
... where studID = 005 and studName = 'Karan'
and bookID =
105 and bookName = 'Portrait of an Unknown Woman' and dateOfIssue
= '2023-01-28'; select * from
libInfo;

```

```

studid | bookid | studname | bookname | dateofissue | countervalue
-----+-----+-----+-----+-----+-----

```

```

1 | 101 | Raj | The Midnight Library | 2023-05-07 18:30:00.000000+0000 | 1
3 | 103 | Trupti | Tokyo Ueno Station | 2022-12-25 18:30:00.000000+0000 | 1
2 | 102 | Krishna | The Little Coffee Shop of Kabul | 2023-03-06 18:30:00.000000+0000 |
1 5 | 105 | Karan | Portrait of an Unknown Woman | 2023-01-27 18:30:00.000000+0000 | 2
4 | 104 | Arya | A Thousand Splendid Suns | 2022-10-02 18:30:00.000000+0000 | 1

```

5. Write a query to show that a student with id 114 has taken a book “UNIX” 2 times.

```

select studID from libInfo where bookName = 'Portrait of an Unknown Woman' and
counterValue = 2 allow filtering;

```

```

studid
-----
5

```

6. Export the created column to a csv file copy libInfo(studID, studName, bookID, bookName, dateOfIssue, counterValue) to 'c:\libInfo.csv'; Using 3 child processes

Starting copy of libinfo.libinfo with columns [studid, studname, bookid, bookname, dateofissue, countervalue].

Processed: 5 rows; Rate: 2 rows/s; Avg. rate: 1 rows/s 5 rows exported to 1 files in 9.163 seconds.

7. Import a given csv dataset from local file system into Cassandra column family
- ```

truncate library_info;
select * from library_info;

```

```

studid | bookid | studname | bookname | dateofissue | countervalue
-----+-----+-----+-----+-----+-----
(0 rows)

```

copy libInfo(studID, studName, bookID, bookName, dateOfIssue, counterValue) to 'c:\libInfo.csv'; Using 3 child processes

Starting copy of libinfo.libinfo with columns [studid, studname, bookid, bookname, dateofissue, countervalue].

Processed: 5 rows; Rate: 2 rows/s; Avg. rate: 1 rows/s 5 rows exported to 1 files in 9.163 seconds.

## Program 04: Hadoop Commands

```
$start-all.sh
```

WARNING: Attempting to start all Apache Hadoop daemons as hadoop in 10 seconds. WARNING: This is not a recommended production deployment configuration.

WARNING: Use CTRL-C to abort. Starting namenodes on

[localhost] Starting datanodes

Starting secondary namenodes

[bmscece-HP-Elite-Tower-600-G9-Desktop-PC]

Starting resourcemanager Starting nodemanagers

#to check all daemons have loaded successfully \$jps

9056 Jps

7475 ResourceManager

6709 NameNode

7160 SecondaryNameNode

7659 NodeManager

6875 DataNode

#mkdir command hdfs dfs

-mkdir /bda

# ls command hadoop fs -ls / Found 4 items drwxr-xr-x - hadoop supergroup 0 2023-05-08 09:40 /abc drwxr-xr-x - hadoop supergroup 0 2023-05-11 13:57 /bda drwxr-xr-x - hadoop supergroup 0 2023-05-04 12:49 /inputbda

drwxr-xr-x - hadoop supergroup 0 2023-04-27 11:44 /sridevi

# to append text in a file in hdfs echo "<Text to append>" | hdfs dfs -appendToFile /user/hduser/myfile.txt OR

hdfs dfs -appendToFile - /user/hduser/myfile.txt and then type the text on the terminal. Once you are done typing then hit 'Ctrl+D'



```
#cat command echo "hello world bda lab" | hdfs dfs -appendToFile - /bda/hello.txt
```

```
hdfs dfs -cat /bda/hello.txt hello world bda
lab
```

```
#put & copyFromLocal command hdfs dfs -put Desktop/hadooplocal.txt
```

```
/bda/hadoop.txt hdfs dfs -copyFromLocal Desktop/hadooplocal.txt /bda/hadoop.txt
```

```
hdfs dfs -cat /bda/hadoop.txt local file created
in the desktop
```

```
get command hdfs dfs -touchz
/bda/labfile.txt
```

```
echo "copying hdfs file to a local file using get command" | hdfs dfs
-appendToFile - /bda/labfile.txt
```

```
hdfs dfs -cat /bda/labfile.txt copying hdfs file to a local file using get
command
```

```
hdfs dfs -get /bda/labfile.txt Desktop/getcmd.txt #Contents of getcmd.txt file in
Desktop is:
```

```
copying hdfs file to a local file using get command
```

```
#copyToLocal command hdfs dfs -touchz
```

```
/bda/ghost.txt echo "new hdfs file in hdfs
```

```
folder" | hdfs dfs -appendToFile -
```

```
/bda/ghost.txt
```

```
hdfs dfs -cat /bda/ghost.txt new hdfs file in hdfs folder hdfs dfs -
copyToLocal /bda/ghost.txt Desktop/bigdata.txt
```

#Contents of bigdata.txt file in desktop is: new hdfs file in hdfs

folder

#mv command hdfs

dfs -ls /bda

Found 4 items

-rw-r--r-- 1 hadoop supergroup 29 2023-05-11 14:39 /bda/ghost.txt

-rw-r--r-- 1 hadoop supergroup 34 2023-05-11 14:26 /bda/hadoop.txt

-rw-r--r-- 1 hadoop supergroup 20 2023-05-11 14:11 /bda/hello.txt

-rw-r--r-- 1 hadoop supergroup 52 2023-05-11 14:32

/bda/labfile.txt hadoop fs -mv /bda/hello.txt

/dir

hdfs dfs -ls /bda

Found 3 items

-rw-r--r-- 1 hadoop supergroup 29 2023-05-11 14:39 /bda/ghost.txt

-rw-r--r-- 1 hadoop supergroup 34 2023-05-11 14:26 /bda/hadoop.txt

-rw-r--r-- 1 hadoop supergroup 52 2023-05-11 14:32

/bda/labfile.txt hdfs dfs -ls

/dir -rw-r--r-- 1 hadoop

supergroup 20 2023-05-11

14:11 /dir

#cp command hadoop fs -cp

/bda /rest

hdfs dfs -ls /bda

Found 3 items

-rw-r--r-- 1 hadoop supergroup 29 2023-05-11 14:39 /bda/ghost.txt

-rw-r--r-- 1 hadoop supergroup 34 2023-05-11 14:26 /bda/hadoop.txt

```
-rw-r--r-- 1 hadoop supergroup 52 2023-05-11 14:32
/bda/labfile.txt
```

```
hdfs dfs -ls /rest
```

```
Found 3 items
```

```
-rw-r--r-- 1 hadoop supergroup 29 2023-05-11 14:50 /rest/ghost.txt
-rw-r--r-- 1 hadoop supergroup 34 2023-05-11 14:50 /rest/hadoop.txt
-rw-r--r-- 1 hadoop supergroup 52 2023-05-11 14:50
/rest/labfile.txt
```

## Program 05: Word Count Program in Hadoop

WCDriver.java

```
//Importing libraries
```

```
import java.io.IOException; import org.apache.hadoop.conf.Configured;
import org.apache.hadoop.fs.Path; import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text; import
org.apache.hadoop.mapred.FileInputFormat; import
org.apache.hadoop.mapred.FileOutputFormat; import
org.apache.hadoop.mapred.JobClient; import
org.apache.hadoop.mapred.JobConf; import org.apache.hadoop.util.Tool;
import org.apache.hadoop.util.ToolRunner; public class WCDriver extends
Configured implements Tool {

 public int run(String args[]) throws IOException
 { if (args.length < 2)
 {
 System.out.println("Please give valid inputs"); return -1;
 }

 JobConf conf = new JobConf(WCDriver.class);
 FileInputFormat.setInputPaths(conf, new Path(args[0]));
 FileOutputFormat.setOutputPath(conf, new Path(args[1]));
 conf.setMapperClass(WCMapper.class);
 conf.setReducerClass(WCReducer.class);
 conf.setMapOutputKeyClass(Text.class);
 conf.setMapOutputValueClass(IntWritable.class);
 conf.setOutputKeyClass(Text.class);
 conf.setOutputValueClass(IntWritable.class);
 JobClient.runJob(conf); return 0;
 }

 // Main Method public static void main(String args[]) throws Exception
 { int exitCode = ToolRunner.run(new WCDriver(), args);
 System.out.println(exitCode);
 }
}
```

```
 }
}
```

### WCMapper.java

```
// Importing libraries import java.io.IOException; import
org.apache.hadoop.io.IntWritable; import
org.apache.hadoop.io.LongWritable; import
org.apache.hadoop.io.Text; import
org.apache.hadoop.mapred.MapReduceBase; import
org.apache.hadoop.mapred.Mapper; import
org.apache.hadoop.mapred.OutputCollector; import
org.apache.hadoop.mapred.Reporter;

public class WCMapper extends MapReduceBase implements
Mapper<LongWritable,Text, Text, IntWritable> {
 // Map function public void map(LongWritable key, Text value,
 OutputCollector<Text,
 IntWritable> output, Reporter rep) throws IOException {

 String line = value.toString();
 // Splitting the line on spaces for (String word : line.split(" "))
 { if (word.length() > 0)
 { output.collect(new Text(word), new
IntWritable(1));
 }
 }
 }
}
```

### WCReducer.java

```
// Importing libraries import java.io.IOException; import
java.util.Iterator; import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text; import
org.apache.hadoop.mapred.MapReduceBase; import
org.apache.hadoop.mapred.OutputCollector; import
```

```
org.apache.hadoop.mapred.Reducer; import
org.apache.hadoop.mapred.Reporter;
```

```
public class WCReducer extends MapReduceBase implements
Reducer<Text,IntWritable, Text, IntWritable> {
// Reduce function public void reduce(Text key, Iterator<IntWritable> value,
OutputCollector<Text, IntWritable> output,Reporter rep) throws
IOException
```

```
{
 int count = 0;
// Counting the frequency of each words while
(value.hasNext())
{
 IntWritable i = value.next(); count += i.get();
}
 output.collect(key, new IntWritable(count)); }
}
```

## Output:

```
Found 2 items
-rw-r--r-- 1 hadoop supergroup 0 2023-06-24 18:18 /optemp/ SUCCESS
-rw-r--r-- 1 hadoop supergroup 0 2023-06-24 18:18 /optemp/part-r-00000
hadoop@msccscse-HP-Elite-Tower-600-G9-Desktop-PC: $ hadoop fs -cat /optemp/part-r-00000
1901 46
hadoop@msccscse-HP-Elite-Tower-600-G9-Desktop-PC: $ hadoop jar /home/hadoop/Desktop/AvgTemp.jar AvgDriver /iptemp/1902 /optemp
2023-06-24 11:03:30.175 INFO impl.MetricsConfig: Loaded properties from hadoop-metrics2.properties
2023-06-24 11:03:30.214 INFO impl.MetricsSystemImpl: Scheduled Metric snapshot period at 10 second(s).
2023-06-24 11:03:30.214 INFO impl.MetricsSystemImpl: JobTracker metrics system started
Exception in thread "main" org.apache.hadoop.mapred.FileAlreadyExistsException: Output directory hdfs://localhost:9000/optemp already exists
 at org.apache.hadoop.mapreduce.lib.output.FileOutputFormat.checkOutputSpec(FileOutputFormat.java:164)
 at org.apache.hadoop.mapreduce.JobSubmitter.checkSpecs(JobSubmitter.java:277)
 at org.apache.hadoop.mapreduce.JobSubmitter.submitJobInternal(JobSubmitter.java:143)
 at org.apache.hadoop.mapreduce.Job$11.run(Job.java:1571)
 at org.apache.hadoop.mapreduce.Job$11.run(Job.java:1568)
 at java.base/java.security.AccessController.doPrivileged(Native Method)
 at java.base/javax.security.auth.Subject.doAs(Subject.java:423)
 at org.apache.hadoop.security.UserGroupInformation.doAs(UserGroupInformation.java:1878)
 at org.apache.hadoop.mapreduce.Job.submit(Job.java:1568)
 at org.apache.hadoop.mapreduce.Job.waitForCompletion(Job.java:1589)
 at AvgDriver.main(AvgDriver.java:22)
 at java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
 at java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62)
 at java.base/jdk.internal.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
 at java.base/java.lang.reflect.Method.invoke(Method.java:566)
 at org.apache.hadoop.util.RunJar.run(RunJar.java:323)
 at org.apache.hadoop.util.RunJar.main(RunJar.java:236)
hadoop@msccscse-HP-Elite-Tower-600-G9-Desktop-PC: $ hadoop jar /home/hadoop/Desktop/AvgTemp.jar AvgDriver /iptemp/1902 /optemp1
2023-06-24 11:03:34.060 INFO impl.MetricsConfig: Loaded properties from hadoop-metrics2.properties
2023-06-24 11:03:34.100 INFO impl.MetricsSystemImpl: Scheduled Metric snapshot period at 10 second(s).
2023-06-24 11:03:34.100 INFO impl.MetricsSystemImpl: JobTracker metrics system started
2023-06-24 11:03:34.162 WARN mapreduce.JobResourceUploader: Hadoop command-line option parsing not performed. Implement the Tool interface and execute your application with ToolRunner to remedy this.
2023-06-24 11:03:34.198 INFO InputFileInputFormat: Total input files to process : 1
2023-06-24 11:03:34.225 INFO mapreduce.JobSubmitter: number of splits:1
2023-06-24 11:03:34.287 INFO mapreduce.JobSubmitter: Submitting tokens for job: job_local1935691243_0001
2023-06-24 11:03:34.287 INFO mapreduce.JobSubmitter: Executing with tokens: []
2023-06-24 11:03:34.349 INFO mapreduce.Job: The url to track the job: http://localhost:8080/
2023-06-24 11:03:34.349 INFO mapreduce.Job: Running job: job_local1935691243_0001
2023-06-24 11:03:34.350 INFO mapred.LocalJobRunner: OutputCommitter set in config null
2023-06-24 11:03:34.354 INFO output.FileOutputCommitter: File Output Committer Algorithm version is 2
2023-06-24 11:03:34.354 INFO output.FileOutputCommitter: FileOutputCommitter skip cleanup _temporary folders under output directory:false, ignore cleanup failures: false
2023-06-24 11:03:34.354 INFO mapred.LocalJobRunner: OutputCommitter is org.apache.hadoop.mapreduce.lib.output.FileOutputCommitter
2023-06-24 11:03:34.391 INFO mapred.LocalJobRunner: Waiting for map tasks
2023-06-24 11:03:34.391 INFO mapred.LocalJobRunner: Starting task: attempt_local1935691243_0001_m_000000_0
2023-06-24 11:03:34.400 INFO output.FileOutputCommitter: File Output Committer Algorithm version is 2
2023-06-24 11:03:34.401 INFO output.FileOutputCommitter: FileOutputCommitter skip cleanup _temporary folders under output directory:false, ignore cleanup failures: false
2023-06-24 11:03:34.407 INFO mapred.Task: Using ResourceCalculatorProcessFree: []
2023-06-24 11:03:34.408 INFO mapred.MapTask: Processing split: hdfs://localhost:9000/iptemp/1902:0+888978
2023-06-24 11:03:34.441 INFO mapred.MapTask: (EQUATOR) 0 kvi 26214396(104857584)
2023-06-24 11:03:34.441 INFO mapred.MapTask: mapreduce.task.io.sort.mb: 100
2023-06-24 11:03:34.441 INFO mapred.MapTask: soft limit at 83886080
2023-06-24 11:03:34.441 INFO mapred.MapTask: bufstart = 0; bufvoid = 104857600
2023-06-24 11:03:34.441 INFO mapred.MapTask: kvstart = 26214396; length = 6553600
2023-06-24 11:03:34.443 INFO mapred.MapTask: Map output collector class = org.apache.hadoop.mapred.MapTask$MapOutputBuffer
```

## Program 06: Average Temperature

```
AverageDriver.java package temp;
import org.apache.hadoop.fs.Path;
import
org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat; public class
AverageDriver {
 public static void main(String[] args) throws Exception { if (args.length != 2) {
 System.err.println("Please Enter the input and output parameters");
 System.exit(-1);
 }
 Job job = new Job();
 job.setJarByClass(AverageDriver.class); job.setJobName("Max temperature");
 FileInputFormat.addInputPath(job, new Path(args[0]));
 FileOutputFormat.setOutputPath(job, new Path(args[1]));
 job.setMapperClass(AverageMapper.class); job.setReducerClass(AverageReducer.class);
 job.setOutputKeyClass(Text.class); job.setOutputValueClass(IntWritable.class);
 System.exit(job.waitForCompletion(true) ? 0 : 1); }
}
```

```
AverageMapper.java package temp;
import java.io.IOException;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.LongWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Mapper;

public class AverageMapper extends Mapper<LongWritable, Text, Text, IntWritable>
{ public static final int MISSING = 9999;
 public void map(LongWritable key, Text value, Mapper<LongWritable,
 Text, Text, IntWritable>.Context context) throws IOException,
 InterruptedException
 {
 int temperature;
```

```

String line = value.toString(); String year =
line.substring(15, 19); if (line.charAt(87) ==
'9') {
 temperature = Integer.parseInt(line.substring(88, 92));
} else {
 temperature = Integer.parseInt(line.substring(87, 92)); }
String quality = line.substring(92, 93); if (temperature != 9999 &&
quality.matches("[01459]"))
context.write(new Text(year), new IntWritable(temperature));
}
}

```

```

AverageReducer.java package temp; import
java.io.IOException;

import org.apache.hadoop.io.IntWritable;

import org.apache.hadoop.io.Text;

import org.apache.hadoop.mapreduce.Reducer;

public class AverageReducer extends Reducer<Text, IntWritable,
Text, IntWritable> {

 public void reduce(Text key, Iterable<IntWritable> values,
Reducer<Text, IntWritable, Text, IntWritable>.Context
context) throws IOException, InterruptedException { int
 max_temp = 0; int count = 0;
 for (IntWritable value : values)
 {
 max_temp += value.get();
 count++;
 } context.write(key, new IntWritable(max_temp / count)); }
}

```



# Output:

```
Bytes Written=0
2023-06-24 11:03:34,740 INFO mapred.LocalJobRunner: Finishing task: attempt local1935691243_0001_r_000000_0
2023-06-24 11:03:34,740 INFO mapred.LocalJobRunner: reduce task executor complete.
2023-06-24 11:03:35,352 INFO mapreduce.Job: Job job_local1935691243_0001 running in uber mode : false
2023-06-24 11:03:35,354 INFO mapreduce.Job: map 100% reduce 100%
2023-06-24 11:03:35,355 INFO mapreduce.Job: Job job_local1935691243_0001 completed successfully
2023-06-24 11:03:35,369 INFO mapreduce.Job: Counters: 36
 File System Counters
 FILE: Number of bytes read=153042
 FILE: Number of bytes written=1504567
 FILE: Number of read operations=0
 FILE: Number of large read operations=0
 FILE: Number of write operations=0
 HDFS: Number of bytes read=1777956
 HDFS: Number of bytes written=8
 HDFS: Number of read operations=15
 HDFS: Number of large read operations=0
 HDFS: Number of write operations=4
 HDFS: Number of bytes read erasure-coded=0
 Map-Reduce Framework
 Map input records=6565
 Map output records=6565
 Map output bytes=59085
 Map output materialized bytes=72221
 Input split bytes=98
 Combine input records=0
 Combine output records=0
 Reduce input groups=1
 Reduce shuffle bytes=72221
 Reduce input records=6565
 Reduce output records=1
 Spilled Records=13130
 Shuffled Maps =1
 Failed Shuffles=0
 Merged Map outputs=1
 GC time elapsed (ms)=7
 Total committed heap usage (bytes)=1159725056
 Shuffle Errors
 BAD_ID=0
 CONNECTION=0
 IO_ERROR=0
 WRONG_LENGTH=0
 WRONG_MAP=0
 WRONG_REDUCE=0
 File Input Format Counters
 Bytes Read=888978
 File Output Format Counters
 Bytes Written=0
hadoop@bmscece-HP-Elite-Tower-600-G9-Desktop-PC: $ hadoop fs -ls /optempl
Found 2 items
-rw-r--r-- 1 hadoop supergroup 0 2023-06-24 11:03 /optempl/ SUCCESS
-rw-r--r-- 1 hadoop supergroup 0 2023-06-24 11:03 /optempl/part-r-00000
hadoop@bmscece-HP-Elite-Tower-600-G9-Desktop-PC: $ hadoop fs -cat /optempl/part-r-00000
1902 21
```

## Program 07: Mean Max Temperature in Hadoop

```
MeanMaxDriver.java package meanmax;
```

```
import org.apache.hadoop.fs.Path;
```

```
import org.apache.hadoop.io.IntWritable;
```

```
import org.apache.hadoop.io.Text;
```

```
import org.apache.hadoop.mapreduce.Job;
```

```
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
```

```
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;
```

```
public class MeanMaxDriver
```

```
{
```

```
 public static void main(String[] args) throws Exception
```

```
{
```

```
 if (args.length != 2)
```

```
{
```

```
 System.err.println("Please Enter the input and output parameters");
```

```
 System.exit(-1);
```

```
 }
```

```
 Job job = new Job();
```

```
 job.setJarByClass(MeanMaxDriver.class); job.setJobName("Max
temperature");
```

```
 FileInputFormat.addInputPath(job, new Path(args[0]));
```

```
 FileOutputFormat.setOutputPath(job, new Path(args[1]));
```

```
 job.setMapperClass(MeanMaxMapper.class);
```

```
 job.setReducerClass(MeanMaxReducer.class); job.setOutputKeyClass(Text.class);
```

```
 job.setOutputValueClass(IntWritable.class);
```

```
 System.exit(job.waitForCompletion(true) ? 0 : 1); }
```

```
}
```

## MeanMaxMapper.java

```
import org.apache.hadoop.mapreduce.Mapper;

public class MeanMaxMapper extends Mapper<LongWritable, Text, Text,
IntWritable>
{
 public static final int MISSING = 9999;
 public void map(LongWritable key, Text value,
Mapper>LongWritable, Text, Text, IntWritable>.Context context)
throws IOException, InterruptedException
 {
 int temperature;
 String line = value.toString();
 String month = line.substring(19, 21);
 if (line.charAt(87) == ''+'')
 {

 temperature = Integer.parseInt(line.substring(88, 92));
 }
 Else
 {
 temperature = Integer.parseInt(line.substring(87, 92));
 }
 String quality = line.substring(92, 93);

 if (temperature != 9999 && quality.matches("[01459]"))
 context.write(new Text(month), new IntWritable(temperature));

 }

}
```

MeanMaxReducer.java package

```
meanmax;
```

```
import java.io.IOException;
```

```
import org.apache.hadoop.io.IntWritable;
```

```
import org.apache.hadoop.io.Text;
```

```
import org.apache.hadoop.mapreduce.Reducer;
```

```
public class MeanMaxReducer extends <Text, IntWritable, Text, IntWritable> {
```

```
 public void reduce(Text key, Iterable<IntWritable> values, Reducer<Text,
 IntWritable, Text, IntWritable>.Context context) throws IOException,
```

```
 InterruptedException { int
```

```
 max_temp = 0;
```

```
 int total_temp = 0; int
```

```
 count = 0; int days = 0;
```

```
 for (IntWritable value : values) {
```

```
 int temp = value.get(); if (temp
```

```
 > max_temp)
```

```
 max_temp = temp; count++;
```

```
 if (count == 3) { total_temp +=
```

```
 max_temp; max_temp = 0;
```

```
 count = 0; days++;
```

```
 }
```

```
 } context.write(key, new IntWritable(total_temp / days)); }
```

```
 }
```

## Output:

```
hadoop@bmscece-HP-Elite-Tower-600-G9-Desktop-PC:~$ start-all.sh
WARNING: Attempting to start all Apache Hadoop daemons as hadoop in 10 seconds.
WARNING: This is not a recommended production deployment configuration.
WARNING: Use CTRL-C to abort.
Starting namenodes on [localhost]
localhost: namenode is running as process 7391. Stop it first and ensure /tmp/hadoop-hadoop-namenode.pid file is empty before retry.
Starting datanodes
localhost: datanode is running as process 7576. Stop it first and ensure /tmp/hadoop-hadoop-datanode.pid file is empty before retry.
Starting secondary namenodes [bmscece-HP-Elite-Tower-600-G9-Desktop-PC]
bmscece-HP-Elite-Tower-600-G9-Desktop-PC: secondarynamenode is running as process 7865. Stop it first and ensure /tmp/hadoop-hadoop-secondarynamenode.pid file is empty before retry.
Starting resource manager
resource manager is running as process 8150. Stop it first and ensure /tmp/hadoop-hadoop-resourcemanager.pid file is empty before retry.
Starting node managers
localhost: nodemanager is running as process 8337. Stop it first and ensure /tmp/hadoop-hadoop-nodemanager.pid file is empty before retry.
hadoop@bmscece-HP-Elite-Tower-600-G9-Desktop-PC:~$ hadoop fs -mkdir /iptemp
hadoop@bmscece-HP-Elite-Tower-600-G9-Desktop-PC:~$ hadoop fs -put /home/hadoop/Desktop/1901 /iptemp
hadoop@bmscece-HP-Elite-Tower-600-G9-Desktop-PC:~$ hadoop fs -put /home/hadoop/Desktop/1902 /iptemp
hadoop@bmscece-HP-Elite-Tower-600-G9-Desktop-PC:~$ hadoop jar /home/hadoop/Desktop/AvgTemp.jar AvgDriver /iptemp/1901 /optemp
2023-06-24 10:18:36,257 INFO impl.MetricsConfig: Loaded properties from hadoop-metrics2.properties
2023-06-24 10:18:36,297 INFO impl.MetricsSystemImpl: Scheduled Metric snapshot period at 10 second(s).
2023-06-24 10:18:36,297 INFO impl.MetricsSystemImpl: JobTracker metrics system started
2023-06-24 10:18:36,357 WARN mapreduce.JobResourceUploader: Hadoop command-line option parsing not performed. Implement the Tool interface and execute your application with ToolRunner to remedy this.
2023-06-24 10:18:36,396 INFO input.FileInputFormat: Total input files to process : 1
2023-06-24 10:18:36,423 INFO mapreduce.JobSubmitter: number of splits:1
2023-06-24 10:18:36,484 INFO mapreduce.JobSubmitter: Submitting tokens for job: job_local1783357305_0001
2023-06-24 10:18:36,484 INFO mapreduce.JobSubmitter: Executing with tokens: []
2023-06-24 10:18:36,543 INFO mapreduce.Job: The url to track the job: http://localhost:8080/
2023-06-24 10:18:36,544 INFO mapreduce.Job: Running job: job_local1783357305_0001
2023-06-24 10:18:36,544 INFO mapred.LocalJobRunner: OutputCommitter set in config null
2023-06-24 10:18:36,548 INFO output.FileOutputCommitter: File Output Committer Algorithm version is 2
2023-06-24 10:18:36,548 INFO output.FileOutputCommitter: FileOutputCommitter skip cleanup _temporary folders under output directory:false, ignore cleanup failures: false
2023-06-24 10:18:36,548 INFO mapred.LocalJobRunner: OutputCommitter is org.apache.hadoop.mapreduce.lib.output.FileOutputCommitter
2023-06-24 10:18:36,598 INFO mapred.LocalJobRunner: Waiting for map tasks
2023-06-24 10:18:36,598 INFO mapred.LocalJobRunner: Starting task: attempt_local1783357305_0001_m_000000_0
2023-06-24 10:18:36,611 INFO output.FileOutputCommitter: File Output Committer Algorithm version is 2
2023-06-24 10:18:36,611 INFO output.FileOutputCommitter: FileOutputCommitter skip cleanup _temporary folders under output directory:false, ignore cleanup failures: false
2023-06-24 10:18:36,617 INFO mapred.Task: Using ResourceCalculatorProcessTree : []
2023-06-24 10:18:36,618 INFO mapred.MapTask: Processing split: hdfs://localhost:9000/iptemp/1901:0+888190
2023-06-24 10:18:36,650 INFO mapred.MapTask: (EQUATOR) 0 kvi 26214396(104857584)
2023-06-24 10:18:36,650 INFO mapred.MapTask: mapreduce.task.io.sort.mb: 100
2023-06-24 10:18:36,650 INFO mapred.MapTask: soft limit at 83886080
2023-06-24 10:18:36,650 INFO mapred.MapTask: bufstart = 0; bufvoid = 104857600
2023-06-24 10:18:36,650 INFO mapred.MapTask: kvstart = 26214396; length = 6553600
2023-06-24 10:18:36,652 INFO mapred.MapTask: Map output collector class = org.apache.hadoop.mapred.MapTask$MapOutputBuffer
2023-06-24 10:18:36,727 INFO mapred.LocalJobRunner:
2023-06-24 10:18:36,728 INFO mapred.MapTask: Starting flush of map output
2023-06-24 10:18:36,728 INFO mapred.MapTask: Spilling map output
2023-06-24 10:18:36,728 INFO mapred.MapTask: bufstart = 0; bufend = 59876; bufvoid = 104857600
2023-06-24 10:18:36,728 INFO mapred.MapTask: kvstart = 26214396(104857584); kvend = 26188144(104752576); length = 26253/6553600
2023-06-24 10:18:36,737 INFO mapred.MapTask: Finished spill 0
2023-06-24 10:18:36,741 INFO mapred.Task: Task:attempt_local1783357305_0001_m_000000_0 is done. And is in the process of committing
2023-06-24 10:18:36,743 INFO mapred.LocalJobRunner: map
2023-06-24 10:18:36,743 INFO mapred.Task: Task:attempt_local1783357305_0001_m_000000_0' done.
2023-06-24 10:18:36,746 INFO mapred.Task: Final Counters for attempt_local1783357305_0001_m_000000_0: Counters: 23
```

## **Program 08: Hadoop Map Reduce program to combine information from the users file along with Information from the posts file by using the concept of join and display user\_id, Reputation and Score**

JoinDriver.java

```
import org.apache.hadoop.conf.Configured;

import org.apache.hadoop.fs.Path;

import org.apache.hadoop.io.Text;

import org.apache.hadoop.mapred.*;

import org.apache.hadoop.mapred.libMultipleInputs;

import org.apache.hadoop.util.*;

public class JoinDriver extends Configured implements Tool
{
 public
 static class KeyPartitioner implements Partitioner<TextPair, Text>
 {
 @Override

 public void configure(JobConf job) {}
 @Override public int getPartition(TextPair key, Textvalue, int
numPartitions)
 {
 return (key.getFirst().hashCode() & Integer.MAX_VALUE) % numPartitions;
 }
 }

 @Override public int run(String[] args) throws Exception {
 if (args.length != 3) {
 System.out.println("Usage: <Department Emp Strength input>
<Department Name input> <output>"); return -1;
 }
 }
}
```

```
}
```

```
JobConf conf = new JobConf(getConf(), getClass()); conf.setJobName("Join
'Department Emp Strength input' with
'Department Name input'");
Path AInputPath = new Path(args[0]);
Path BInputPath = new Path(args[1]);
Path outputPath = new Path(args[2]);
```

```
MultipleInputs.addInputPath(conf, AInputPath, TextInputFormat.class, Posts.class);
```

```
MultipleInputs.addInputPath(conf, BInputPath, TextInputFormat.class, User.class);
```

```
FileOutputFormat.setOutputPath(conf, outputPath);
conf.setPartitionerClass(KeyPartitioner.class);
conf.setOutputValueGroupingComparator(TextPair.FirstComparator.class) ;
conf.setMapOutputKeyClass(TextPair.class); conf.setReducerClass(JoinReducer.class);
conf.setOutputKeyClass(Text.class);
```

```
JobClient.runJob(conf); return 0; } public static void main(String[] args)
throws Exception { int exitCode = ToolRunner.run(new JoinDriver(), args);
System.exit(exitCode);
}
}
```

```
JoinReducer.java import java.io.IOException;
import java.util.Iterator; import
org.apache.hadoop.io.Text; import
org.apache.hadoop.mapred.*;
public class JoinReducer extends MapReduceBase implements Reducer<TextPair, Text, Text,
Text> {
```

```
@Override public void reduce (TextPair key, Iterator<Text> values,
OutputCollector<Text, Text> output, Reporter reporter) throws
IOException {
 Text nodeId = new Text(values.next()); while
 (values.hasNext()) { Text node =
 values.next();
 Text outValue = new Text(nodeId.toString() + "\t\t" + node.toString());
```

```

 output.collect(key.getFirst(), outValue);
 }
}
}

```

## User.java

```

import java.io.IOException; import java.util.Iterator; import
org.apache.hadoop.conf.Configuration; import
org.apache.hadoop.fs.FSDataInputStream; import
org.apache.hadoop.fs.FSDataOutputStream; import
org.apache.hadoop.fs.FileSystem; import
org.apache.hadoop.fs.Path; import
org.apache.hadoop.io.LongWritable;

```

```

import org.apache.hadoop.io.Text; import
org.apache.hadoop.mapred.*; import
org.apache.hadoop.io.IntWritable;

```

```

 public class User extends MapReduceBase implements
Mapper<LongWritable, Text, TextPair, Text> {
 @Override public void map(LongWritable key, Text value,
OutputCollector<TextPair, Text> output, Reporter reporter) throws
IOException {
 String valueString = value.toString();
 String[] SingleNodeData = valueString.split("\t"); output.collect(new
TextPair(SingleNodeData[0], "1"), new
Text(SingleNodeData[1]));
 }
}

```

## //Posts.java

```

import java.io.IOException; import
org.apache.hadoop.io.*; import
org.apache.hadoop.mapred.*;
public class Posts extends MapReduceBase implements
Mapper<LongWritable, Text, TextPair, Text>{
 @Override public void map(LongWritable key, Text value,
OutputCollector<TextPair, Text> output, Reporter reporter) throws IOException
{

```



```
String valueString = value.toString(); String[] SingleNodeData =
valueString.split("\t"); output.collect(new TextPair(SingleNodeData[3],
"0"), new
Text(SingleNodeData[9]));
}
}
```

// TextPair.java

```
} public Text getFirst() { return
first; }
```

```
public Text getSecond() { return second;
}
```

```
@Override public void write(DataOutput out) throws IOException {
first.write(out);
second.write(out); }
```

```
@Override public void readFields(DataInput in) throws IOException {
first.readFields(in);
second.readFields(in);
}
```

```
@Override public int
hashCode() {
return first.hashCode() * 163 + second.hashCode(); }
```

```
@Override public boolean equals(Object o)
```

```
{
if (o instanceof TextPair)
{
TextPair tp = (TextPair) o; return first.equals(tp.first)
&& second.equals(tp.second);
}
return false;
}
```

```
@Override public String toString()
{
```

```

return first + "\t" + second;
}
@Override public int compareTo(TextPair tp) {
int cmp = first.compareTo(tp.first); if (cmp != 0)
{ return cmp; } return
second.compareTo(tp.second);
}
// ^^ TextPair // vv TextPairComparator public static class Comparator extends
WritableComparator {
private static final Text.Comparator TEXT_COMPARATOR = new
Text.Comparator();
public Comparator() { super(TextPair.class);
}
@Override public int compare(byte[] b1, int s1, int l1, byte[]
b2, int s2, int l2) { try {
int firstL1 = WritableUtils.decodeVIntSize(b1[s1]) + readVInt(b1, s1); int firstL2 =
WritableUtils.decodeVIntSize(b2[s2]) + readVInt(b2, s2); int cmp =
TEXT_COMPARATOR.compare(b1, s1, firstL1, b2, s2, firstL2); if (cmp != 0) { return cmp;
} return TEXT_COMPARATOR.compare(b1, s1 + firstL1, l1 - firstL1,
b2, s2 + firstL2, l2 - firstL2); } catch (IOException
e) { throw new IllegalArgumentException(e);
}
} } static {
WritableComparator.define(TextPair.class, new Comparator());
} public static class FirstComparator extends WritableComparator {
private static final Text.Comparator TEXT_COMPARATOR = new
Text.Comparator(); public FirstComparator() { super(TextPair.class); }
@Override public int compare(byte[] b1, int s1, int l1, byte[]
b2, int s2, int l2) {
try { int firstL1 = WritableUtils.decodeVIntSize(b1[s1]) + readVInt(b1, s1); int firstL2 =
WritableUtils.decodeVIntSize(b2[s2]) + readVInt(b2, s2);
return TEXT_COMPARATOR.compare(b1, s1, firstL1, b2, s2, firstL2);
} catch (IOException e)
{
throw new IllegalArgumentException(e);
}
}
@Override public int compare(WritableComparable a, WritableComparable b)

```

```

{
if (a instanceof TextPair && b instanceof TextPair)
{
return (((TextPair) a).first.compareTo(((TextPair) b).first);
}
return super.compare(a, b);
}
}

}

```

## Output:

```

Shuffle Errors
BAD_ID=0
CONNECTION=0
IO_ERROR=0
WRONG_LENGTH=0
WRONG_MAP=0
WRONG_REDUCE=0
File Input Format Counters
Bytes Read=0
File Output Format Counters
Bytes Written=85
hduser@bnsce-Precision-T1700:~/khushil/Join/MapReduceJoin$ hdfs dfs -cat /khushil_join/output2/part-00000
A11 50 Finance
B12 100 HR
C13 250 Manufacturing
Dept_ID Total_Employee Dept_Name
hduser@bnsce-Precision-T1700:~/khushil/Join/MapReduceJoin$

```

## Program 09: Word Count in Spark

```
scala> val data = sc.textFile("sridevi/sparkdata.txt") data: org.apache.spark.rdd.RDD[String] =
swati/sparkdata.txt MapPartitionsRDD[1] at textFile at <console>:24
```

```
scala> data.collect; res0: Array[String] = Array(hello world, this is BDA spark lab)
```

```
scala> val splitdata = data.flatMap(line => line.split(" "));
```

```
splitdata: org.apache.spark.rdd.RDD[String] = MapPartitionsRDD[2] at flatMap at
<console>:25
```

```
scala> splitdata.collect;
```

```
res1: Array[String] = Array(hello, world,, this, is, BDA, spark, lab)
```

```
scala> val mapdata = splitdata.map(word => (word,1));
```

```
mapdata: org.apache.spark.rdd.RDD[(String, Int)] = MapPartitionsRDD[3] at map at
<console>:25
```

```
scala> mapdata.collect; res2: Array[(String, Int)] = Array((hello,1), (world,,1), (this,1),
(is,1), (BDA,1), (spark,1), (lab,1))
```

```
scala> val reducedata = mapdata.reduceByKey(_+_); reducedata:
```

```
org.apache.spark.rdd.RDD[(String, Int)] = ShuffledRDD[4] at reduceByKey at
<console>:25
```

```
scala> reducedata.collect; res3: Array[(String, Int)] = Array((this,1), (is,1), (hello,1),
(world,,1), (lab,1), (spark,1), (BDA,1))
```

**Program 10: Using RDD and FlatMap count how many times each word appears in a file and write out a list of words whose count is strictly greater than 4 using Spark.**

```
scala> val textFile = sc.textFile("sridevi/word.txt")
textFile: org.apache.spark.rdd.RDD[String] = swati/word.txt MapPartitionsRDD[1] at textFile
at <console>:24
```

```
scala> val counts = textFile.flatMap(line => line.split(" ")).map(word
=> (word, 1)).reduceByKey(_ + _) counts: org.apache.spark.rdd.RDD[(String, Int)] =
ShuffledRDD[4] at reduceByKey at <console>:25
```

```
scala> import scala.collection.immutable.ListMap import
scala.collection.immutable.ListMap
```

```
scala> val sorted=ListMap(counts.collect.sortWith(_._2 > _._2):_*)// sort in descending order
based
sorted: scala.collection.immutable.ListMap[String,Int] =
ListMap(hello -> 6, world -> 5, this -> 2, is -> 2, lab -> 2, BDA
-> 2, word -> 1)
```

```
scala> println(sorted)
ListMap(hello -> 6, world -> 5, this -> 2, is -> 2, lab -> 2, BDA
-> 2, word -> 1)
```

```
scala> for((k,v)<-sorted){
 | if(v>4)
 | {
 | print(k+",")
 | print(v)
 | println()
 | }
 | }
hello,6
```