X

Course > 3. Perip... > 82C55 > Weekly ...

<

🎞	📕	✍✔	✍✔

>

Weekly Quiz 3

Question

1/1 point (graded)

A1 = 0; A0 = 0; RD(Active low) = 1; WR(Active low) = 0; CS(Active low) = 0; Reset = 0

- ⦿ Data Bus >> Port A

- ◯ Data Bus >> Port C

- ◯ Data Bus >> Control

- ◯ Reset the IC

✔

Submit	You have used 2 of 2 attempts

Question

1/1 point (graded)

A1 = 1; A0 = 0; RD(Active low) = 0; WR(Active low) = 1; CS(Active low) = 0; Reset = 1

○ Data Bus >> Port C

○ Port C >> Data Bus

○ Nothing Happen

● Reset the IC

✔

| Submit | You have used 2 of 2 attempts |

Question

1.0/1.0 point (graded)

A0 = 0; A1 = 1; RD(Active low) = 1; WR(Active low) = 0; CS(Active low) = 0; Reset = 0

● Data Bus >> Port C

○ Data Bus >> Port A

○ Data Bus >> Control

✔

| Submit | You have used 1 of 2 attempts |

Question

1/1 point (graded)

What is the meaning of the control word: 01111110

⦿ PC7 Reset

◯ PC2 Set

◯ Both are wrong answer

✔

Submit	You have used 1 of 2 attempts

Question

1/1 point (graded)

What is the meaning of the control word: 00000000

◯ PC7 Reset

◯ PC0 Set

⦿ Both are wrong answer

✔

Submit	You have used 1 of 2 attempts

Question

1/1 point (graded)

We want to PC5 set: Which one is correct answer?

◯ 01010XXX

◯ 0XXX1010

(◉) 0XXX1011

✔

| Submit | You have used 1 of 2 attempts |

Question

1/1 point (graded)

What is the meaning of the control word: 10000000

(○) Port-A, Port-B and Port-C all of them can be used for handshaking output device

(◉) Port-A, Port-B and Port-C all of them can be used for normal output device

(○) Port-A, Port-B and Port-C all of them can be used for normal iutput device

(○) It is in Bit-reset mode so all answers are wrong

✔

| Submit | You have used 2 of 2 attempts |

Question

1/1 point (graded)

What is the meaning of the control word: 00111110

(○) Port-A can be used for normal input device and Port-B can be used for handshaking input device

(○) Port-A can be used for handshaking input device and Port-B can be used for normal input device

◯ Port-A can be used for handshaking input device and Port-B also can be used for handshaking input device

🔘 It is in Bit-reset mode so all answers are wrong

✔

| Submit | You have used 1 of 2 attempts |

Question

1/1 point (graded)

If we want to interface IO devices in following way, what should be the control word: We would like to use a handshaking input device like Keyboard in port-A and handshaking input device mouse in port-B

🔘 10110110

◯ 00110110

◯ 1011X11X

◯ 1000X00X

✔

| Submit | You have used 1 of 2 attempts |

Question

1/1 point (graded)

If we want to interface IO devices in following way, what should be the control word: We would like to use all the

ports Port-A, Port-B and Port-C for normal input device

○ 11111111

⦿ 10011011

○ 1XX11X11

○ 11100100

✔

| Submit | You have used 1 of 2 attempts |

❮ Previous

Next ❯

About Us

BracU Home

USIS

Course Catalog

Copyright - 2020