

TSMS POS Transaction Payload Guidelines

Overview

This document provides the official format and requirements for POS terminal providers and tenants to submit single or batch transactions to the TSMS system.

1. Transaction Submission Structure

Transaction Format

```
{
  "submission_uuid": "uuid-string",
  "tenant_id": "integer",
  "terminal_id": "integer",
  "submission_timestamp": "ISO8601-UTC",
  "transaction_count": 1,
  "payload_checksum": "64-char-hex",

  "transaction": {
    "transaction_id": "uuid-string",
    "transaction_timestamp": "ISO8601-UTC",
    "receipt_no": "000000001",
    "gross_sales": "decimal",
    "net_sales": "decimal",
    "promo_status": "string",
    "customer_code": "string",
    "payload_checksum": "64-char-hex",

    "adjustments": [
      { "adjustment_type": "string", "amount": "decimal" }
    ],

    "taxes": [
      { "tax_type": "string", "amount": "decimal" }
    ]
  }
}
```

2. Field Requirements

Submission Level Fields

- **submission_uuid** (string, required): Unique UUID v4 for the submission
- **tenant_id** (integer, required): Tenant identifier assigned by TSMS
- **terminal_id** (integer, required): POS terminal identifier assigned by TSMS
- **submission_timestamp** (ISO8601 string, required): UTC timestamp when submission was sent (format: YYYY-MM-DDTHH:MM:SS)
- **transaction_count** (integer, required): Number of transactions in payload (1 for single, >1 for batch)

- **payload_checksum** (string, required): SHA-256 hash (64 hex characters) of full submission payload

Transaction Level Fields

- **transaction_id** (string, required): Unique UUID v4 for the transaction.
- **transaction_timestamp** (ISO8601 string, required): UTC timestamp when sale occurred (format: YYYY-MM-DDTHH:MM:SS).
- **receipt_no**: (string, required): local transaction sequential number.
- **gross_sales** (decimal, required): Total gross sales amount before any deductions (≥ 0 , 2 decimal places).
- **net_sales** (decimal, required): Net sales amount after all deductions (2 decimal places).
- **promo_status** (string, required): Promotional status ("WITH_APPROVAL", "WITHOUT_APPROVAL", "INACTIVE").
- **customer_code** (string, required): Customer identifier (cannot be empty).
- **payload_checksum** (string, required): SHA-256 hash (64 hex characters) of transaction payload.
- **adjustments** (array, required): Minimum 7 adjustment entries.
- **taxes** (array, required): Minimum 4 tax entries.

Adjustment Fields

- **adjustment_type** (string, required): Type of adjustment.
- **amount** (decimal, required): Adjustment amount (2 decimal places).

Tax Fields

- **tax_type** (string, required): Type of tax.
- **amount** (decimal, required): Tax amount (2 decimal places).

3. Financial Validation Rules

Core Financial Formula

$$\text{net_sales} = \text{gross_sales} - \text{total_adjustments} - \text{other_tax}$$

Where:

- **gross_sales**: Total sales amount before deductions.
- **total_adjustments**: Sum of all adjustment amounts.
- **other_tax**: Sum of tax amounts where $\text{tax_type} \neq \text{'VAT'}$.

Validation Tolerance

- Financial calculations allow ± 0.01 rounding difference.
- All monetary values must have exactly 2 decimal places.

Example Calculation

Gross Sales: 1,000.00

Adjustments: 50.00 (promo) + 20.00 (senior) = 70.00 total

Other Tax: 10.00 (OTHER_TAX only, VAT excluded)

Net Sales: 1,000.00 - 70.00 - 10.00 = 920.00

4. Required Field Types

Required Adjustment Types (7 minimum)

1. promo_discount
2. senior_discount
3. pwd_discount
4. vip_card_discount
5. service_charge_distributed_to_employees
6. service_charge_retained_by_management
7. employee_discount

Required Tax Types (4 minimum)

1. VAT
2. VATABALE_SALES
3. SC_VAT_EXEMPT_SALES
4. OTHER_TAX

5. Field Ordering Requirements

Submission Level Ordering

submission_uuid → tenant_id → terminal_id → submission_timestamp → transaction_count → payload_checksum → transaction/transactions

Transaction Level Ordering

transaction_id → transaction_timestamp → receipt_no → gross_sales → net_sales → promo_status → customer_code → payload_checksum → adjustments → taxes

Critical: payload_checksum must appear after all scalar fields but before array fields adjustments, taxes.

6. Payload Checksum Computation

Algorithm

- Use SHA-256 hashing algorithm
- Output must be 64 hexadecimal characters
- Use compact JSON format (no extra whitespace)

Transaction Process

A. Build the transaction object (pre-checksum)

- Timestamps = ISO-8601 second precision with Z.
- Number fields must be numbers (not strings).
- Do not include payload_checksum yet.

Example:

```
{
  "transaction_id": "925a07fa-37c4-48fa-98c6-4ab059485594",
  "transaction_timestamp": "2025-10-01T21:30:06Z",
  "receipt_no ": " <your_receipt_number> ",
  "gross_sales": 14806.00,
  "net_sales": 14806.00,
  "promo_status": "WITH_APPROVAL",
  "customer_code": "C-B1023",
  "adjustments": [
    {"adjustment_type": "promo_discount", "amount": 0.00},
    {"adjustment_type": "senior_discount", "amount": 0.00},
    {"adjustment_type": "pwd_discount", "amount": 0.00},
    {"adjustment_type": "vip_card_discount", "amount": 0.00},
    {"adjustment_type": "service_charge_distributed_to_employees", "amount": 0.00},
    {"adjustment_type": "service_charge_retained_by_management", "amount": 0.00},
    {"adjustment_type": "employee_discount", "amount": 0.00}
  ],
  "taxes": [
    {"tax_type": "VAT", "amount": 1528.43},
    {"tax_type": "VATABLE_SALES", "amount": 12736.87},
    {"tax_type": "SC_VAT_EXEMPT_SALES", "amount": 510.00},
    {"tax_type": "OTHER_TAX", "amount": 0.00}
  ]
}
```

B. Canonicalize the transaction JSON (String to hash)

Apply these strict rules:

- Remove transaction.payload_checksum (not present yet).
- Sort object keys lexicographically at every level.
- Minify: no spaces, no newlines, no tabs.
- Normalize numbers: culture-invariant; trim trailing zeros and unnecessary decimal points (14806.00 → 14806, 0.00 → 0, 1528.40 → 1528.4).
- Keep array order as given.
- Datetime must be exactly 2025-10-01T21:30:06Z.
- Encode to UTF-8 without BOM.

111111111111112

```
{"adjustments":[{"adjustment_type":"promo_discount","amount":0},{ "adjustment_type":"senior_discount",
,"amount":0},{ "adjustment_type":"pwd_discount","amount":0},{ "adjustment_type":"vip_card_discount",
"amount":0},{ "adjustment_type":"service_charge_distributed_to_employees","amount":0},{ "adjustment_t
ype":"service_charge_retained_by_management","amount":0},{ "adjustment_type":"employee_discount",
"amount":0}], "customer_code":"C-
B1023", "gross_sales":14806, "net_sales":14806, "promo_status":"WITH_APPROVAL", "taxes":[{"amount":15
28.43, "tax_type":"VAT"}, {"amount":12736.87, "tax_type":"VATABLE_SALES"}, {"amount":510, "tax_type":"SC
_VAT_EXEMPT_SALES"}, {"amount":0, "tax_type":"OTHER_TAX"}], "transaction_id":"925a07fa-37c4-48fa-
98c6-4ab059485594", "transaction_timestamp":"2025-10-
01T21:30:06Z", "receipt_no":"<your_receipt_no>"}
```

C. Compute the transaction checksum

- Hash = SHA-256 over the URF-8 bytes of the canonical string.
- Hex output: lowercase, 64 chars.

Example.

transaction.payload_checksum =

"bd96f1fd3c5a909427cfc4bcba4962e98d23b7d37b01350908428402fe8cc1b4"

D. Build the submission object (pre-checksum)

Rules:

- terminal_id must belong to tenant_id (server rejects otherwise).
- Single transaction: use key "transaction". (Batches use "transactions".)
- Include the transaction **with** its payload_checksum from step 3.
- Set transaction_count accurately.

Example:

```
{
  "submission_uuid": "c6216c04-2494-4a6a-bee1-5218b15cc221",
  "tenant_id": 15,
  "terminal_id": 30,
  "submission_timestamp": "2025-10-13T16:10:31Z",
  "receipt_no ": " <your_receipt_number> ",
  "transaction_count": 1,

  "transaction": {
    "transaction_id": "925a07fa-37c4-48fa-98c6-4ab059485594",
    "transaction_timestamp": "2025-10-01T21:30:06Z",
    "gross_sales": 14806,
    "net_sales": 14806,
    "promo_status": "WITH_APPROVAL",
```

```

"customer_code": "C-B1023",
"payload_checksum": "bd96f1fd3c5a909427cfc4bcba4962e98d23b7d37b01350908428402fe8cc1b4",

  "adjustments": [
    {"adjustment_type": "promo_discount", "amount": 0},
    {"adjustment_type": "senior_discount", "amount": 0},
    {"adjustment_type": "pwd_discount", "amount": 0},
    {"adjustment_type": "vip_card_discount", "amount": 0},
    {"adjustment_type": "service_charge_distributed_to_employees", "amount": 0},
    {"adjustment_type": "service_charge_retained_by_management", "amount": 0},
    {"adjustment_type": "employee_discount", "amount": 0}
  ],

  "taxes": [
    {"tax_type": "VAT", "amount": 1528.43},
    {"tax_type": "VARIABLE_SALES", "amount": 12736.87},
    {"tax_type": "SC_VAT_EXEMPT_SALES", "amount": 510},
    {"tax_type": "OTHER_TAX", "amount": 0}
  ]
}

```

E. Canonicalize the submission JSON (string to hash)

- Remove submission.payload_checksum (not present yet).
- Apply the **same** canonicalization rules as step 2.
- The nested transaction **must include** the payload_checksum from step 3.

Canonical submission sting:

```

{"submission_timestamp":"2025-10-13T16:10:31Z","submission_uuid":"c6216c04-2494-4a6a-bee1-5218b15cc221","tenant_id":15,"terminal_id":30,"transaction":{"adjustments":[{"adjustment_type":"promo_discount","amount":0},{"adjustment_type":"senior_discount","amount":0},{"adjustment_type":"pwd_discount","amount":0},{"adjustment_type":"vip_card_discount","amount":0},{"adjustment_type":"service_charge_distributed_to_employees","amount":0},{"adjustment_type":"service_charge_retained_by_management","amount":0},{"adjustment_type":"employee_discount","amount":0}], "customer_code":"C-B1023","gross_sales":14806,"net_sales":14806,"payload_checksum":"bd96f1fd3c5a909427cfc4bcba4962e98d23b7d37b01350908428402fe8cc1b4","promo_status":"WITH_APPROVAL","taxes":[{"amount":1528.43,"tax_type":"VAT"}, {"amount":12736.87,"tax_type":"VARIABLE_SALES"}, {"amount":510,"tax_type":"SC_VAT_EXEMPT_SALES"}, {"amount":0,"tax_type":"OTHER_TAX"}], "transaction_id":"925a07fa-37c4-48fa-98c6-4ab059485594","transaction_timestamp":"2025-10-01T21:30:06Z","receipt_no "<your_receipt_number> ", "transaction_count":1}

```

F. Compute the submission checksum

- Hash = **SHA-256** over the UTF-8 bytes of the canonical submission string.

- Hex output: lowercase, 64 chars.

Submission checksum example:

submission.payload_checksum =

"fb3ccfcb5e6ce98a1e53cb5821e876c50c4928edeefecea12ec00def5a8388be"

G. Final JSON to send (include both checksums)

Headers:

Content-Type: application/json; charset=utf-8

Body:

```
{
  "submission_uuid": "c6216c04-2494-4a6a-bee1-5218b15cc221",
  "tenant_id": 15,
  "receipt_no ": " <your_receipt_number> ",
  "terminal_id": 30,
  "submission_timestamp": "2025-10-13T16:10:31Z",
  "transaction_count": 1,
  "payload_checksum": "fb3ccfcb5e6ce98a1e53cb5821e876c50c4928edeefecea12ec00def5a8388be",
  "transaction": {
    "transaction_id": "925a07fa-37c4-48fa-98c6-4ab059485594",
    "transaction_timestamp": "2025-10-01T21:30:06Z",
    "gross_sales": 14806,
    "net_sales": 14806,
    "promo_status": "WITH_APPROVAL",
    "customer_code": "C-B1023",
    "payload_checksum":
"bd96f1fd3c5a909427cfc4bcba4962e98d23b7d37b01350908428402fe8cc1b4",
    "adjustments": [
      {"adjustment_type": "promo_discount", "amount": 0},
      {"adjustment_type": "senior_discount", "amount": 0},
      {"adjustment_type": "pwd_discount", "amount": 0},
      {"adjustment_type": "vip_card_discount", "amount": 0},
      {"adjustment_type": "service_charge_distributed_to_employees", "amount": 0},
      {"adjustment_type": "service_charge_retained_by_management", "amount": 0},
      {"adjustment_type": "employee_discount", "amount": 0}
    ],
    "taxes": [
      {"tax_type": "VAT", "amount": 1528.43},
      {"tax_type": "VATABLE_SALES", "amount": 12736.87},
```

```
        {"tax_type": "SC_VAT_EXEMPT_SALES", "amount": 510},
        {"tax_type": "OTHER_TAX", "amount": 0}
    ]
}
```

Important Notes

- Mismatched tenant_id vs terminal_id (server returns 422).
- Extra spaces/newlines or different key order when hashing vs sending.
- Trailing zeros in numbers (e.g., 14806.00) when hashing, but trimmed on server.
- Non-UTC timestamps, milliseconds included, or different offsets.
- Uppercase hex for checksums (use lowercase).
- Byte-order mark (BOM) in the request body.

API Token Requirements

- Each POS terminal receives a unique API token
- Include token in Authorization: Bearer {token} header
- Tokens are terminal-specific and cannot be shared

Terminal Enrollment

- POS terminals must be enrolled in TSMS before transaction submission
- Enrollment is required for both live and testing environments
- Contact TSMS technical team for enrollment process

8. API Endpoints

Submit Transaction

Method: POST

URL: <https://stagingtsms.pitx.com.ph/api/v1/transactions/official>

Headers:

- Authorization: Bearer {api_token}
- Content-Type: application/json

Void Transaction

Method: PUT

URL: https://stagingtsms.pitx.com.ph/api/v1/transactions/{transaction_id}/void

Headers:

- Authorization: Bearer {api_token}
- Content-Type: application/json

Body:

```
{
  "transaction_id": "{transaction_id}",
  "void_reason": "string",
  "payload_checksum": "64-char-hex"
}
```

9. Payload Guide

A. Build the transaction object (pre-checksum)

- Timestamps = ISO-8601 second precision with Z.
- Number fields must be numbers (not strings).
- Do not include payload_checksum yet.

Example:

```
{
  "transaction_id": "925a07fa-37c4-48fa-98c6-4ab059485594",
  "transaction_timestamp": "2025-10-01T21:30:06Z",
  "receipt_no ": " <your_receipt_number> ",
  "gross_sales": 14806.00,
  "net_sales": 14806.00,
  "promo_status": "WITH_APPROVAL",
  "customer_code": "C-B1023",
  "adjustments": [
    {"adjustment_type": "promo_discount", "amount": 0.00},
    {"adjustment_type": "senior_discount", "amount": 0.00},
    {"adjustment_type": "pwd_discount", "amount": 0.00},
    {"adjustment_type": "vip_card_discount", "amount": 0.00},
    {"adjustment_type": "service_charge_distributed_to_employees", "amount": 0.00},
    {"adjustment_type": "service_charge_retained_by_management", "amount": 0.00},
    {"adjustment_type": "employee_discount", "amount": 0.00}
  ],
  "taxes": [
    {"tax_type": "VAT", "amount": 1528.43},
    {"tax_type": "VATABLE_SALES", "amount": 12736.87},
    {"tax_type": "SC_VAT_EXEMPT_SALES", "amount": 510.00},
    {"tax_type": "OTHER_TAX", "amount": 0.00}
  ]
}
```

B. Canonicalize the transaction JSON (String to hash)

Apply these strict rules:

- Remove transaction.payload_checksum (not present yet).
- Sort object keys lexicographically at every level.
- Minify: no spaces, no newlines, no tabs.
- Normalize numbers: culture-invariant; trim trailing zeros and unnecessary decimal points (14806.00 → 14806, 0.00 → 0, 1528.40 → 1528.4).
- Keep array order as given.
- Datetime must be exactly 2025-10-01T21:30:06Z.
- Encode to UTF-8 without BOM.

Canonical transaction string (already normalized/sorted/minified):

```
{"adjustments":[{"adjustment_type":"promo_discount","amount":0},{"adjustment_type":"senior_discount","amount":0},{"adjustment_type":"pwd_discount","amount":0},{"adjustment_type":"vip_card_discount","amount":0},{"adjustment_type":"service_charge_distributed_to_employees","amount":0},{"adjustment_type":"service_charge_retained_by_management","amount":0},{"adjustment_type":"employee_discount","amount":0}],"customer_code":"C-B1023","gross_sales":14806,"net_sales":14806,"promo_status":"WITH_APPROVAL","taxes":[{"amount":1528.43,"tax_type":"VAT"},{"amount":12736.87,"tax_type":"VATABLE_SALES"},{"amount":510,"tax_type":"SC_VAT_EXEMPT_SALES"},{"amount":0,"tax_type":"OTHER_TAX"}],"transaction_id":"925a07fa-37c4-48fa-98c6-4ab059485594","transaction_timestamp":"2025-10-01T21:30:06Z","receipt_no":"<your_receipt_no>"}
```

C. Compute the transaction checksum

- Hash = SHA-256 over the UTF-8 bytes of the canonical string.
- Hex output: lowercase, 64 chars.

Example.

transaction.payload_checksum =

"bd96f1fd3c5a909427cfc4bcba4962e98d23b7d37b01350908428402fe8cc1b4"

D. Build the submission object (pre-checksum)

Rules:

- terminal_id must belong to tenant_id (server rejects otherwise).
- Single transaction: use key "transaction". (Batches use "transactions".)
- Include the transaction **with** its payload_checksum from step 3.
- Set transaction_count accurately.

Example:

```
{
  "submission_uuid": "c6216c04-2494-4a6a-bee1-5218b15cc221",
  "tenant_id": 15,
```

```

"terminal_id": 30,
"submission_timestamp": "2025-10-13T16:10:31Z",
"receipt_no ": " <your_receipt_number> ",
"transaction_count": 1,

"transaction": {
  "transaction_id": "925a07fa-37c4-48fa-98c6-4ab059485594",
  "transaction_timestamp": "2025-10-01T21:30:06Z",
  "gross_sales": 14806,
  "net_sales": 14806,
  "promo_status": "WITH_APPROVAL",
  "customer_code": "C-B1023",
  "payload_checksum": "bd96f1fd3c5a909427cfc4bcba4962e98d23b7d37b01350908428402fe8cc1b4",

  "adjustments": [
    {"adjustment_type": "promo_discount", "amount": 0},
    {"adjustment_type": "senior_discount", "amount": 0},
    {"adjustment_type": "pwd_discount", "amount": 0},
    {"adjustment_type": "vip_card_discount", "amount": 0},
    {"adjustment_type": "service_charge_distributed_to_employees", "amount": 0},
    {"adjustment_type": "service_charge_retained_by_management", "amount": 0},
    {"adjustment_type": "employee_discount", "amount": 0}
  ],

  "taxes": [
    {"tax_type": "VAT", "amount": 1528.43},
    {"tax_type": "VATABLE_SALES", "amount": 12736.87},
    {"tax_type": "SC_VAT_EXEMPT_SALES", "amount": 510},
    {"tax_type": "OTHER_TAX", "amount": 0}
  ]
}
}

```

E. Canonicalize the submission JSON (string to hash)

- Remove submission.payload_checksum (not present yet).
- Apply the **same** canonicalization rules as step 2.
- The nested transaction **must include** the payload_checksum from step 3.

Canonical submission sting:

```

{"submission_timestamp":"2025-10-13T16:10:31Z","submission_uuid":"c6216c04-2494-4a6a-bee1-5218b15cc221","tenant_id":15,"terminal_id":30,"transaction":{"adjustments":[{"adjustment_type":"prom o_discount","amount":0},{"adjustment_type":"senior_discount","amount":0},{"adjustment_type":"pwd_di scount","amount":0},{"adjustment_type":"vip_card_discount","amount":0},{"adjustment_type":"service_c harge_distributed_to_employees","amount":0},{"adjustment_type":"service_charge_retained_by_manage ment","amount":0},{"adjustment_type":"employee_discount","amount":0}], "customer_code":"C- B1023","gross_sales":14806,"net_sales":14806,"payload_checksum":"bd96f1fd3c5a909427cfc4bcba4962e

```

```
98d23b7d37b01350908428402fe8cc1b4","promo_status":"WITH_APPROVAL","taxes":[{"amount":1528.43,"tax_type":"VAT"},{"amount":12736.87,"tax_type":"VARIABLE_SALES"},{"amount":510,"tax_type":"SC_VAT_EXEMPT_SALES"},{"amount":0,"tax_type":"OTHER_TAX"}],"transaction_id":"925a07fa-37c4-48fa-98c6-4ab059485594","transaction_timestamp":"2025-10-01T21:30:06Z","receipt_no ": "<your_receipt_number> ","transaction_count":1}
```

F. Compute the submission checksum

- Hash = **SHA-256** over the UTF-8 bytes of the canonical submission string.
- Hex output: lowercase, 64 chars.

Submission checksum example:

submission.payload_checksum =

"fb3ccfcb5e6ce98a1e53cb5821e876c50c4928edeefecea12ec00def5a8388be"

G. Final JSON to send (include both checksums)

Headers:

Content-Type: application/json; charset=utf-8

Body:

```
{
  "submission_uuid": "c6216c04-2494-4a6a-bee1-5218b15cc221",
  "tenant_id": 15,
  "receipt_no ": " <your_receipt_number> ",
  "terminal_id": 30,
  "submission_timestamp": "2025-10-13T16:10:31Z",
  "transaction_count": 1,
  "payload_checksum": "fb3ccfcb5e6ce98a1e53cb5821e876c50c4928edeefecea12ec00def5a8388be",
  "transaction": {
    "transaction_id": "925a07fa-37c4-48fa-98c6-4ab059485594",
    "transaction_timestamp": "2025-10-01T21:30:06Z",
    "gross_sales": 14806,
    "net_sales": 14806,
    "promo_status": "WITH_APPROVAL",
    "customer_code": "C-B1023",
    "payload_checksum":
      "bd96f1fd3c5a909427cfc4bcba4962e98d23b7d37b01350908428402fe8cc1b4",
    "adjustments": [
      {"adjustment_type": "promo_discount", "amount": 0},
```

```

    {"adjustment_type": "senior_discount", "amount": 0},
    {"adjustment_type": "pwd_discount", "amount": 0},
    {"adjustment_type": "vip_card_discount", "amount": 0},
    {"adjustment_type": "service_charge_distributed_to_employees", "amount": 0},
    {"adjustment_type": "service_charge_retained_by_management", "amount": 0},
    {"adjustment_type": "employee_discount", "amount": 0}
  ],
  "taxes": [
    {"tax_type": "VAT", "amount": 1528.43},
    {"tax_type": "VARIABLE_SALES", "amount": 12736.87},
    {"tax_type": "SC_VAT_EXEMPT_SALES", "amount": 510},
    {"tax_type": "OTHER_TAX", "amount": 0}
  ]
}

```

9. Error Handling

Common HTTP Status Codes

- **200:** Success
- **401:** Unauthorized (invalid/missing API token)
- **422:** Validation failed (invalid payload structure/data)
- **404:** Transaction not found (for void operations)
- **429:** Rate limit exceeded

Error Response Format

```

{
  "success": false,
  "message": "Validation failed",
  "errors": {
    "field_name": ["Error message 1", "Error message 2"],
    "structure": "Payload does not follow standard TSMS structure"
  },
  "structure_hint": "Ensure payload follows standard TSMS structure with payload_checksum positioned correctly"
}

```

Validation Error Types

- **Missing required fields**
- **Invalid data types/formats**
- **Financial calculation mismatches**
- **Missing required adjustment/tax types**
- **Field ordering violations**

- **Checksum validation failures**

10. Contact Information

For questions or integration support, contact the TSMS technical team:

- **Email:** rgalisanao@pitx.com.ph
- **Subject:** TSMS Integration Support

Examples

Transaction Example

```
{
  "submission_uuid": "e3b0c442-98fc-1c14-9afb-4c8996fb9242",
  "tenant_id": 45,
  "terminal_id": 5,
  "submission_timestamp": "2025-07-19T12:00:00Z",
  "transaction_count": 1,
  "payload_checksum": "7bccb261eb499ce776df26a37a57ac413acde53dbe587d2450ef14d895f3b507",
  "transaction": {
    "transaction_id": "f47ac10b-58cc-4372-a567-0e02b2c3d529",
    "transaction_timestamp": "2025-07-19T12:00:01Z",
    "gross_sales": 1000.00,
    "net_sales": 920.00,
    "promo_status": "WITH_APPROVAL",
    "customer_code": "CUST001",
    "payload_checksum": "7ba832a4d51f858298c8ccecb7de11eca740b7b400fc22b20f2a4b4ffa4c02d6",
    "adjustments": [
      {"adjustment_type": "promo_discount", "amount": 50.00},
      {"adjustment_type": "senior_discount", "amount": 20.00},
      {"adjustment_type": "pwd_discount", "amount": 0.00},
      {"adjustment_type": "vip_card_discount", "amount": 0.00},
      {"adjustment_type": "service_charge_distributed_to_employees", "amount": 0.00},
      {"adjustment_type": "service_charge_retained_by_management", "amount": 0.00},
      {"adjustment_type": "employee_discount", "amount": 0.00}
    ],
    "taxes": [
      {"tax_type": "VAT", "amount": 120.00},
      {"tax_type": "VARIABLE_SALES", "amount": 0.00},
      {"tax_type": "SC_VAT_EXEMPT_SALES", "amount": 0.00},
      {"tax_type": "OTHER_TAX", "amount": 10.00}
    ]
  }
}
```

}

Version: 2.0 **Last Updated:** September 9, 2025 **Document Status:** Official TSMS Integration Guide