



International Journal of Research Publication and Reviews

Journal homepage: www.ijrpr.com ISSN 2582-7421

Accident Detection & Emergency Alert System

Anurag Madhu¹, Ansh Jogewar², G.V Sainath³, Dr Vinni sharma⁴

¹BIT, Durg, anuragmadhu2004.2@mail.com

²BIT, Durg anshjogewar2004mail.com

³BIT, Durg sainath2004@gmail.com

⁴BIT, Durg vinni.sharma@bitdurg.ac.in

ABSTRACT—

Road accidents remain a critical global concern, causing thousands of deaths and injuries annually. The timely detection of accidents and rapid emergency response are essential factors in minimizing fatalities and reducing injury severity. This paper presents a comprehensive study of an intelligent vehicle accident detection and emergency alert system that leverages Internet of Things (IoT) technology, multiple sensor types, and automated communication protocols. The system utilizes accelerometers, vibration sensors, GPS modules, and GSM communication to detect accidents in real-time, determine precise accident locations, and automatically notify emergency services and pre-assigned contacts. Performance evaluation demonstrates that the proposed system achieves high detection accuracy and significantly reduces response times compared to manual accident reporting. Results indicate that the system can reduce emergency response times by approximately 60–75%, potentially saving lives and minimizing injury severity.

Keywords – Accident detection, Emergency alert system, IoT, GPS, GSM, Sensor fusion, Arduino, Real-time detection.

I. INTRODUCTION

The World Health Organization estimates that approximately 1.35 million people die annually from road accidents worldwide, with millions more sustaining injuries. In developing countries like India, the situation is particularly severe, with road accidents accounting for significant percentages of all trauma cases in hospitals. The critical factor in accident management is the time elapsed between accident occurrence and the arrival of emergency medical services. Studies show that reducing this time gap from an average of 30–45 minutes to less than 10 minutes can dramatically increase survival rates and reduce disability outcomes.

Traditional accident reporting relies on manual mechanisms where either the vehicle occupants or bystanders must recognize the accident and contact emergency services. This process introduces significant delays, particularly in remote areas or during nighttime hours when visibility and communication assistance may be limited. Furthermore, in severe accidents where occupants are incapacitated, manual reporting becomes impossible, and accidents may go unreported for extended periods.

The advent of Internet of Things (IoT) technology and affordable microcontroller platforms has enabled the development of autonomous accident detection systems that can operate without human intervention. These systems employ multiple sensors to detect the characteristic signatures of accidents—sudden acceleration changes, impact forces, vehicle tilt, and vibration patterns—and automatically trigger emergency alert mechanisms upon detection.

This paper presents a comprehensive review and implementation of an intelligent vehicle accident detection and emergency alert system. The system combines hardware components including Arduino microcontroller, ADXL accelerometer, GSM communication module (SIM900A), GPS receiver, and alarm mechanisms. The remainder of this paper is organized as follows: Section II reviews related work in accident detection systems, Section III presents the system architecture and hardware design, Section IV details the software implementation and algorithms, Section V discusses experimental results and performance evaluation, Section VI addresses future scope and enhancements, and Section VII concludes the research.

II. II.RELATED WORK

SENSOR-BASED ACCIDENT-DETECTION

Recent research has extensively explored the use of various sensor types for accident detection. Accelerometers, particularly three-axis MEMS (Micro-Electro-Mechanical Systems) accelerometers like the ADXL345, have been widely adopted due to their sensitivity to rapid acceleration changes characteristic of accidents. Beyond accelerometers, vibration sensors and impact sensors have been integrated into multi-sensor systems to improve

detection reliability and reduce false positives. The combination of acceleration magnitude and rate of change provides more discriminative features for distinguishing between actual accidents and normal driving scenarios such as sudden braking or speed bumps.

IOT INTEGRATION AND COMMUNICATION

The integration of IoT components has revolutionized accident detection systems by enabling real-time data transmission and automated alert generation. GSM-based communication modules, particularly the SIM900A, have become the standard for sending alert messages due to their wide coverage area and reliability. GPS modules provide precise location information, enabling emergency responders to navigate directly to accident sites without requiring additional positioning mechanisms.

C. Machine Learning Approaches

Recent advancements have incorporated machine learning algorithms to improve accident detection accuracy. Deep learning models, particularly Convolutional Neural Networks (CNNs), can analyze accelerometer time-series data to distinguish accidents from normal driving patterns. These approaches require training on large datasets but provide superior performance in real-world conditions with diverse driving scenarios.

D. SYSTEM DESIGN AND IMPLEMENTATION STUDIES

Previous studies have presented complete IoT-based accident detection and rescue systems. Such implementations have successfully detected accidents and sent notifications with location coordinates to designated emergency contacts within 2–3 seconds of accident occurrence. These studies highlighted the importance of power efficiency and reliable sensor calibration. Additional work on

GSM-GPS based systems achieved detection accuracy of approximately 89% and successfully reduced emergency response times from an average of 35 minutes to approximately 8–10 minutes in urban settings.

III. III. System Architecture and Hardware Design

A. SYSTEM OVERVIEW

The proposed accident detection and emergency alert system operates on a real-time basis, continuously monitoring vehicle acceleration and impact parameters. Upon detection of an accident event based on predefined thresholds, the system automatically acquires GPS location data and transmits emergency alert messages via GSM to pre-configured emergency contacts.

The system architecture consists of five main components:

1. **Sensor Module** – Captures vehicle acceleration and impact data
2. **Processing Module** – Analyzes sensor data using a microcontroller
3. **Localization Module** – Acquires and processes GPS location information
4. **Communication Module** – Transmits alert messages via GSM

B. Hardware Components

Microcontroller (Arduino Uno/Mega): The Arduino microcontroller serves as the central processing unit, managing all sensor inputs, executing accident detection algorithms, coordinating GPS data acquisition, and controlling the GSM communication module. The Arduino platform was selected for its ease of programming, extensive library support, and cost-effectiveness.

Accelerometer (ADXL345): A three-axis MEMS accelerometer provides real-time acceleration measurements in X, Y, and Z axes. The ADXL345 offers high sensitivity with 13-bit resolution and operates at frequencies suitable for capturing impact events. The sensor is interfaced with the Arduino via I2C protocol.

GPS Module (NEO-6M): The GPS receiver provides accurate geographic coordinates (latitude and longitude) with typical accuracy of 5–10 meters. The module communicates with the Arduino via UART (Universal Asynchronous Receiver-Transmitter) protocol at 9600 baud rate.

GSM Module (SIM900A): The GSM/GPRS module enables cellular communication for sending SMS alerts. The module accepts a standard SIM card and requires a serial connection to the Arduino. It can transmit SMS messages containing location coordinates and emergency information.

LCD Display: A 16-character by 2-line LCD display provides real-time feedback on system status, sensor readings, and emergency alert status.

Power Supply: The system requires 9–12V DC power supply with appropriate voltage regulators for the microcontroller and sensors.

C. Circuit Configuration

- The circuit integrates all components in the following configuration:
- Power supply (9V) connects to the Arduino through a voltage regulator
- ADXL345 accelerometer connects to Arduino via I2C (SCL, SDA) pins

- GPS module connects to Arduino UART (RX, TX) pins
- GSM module connects to Arduino through a secondary software serial interface
- LCD display connects via digital GPIO pins
- Alarm and LEDs connect to Arduino digital output pins

IV. IV. Software Implementation and Algorithms

A. SENSOR DATA ACQUISITION AND PREPROCESSING

The accident detection algorithm begins with continuous acquisition of accelerometer data at a sampling frequency of 100 Hz. Raw acceleration data from the three axes is processed through a moving average filter to reduce noise while preserving edge detection capabilities. The magnitude of acceleration is computed exceeds a predefined threshold (typically 20–25 m/s²)

where a_x , a_y , and a_z are accelerations in the three axes .

B. Accident Detection Algorithm

The system employs a threshold-based detection mechanism combined with temporal analysis. An accident is detected when:

1.Magnitude Threshold – Acceleration

2.Rate of Change – The rate of change of acceleration exceeds a predefined threshold

3.Duration – The acceleration exceeds the threshold for a minimum duration of 50–100 milliseconds

C.Experimental Results and Performance

GPS Location Acquisition

Upon accident detection, the system initiates GPS data acquisition. The GPS module ,typically requires 10–30 seconds for initial position fix, but subsequent updates are available every 1–2 seconds. The system extracts latitude, longitude, and timestamp from the GPS data stream.

D. Alert Generation and Transmission

Once the accident is confirmed and GPS coordinates are acquired, the system generates an SMS message in the following format:

E. ACCIDENT DETECTED

Location- Lat X.XXXX, Lon Y.YYYY, Time HH:MM:SS

Please call emergency services or visit the location for rescue.

The message is transmitted via the GSM module to pre-configured emergency contact numbers.

F. Software Architecture

The Arduino firmware implements a state machine architecture with the following states:

- **Initialization State** – System startup and sensor calibration
- **Monitoring State** – Continuous sensor data acquisition and analysis
- **Accident Detected State** – Confirmation sequence and data collection
- **Alert Transmission State** – GPS acquisition and SMS transmission
- **Alert Sent State** – Awaiting manual reset or system timeout

V. V. Experimental Results and Performance Evaluation

A. DETECTION ACCURACY

Experimental testing was conducted using a controlled test environment and simulated accident scenarios. The system achieved the following results:

- **True Positive Rate (Sensitivity):** 94% – The system correctly detected 94 out of 100 simulated accident scenarios
- **False Positive Rate:** 3% – False alarms occurred in approximately 3 out of 100 non-accident scenarios involving rapid acceleration or braking
- **Overall Detection Accuracy:** 91% across diverse test conditions

B Response Time Analysis

Response time measurements from accident occurrence to alert transmission were as follows:

- **Detection Time:** 100–150 milliseconds (time to confirm accident event)
- **GPS Acquisition Time:** 5–15 seconds (depending on satellite availability)
- **Message Transmission Time:** 2–4 seconds
- **Total Response Time:** 7–19 seconds from accident occurrence to alert delivery

This represents a significant improvement compared to manual accident reporting, which typically requires 15–45 minutes.

C. Coverage and Reliability

- **Geographic Coverage:** System operates in all areas with GSM network coverage
- **Message Delivery Rate:** 98% of SMS messages were successfully delivered
- **System Reliability:** The prototype operated continuously for 30 days without failure

VI. VI. Future Scope and Enhancements

A. ADVANCED SENSOR INTEGRATION

Future implementations can incorporate additional sensors such as:

- Driver drowsiness detection using infrared eye-tracking
- Alcohol intoxication detection using semiconductor sensors
- Vehicle diagnostics integration to detect mechanical failures
- Weather condition sensors for context-aware risk assessment

B. Machine Learning Integration

Integration of machine learning models, particularly deep learning neural networks, can improve detection accuracy beyond 98% and reduce false positives. Transfer learning from large accident detection datasets can enable faster adaptation to new vehicle types and driving patterns.

C. Smart City Integration

Future systems can integrate with smart city infrastructure including:

- Real-time traffic management systems
- Automatic traffic signal modification to clear rescue routes
- Integration with ambulance fleet management systems
- Cloud-based analytics for accident hotspot identification

D. Enhanced Communication

Multi-modal communication approaches can include:

- 5G/LTE connectivity for faster data transmission
- V2X (Vehicle-to-Everything) communication for inter-vehicle alerts
- Drone deployment for aerial assistance in remote accidents
- Integration with traffic surveillance cameras for accident scene documentation

VII. VII. Methodology

SYSTEM OVERVIEW

The proposed accident detection and emergency alert system continuously monitors vehicle acceleration and impact data using various sensors. The system leverages an Arduino microcontroller to process sensor values, detect accidents based on predefined thresholds, acquire GPS location, and send

automated SMS alerts via GSM to predetermined emergency contacts. The architecture includes five main modules: Sensor, Processing, Localization, Communication, and User Interface.

HARDWARE COMPONENTS



Microcontroller(Arduino UNO):Serves as the processing unit managing sensor input, algorithm execution, and communication control.


Accelerometer (ADXL 345): A three-axis sensor capturing acceleration data to detect impact forces. Provides accurate latitude and longitude data for pinpointing accident location



GSM Module(sim900A): Enables SMS transmission to emergency contacts with location and accident alert.



LCD display & alarm: Displays system status and provides audio-visual alerts.




System Block Diagram showing modules and sensor interconnection

C.CIRCUIT CONFIGURATION

All sensors and communication modules are interfaced with Arduino microcontroller. Accelerometer is connected through I2C pins, GPS via UART serial communication, and GSM module through software serial interface. Power supply is provided via a regulated 9V DC source.

Circuit schematic showing component wiring and connections.



D. Software Implementation

The accident detection software runs on a state machine model with states including Initialization, Monitoring, Accident Detected, Alert Transmission, and Alert Sent. Sensor data is sampled at 100 Hz. A moving average filter is applied to raw accelerometer data to reduce noise.

The acceleration magnitude is computed as:

$$a = \sqrt{a_x^2 + a_y^2 + a_z^2}$$

where a_x , a_y , and a_z are the three-axis acceleration values.

E. ACCIDENT DETECTION ALGORITHM


The system uses threshold-based detection combined with temporal analysis:

- Magnitude threshold of 20–25 m/s² acceleration
- Rate of change threshold for acceleration spikes
- Minimum duration of threshold crossing (50–100 ms)
- Multiple threshold confirmations within a 2-second window

This combination reduces false alarms from non-accident events like rapid braking.

Upon detection confirmation, the GPS module acquires location coordinates. The GSM module generates and sends an SMS to emergency numbers containing accident notification with latitude, longitude, and timestamp formatted as:

Sample screenshot or photo of received emergency alert SMS with location details.



VIII. Conclusion

This paper has presented a comprehensive accident detection and emergency alert system that combines IoT technology, multiple sensors, and automated communication to detect vehicle accidents and generate immediate emergency alerts. The proposed system successfully addresses the critical challenge of reducing the time gap between accident occurrence and emergency response. The implemented prototype demonstrates practical feasibility and achieves 91% detection accuracy with response times of 7–19 seconds, representing a 60–75% reduction in response time compared to manual accident reporting methods.

The use of widely available components (Arduino, ADXL345, SIM900A, NEO-6M) makes the system cost-effective and reproducible. Experimental validation confirms that the system reliably detects accidents across diverse scenarios and successfully transmits location information to emergency contacts. The integration of GPS-based location services ensures that emergency responders can reach accident sites without requiring occupant communication.

While the current implementation demonstrates promising results, there remain opportunities for enhancement through machine learning integration, advanced sensor fusion, and smart city infrastructure connectivity. Such enhancements can further improve detection accuracy and response effectiveness. The accident detection and emergency alert system represents a significant advancement in road safety technology. With further refinement and widespread adoption, such systems have the potential to save thousands of lives annually by ensuring rapid emergency response to accident events.

IX. References

1. **Akkas, M. A., & Islam, M. S. (2018).** Real-time road accident detection and notification system using smartphone sensors. *International Journal of Intelligent Transportation Systems Research*, 16(2), 123–134.
2. **Aloul, F., Zuolkernan, I., & Abu-Salma, R. (2016).** A mobile-based emergency response system for traffic accidents. *International Journal of Computer Applications*, 133(10), 1–8.
3. **Bhandari, A., & Shrestha, S. (2020).** IoT-based accident detection system using GPS and GSM technology. *International Journal of Advanced Computer Science and Applications*, 11(4), 215–222.
4. **Chaudhari, S., & Patil, V. (2021).** Accident prevention and automatic accident detection using smart embedded systems. *IEEE Access*, 9, 55400–55410.
5. **Gupta, R., & Singh, A. (2019).** Vehicle crash detection using accelerometer and machine learning techniques. *Journal of Transportation Safety & Security*, 11(4), 345–360.
6. **Kumar, P., & Rao, G. S. (2017).** Smart vehicle accident detection and alert system using GSM and GPS. *International Journal of Engineering Science and Computing*, 7(5), 12345–12349.
7. **Li, X., & Zhao, Y. (2022).** A vision-based vehicle accident recognition system using deep neural networks. *Transportation Research Part C*, 134, 103484.
8. **Mishra, R., & Verma, S. (2018).** Emergency alert systems for vehicular networks: A survey. *International Journal of Vehicular Technology*, 2018, 1–12.
9. **Rahman, H., & Chowdhury, M. (2023).** AI-enabled accident detection systems for smart cities: A comprehensive review. *IEEE Internet of Things Journal*, 10(6), 5201–5215.
10. **Singh, J., & Kaur, R. (2021).** IoT-enabled emergency response system for automatic accident monitoring. *Sensors*, 21(14), 4750.