

ServiceNow

Service Portal Client Side API – SPModal

Show alerts, prompts, and confirmation dialogs in Service Portal widgets. The SPModal class is available in Service Portal client scripts.

alert(string message).then(fn):



Displays a alert.

Eg:

```
1 <button ng-click='c.onAlert()' class='btn btn-default'>
2   Alert
3 </button>

1 function aaa($scope, spUtil, spModal) {
2   var c = this;
3   c.onAlert = function(){
4     spModal.alert('How are you today').then(function (answer){
5       c.s = answer;
6     });
7   }
}
```

Output:



confirm(string message).then(fn):


Displays a confirmation message.

Eg:

```
1 <button ng-click='c.onconfirm()' class= 'btn btn-default'>
2   Confirm
3 </button>

1 * function aaa($scope, $util, spModal) {
2   var c = this;
3   c.onconfirm = function()
4   {
5     spModal.confirm('you want to submit').then(function(confirm){
6       c.confirm = confirm;
7     });
8   }
9 }
10 }
```

Output:



open(object options).then(fn):

Opens the modal window using the specified options.

Options:

backdrop: Boolean|String. Controls the presence of a backdrop.

buttons: Arrays. The buttons to show on the dialog. The default is cancel and ok.

input: Boolean. When True, shows an input field on the dialog.

keyboard: Boolean. When true, indicates that the dialog is closable use ESC key.

message: String. HTML that goes in the header.

noDismiss: Boolean. When true, indicates that the header section that contain the close icon is present.

shared: Client-side Object. Shares data with the embedded widget client script.

size: String. Size of the window. Valid Values are 'sm' or 'lg'.

title: String. HTML that goes in the header.

value: String. Value of the input field.



widget: String. Widget ID or sys_id to emded in the dialog.

widgetInput: Object. Sent to the embedded widget as input.

Eg:

```
1 <button ng-click="c.onconfirm()" class="btn btn-default">
2   Label
3 </button>
4 <div ng-show = 'c.name'>
5   {{c.name}}
6 </div>
7
1 function aaa($scope, spUtil, spModal) {
2   var c = this;
3   c.onconfirm = function()
4   {
5     spModal.open({
6       backdrop: 'true',
7       title: 'hello world',
8       message: 'This is Service Portal',
9       widget: 'current-status',
10      input: true,
11      value: c.name
12    }).then(function(name){
13      c.name = name;
14    })
15  }
```

Output:



Prompt(string message, string default).then(fn):

Displays a prompt for user input.

Eg:

```
1 <button ng-click="c.onprompt()" class="btn btn-default">
2   Prompt
3 </button>
4 <div ng-show="c.name">
5   {{c.name}}
6 </div>
7
1 function aaa($scope, spUtil, spModal) {
2   var c = this;
3   c.onprompt = function(){
4     spModal.prompt('what is you name', c.name).then(function(name) {
5       c.name = name;
6     })
7   }
8 }
```

Output:

